

IBM Security Identity Manager
Version 7.0.0.2

Reference Topics



IBM Security Identity Manager
Version 7.0.0.2

Reference Topics



Table of contents

Table list	vii
Chapter 1. Application extensions	1
WorkflowApplication interface	1
Application extension methods	1
Registering extensions	2
Chapter 2. Application programming interfaces	5
Applications API	5
Self registration API	6
Access control information list (ACI) API	6
IBM Security Identity Manager group API	6
Provisioning policy API	7
Recertification policy API	7
Reconciliation API	7
Authentication API	8
Data services API	8
IBM Directory Integration API	8
JavaScript API	9
Mail API	9
Password rules API	9
Policy analysis API	9
Service provider API	10
Single sign-on API	10
Web services API	10
Workflow API	14
Chapter 3. Dictionary for a password policy	15
Chapter 4. Dataservices attributes for recertification	17
Chapter 5. Date range customization	19
Chapter 6. Workflow extensions	21
Policy enforcement extension	21
Recertification extensions	21
Wait extension	23
Chapter 7. REST APIs	25
Download REST APIs	26
REST API code samples	26
Invoking REST APIs in a domain different from the originating web page	26
Filter configuration for REST search services	27
Chapter 8. Dynamic tags in mail templates	31
Mail templates	36
Manual service default messages	36
Recertification default messages	38

Workflow default messages	44
Chapter 9. JavaScript extensions overview	55
Packaged extensions	56
AttributesExtension	56
DelegateExtension	57
EmailContextExtension	57
EnroleExtension	57
IdentityPolicyExtension	57
LoopCountExtension	58
Model extensions package	58
PersonPlacementRulesExtension	59
PostOfficeExtension	60
ProvisioningPolicyExtension	60
ReminderExtension	60
ServiceExtension	60
SubjectExtension	61
WorkflowExtension	61
Registering JavaScript extensions	62
Configuring scriptframework.properties	63
Migration of custom FESI extensions to the IBM JSEngine	64
Best practice in handling function returns	64
Plain Old Java Object (POJO) example	65
Conversion to a script extension	67
Creation of a constructor	68
Chapter 10. JavaScript extension reference	71
How to read the reference pages	72
Account	74
Account.getAndDecryptPassword()	74
Account.setAndEncryptPassword()	75
AccountSearch	75
AccountSearch.searchByOwner()	76
AccountSearch.searchByUid()	76
AccountSearch.searchByUidAndService()	77
AccountSearch.searchByURI()	77
Activity	78
Activity.auditEvent()	79
Activity.description	80
Activity.duedate	80
Activity.getSubProcesses()	80
Activity.guid	81
Activity.id	81
Activity.index	81
Activity.name	81
Activity.participant	82
Activity.resultDetail	82
Activity.resultSummary	82
Activity.setResult()	82
Activity.started	83
Activity.state	83
Activity.subtype	84

Activity.type	84	Participant.implementation	119
AttributeChangeOperation	84	Participant.name	119
AttributeChangeOperation.attr	85	Participant.type	119
AttributeChangeOperation.op	85	ParticipantType	119
AttributeChangeOperation.values[]	85	Person	121
ContainerSearch	86	Person.getAllAssignmentAttributes()	123
ContainerSearch.searchByFilter()	86	Person.getAndDecryptSynchPassword()	123
ContainerSearch.searchByURI()	87	Person.getAndDecryptPersonPassword()	124
Context	87	Person.getRoleAssignmentData()	124
Context.getAccountParameter()	89	Person.getRoleAssignmentData(String	
Context.getActivityResult()	89	roleAssignedDN)	125
Context.getActivityResultById()	89	Person.getRoles()	126
Context.getLoopCount()	90	Person.getNewRoles()	126
Context.getLoopCountById()	90	Person.getRemovedRoles()	126
Context.getProcessType()	90	Person.isInRole()	127
Context.getRequestee()	91	Person.removeRole()	127
Context.getService()	91	Person.removeRoleAssignmentData()	128
Context.isAccountDataChanged()	91	Person.updateRoleAssignmentData()	128
Delegate	92	PersonSearch	129
DirectoryObject	92	PersonSearch.searchByFilter()	130
DirectoryObject.addProperty()	93	PersonSearch.searchByURI()	130
DirectoryObject.dn	94	PostOffice	131
DirectoryObject.getChanges()	95	PostOffice.getAllEmailMessages()	131
DirectoryObject.getProperty()	95	PostOffice.getEmailAddress()	132
DirectoryObject.getPropertyAsDate()	96	PostOffice.getPersonByEmailAddress()	132
DirectoryObject.getPropertyAsString()	96	PostOffice.getTopic()	132
DirectoryObject.getPropertyNames()	97	Process	132
DirectoryObject.name	97	Process.auditEvent()	134
DirectoryObject.profileName	97	Process.comment	135
DirectoryObject.removeProperty(name)	98	Process.description	135
DirectoryObject.removeProperty(name,value)	98	Process.getActivity()	135
DirectoryObject.setProperty()	99	Process.getParent()	136
EmailContext	100	Process.getRootProcess()	136
Enrole	102	Process.getRootRequesterName()	137
Enrole.generatePassword()	103	Process.guid	137
Enrole.getAttributeValue()	103	Process.getSubProcesses()	137
Enrole.getAttributeValues()	104	Process.id	138
Enrole.localize()	104	Process.name	138
Enrole.log()	104	Process.parentId	138
Enrole.logError()	105	Process.requesteeDN	138
Enrole.logInfo()	106	Process.requestorDN	139
Enrole.logWarning()	106	Process.requesteeName	139
Enrole.toGeneralizedTime()	107	Process.requestorName	139
Enrole.toMilliseconds()	107	Process.requestorType	140
Enrole.traceMax()	108	Process.resultDetail	140
Enrole.traceMid()	108	Process.resultSummary	140
Enrole.traceMin()	109	Process.setRequesteeData()	140
Error	110	Process.setResult()	141
Error.setMessage()	110	Process.setSubjectData()	141
Error.getMessage()	110	Process.started	142
Error.setErrorCode()	111	Process.state	142
Error.getErrorCode()	111	Process.subject	142
ExtendedPerson	111	Process.type	143
ExtendedPerson.getOwnershipType()	112	ProcessData	143
ExtendedPerson.setOwnershipType()	113	ProcessData.get()	143
IdentityPolicy	113	ProcessData.set()	144
IdentityPolicy.getNextCount()	113	RecertificationWorkflow	144
IdentityPolicy.userIDExists()	114	Reminder	145
PackagedApprovalDocument	115	Role	145
PackagedApprovalItem	117	Role.getAssignmentAttributes()	146
Participant	118	Role.getAllAssignmentAttributes()	147

Role.getOwner()	147
Role.setAssignmentAttributes()	148
RoleAssignmentAttribute	148
RoleAssignmentAttribute.getName()	148
RoleAssignmentAttribute.getRoleName()	149
RoleAssignmentAttribute.getRoleDN	149
RoleAssignmentObject	150
RoleAssignmentObject.getAssignedRoleDN()	151
RoleAssignmentObject.getDefinedRoleDN()	152
RoleAssignmentObject.addProperty()	152
RoleAssignmentObject.getChanges()	152
RoleAssignmentObject.getProperty()	153
RoleAssignmentObject.getPropertyNames()	154
RoleAssignmentObject.removeProperty()	154
RoleAssignmentObject.setProperty()	154
RoleSearch	155
RoleSearch.searchByName()	155
RoleSearch.searchByURI()	156
SeparationOfDutyRuleViolation	156
Service	157
ServiceSearch	157
ServiceSearch.searchByFilter()	158
ServiceSearch.searchByName()	158
ServiceSearch.searchByURI()	159
ServiceSearch.searchForClosestToPerson()	159

Chapter 11. Provisioning policy parameter usage scenarios 161

Chapter 12. Provisioning policy entitlement parameters 163

Provisioning policy constant	163
Provisioning policy Null types	163
Provisioning policy JavaScript functions	163
Provisioning policy regular expressions.	166

Chapter 13. Service selection policy JavaScript. 167

Service selection policy JavaScript objects	167
Service selection policy script example	167

Chapter 14. SubForm control type . . . 169

SubForm contextual parameters	169
HTTP request parameter naming convention	170
Process to write a SubForm.	171

Chapter 15. Supplemental property files 173

Properties files	173
Modifiable property files	173
adhocreporting.properties	175
CustomLabels.properties	182
enroleAuditing.properties	183
enRoleAuthentication.properties	185
enRoleLogging.properties	187
enrolepolicies.properties	197
enroleStartup.properties	200
enroleworkflow.properties	201
helpmappings.properties	202

reportingLabels.properties	203
reporttabledeny.properties	203
scriptframework.properties (Suggested).	204
SelfServiceHelp.properties	205
SelfServiceHomePage.properties	206
SelfServiceScreenText.properties	206
SelfServiceUI.properties	207
ui.properties.	209
UIConfig.properties	218

Chapter 16. System property configuration in enRole.properties . . 221

Properties files	221
Application server properties	221
Remote services properties	224
Web services properties	225
Organization properties	226
LDAP server properties	227
Search and LDAP control properties.	228
Person profile properties	231
Profile and schema cache properties.	231
Messaging properties.	232
Scheduling properties	234
Password transaction monitor properties	235
XML and DTD properties	236
LDAP connection pool properties.	236
Password encryption properties	238
Challenge response encoding properties	240
System listening port properties	240
Mail properties.	241
Workflow properties	241
Reconciliation properties	247
Shared secret properties	251
Lifecycle rule properties.	251
Product name properties	252
Application client request properties	252
Reverse password synchronization properties	252
Post office properties	253
Database resource bundle properties.	254
Database cleanup properties	254
Create password check box properties	255
Access catalog properties	255
Identity feed properties	256
Upgrade properties	257
Multiple password-synch agent properties.	257
Concurrency properties	258
Required field properties	258

Chapter 17. IBM Security Identity Manager virtual appliance command line interface. 261

IBM Security Identity Manager virtual appliance command line interface commands	261
IBM Security Identity Manager virtual appliance command line interface commands for IBM Security Identity Manager	263
Tailing logs and archiving logs	264
Adding a JVM property	265
Management SSL certificate	267

Chapter 18. Sample configuration response file.	269
Index	271

Table list

1. Filters and their supported values	27	30. Web services properties	225
2. Syntax and example of using JavaScript code to replace message content.	31	31. Organization properties	226
3. Syntax and examples of using a RE tag to replace message content.	32	32. LDAP server properties	227
4. Syntax and example of using tags to replace message content.	33	33. Search and LDAP control properties	228
5. Syntax and examples of ITIMURL.	33	34. Person profile property	231
6. Escape characters	34	35. Profile and schema cache properties	232
7. Host components and script extensions	55	36. Messaging properties	233
8. Script class keys	63	37. Scheduling properties.	234
9. Script extensions	71	38. Password transaction monitor properties	235
10. Provisioning policy examples	161	39. XML and DTD properties	236
11. Sample provisioning policies	161	40. LDAP connection pool properties	236
12. SubForm parameters	169	41. Encryption properties.	238
13. SubForm parameters	170	42. Challenge response encoding properties	240
14. Properties files	173	43. System configuration properties	240
15. adhocreporting.properties properties	175	44. Mail services properties	241
16. enroleAuditing.properties properties	184	45. Workflow configuration properties	241
17. enRoleAuthentication.properties properties	186	46. Reconciliation properties.	247
18. enRoleLogging.properties properties	187	47. Shared secret hashing properties	251
19. enrolepolicies.properties properties	198	48. Lifecycle rule properties	251
20. enroleStartup.properties properties	200	49. Product property	252
21. enroleworkflow.properties properties	202	50. Application client request properties.	252
22. helpmappings.properties properties	202	51. Reverse password synchronization properties	253
23. reporttabledeny.properties	203	52. Post office properties	253
24. SelfServiceHelp properties	205	53. Database resource bundle properties.	254
25. SelfServiceUI. properties	207	54. Database cleanup properties	255
26. ui.properties properties	210	55. Create password check box default properties	255
27. UIConfig.properties	218	56. Access catalog properties	255
28. Application server properties	221	57. Default identity feed properties	256
29. Remote services properties	224	58. Default upgrade properties	257
		59. Multiple password-synch agent properties	257
		60. Account concurrency properties	258
		61. Required field properties.	258

Chapter 1. Application extensions

Application extensions can be defined in Java™ class files and run from a workflow.

Application extensions are typically defined in one or more Java class files. They are used when a set of functions needs to be run from a workflow. The functions can be implemented to receive input parameters from a workflow and return parameters back to the workflow.

WorkflowApplication interface

Application extensions that require access to the current workflow context information must implement the `WorkflowApplication` interface.

If the extension does not require any workflow context information, implementing this interface is not required. The following example is a code snippet for implementing the `WorkflowApplication` interface. For a complete example, see the information in the `extensions.zip` file.

From the Appliance Dashboard on the IBM® Security Identity Manager virtual appliance console, click **Configure > Advanced Configuration > Custom File Management**. From the **All Files** tab, go to `directories/utilities` and download the `extensions.zip` file and extract it.

```
public class CustomEmail implements WorkflowApplication {
    public CustomEmail() {
    }
}
```

When you implement the `WorkflowApplication` interface you must define a `setContext` method that accepts a `WorkflowExecutionContext` object. Store this object in a member variable in the implementing class.

```
// The context of the workflow. Passed in from the workflow engine
protected WorkflowExecutionContext ctx;
/**
 * Passes the workflow execution context to the application.
 *
 * @param context WorkflowExecutionContext holding information about the
 * currently executing activity.
 */
public void setContext(WorkflowExecutionContext ctx) {
    this.ctx = ctx;
}
```

Application extension methods

The application can contain whatever processing is required to accomplish the task. An extension can contain any number of methods that can be exposed to the workflow.

The following example is a code snippet of a method that is available in the workflow for the extension node. For a complete example, see the information in the `extensions` directory.

From the Appliance Dashboard on the IBM Security Identity Manager virtual appliance console, click **Configure > Advanced Configuration > Custom File Management**. From the **All Files** tab, go to directories/utilities and download the `extensions.zip` file and extract it.

```
/**
 * Method sendMailByProperty.
 * This method is called to send an e-mail to an e-mail address specified by
 the
 * "recipient" property in the specified property file.
 * @param person - the requestee's person object
 * @param mailTag - the mailtag for this message. Used to look up properties
 * @param propertyFileName - the name of the property file that contains
 * this message's data
 * @param attrList - an optional list of tag/value pairs
 * @return ActivityResult - a workflow activity result object
 */
public ActivityResult sendMailByProperty(Person person,
String mailTag,
String propertyFileName,
String attrs) {
String recipient_email = "";
try {
processSendMail(person,mailTag,propertyFileName,recipient_email,
attrs);
return new ActivityResult(ActivityResult.STATUS_COMPLETE,
ActivityResult.SUCCESS,
"Sent Mail",
null);
} catch (CustomEMailDataException e) {
return new ActivityResult(ActivityResult.STATUS_COMPLETE,
ActivityResult.FAILED,
e.getMessage(),
null);
}
}
```

Application Extension methods can receive inputs from the workflow. The inputs defined in the workflow extension window maps to the method arguments (ensure that the types match). The `sendMailByProperty` method returns an `ActivityResult` object. This method allows the application to communicate back to the caller a status and a return value, if necessary. The `ActivityResult` object has member variables for status (int), summary, (String), detail (List), and description (String). Return values are in the detail list. The order of the values in the list must correspond to the order of the output parameters as defined in the extension window. See the IBM Security Identity Manager API documentation for a complete description of the `ActivityResult` class.

Registering extensions

For the workflow to make the extension available with the extension node, it must first be registered in the `workflowextensions.xml` file. From the **Appliance Dashboard** of the IBM Security Identity Manager virtual appliance console, select **Configure > Advanced Configuration > Library and Workflow Extension**. Use the Library and Workflow Extension page to register the file.

Each method requires an activity entry in the XML file. The activity entry includes these aspects:

Activity ID

An activity ID is required and must be unique in the workflow. This name is in the extension window activity type menu.

Implementation type

The implementation type contains the class name and the method name that is started by this extension.

Parameters sections

The parameters sections list the input and out parameters and their data types. These parameters are in the extension window Input/Out Parameters.

Transition restriction

The transition restriction defines the join type. Split type can also be defined. For more information, see the information in the extensions.zip file.

From the Appliance Dashboard on the IBM Security Identity Manager virtual appliance console, click **Configure > Advanced Configuration > Custom File Management**. From the **All Files** tab, go to directories/utilities and download the extensions.zip file and extract it.

```
<ACTIVITY ACTIVITYID="SendMailByProperty" LIMIT="600000">
  <IMPLEMENTATION_TYPE>
<APPLICATION
  CLASS_NAME="com.ibm.itim.CustomWorkflowExtensions.CustomEmail"
  METHOD_NAME="sendMailByProperty"/>
  </IMPLEMENTATION_TYPE>
  <PARAMETERS>
<IN_PARAMETERS PARAM_ID="inperson" TYPE="Person"/>
<IN_PARAMETERS PARAM_ID="mailtag" TYPE="String"/>
<IN_PARAMETERS PARAM_ID="propertyfilename" TYPE="String"/>
<IN_PARAMETERS PARAM_ID="attributelist" TYPE="String"/>
  </PARAMETERS>
  <TRANSITION_RESTRICTION JOIN="XOR"/>
</ACTIVITY>
```

The Application Extension class file must be in a JAR file. Do these steps:

1. From the top-level menu of the **Appliance Dashboard**, select **Configure > Advanced Configuration > Library and Workflow Extension** to display the Library and Workflow Extension page.
2. Click **New** to add an external library.
3. In the Add External Library window, upload the JAR file.
4. Paste the extension information in the **Extension** field.
5. Click **Save Configuration**.
6. From the **Server Control** widget on the **Appliance Dashboard**, restart the server before the extensions are available in the workflow.

Chapter 2. Application programming interfaces

Application programming interfaces (APIs) are part of a plug-in model that you can use to add applications without disrupting existing applications.

Remote application programs run outside of the IBM Security Identity Manager server Java virtual machine (JVM). Classes outside of the application packages are not intended to be started by a remote application. Classes in remote applications are documented under the IBM Security Identity Manager application packages. Server extensions, which run in the IBM Security Identity Manager server JVM, can use any of the classes listed in the published API documentation (Javadoc). They are Java classes that run in the same JVM of the caller. These APIs are used to develop IBM Security Identity Manager customization and extensions that can plug into IBM Security Identity Manager.

Several application APIs can be started by a remote application. A few server extension APIs in the `dataservices` package are included also. The following application APIs are intended to be started by a remote application:

Provisioning Policy API

Can search, add, modify, and delete provisioning policies in IBM Security Identity Manager from a remote application.

Group API

Can search, add, modify, and delete an IBM Security Identity Manager group.

ACI API

Can search, add, modify, and delete an access control information list (access right), but it does not verify authorization.

Reconciliation API

Can get, add, modify, and delete a reconciliation schedule for a particular service and triggers reconciliation.

The following server extension APIs are included:

- `com.ibm.itim.common.ComplexAttributeValue`
- `com.ibm.itim.dataservices.model.ComplexAttributeHandler`
- `com.ibm.itim.dataservices.model.domain.access.Access`
- `com.ibm.itim.dataservices.model.domain.access.ProvisioningConfiguration`
- `com.ibm.itim.dataservices.model.domain.access.NotificationOption`

Applications API

Use the applications API to create customized or alternative user interfaces. This API provides an interface to the IBM Security Identity Manager provisioning platform.

The applications API provides a set of Java classes that abstract the more frequently used functions of the provisioning platform. Examples are identity management, password management, and account management. The classes that make up this API are the same classes that IBM Security Identity Manager uses for its user interface.

For more information, see the documentation that is provided with the Applications API. Do these steps:

1. Log on to the IBM Security Identity Manager virtual appliance console to open the **Appliance Dashboard**.
2. From the top-level menu of the **Appliance Dashboard**, select **Configure > Advanced Configuration > Custom File Management** to display the Custom File Management page.
3. Click the **All Files** tab.
4. Go to directories/utilities.
5. Select extensions.zip and click **Download**.
6. Extract the extensions.zip file.
7. Go to `/extensions/version_number/doc/applications`. For example, *version_number* is 7.0.

For sample codes, see `/extensions/version number/examples/apps`.

Self registration API

Part of the applications API, the self registration API provides an interface to create a person in the provisioning platform without a user context.

The self registration API can be called without a user context. It is set up to start without accessing the system with an IBM Security Identity Manager account login and password. The Self Registration API is part of a customizable process. The process provides an example JavaServer Pages (JSP) page as a product extension based on the default `inetOrgPerson` class. The JSP calls the Self Registration API to create a user.

Access control information list (ACI) API

The ACI API provides an interface for managing the IBM Security Identity Manager access control list, container-by-container.

A remote client can use basic add, list, modify, and delete operations for managing the access control list. However, the ACI API cannot verify authorization to the user.

This API exists in the `com.ibm.itim.apps.acl.AccessControlListManager` class.

IBM Security Identity Manager group API

The IBM Security Identity Manager group API provides system group management capabilities, namely APIs to manage groups on the IBM Security Identity Manager service and groups on managed services. The APIs also provide search capabilities for these groups.

The IBM Security Identity Manager group API provides an interface for managing the groups on either the IBM Security Identity Manager service or on other managed services. You can search, add, modify, or delete these groups. You can also add and remove users in a group on either the IBM Security Identity Manager service or on a managed service.

For groups on the IBM Security Identity Manager service, the API exists in the following classes:

- `com.ibm.itim.apps.system.SystemRoleManager`
- `com.ibm.itim.apps.system.SystemRoleMO`

- `com.ibm.itim.apps.system.SystemUserMO`

For groups on a managed service, the API exists in the following classes:

- `com.ibm.itim.apps.provisioning.GroupManager`
- `com.ibm.itim.apps.provisioning.GroupMO`

Provisioning policy API

The IBM Security Identity Manager provisioning policy API provides an interface to manage provisioning policies that are defined in IBM Security Identity Manager.

This API can search, add, modify, and delete provisioning policy. The API exists in the following classes:

- `com.ibm.itim.apps.policy.ProvisioningPolicyManager`
- `com.ibm.itim.apps.policy.ProvisioningPolicyMO`

Recertification policy API

The IBM Security Identity Manager recertification policy API provides an interface to manage recertification policies that are defined in Security Identity Manager.

This API provides capabilities to search, add, modify, delete, and run recertification policies.

The following classes or interfaces are exposed to provide recertification policy management capabilities through APIs.

1. Core classes:

- `com.ibm.itim.apps.policy.RecertificationPolicyManager`
- `com.ibm.itim.apps.policy.RecertificationPolicyMO`
- `com.ibm.itim.dataservices.model.policy.recert.RecertificationPolicy`

2. Dependent classes:

- `com.ibm.itim.dataservices.model.policy.recert.RecertificationParticipant`
- `com.ibm.itim.dataservices.model.policy.RoleTarget`
- `com.ibm.itim.dataservices.model.policy.GroupTarget`
- `com.ibm.itim.dataservices.model.policy.ServiceTarget`
- `com.ibm.itim.scheduling.RecurringTimeSchedule`

3. Abstract classes extended by recertification policy directly or indirectly:

- `com.ibm.itim.dataservices.model.policy.DirectoryPolicy`
- `com.ibm.itim.dataservices.model.policy.ScopedPolicy`
- `com.ibm.itim.dataservices.model.policy.ServicePolicy`

4. Interface implemented by recertification policy or dependent classes directly or indirectly:

- `com.ibm.itim.dataservices.model.policy.Policy`
- `com.ibm.itim.dataservices.model.policy.IPolicyTarget`
- `com.ibm.itim.scheduling.Schedulable`

Reconciliation API

The reconciliation API can create and query reconciliations and reconciliation parameters.

The Reconciliation API provides an interface to manage reconciliation schedules of services. You can:

- Get and set reconciliation schedules to a service.

- Modify the reconciliation schedules collection, which includes additions and deletions.
- Set the new collection.
- Trigger a specific reconciliation schedule to run.

The API exists in the following classes:

- `com.ibm.itim.apps.recon.ReconManager`
- `com.ibm.itim.apps.recon.ReconUnitData`

Authentication API

Use the authentication API for working with different trusted identity stores such as identity information. This information can be stored on a Windows domain server or an LDAP directory. It includes the use of different types of keys, typically passwords, to unlock the application for a user.

The authentication API contains the authentication client API, which makes authentication requests, and the authentication provider API, which implements authentication requests.

Data services API

The data services API provides an interface to the IBM Security Identity Manager data model.

This API abstracts the more commonly used data model entities such as identities, accounts, access, and services in the provisioning process. It includes a generic interface to handle complex attributes. Data synchronization depends on Data Services APIs. Furthermore, the data services API provides the data model that the Applications API uses.

Although the ability to change the data model is provided in this API, this ability is not its focus. The Data Services API is low level. It abstracts the physical layout of the data store (directory structure). It does not provide the business logic that the provisioning applications with the platform provide.

IBM Directory Integration API

With this API, IBM Security Directory Integrator can import identity information into IBM Security Identity Manager. It manages accounts in the IBM Security Identity Manager data store on external resources that use IBM Security Directory Integrator.

The following features are included in this API:

Note: Directory Service Markup Language version 2 (DSMLv2) was deprecated.

- A Directory Service Markup Language version 2 (DSMLv2) ServiceProvider. You can use it to import data. IBM Security Identity Manager acts as a DSMLv2 client. IBM Security Directory Integrator acts as a DSMLv2 server.
- A DSMLv2 event handler. You can use it to import data into IBM Security Identity Manager. IBM Security Identity Manager acts as a DSMLv2 server. IBM Security Directory Integrator acts as a DSMLv2 client.

- Ready-to-use schema support for communicating with IBM Security Directory Integrator. You can use IBM Security Directory Integrator as an endpoint and define it as a service instance in the IBM Security Identity Manager user interface for identity feed.

JavaScript API

The JavaScript API extends the scripting components that are specific to the scripting language that is configured with the product.

IBM Security Identity Manager provides a method to register new JavaScript extensions with the server. You can use the JavaScript API to add additional objects and functions to the interpreter's glossary. A client can create and register additional objects and functions with the interpreter to run at run time.

The JavaScript API provides information about access participants, such as participant type, workflow participants, group access management, and access notification context.

Mail API

Use the mail API to customize mail content, format, and notification recipients.

Clients who use this API can make notification requests and extend construction of notification messages. The Mail API contains the Mail Client API, which makes notification requests, and the Mail Provider API, which implements notification requests.

The mail API also contains a function that is called Post Office that prevents workflow participants from receiving multiple email notifications that have similar content. Similar emails are stored, combined into a single email notification, and forwarded to a user.

Password rules API

The password rules API provides an interface to customize the standard password rule set and random password generation process.

You can use the password rules framework to customize the mechanism of generating passwords by the IBM Security Identity Manager server. Use one of the following ways to add custom logic to the password framework:

- A custom rule
- A custom generator
- Custom rules and a custom generator

Policy analysis API

The policy analysis API provides an interface to information about policies that are defined in the IBM Security Identity Manager Server. It is an interface to the access granted to a specific individual.

The API contains a set of Java classes that retrieve and abstract the provisioning policy information that controls access to managed resources. The Provisioning Policy API reports the provisioning policy enforcement in the system, but it does

not support client modification of the policy. A client can use the policy information for auditing or deciding about potential policy enforcement changes.

Service provider API

The service provider API provides custom connectors. The connectors can be used from the IBM Security Identity Manager provisioning platform or any other Java-based provisioning platform that supports the same interface.

Service provider APIs define the interface that the IBM Security Identity Manager adapter needs to implement and communicate to remote adapter agents. The adapter agent implementation does not rely on IBM Security Identity Manager APIs except for the set of asynchronous notification APIs provided under Service Provider APIs.

The following operations are included in the interface between the provisioning platform and the connector:

- Add
- Change password
- Delete
- Modify
- Restore
- Search
- Suspend
- Test

The provisioning platform performs all of the operations needed to determine the actions and their parameters that are to be run against resources. The connector runs those operations on the resource within requirements that are related to the resource.

Single sign-on API

The single sign-on API provides a single sign-on interface to accessible resources.

Some IBM Security Identity Manager installations might require integration with third party, single sign-on providers. Typically, such single sign-on providers protect a set of web-based resources with an authentication data store that is managed separately from IBM Security Identity Manager. The first time a client attempts to access any protected resource, the single sign-on provider provides authentication. If access is granted, the provider passes a token that indicates the identity of the authenticated user to all resources that are accessed later.

Web services API

This API consists of multiple web services, which are grouped by function. The services are listed alphabetically except the `WSSessionService`. This service is listed first since it is the first service that is called by any application. The session object that is returned by its login method is used as a parameter in all subsequent services.

WSSessionService

The WSSessionService web service provides authentication, session creation, and password challenge authentication. A client calls WSSessionService before you start any other web services. WSSessionService returns a session (handle) object that must be passed to the other web service calls to maintain a threaded conversation. The service provides the following operations:

- Login.
- Logout.

You can also use the WSUnauthService web service for other operations.

WSAccessService

The WSAccessService web service provides the following operations:

- Create a user access.
- Retrieve existing user access of a person.
- Remove user access.
- Search access entitlements available to a person.

The service provides following operations:

- Create and modify accesses.
- Do access searches.

WSAccountService

The WSAccountService web service provides the following operations to do account-related tasks:

- Create, modify, and other simple account operations.
- Retrieve default account attributes for a new account as specified by the provisioning policy.
- Retrieve the account profile name for a service.

WSExtensionService

The WSExtensionService web service provides a framework to extend the existing web services that are used by users. The service provides the users to create an operation to show a new Security Identity Manager API. The detailed steps to create an extension service are specified in the ITIMWS.odt file, which is in the extensions.zip file.

From the Appliance Dashboard on the IBM Security Identity Manager virtual appliance console, click **Configure > Advanced Configuration > Custom File Management**. From the **All Files** tab, go to directories/utilities and download the extensions.zip file and extract it. View the ITIMWS.odt file in \extensions\7.0\doc\ws.

WSGroupService

The WSGroupService web service provides group management functions. The service provides the following operations:

- Create and remove groups.
- Search groups.

- Manage group membership.

WSOrganizationalContainerService

The `WSOrganizationalContainerService` web service provides Security Identity Manager organization tree traversal and retrieval methods.

WSPasswordService

The `WSPasswordService` web service provides password management functions. The service provides the following operations:

- Validates the password as per the password policy rules.
- Enables change or generate password.

WSPersonService

The `WSPersonService` web service provides person-object related methods. The service provides the following operations:

- Create, modify, suspend, restore, delete, and other simple person operations.
- Retrieve the services to which a person is entitled in Security Identity Manager or accounts.
- Do person searches.
- Retrieve the person object of the Principal.

WSProvisioningPolicyService

The `WSProvisioningPolicyService` web service deals with the provisioning policy. The service provides the following operations:

- Search provisioning policies.
- Create, modify, and delete provisioning policies.

WSRequestService

The `WSRequestService` web service provides the Security Identity Manager request related functions. The service provides the following operations:

- Search for completed requests.
- Retrieve pending requests.
- Retrieve the request object that is based on the process ID or request ID.

WSRoleService

The `WSRoleService` web service provides role-based capabilities in the Security Identity Manager. The service provides the following operations:

- Create and modify roles.
- Do role searches.
- Manage role hierarchy.

WSSearchDataService

The `WSSearchDataService` web service provides functions to search various Security Identity Manager directory objects. The search method does not enforce the

Security Identity Manager ACIs, but a valid Security Identity Manager session is required to call these methods. The service provides the following operations:

- Search for persons from root container.
- Search for persons that are having an Security Identity Manager account.
- Search for the possible delegates within Security Identity Manager for the logged-in user.
- Retrieve the searchable attributes of an entity in Security Identity Manager.
- Retrieve common searchable attributes for the Security Identity Manager entity.

WSServiceService

The WSServiceService web service provides Security Identity Manager-based managed services (end-point configuration) functions. The service provides the following operations:

- Retrieve support data. For example, group data for UNIX, Linux, or Microsoft Windows services.
- Determine whether a password is required when provisioning on a service.
- Retrieve services that are configured on Security Identity Manager.

WSSharedAccessService

The WSSharedAccessService web service provides many functions for the shared access module that is introduced in Security Identity Manager . The web service clients must call the login method before it calls any other web services. The service provides the following operations:

- Retrieve authorized shared accesses.
- Retrieve the credentials.
- Check in or checkout credentials.

Note: You must install and enable the shared access module in order to use the WSSharedAccessService API.

For more information, see Shared access web services API.

WSSystemUserService

The WSSystemUserService web service provides the functions that are related to system users. The service provides the following operations:

- Manage delegates, that is, add, modify, or delete delegates.
- Retrieve all the system roles.
- Configure challenge response.
- Search for system users who have an Security Identity Manager account.

WSToDoService

The WSToDoService web service provides the functions to manage the different activities available in Security Identity Manager. The service provides the following operations:

- Approve or reject activities.
- Retrieve or Submit Request for information activity details.
- Retrieve the pending activities of the logged-in user.

WSUnauthService

The WSUnauthService web service provides an interface for all the web service APIs that do not require the Security Identity Manager authentication. The service provides the following operations:

- Version information.
- Reset password by using the challenge responses.
- Password policies.

Workflow API

Use the workflow API for custom code that can be called from a workflow process as a custom Java application or a JavaScript function. This custom code can then do special business logic, query external data stores, or provide integration with other workflow engines.

The Workflow API consists of a set of Java classes. The classes abstract the more commonly used concepts of the workflow environment, such as processes, activities, and relevant data.

The Workflow API supports new access request types. The access owner is a participant type.

The Workflow API provides methods for updating the recertification state and provides audit information for recertification. Audit records contain information about the recertification configuration and the *who*, *what*, and *when* of recertification tasks. These audits provide more useful reports about recertification compliance of users, accounts, and accesses. Consumers of the recertification policies can also have their recertification process audited in a reportable way.

Chapter 3. Dictionary for a password policy

You can create a dictionary for a password policy rule that rejects certain terms as passwords.

To use a dictionary for a password policy rule, you must first create and load a `dictionary.ldif` file to the IBM Security Identity Manager Server. To create a dictionary for a password policy rule:

1. Using an ASCII or other plain text editor, create a dictionary that contains the list of terms in an LDAP Data Interchange Format (LDIF) file.

For example, create a file similar to this `dictionary.ldif` file, which specifies the domain as `dc=com`:

```
dn: erword=test,erdictionaryname=password, ou=itim, dc=com
erWord: test
objectclass: top
objectclass: erDictionaryItem
```

```
dn: erword=secret,erdictionaryname=password, ou=itim, dc=com
erWord: secret
objectclass: top
objectclass: erDictionaryItem
```

```
dn: erword=password,erdictionaryname=password, ou=itim, dc=com
erWord: password
objectclass: top
objectclass: erDictionaryItem
```

2. Use an LDAP browser to import the `dictionary.ldif` file on to the IBM Security Identity Manager Server.

The dictionary file can now be used in the password strength rule.

Chapter 4. Dataservices attributes for recertification

IBM Security Identity Manager provides optional attributes in the `erAccountItem` object class to represent different values for recertification.

Overview

The dataservices attributes for recertification are relevant only if recertification is enabled for specific accounts or accesses.

The following optional attributes are provided:

- `erLastCertifiedDate`
- `erRecertificationLastAction`
- `erAccessLastCertifiedDate`
- `erAccessRecertificationLastAction`

`erLastCertifiedDate`

The `erLastCertifiedDate` attribute is updated by the account recertification process only, but not for accesses. An optional attribute for the timestamp of the last time the account was marked as recertified. This attribute is updated on approved recertifications regardless of recertification policy schedule type, whether rolling or calendar style.

This attribute is updated for both approvals during normal recertification cycle and through the `recertificationOverride` option outside of the normal recertification policy run. The absence of a value means that recertification was never approved for this account. The Account data services object from the `com.ibm.itim.dataservices.model.domain` package defines the `setLastCertifiedDate()` and `getLastCertifiedDate()` methods for accessing this attribute. When an account is *certified*, this attribute must be updated along with `reRecertificationLastAction`.

`erRecertificationLastAction`

The `erRecertificationLastAction` attribute is updated by the account recertification process only, but not for accesses. This attribute requires a getter and setter method defined on the Account data services object class `com.ibm.itim.dataservices.model.domain` package:

```
public void setRecertificationLastAction(String recertificationAction)
public String getRecertificationLastAction()
```

This optional attribute describes the action taken the last time recertification was run. The following values are valid:

- `com.ibm.itim.dataservices.model.domain.Account.CERTIFIED = 'CERTIFIED'`
- `com.ibm.itim.dataservices.model.domain.Account.CERTIFIED_ADMIN = 'CERTIFIED_ADMIN'`
- `com.ibm.itim.dataservices.model.domain.Account.REJECTED_MARK = 'REJECTED_MARK'`
- `com.ibm.itim.dataservices.model.domain.Account.REJECTED_SUSPEND = 'REJECTED_SUSPEND'`

erAccessLastCertifiedDate

The erAccessLastCertifiedDate attribute is specific to accesses that are defined on an account. This multivalued attribute holds the access group definition distinguished name and timestamp that shows when that access was last certified as a delimited string.

Example

```
eraccesslastcertifieddate: erntlocalname=users,  
erglobalid=7281584268561021074,ou=services,  
erglobalid=00000000000000000000,ou=hawk,o=ibm,  
c=us;;200711202115Z
```

This example shows the last recertification date for the access that is associated with the access defined for the group specified by the distinguished name. Only one value for this attribute per access is defined for the account.

erAccessRecertificationLastAction

The erAccessRecertificationLastAction attribute is specific to recertification state of accesses that are defined on an account. This multivalued attribute holds the access group definition distinguished name and recertification last action taken as a delimited string. It serves the same purpose for accesses as erRecertificationLastAction does for accounts.

Example

```
eraccessrecertificationlastaction: erntlocalname=users,  
erglobalid=7281584268561021074,  
ou=services,erglobalid=00000000000000000000,  
ou=hawk,o=ibm,c=us;;CERTIFIED
```

This example shows the last recertification action for the access that is associated with the group definition distinguished name. The values for the action are the same as described for the erRecertificationLastAction attribute. Only one value for this attribute per access is defined for the account.

Chapter 5. Date range customization

IBM Security Identity Manager provides additional date range customization, which is not available through the standard Form Designer applet.

With these options, you can control the years available to users when they customize a date. The following options must be configured manually on the following form template that is stored in the directory server:

```
erformname=inetOrgPerson,ou=formTemplates,ou=itim,ou=tivsys,dc=com
```

You can specify options that define the range of years to be displayed. You also can specify the standard range of years, a special extended max year such as 9999, or special minimum value such as 1900. You have options to display all years between the standard range and extended dates.

The options are:

minYear

Minimum year to display.

spanMinYearRange

When set to a value of false, displays all years between minYear and minRangeYear.

minRangeYear

Starting year for the standard range of years. The default is 1990.

maxRangeYear

Ending year for the standard range of years. The default is 2010.

spanYearRange

When the value is false, displays all years between maxRangeYear and maxYear.

maxYear

Maximum year to display.

Chapter 6. Workflow extensions

Workflow extensions provide a means to alter or extend workflow functions.

Policy enforcement extension

The policy enforcement extension assesses the accounts that are associated with a Person or BPPerson and enforces the policies in place for that person.

Overview

A policy enforcement extension is code that can be called directly from a workflow. Workflows that change a person object typically use this extension.

The extension is implemented in `com.ibm.itim.workflowextensions.PersonExtensions`.

The following extensions are provided:

- `enforcePolicyForPerson(Person, skipNonEntitledAccountsEvaluation)`
- `enforcePolicyForPerson(BPPerson, skipNonEntitledAccountsEvaluation)`

The extensions work identically on the specified Person or BPPerson.

`skipNonEntitledAccountsEvaluation` is a string, either true or false.

- If false, then all accounts applicable to the person are evaluated. All accounts that the person owns are considered when the extension enforces provisioning policies.
- If true, then policy enforcement proceeds as follows:
 1. Identify all services applicable for the person store them in a collection.
 2. Check for removed roles in the change list of the specified person.
 3. Merge the list of services that are identified in step 1 and step 2.

This process specifies that only accounts calculated from the person's role change are considered for policy enforcement. No other accounts are considered.

Therefore, some accounts are not considered: accounts where the person's role is removed, and accounts that are already provisioned for those roles.

For examples of how the extensions are used, see the Add, Modify, and Transfer operations in Operations management.

Recertification extensions

The recertification extensions track the recertification state in a workflow.

Overview

A recertification extension is code that can be called directly from a workflow. An extension defined for accounts also handles the recertification state for accesses, and uses `dataservices` to update attributes stored on the account object in data

services. These extension methods are integrated into the AccountExtensions class from the com.ibm.itim.workflowextensions package.

Because the recertification extensions provided are considered activities by the workflow engine, any failure in those extensions is returned as a failure when the activity completes. This result causes the recertification workflow to fail, and its failure is audited in the RECERTIFICATIONLOG audit table as well.

The following extensions are provided:

- recertificationMark
- recertificationMarkAccess
- recertificationSuspend
- recertificationCertify
- recertificationCertifyAccess
- recertificationAdminCertify
- recertificationAdminCertifyAccess

recertificationMark

The public ProcessResult recertificationMark(Account) extension updates erLastRecertificationAction for the target type, updating the erLastRecertificationAction attribute to:

```
com.ibm.itim.dataservices.model.domain.Account.REJECTED_MARK = 'REJECTED_MARK'
```

The recertification action is audited in RECERTIFICATIONLOG table for use by reports.

recertificationMarkAccess

The public ProcessResult recertificationMark(UserAccessAccount) extension has the same function for accesses as recertificationMark() has for users and accounts. It updates the erAccessLastRecertificationAction attribute specific to the UserAccess passed in to:

```
com.ibm.itim.dataservices.model.domain.Account.REJECTED_MARK = 'REJECTED_MARK'
```

The recertification action is audited in RECERTIFICATIONLOG table for use by reports.

Note: This method is for suspending accounts only. No method for suspending access is provided.

recertificationSuspend

The public ProcessResult recertificationSuspend(Account) extension updates erLastRecertificationAction for the account. It updates the erLastRecertificationAction attribute to:

```
com.ibm.itim.dataservices.model.domain.Account.REJECTED_SUSPEND = 'REJECTED_SUSPEND'
```

The recertification action is audited in RECERTIFICATIONLOG table for use by reports.

Note: This method is for suspending accounts only. No method for suspending access is provided.

recertificationCertify

The public `ProcessResult recertificationCertify(Account)` extension updates `erLastRecertificationAction` for the target type. It updates the `erLastRecertificationAction` attribute to:

```
com.ibm.itim.dataservices.model.domain.Account.CERTIFIED = 'CERTIFIED'
```

The recertification action is audited in `RECERTIFICATIONLOG` table for use by reports. This extension also updates the `erLastCertifiedDate` attribute with the current timestamp.

recertificationCertifyAccess

The public `ProcessResult recertificationCertify(UserAccessAccount)` extension updates `erLastAccessRecertificationAction` for the access. It updates the `erLastRecertificationAction` attribute for the specified `UserAccess` to:

```
com.ibm.itim.dataservices.model.domain.Account.CERTIFIED = 'CERTIFIED'
```

The recertification action is audited in `RECERTIFICATIONLOG` table for use by reports. This extension also updates the `erAccessLastCertifiedDate` attribute for the `accessAttribute` with the current timestamp.

Note: This method is the access version of `recertificationCertify` for users and accounts.

recertificationAdminCertify

The public `ProcessResult recertificationAdminCertify(Account)` extension updates `erLastRecertificationAction` for the target type. It updates the `erLastRecertificationAction` attribute to:

```
com.ibm.itim.dataservices.model.domain.Account.CERTIFIED_ADMIN = 'CERTIFIED_ADMIN'
```

The recertification action is audited in `RECERTIFICATIONLOG` table for use by reports. This extension also updates the `erLastCertifiedDate` attribute with the current timestamp.

recertificationAdminCertifyAccess

The public `ProcessResult recertificationAdminCertify(UserAccessAccount)` extension updates `erLastRecertificationAction` for the access. It updates the `erAccessLastRecertificationAction` attribute for the `UserAccess` passed in to:

```
com.ibm.itim.dataservices.model.domain.Account.CERTIFIED_ADMIN = 'CERTIFIED_ADMIN'
```

The recertification action is audited in `RECERTIFICATIONLOG` table for use by reports. This extension also updates the `erAccessLastCertifiedDate` attribute for the `accessAttribute` with the current timestamp.

Note: This method is the access version of `recertificationAdminCertify` for users and accounts.

Wait extension

The wait extension pauses the workflow until a specified time.

Overview

A wait extension is code that can be called directly from a workflow. It is implemented in the `WaitExtension` class in the `com.ibm.itim.workflowextensions` package.

The following extension is provided:

- `scheduleTimeout`

scheduleTimeout

The public `ProcessResult scheduleTimeout(Date)` extension suspends the workflow until the time specified by `Date`, which is the standard `Date` object in JavaScript. When the specified time is reached, the extension activity is complete and the workflow continues.

Embed the wait extension in a loop in the workflow if you want the workflow to check a condition and continue only when the condition is no longer met. The loop requires the following logic:

- Check the condition.
- Calculate the target date for the wait extension from the current date. Use JavaScript.
- Run the wait extension. Use the calculated target date for `scheduleTimeout(Date)`.

For more information about `Date`, see a JavaScript reference like the following: [JavaScript Date Reference](#). Another possible reference is the [ECMAScript\(r\) Language Specification](#), published by ECMA International, which now administers the standards that are the basis for JavaScript and other scripting languages.

Examples

- A workflow loop checks CPU load and continues only when CPU load falls below the desired level.
 1. Check CPU load.
 - If CPU load is below the desired threshold: Exit the loop.
 - If CPU load is above the desired threshold: Calculate the target `DATE` and then run the wait extension.
 2. When the wait extension is complete, loop to check CPU load again.
- Enforce dynamically calculated timeouts for long-running workflow activities. For example, implement an approval that is pending for *two working days*.
 1. Calculate the target `DATE`. Use JavaScript. The calculation needs to account for workflows that are triggered near a weekend. For example, consider the desired period of two working days. If the workflow is triggered on a Friday, the target date is Tuesday (four elapsed days). If the workflow is triggered on a Monday, then the target date is Wednesday (two elapsed days).
 2. Branch workflow execution that uses a fork type of `AND`. Put the approval on one branch and the wait extension with the target `DATE` on the other branch.
 3. Merge the two branches with a join type of `OR`.
The workflow continues when either branch is complete: an approval is submitted or the wait extension times out.

Chapter 7. REST APIs

You can develop custom applications by using the REST application programming interfaces (APIs) that come with the IBM Security Identity Manager. The REST APIs are available so that you can administer the tasks outside of the IBM Security Identity Manager user interface. The topic provides information about the functions that REST APIs support.

The REST APIs are segregated into a set of functional components of IBM Security Identity Manager that are listed in the following section.

Person Management

View or edit user profiles.

System User Management

Search capability for the IBM Security Identity Manager system users based on unique identifiers.

Password Management

Change or reset the password, and recover the forgotten password.

Access Management

Request, view, edit, or delete the access.

Activity Management

View and act on your activities.

Delegation Management

Delegate activities, view, edit, and delete the delegation schedule.

Generic Search APIs

Assorted set of search capabilities that are provided by the REST APIs.

In addition, IBM Security Identity Manager virtual appliance provides a set of APIs for the following administration or management tasks.

Widgets

View cluster status, server controls, statistics, notifications, middleware and server monitoring, and other information.

Analysis and Diagnostics Monitoring

Analysis and diagnostics tools such as memory statistics, CPU usage, performance metrics, service statistics, monitoring, and other aspects.

System Settings Management

Control of system settings such as host name, date or time, network settings, audit events, support files, snapshots, SNMP monitoring, licensing, firmware settings, fix packs, and other aspects.

Management and Application Interfaces Management

View and work on your management and application interfaces.

Hosts File management

Handle host names, IP addresses, and other services.

Download REST APIs

REST APIs are packaged in a compressed file. IBM Security Identity Manager 7.0.0.2 consists of two compressed files for you to use the REST APIs according to the requirements.

Download these two compressed files from <http://www.ibm.com/support/docview.wss?uid=swg27045716> for your requirements.

- REST_API_Doc.zip
- RAPI_DOCS.zip

Extract the compressed files to your local folder. For more information, view the `readme.html` file.

REST API code samples

The REST API code samples are annotated. The annotations provide information about how to use the samples in your test environment.

The REST API annotated code samples are available in the `html` directory of the `RAPI_DOCS.zip` file.

Do these steps to access the REST APIs:

1. Log on to the IBM Security Identity Manager virtual appliance console to open the **Appliance Dashboard**.
2. From the top-level menu of the **Appliance Dashboard**, select **Configure > Advanced Configuration > Custom File Management** to display the Custom File Management page.
3. Click the **All Files** tab.
4. Go to `directories/utilities`.
5. Select `RAPI_DOCS.zip` and click **Download**.
6. Extract the `RAPI_DOCS.zip` file.
7. Go to the `Virtual_Appliance_REST_API_Docs` directory.
8. Open the `index.html` file to view the REST API documentation.

Invoking REST APIs in a domain different from the originating web page

IBM Security Identity Manager REST APIs support cross-origin resource sharing (CORS). CORS describes a mechanism for supporting requests that a web page sends to a server that is not in the same domain as the originating web page. You can configure CORS to control which origins can work with the IBM Security Identity Manager REST APIs.

About this task

You can modify a list of trusted domains that can access Identity Service Center REST APIs. Complete the steps.

Procedure

1. From the top-level menu of the **Appliance Dashboard**, select **Configure > Advanced Configuration > Custom File Management**.
2. On the Custom File Management page, click the **All Files** tab.

3. Go to `directories/data`.
4. Select the `rest.properties` file to work with it. For more information, see [Managing the custom files](#).
5. From the top-level menu of the **Appliance Dashboard**, select **Configure > Advanced Configuration > Update Property**.
6. On the Update Property page, click the **All Properties** tab.
7. Click the **Identity server property files** tab.
8. Select the `rest.properties` file to work with it. For more information, see [Managing the server properties](#).
9. In the `ui.CORSOrigin` property, set the trusted domains. You can add multiple domains that are separated by white space.

Results

The domains that are listed in the `ui.CORSOrigin` property can only access the IBM Security Identity Manager REST APIs.

Filter configuration for REST search services

Use the following information to learn how the IBM Security Identity Manager REST search services create the search filter expression.

You can configure the filters and the HTTP request URL query parameters to control the data that the REST search services return.

Note:

To use a specific filter configuration for a request, the REST client can supply 'filterId' as a URL query parameter and its value must be the filter identifier that is configured in the `custom/rest/searchfilter.json` file. See "Examples" on page 28.

For more information about how to define the filter identifier, see [Defining the filter identifier for REST search service](#). The REST service uses the corresponding filter configuration in the following table to create the filter expression.

Table 1. Filters and their supported values

Filters	Description
"filterTemplate"	<p>A template string for the filter expression. For example,</p> <ul style="list-style-type: none"> • <code>"(&(&(date>=\${fromDate})(date<=\${toDate}))){filterExpression}"</code>. <i>fromDate</i> and <i>toDate</i> are the URL parameter names and their values are placed in the template. • <code>{filterExpression}</code> is replaced with the expression that is created with remaining URL parameters as described in the table. <p>Note: <code>filterTemplate</code> is an optional configuration for a filter. If the <code>filterTemplate</code> is not specified, then it is equivalent to <code>"filterTemplate": "{filterExpression}"</code>.</p>
"joinOperator"	An operator that is applied to join the logical expressions. Supported values are <code>&</code> and <code> </code> .
"multivalueJoinOperator"	An operator that is applied to join the logical expressions that are created for the multiple value URL parameters. Supported values are <code>&</code> and <code> </code> .
"comparisonOperator"	An operator that is applied for an attribute and its value comparison. Supported values are <code>=</code> , <code>!=</code> , <code>~=</code> , <code>>=</code> , <code><=</code> , <code>></code> , <code><</code> .

Table 1. Filters and their supported values (continued)

Filters	Description
"baseFilter"	<p>You can substitute attributes of the current Identity Service Center account or the owner of the account into the base search filter. These attributes are used when the filter is evaluated. The notation <code>\$(xxxx)</code> is used to specify where the substitution is made, and <code>xxxx</code> specifies what attribute value is to be substituted. The special string systemUser represents the user account of the current Identity Service Center user. You can qualify systemUser to specify an account attribute, such as <code>\$(systemUser.eruid)</code>. You can also reference attributes of the owner of the account, such as <code>\$(systemUser.owner.cn)</code>. Only attributes of the current account or the owner of the account can be used as substitutions into the base search filter. If a substitution cannot be evaluated or is evaluated to an empty string, a substitution value of <code>_undefined_</code> is used instead.</p> <p>For example, <code>"baseFilter": "(!uid=\$(systemUser.owner.uid))"</code></p>
"allowWildcard"	<p>Specifies whether to use <code>*</code> as wildcard in the final filter expression or escape it. Supported values are true and false.</p>

Rules that apply to populate the filterTemplate

- If a parameter in the template is not supplied as URL query parameter in the HTTP request, it is removed from the expression. For example,
 The filterTemplate is `"(&(cn=xyz)(sn=${sn}))"` and
 the request URL is `"/rest/people"`
 The resultant expression is `(cn=xyz)`.
- String `$(filterExpression)` in the filterTemplate is replaced by the filter expression that is created by using the filter configuration and URL parameters that are not provided in the filter template. For example,
 The filterTemplate is `"(&(cn=xyz)(sn=${sn})$(filterExpression))"` and
 the request URL is `"/rest/people?sn=abc&email=pqr@site.com"`
 The resultant expression is `(&(cn=xyz)(sn=abc)(email=pqr@site.com))`. In this example, `sn`, `email` are two URL query parameters but `email` is used to create `$(filterExpression)` because `sn` is already used in the template.

Conditions in the filterExpression for joinOperator, multivalueJoinOperator, comparisonOperator, allowWildcard

- If a URL parameter contains multiple values, then the template expression for that parameter is constructed by using `multivalueJoinOperator`.
 The filterTemplate is `"(&(cn=pqr)(sn=${sn}))"` and
 the request url is `"/rest/people?sn=abc&sn=xyz"` and
 the `multivalueJoinOperator` is `|`
 The resultant expression is `(&(cn=pqr)(|(sn=abc)(sn=xyz)))`.
- If a URL parameter contains single value, then that value is placed in the template.
 The filterTemplate is `(&(cn=abc)(sn=${sn}))"` and
 the request url is `"/rest/people?sn=xyz"`
 The resultant expression is `(&(cn=abc)(sn=xyz))`.

Examples

Example 1 - Person search without using the filter identifier

The PERSON_SEARCH is the REST service endpoint key for the person search capability. You must set a value for the PERSON_SEARCH that you can use as a filter identifier for person search capability when you create a request URL. You might not know the REST service endpoint keys for all the supported functions. You can use the dictionary service to know about all the supported REST service endpoint keys. Access <http://hostname:port/itim/rest/dictionary> to find the REST service endpoint keys.

You want to search for a person. Example 1 explains how to use the REST service, without providing any explicit filter identifier. Complete the following steps:

1. Set the value for the PERSON_SEARCH in the `itim/data/rest.properties` file. For example, `PERSON_SEARCH=customPersonSearch`.
2. Define the `customPersonSearch` filter in the `custom/rest/searchfilter.json` file. For example,

```
"customPersonSearch": {
  "joinOperator": "&",
  "multivalueJoinOperator": "|",
  "comparisonOperator": "=",
  "baseFilter": "(!(uid=${systemUser.owner.uid}))",
  "allowWildcard": "false"
}
```

If the request URL is:

```
/itim/rest/people?cn=abc&sn=pqr&sn=xyz*
```

and you log in as a user *user1*

Then, the filter expression is:

```
(&(&(cn=abc)(| (sn=pqr) (sn=xyz\2a)))(!(uid=user1))
```

Example 2 - Request search by using the filter identifier

You want to search for the requests. Example 2 explains how to use the REST service with the filter identifier. Complete the following steps.

1. Assume that the filter identifier `requestSearch` is already defined for the request search REST service endpoint key.
2. Define the `requestSearch` filter in the `custom/rest/searchfilter.json` file. For example,

```
"requestSearch": {
  "filterTemplate":
    "(&(&(date>=${fromDate})(date<=${toDate}))){filterExpression}",
  "comparisonOperator": "=",
  "joinOperator": "|",
  "multivalueJoinOperator": "|",
  "allowWildcard": "true"
}
```

If the request URL is:

```
/itim/rest/requests/quicksearches?filterId=requestSearch&fromDate=1425061800000
&toDate=1427826513600&accessName=*finance*&justification=*payroll*&limit=5
```

Then, the filter expression is:

```
(&(&(date>=1425061800000)(date<=1427826513600))(|(justification=*payroll*)(accessName=*finance*)))
```

Chapter 8. Dynamic tags in mail templates

IBM Security Identity Manager mail templates allow dynamic retrieval, substitution, and decision making in creating a message.

Dynamic content tags and examples

Security Identity Manager provides dynamic content tags to allow text substitution and enable translation. The tags are used for the emails that are generated by these tasks:

- Designing workflows
- Specifying mail activity
- Manual service notification
- Recertification notification
- Post office
- Reminder template
- Default system notifications
- Delegation notifications

These tags are associated with dynamic content:

JavaScript code

Handles JavaScript and runs the JavaScript content that is contained between the open and close tags. This tag contains child tags unless they return a string. JavaScript code is called in `<JS>MyJavaScriptCode</JS>` delimiters.

Table 2. Syntax and example of using JavaScript code to replace message content.

Syntax	Example
<code><JS>text or JavaScript tag</JS></code>	Enter each <code><JS></JS></code> statement as a single line: An account request has been initiated for <code><JS>process.requesteeName;</JS></code> <code><JS>if (var x=process.getParent() !=null)</code> return x <code></JS></code>
<code><JS escapeentities="false">text or JavaScript tag</JS></code>	When specified as "false", any text that is returned by the JavaScript execution does not have its HTML entity tags escaped. For instance, the <code><</code> character does not return as <code>&lt;</code> . This option might be useful when the execution of the JavaScript code returns XML. For example, embedding XHTML body notifications inside the XHTML body of the post office template. The default for this attribute is "true", so not specifying the tag escapes the characters.

Table 2. Syntax and example of using JavaScript code to replace message content. (continued)

Syntax	Example
<JS removexhtmlheader="false">text or JavaScript tag</JS>	<p>If removexhtmlheader="true" is in the JS tag, any text that is returned from the JavaScript does not have the DTD statement in the XHTML content. The text that is returned from the JavaScript has the DTD statement in the XHTML content when either of the following conditions exist:</p> <ul style="list-style-type: none"> • removexhtmlheader="false". • It is not placed in the JS tag. <p>The default value of this attribute is false. Not specifying the flag in the tag puts the DTD statement in the XHTML content.</p>

Replace tag

Formats the message that is represented by the key to allow string replacement. The formatted string can have zero or more parameters. Parameters can contain strings, activity IDs, or JavaScript. The string inside the key must exist in the CustomLabels.properties file. Strings are sourced from a CustomLabels.properties resource bundle file or from the Labels.properties file.

The key of the string replacement can be specified with the key attribute or by adding a **KEY** tag between **RE** tags. Specifying a key that uses both the attribute and tag at the same time results in an exception.

The tag has these parameters:

Key Represents the resource bundle key for a **RE** tag. For example:

```
<RE key="key">
</RE>
```

PARAM Represents the parameters for a **RE** tag. For example:

```
<RE key="key">
<PARAM>with plain text</PARAM>
</RE>
```

Table 3. Syntax and examples of using a RE tag to replace message content.

Syntax	Example
<pre><RE key="message key"> <PARAM>text or JavaScript tag</PARAM> </RE></pre> <p>or enter each <KEY></KEY> statement as a single line:</p> <pre><RE><KEY>message key or JavaScript tag to return a key </KEY> <PARAM>text or JavaScript tag</PARAM> </RE></pre> <p>The KEY can be specified by either an attribute on the RE tag, or as a subelement of the RE tag by using the tag KEY.</p>	<pre><RE key="message key"> <PARAM>with plain text</PARAM> <PARAM><JS>process.requesteeName; </JS></PARAM></RE></pre> <p>Output:</p> <p>This is a formatted string replacement example with plain text and JavaScript code for requestee name John Smith.</p>

Table 3. Syntax and examples of using a RE tag to replace message content. (continued)

Syntax	Example
<p>To enable string replacement for translation, specify a custom label in a CustomLabels.properties file to overwrite a Labels.properties key.</p> <p>For example, the Labels.properties file contains this key/value pair. readOnlyDateFormat=MMM dd, yyy hh:mm:ss z</p> <p>To override this format, add the same key to the CustomLabels.properties file.</p>	<pre><RE key="readOnlyDateFormat"> <PARM><JS>if (process.scheduled !=null) return process.scheduled.getTime(); else return "";</JS></PARM></RE></pre> <p>Output: Apr 18, 2005 05:20:52 EDT</p>

Non-compliant message tag

Represents a message that describes the noncompliant attributes of an account. For example:

```
<CAMessage/>
```

Dynamic content message tags

Tags are delimited in <TAG/> syntax, such as the following examples:

Table 4. Syntax and example of using tags to replace message content.

Syntax	Example
<TagName/>	<pre><CAMessage/></pre> <p>Returns a string that describes the non-compliant attributes of an account.</p>
	<pre><ManualServiceAddAccount/></pre> <p>Returns a string that contains the text body for manual service email notification.</p>
	<pre><rfiActivityHasBeenSubmitted/></pre> <p>Returns a string that contains the text body of an RFI activity that was submitted in an account request workflow.</p>

ID tag Represents the activity ID in the form: Process.ActivityId. For example:

```
<ID/>
```

ITIMURL tag

Based on group membership of the person. It represents the URL of the IBM Security Identity Manager Server. A forced URL can be applied by using the forcedurl attribute of the tag. This attribute contains constant values such as the value console, enduser, or ISC.

Table 5. Syntax and examples of ITIMURL.

Syntax	Example
<ITIMURL/>	Based on group membership of the person. It represents the URL of the IBM Security Identity Manager Server.

Table 5. Syntax and examples of ITIMURL. (continued)

Syntax	Example
<ITIMURL forcedurl="enduser"/>	Represents the URL of the graphical user interface on the IBM Security Identity Manager Server. If the forcedurl attribute is used, the URL is not generated based on the group membership of the person. These values are associated with this attribute:
<ITIMURL forcedurl="console"/>	
<ITIMURL forcedurl="servicecenter"/>	
	<p>enduser The URL points at the self-service graphical user interface.</p> <p>console The URL points at the administrator graphical user interface.</p> <p>servicecenter The URL points at the service center graphical user interface.</p>

Properties file values

To change templates, you can add a property in the CustomLabels.properties file or create your own properties and values by using the Update Property page from the **Appliance Dashboard** of the IBM Security Identity Manager virtual appliance console. See Managing the server properties.

Required escape characters and JavaScript

The following characters must be escaped by using the appropriate HTML entity form that has the format *&entity;*. This action ensures that the notification template XML is well-formed.

Table 6. Escape characters

Escape character	Character
<	Less Than (<)
>	Greater Than (>)
"e;	Quotation ("")
'	Apostrophe ('')
&	Ampersand (&)

For example, to use the following JavaScript

```
if (i<4) return "less than four";
```

the dynamic content tag is

```
<JS> if (i&lt;4) return &quote;less than four&quote;;</JS>
```

Common formatting patterns in the XHTML body

Default messages are formatted with a common pattern in the XHTML body and also contain message-unique statements.

For example, the XHTML for the to-do reminder template calls a common style sheet (the `imperatives.css` file) and logos. Message-unique statements are similar to the following ones:

```
<!-- Start of notification body -->
    <textBody/>
        <RE key="escalation_note"/> <escalationTime/>
    </td>
</tr>
<!-- End of notification body -->
```

The following example shows a complete set of statements in an XHTML body:

```
<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE html
    PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN"
    "http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">
<html xmlns="http://www.w3.org/1999/xhtml" xml:lang="en" lang="en">
<head>
<title>${TITLE}</title>
<meta content="text/html; charset=UTF-8" http-equiv="Content-Type" />
<link type="text/css" title="Styles" rel="stylesheet"
    href="${BASE_URL/console/css/imperative.css}" />
</head>

<!-- Put Next statement on one line -->

<body topmargin="0" marginheight="0" leftmargin="0" marginwidth="0"
    bgcolor="ffffff">

<!-- Block for the Template Header part -->
<table width="100%" border="0" cellpadding="0" cellspacing="0">
    <tbody>
        <tr>
            <!-- Security logo -->
            <td width="186" background="${BASE_URL/console/html/images/mid-part-1.gif}"
                </td>
            <!-- Middle part -->
            <td background="${BASE_URL/console/html/images/mid-part-1.gif" width="692"></td>
            <!-- IBM logo -->
            <td background="${BASE_URL/console/html/images/ibm_banner.gif" width="96"></td>
        </tr>
    </tbody>
</table>

<!-- Title Bar -->
<table width="100%" border="0" cellpadding="0" cellspacing="0">
    <tbody>

        <tr>
            <td background="${BASE_URL/console/html/images/titlebar_middle.gif"
                height="23" width="8">
                </td>
            <!-- ISIM Notification Lable -->
            <td background="${BASE_URL/console/html/images/titlebar_middle.gif"
                height="23" classpath="portfolio-header" width="979">${TITLE}</td>
            <td background="${BASE_URL/console/html/images/titlebar_middle.gif"
                height="23" width="5"></td>
        </tr>
    </tbody>
</table>

<table width="100%" border="0" cellpadding="0" cellspacing="0">
    <tbody>
```

```

<tr>
  <!-- Background for the template body -->
  <td background="$BASE_URL/console/html/images/portfolio_background.gif"
    height="148">
    <table border="0" cellspacing="0" cellpadding="0" width="100%">
      <tr>
        <td align="left" class="text-description" height="65">
          <!-- Start of notification body -->
          <textBody/>
          <RE key="escalation_note"/> <escalationTime/>
        </td>
      </tr>
    </table>
    <!-- End of notification body -->
  </td>
</tr>
</tbody>
</table>
<!-- Copy Right Table -->
<table width="100%" border="0" cellpadding="0" cellspacing="0">
  <tbody>
    <tr bgcolor="#9d9d9d" align="center" valign="middle">
      <td class="text-description"><span class="cont1" id="W57ea57ea"><span
        class="txt" id="text">IBM Copyright 2007</span></span></td>
    </tr>
  </tbody>
</table>
</body>
</html>

```

Mail templates

You define mail templates to deliver customized message notifications. The templates use several customization functions.

Templates have these main parts:

Subject

Describes an activity to a recipient of the notification. The subject can consist of plain text and dynamic content tags. If no subject is specified for manual service activities, no email is sent.

Text body

Describes the outcome of an activity, such as an account approval. The content can consist of plain text, dynamic content tags, and JavaScript code.

XHTML body

Provides the content of the email as an HTML message.

Dynamic content can include dynamic content message tags, JavaScript code, and tags that replace variables with other values or reference a property that allows translation with the `CustomLabels.properties` file.

Manual service default messages

IBM Security Identity Manager provides default notification templates for messages that participants that are service owners receive when changes occur to accounts or passwords for manual services that they own.

Default notification templates

IBM Security Identity Manager provides these default notification templates:

<ManualServiceAddAccount/>

Provides default text sent to a participant when an account is added for the user of a manual service.

<ManualServiceModifyAccount/>

Provides default text sent to a participant when an account is modified for the user of a manual service.

<ManualServiceDeleteAccount/>

Provides default text sent to a participant when an account is deleted for the user of a manual service.

<ManualServiceRestoreAccount/>

Provides default text sent to a participant when an account is restored for the user of a manual service.

<ManualServiceSuspendAccount/>

Provides default text sent to a participant when an account is suspended for the user of a manual service.

<ManualServiceChangePassword/>

Provides default text sent to a participant when a password change occurs for the user of a manual service.

Properties used for translation

If the properties exist in the CustomLabels.properties file, their value is used. Otherwise, the values of the properties in Labels.properties file are used. These properties contain the translated versions of the messages (with parameter substitution) that make up the dynamic tags. Change their values in the CustomLabels.properties file if you want different text. Do not change the defaults in the Labels.properties file.

The properties include these items:

```

manualServiceWorkOrderAddOperationMessage
manualServiceAttributeName
manualServiceAttributeValue
manualServiceAttributeAction
manualServiceAddAction
manualServiceRemoveAction
manualServiceReplaceAction
manualServiceWorkOrderChangePwdOperationMessage
manualServiceWorkOrderPwdValueMessage
manualServiceWorkOrderDeleteOperationMessage
manualServiceWorkOrderModifyOperationMessage
manualServiceWorkOrderRestoreOperationMessage
manualServiceWorkOrderSuspendOperationMessage
manualServiceUnknownPerson

```

Notification script example

A default notification script for a manual service provides a message that is sent to a participant. For example, the ManualServiceAddAccount notification output is similar to this example:

```

Attribute Name: Attribute Value
myattr: TT
Password: secret
Owner: Auditor
User ID: auditor1

```

Description: manual service operation
Requestee: Auditor
Subject: auditor1
Request Initiated: Jun 28, 2007 05:11:05 IST

Requested by process:
Process Name: Account Add
Description: Account Add Process
Requester: System Administrator
Requestee: Auditor
Subject: auditor1

Output example

The `<ManualServiceAddAccount/>` template provides a message that uses some of the values in the `Labels.properties` file:

```
manualServiceWorkOrderAddOperationMessage  
manualServiceAttributeName : manualServiceAttributeValue  
{insert real attribute names here} : {insert real attribute values here}
```

The `<ManualServiceModifyAccount/>` tag generates:

```
manualServiceWorkOrderModifyOperationMessage  
{Place the following attributes on one line:}  
manualServiceAttributeName : manualServiceAttributeValue  
    : manualServiceAttributeAction  
{insert real attribute names here} : {insert real attribute values here} :  
{depending on what needs to be done, one of the following: }  
{Place the following attributes on one line:}  
{manualServiceAddAction,manualServiceReplaceAction,  
    manualServiceRemoveAction}
```

Recertification default messages

IBM Security Identity Manager provides default message templates for recertification messages.

Default recertification templates

IBM Security Identity Manager provides default message templates for recertification messages. You cannot change the following templates:

Suspend Account

Provides default text that requests a participant to recertify use of an account. Declining the request suspends the account.

For example, the participant receives this message:

```
Recertification required for account myaccount on service shortword-linux
```

```
You have received a recertificaton request for account myaccount on service  
shortword-linux owned by firstname lastname.
```

```
Rejection of this recertification request will result in the suspension of  
account myaccount on shortword-linux.
```

```
Activity:Recertification of Account/Access  
Date submitted:Apr 26, 2007 10:34:51 IST  
Request type:Recertification  
Requested for:firstname lastname  
Requested by:SYSTEM
```


Access/Account:myaccount
Description:

Due date:Apr 27, 2007 10:34:57 IST

Delete Account

Provides default text that requests a participant to recertify use of an account. Declining the request deletes the account.

For example, the participant receives this message:

Recertification required for account myaccount on service shortword-linux

You have received a recertificaton request for account myaccount on service shortword-linux owned by firstname lastname.

Rejection of this recertification request will result in the deletion of account myaccount on shortword-linux.

Activity:Recertification of Account/Access
Date submitted:Apr 26, 2007 10:34:51 IST
Request type:Recertification
Requested for:firstname lastname
Requested by:SYSTEM
Access/Account:myaccount
Description:
Due date:Apr 27, 2007 10:34:57 IST

Mark Account

Provides default text that is sent to a participant to recertify use of an account. Declining the request marks the account for a subsequent action on the account.

For example, the participant receives this message:

Recertification required for account myaccount on service shortword-linux.

You have received a recertificaton request for account myaccount on service shortword-linux owned by firstname lastname.

Rejection of this recertification request will result in account myaccount on shortword-linux being marked as rejected for recertification.

Activity:Recertification of Account/Access
Date submitted:Apr 26, 2007 10:34:51 IST
Request type:Recertification
Requested for:firstname lastname
Requested by:SYSTEM
Access/Account:myaccount
Description:
Due date:Apr 27, 2007 10:34:57 IST

Mark Access

Provides default text that is sent to a participant to recertify use of an account on an access. Declining the request marks the access for a subsequent action on the account.

For example, the participant receives this message:

Recertification required for account myaccount on access myaccess.

You have received a recertificaton request for account myaccount on access myaccess owned by firstname lastname.

Rejection of this recertification request will result in access myaccess being marked as rejected for recertification.

Activity:
Date submitted:Apr 26, 2007 10:34:51 IST /* Need to fill this data */
Request type:
Requested for:
Requested by:
Access/Account:
Description:
Due date:Apr 27, 2007 10:34:57 IST

Delete Access

Provides default text that requests a participant to recertify use of an account on an access. Declining the request deletes the account on the access.

For example, the participant receives this message:

Recertification required for account myaccount on access myaccess.

You have received a recertificaton request for account myaccount on access myaccess owned by firstname lastname.

Rejection of this recertification request will result in the deletion of access myaccess.

Activity:
Date submitted:Apr 26, 2007 10:34:51 IST /* Need to fill this data */
Request type:
Requested for:
Requested by:
Access/Account:
Description:
Due date:Apr 27, 2007 10:34:57 IST

Account Suspended

Provides default text that is sent to a participant, confirming suspension of an account, after a participant declines a recertification request.

For example, the participant receives this message:

Account myaccount on service shortword-linux has been suspended due to rejection of a recertification request

The account myaccount on service shortword-linux owned by firstname lastname has been suspended due to rejection of a recertification request.

Activity:Recertification of Account/Access
Date submitted:Apr 26, 2007 10:34:51 IST
Request type:Recertification
Requested for:firstname lastname
Requested by:SYSTEM
Access/Account:myaccount
Description:

Account Deleted

Provides default text that is sent to a participant, confirming deletion of an account, after a participant declines a recertification request.

For example, the participant receives this message:

Account myaccount on service shortword-linux has been deleted due to rejection of a recertification request

The account myaccount on service shortword-linux owned by firstname lastname has been deleted due to rejection of a recertification request.

Activity:Recertification of Account/Access
Date submitted:Apr 26, 2007 10:34:51 IST

Request type:Recertification
Requested for:firstname lastname
Requested by:SYSTEM
Access/Account:myaccount
Description:
Due date:Apr 27, 2007 10:34:57 IST

Account Marked

Provides default text that is sent to a participant, confirming that an account is marked for suspension, after a participant declines a recertification request.

For example, the participant receives this message:

Account myaccount on service shrotword-linux has been marked as rejected for recertification due to rejection of a recertification request

The account myaccount on service shortword-linux owned by firstname lastname has been marked as rejected for recertification due to rejection of a recertification request.

Activity:Recertification of Account/Access
Date submitted:Apr 26, 2007 10:34:51 IST
Request type:Recertification
Requested for:firstname lastname
Requested by:SYSTEM
Access/Account:myaccount
Description:
Due date:Apr 27, 2007 10:34:57 IS

Access Marked

Provides default text that is sent to a participant. It confirms that an account on an access is marked for subsequent action after a participant declines a recertification request.

The template contains these statements:

Account myaccount on access myaccess has been deleted due to rejection of a recertification request.

The account myaccount on access myaccess owned by firstname lastname has been marked as rejected for recertification due to rejection of a recertification request.

Activity:
Date submitted:Apr 26, 2007 10:34:51 IST
Request type:
Requested for:
Requested by:
Access/Account:
Description:
Due date:Apr 27, 2007 10:34:57 IST

Access Removed

Provides default text that is sent to a participant, confirming deletion of an account on an access, after a participant declines a recertification request.

For example, the participant receives this message:

Account myaccount on access myaccess has been deleted due to rejection of a recertification request.

The account myaccount on access myaccess owned by firsnme lastname has been deleted due to rejection of a recertification request.

Activity:
Date submitted:Apr 26, 2007 10:34:51 IST
Request type:
Requested for:

Requested by:
Access/Account:
Description:
Due date: Apr 27, 2007 10:34:57 IST

User Recertification Pending

Provides default text that is sent to a participant, confirming that a user recertification is pending, after a recertification request is initiated.

For example, the participant receives this message:

You have received a recertification request for user `firstname lastname`. The recertification includes their membership in `X` role(s) and ownership of `Y` account(s). Please indicate whether the user still requires these resources:

The account `myaccount` on access `myaccess` owned by `firstname lastname` has been deleted due to rejection of a recertification request.

Activity: Recertification of Account/Access/User
Date submitted: Sep 08, 2008 04:10:32 EDT
Request type: Recertification
Requested for: `firstname lastname`
Requested by: System
Due date: Sep 18, 2008 04:10:34 EDT

User Recertification Rejected

Provides default text that is sent to a participant, confirming that one or more resources were declined in a user recertification request.

For example, the participant receives this message:

One or more resources for user `firstname lastname` have been rejected during recertification.

The account `myaccount` on access `myaccess` owned by `firstname lastname` has been deleted due to rejection of a recertification request.

Activity: Recertification of Account/Access/User
Date submitted: Sep 08, 2008 06:30:07 EDT
Request type: Recertification
Requested for: `firstname lastname`
Requested by: System

The following roles were rejected:
`rolename`

The following accounts were rejected, along with all groups associated with the accounts:
Account `"uid"` on service `"servicename"`

The following groups were rejected, but the account was accepted:
Group `"groupname"` for account `"uid"` on service `"servicename"`

Properties file values

To change templates, you can use all of the `key=value` statements in the `CustomLabels.properties` file, or create your own properties and values. Use the Update Property page from the **Appliance Dashboard** of the IBM Security Identity Manager virtual appliance console. See *Managing the server properties*.

The properties include these items on one line:

```
recertOn={0} on {1}
recertTemplateSubject=Recertification required
for account {0} on service {1}
recertTemplateAccessSubject=Recertification required
```

for account {0} on access {1}
 recertTemplateBody=You have received a recertificaton request
 for account {0} on service {1} owned by {2}.
 recertTemplateAccessBody=You have received a recertificaton request
 for account {0} on access {1} owned by {2}.
 recertDeclineSuspendsBody=Rejection of this recertification request
 will result in the suspension of account {0} on {1}.
 recertDeclineDeletesBody=Rejection of this recertification request
 will result in the deletion of account {0} on {1}.
 recertDeclineMarksBody=Rejection of this recertification request
 will result in account {0} on {1} being marked as rejected for recertification.
 recertDeclineDeletesAccessBody=Rejection of this recertification request
 will result in the deletion of access {0}.
 recertDeclineMarksAccessBody=Rejection of this recertification request
 will result in access {0} being marked as rejected for recertification.
 recertDeclinedAcctSuspendedSubj=Account {0} on service {1} has
 been suspended due to rejection of a recertification request
 recertDeclinedAcctDeletedSubj=Account {0} on service {1} has
 been deleted due to rejection of a recertification request
 recertDeclinedAcctMarkedSubj=Account {0} on service {1} has
 been marked as rejected for recertification due to rejection
 of a recertification request
 recertDeclinedAccessDeletedSubj=Account {0} on access {1} has
 been deleted due to rejection of a recertification request
 recertDeclinedAccessMarkedSubj=Account {0} on access {1} has
 been marked as rejected for recertification due to rejection
 of a recertification request
 recertDeclinedAcctSuspendedBody=The account {0} on
 service {1} owned by {2} has been suspended due to rejection
 of a recertification request.
 recertDeclinedAcctDeletedBody=The account {0} on service {1}
 owned by {2} has been deleted due to rejection of a recertification request.
 recertDeclinedAcctMarkedBody=The account {0} on service {1}
 owned by {2} has been marked as rejected for recertification
 due to rejection of a recertification request.
 recertDeclinedAccessDeletedBody=The account {0} on access {1}
 owned by {2} has been deleted due to rejection of a recertification request.
 recertDeclinedAccessMarkedBody=The account {0} on access {1}
 owned by {2} has been marked as rejected for recertification
 due to rejection of a recertification request.
 userRecertTemplateSubject=Recertification required for user {0}
 userRecertTemplateBody=You have received a recertificaton request
 for user {0}. The recertification includes their membership in {1} role(s)
 and ownership of {2} account(s). Please indicate whether the user still
 requires these resources.
 userRecertDeclinedSubj=Recertification request rejected for user {0}
 userRecertDeclinedBody=One or more resources for user {0} have been
 rejected during recertification.
 userRecertRolesRejectedLabel=The following roles were rejected:
 userRecertAccountsRejectedLabel=The following accounts were rejected,
 along with all groups associated with the accounts:
 userRecertGroupsRejectedLabel=The following groups were rejected,
 but the account was accepted:
 userRecertAcctLabel=Account "{0}" on service "{1}"
 userRecertGroupLabel=Group "{0}" for account "{1}" on service "{2}"

Recertification template key definitions

Recertification templates use the following key definitions:

name=Activity
 timeScheduled=Date submitted
 recertRequestType=Request type
 recertRequestedFor=Requested for
 recertRequestedBy=Requested by
 recertAccountAccess=Access/Account

```
recertDueDate=Due date
recertRequestTypeName=Recertification
readOnlyDateFormat=MMM dd, yyyy hh:mm:ss z
```

Workflow default messages

IBM Security Identity Manager provides default workflow messages.

Default workflow templates

All the workflow notice templates can be customized. IBM Security Identity Manager provides these default workflow notice templates:

Activity Timeout Template

Provides information that the workflow activity is timed out and terminated. By default, this template is enabled.

For example, the template provides this message:

```
Workflow activity is being timed out and will be terminated
by the workflow system.
```

```
The following activity has timed out.The activity will be terminated
by the workflow system and the result set to Terminated.
```

Activity Information

```
View Changes: http://localhost:9090/itim/console
Activity ID: ADAapproval
Activity: AD Account Approval
Time Started: Jun 09, 2007 12:28:45 IST
Time Completed:
Result Summary: Escalated
State: Running
Activity Type: Manual Approval/Reject
```

Process Information

```
Process ID: 1099575082113388748
Activity: Default AD Account Approval Workflow
Description:
State:Running
Date submitted: Jun 09, 2007 12:23:41 IST
Time Completed:
Result Summary:
Requester: 1099572462907357646
Requestee: firstname lastname
Subject:
Comment:
Detail:
```

The subject statement is:

```
<RE key="activity_timeout_subject" />
```

The plain text is:

```
<RE key="activity_timeout_message" />
```

```
<RE key="activity_timeout_detail" />
```

```
<RE key="activityInformation" />
<ITIMURL/>
<RE key="activityID"/>: <JS>activity.id;</JS>
<RE key="name"/>: <JS>activity.name;</JS>
<RE key="timeStarted"/>: <RE key="readOnlyDateFormat"><PARM>
<JS>if (activity.started != null)
return activity.started.getTime();
else return '';</JS></PARM></RE>
<RE key="timeCompleted"/>: <RE key="readOnlyDateFormat"><PARM>
<JS>if (activity.completed != null)
return activity.completed.getTime();
else return '';</JS></PARM></RE>
```

```

<RE key="resultSummary"/>: <RE><KEY>
<JS>process.STATE_PREFIX + activity.resultSummary;
</JS></KEY></RE>
<RE key="state"/>: <RE><KEY><JS>process.STATE_PREFIX+activity.state;
</JS></KEY></RE>
<RE key="activityType"/>: <RE><KEY>
<JS>activity.TYPE_PREFIX + activity.type;</JS>
</KEY></RE>
<RE><KEY><JS>activity.TYPE_PREFIX + activity.subtype;</JS></KEY></RE>

<RE key="processInformation" />

<RE key="processID"/>: <JS>process.id;</JS>
<RE key="name"/>: <RE><KEY><JS>process.name;</JS></KEY></RE>
<RE key="description"/>: <RE><KEY>
<JS>process.description;</JS></KEY></RE>
<RE key="state"/>: <RE><KEY><JS>process.STATE_PREFIX + process.state;
</JS></KEY></RE>
<RE key="timeScheduled"/>: <RE key="readOnlyDateFormat"><PARM>
<JS>if (process.scheduled != null) return process.scheduled.getTime();
else return '';</JS></PARM></RE>
<RE key="timeCompleted"/>: <RE key="readOnlyDateFormat"><PARM>
<JS>if (process.completed != null) return process.completed.getTime();
else return '';</JS></PARM></RE>
<RE key="resultSummary"/>: <RE><KEY>
<JS>process.STATE_PREFIX + process.resultSummary;
</JS></KEY></RE>
<RE key="requester"/>: <JS>process.requestorName;</JS>
<RE key="requestedFor"/>: <JS>process.requesteeName;</JS>
<RE key="subject"/>: <JS>process.subject;</JS>
<RE key="comment"/>: <JS>process.comment;</JS>
<RE key="detail"/>: <JS>process.resultDetail;</JS>

```

Change Account Template

Provides information that the workflow activity has modified account information. By default, this template is disabled.

For example, the template provides this message:

Modified Account Information from IBM Security Identity Manager

The following ITIM Service [ITIM] account has been modified:

```

View Changes: http://localhost:9090/itim/console
Process Reference: 875016861865594505
Account ID: myaccount
Owner Name: firstname lastname
Time Completed: Jun 08, 2007 09:52:24 IST

```

The subject statement is:

```
<RE key="change_account_subject"/>
```

The plain text is:

```

<RE key="account_changed"><PARM>
<RE key="service_name_with_profile_name"><PARM>
<JS>EmailContext.getAccountServiceName();</JS></PARM>
<PARM><RE><KEY><JS>EmailContext.getAccountServiceProfileName();
</JS></KEY></RE></PARM></RE></PARM></RE>
<ITIMURL/>
<RE key="processRef"/>: <JS>process.id;</JS>
<JS>if (EmailContext.getTransactionId() != '0')
{ '<RE key="TRANSACTION_ID_LABEL"/>: ' + EmailContext.getTransactionId(); }
</JS>
<RE key="accountID"/>: <JS>EmailContext.getAccountUserId();</JS>
<RE key="accountOwnerName"/>: <JS>EmailContext.getAccountOwnerName();</JS>
<RE key="timeCompleted"/>: <RE key="readOnlyDateFormat"><PARM>
<JS>(new Date()).getTime();</JS></PARM></RE>
<JS>if (EmailContext.hasNewAccess()) { '<RE key="accountNewAccess"/>:
<JS>EmailContext.getAccountNewAccessAsString();</JS>\n'; }</JS>
<JS>if (EmailContext.hasRemovedAccess()) { '<RE key="accountRemovedAccess"/>:
<JS>EmailContext.getAccountRemovedAccessAsString();</JS>\n'; }</JS>
<JS>if (EmailContext.getTransactionId() != '0')
{ '<RE key="RETRIEVE_PASSWORD_TITLE"/>: ' +
EmailContext.getPasswordRetrievalUrl(); }
</JS>

```

```

<JS>if (EmailContext.getTransactionId() != '0')
{ <RE key="passwordExpireLabel"/>:
<JS>if (EmailContext.getPasswordExpirePeriod() == 0)
{ <RE key="passwordneverexpire"/>; }
else { EmailContext.getPasswordExpirePeriod(); }</JS>; }</JS>
<JS>if (EmailContext.getTransactionId() != '0')
{ <JS>if (EmailContext.getPasswordExpirePeriod() == 0)
{ <RE key="additionalMsgForPwdRetrieval"/>; }</JS>; }</JS>

```

Compliance Template

Provides information that an account is not compliant with a provisioning policy. By default, this template is enabled.

For example, the template provides this message:

```

Compliance Alert for winlocal
Account [helpdesk35] is not compliant with the provisioning policy.
The value [Performance Log Users] of attribute [Local Groups]
should be [removed].
View Changes: http://99.99.999.99:80/itim/console

```

The subject statement is:

```

<RE key="compliance_alert_subject" >
<PARAM><JS>var service = context.getService();
return service.getProperty("erservicename")[0];</JS>
</PARAM>
</RE>

```

The plain text is:

```

<CAMessage/>
<RE key="itimUrl"/>:<ITIMURL/>

```

Delegation Template

Provides the default template for delegation, which includes the new delegation information. By default, this template is enabled and cannot be disabled. If any exception is thrown while evaluating JavaScript in the notification template or parsing the notification template, then the default delegation notification is sent.

For example, the template provides this message:

You have been selected to be the delegate:

For: John Doe

From: Tue Jul 03 08:00:13 IST 2012

To: Fri Jul 06 20:00:13 IST 2012

The subject statement is:

```

<RE key="delegationMailSubject"/>

```

The plain text is:

```

<RE key="delegationMailContent"/>

```

```

<RE key="delegationMailDelegator"/>:<JS>Delegate.getDelegator().name;</JS>

```

```

<RE key="delegationMailFrom"/>:<JS>Delegate.getStartDate();</JS>

```

```

<RE key="delegationMailTo"/>:<JS>Delegate.getEndDate();</JS>

```

Deprovision Account Template

Provides information that the workflow activity has removed an account. By default, this template is enabled.

For example, the template provides this message:

Your account has been removed by IBM Security Identity Manager.

The following Odessa Service [ADProfile] account has been deprovisioned.

```

View Changes: http://host:9080/itim/self
Process Reference: 5870349043636872731

```


Account ID: myaccount
Owner Name: myname
Reason: Policy Enforcement
Time completed: May 03, 2007 03:54:22 IST

The subject statement is:

```
<RE key="remove_account_subject" />
```

The plain text is:

```
<RE key="account_deprovisioned">  
<PARAM><RE key="service_name_with_profile_name">  
<PARAM><JS>EmailContext.getAccountServiceName();</JS></PARAM>  
<PARAM><RE><KEY><JS>EmailContext.getAccountServiceProfileName();  
</JS></KEY></RE></PARAM></RE></PARAM></RE>  
<ITIMURL/>  
<RE key="processRef"/>: <JS>process.id;</JS>  
<RE key="accountID"/>: <JS>EmailContext.getAccountUserId();</JS>  
<RE key="accountOwnerName"/>: <JS>EmailContext.getAccountOwnerName();</JS>  
<RE key="reason"/>: <JS>EmailContext.getReason();</JS>  
<RE key="deprovisionCompleted"/>: <RE key="readOnlyDateFormat">  
<PARAM><JS>(new Date()).getTime();</JS></PARAM></RE>
```

Manual Activity Approval Template

Provides information that the user should provide information for a request. By default, this template is enabled.

For example, the template provides this message:

Pending workflow action: Case 884088984804067042.884090864796694775

You have been requested to submit information for the following request

View Changes: <http://localhost:9090/itim/console>

Description:

Requestee: firstname lastname

Subject: subject

Request Initiated: Jun 08, 2007 10:27:29 IST

Process Reference: 884088984804067042

Requested by process:

Process ID: 884066904196868932

Process Name: Provision Account

Description: Provisioning Account Process

Requester: System Administrator

Requestee: firstname lastname

Subject: subject

The subject statement is:

```
<RE key="pending_workitem_subject"><PARAM><ID /></PARAM></RE>
```

The plain text is:

```
<RE key="wiApproval_message" />  
<ITIMURL/>  
<RE key="description"/>: <RE><KEY><JS>process.description;</JS></KEY></RE>  
<RE key="requestedFor"/>: <JS>process.requesteeName;</JS>  
<RE key="subject"/>: <JS>process.subject;</JS>  
<JS>if (process.subjectAccess!=null) if (process.subjectAccess.length>0)  
{ '<RE key="accessName"/>: <JS>process.subjectAccess;</JS>\n'; }</JS>  
<RE key="requestInit"/>: <RE key="readOnlyDateFormat"><PARAM>  
<JS>if (process.started != null) return process.started.getTime();  
else return '';</JS></PARAM></RE>  
<RE key="processRef"/>: <JS>process.id;</JS>  
<JS>if (process.parentId == '0') { '<RE key="requestedBy"/>:  
<JS>process.requestorName;</JS>'; }</JS>  
  
<JS>if (process.parentId != '0') { '<RE key="parent_process"/>'; }</JS>  
<JS>if (process.parentId != '0')  
{ '<RE key="processID"/>: ' + process.parentId; }</JS>  
<JS>if (process.parentId != '0') { '<RE key="processName"/>:  
<RE><KEY><JS>if (process.parentId != '0') { process.getParent().name; }  
</JS></KEY></RE>'; }</JS>  
<JS>if (process.parentId != '0') { '<RE key="description"/>:  
<RE><KEY><JS>if (process.parentId != '0')
```

```

    { process.getParent().description; } </JS></KEY></RE>'; }</JS>
    <JS>if (process.parentId != '0')
    { '<RE key="requester"/>: ' + process.getParent().requestorName; }
    </JS>
    <JS>if (process.parentId != '0')
    { '<RE key="requestedFor"/>: ' + process.getParent().requesteeName; }
    </JS>
    <JS>if (process.parentId != '0')
    { '<RE key="subject"/>: ' + process.getParent().subject; }</JS>

```

Manual Activity RFI Template

Provides the default template for request for information workflow activities. By default, this template is enabled

For example, the template provides this message:

```

You have been requested to submit information for the following request
http://localhost:9080/itim/self/ReviewActivities.do?
  activity=3053543743245419023
Description:
Requestee: Shoe Flower
Subject: shoe1
Request Initiated: Aug 03, 2007 11:48:52 IST
Process Reference: 305354339468639238

Requested by process:
  Process ID: 3053541330639294422
  Process Name: Provision Account
  Description: Provision Account Process
  Requester: System Administrator
  Requestee: Shoe Flower
  Subject: shoe1

```

The subject statement is:

```
<RE key="pending_workitem_subject"><PARM><ID /></PARM></RE>
```

The plain text is:

```

<RE key="wiRFI_message" />
<ITIMURL/>
<RE key="description"/>: <RE><KEY>
<JS>process.description;</JS></KEY></RE>
<RE key="requestedFor"/>: <JS>process.requesteeName;</JS>
<RE key="subject"/>: <JS>process.subject;</JS>
<JS>if (process.subjectAccess!=null)
  if (process.subjectAccess.length>0)
  { '<RE key="accessName"/>:
    <JS>process.subjectAccess;</JS>\n'; }</JS>
<RE key="requestInit"/>: <RE key="readOnlyDateFormat"><PARM>
<JS>if (process.started != null) return process.started.getTime();
else return '';</JS></PARM></RE>
<RE key="processRef"/>: <JS>process.id;</JS>
<JS>if (process.parentId == '0') { '<RE key="requestedBy"/>:
  <JS>process.requestorName;</JS>'; }</JS>

<JS>if (process.parentId != '0') { '<RE key="parent_process"/>'; }
</JS>
  <JS>if (process.parentId != '0')
  { '<RE key="processID"/>: ' + process.parentId; }</JS>
  <JS>if (process.parentId != '0') { '<RE key="processName"/>:
  <RE><KEY><JS>if (process.parentId != '0') { process.getParent().name; }
  </JS></KEY></RE>'; }</JS>
  <JS>if (process.parentId != '0') { '<RE key="description"/>:
  <RE><KEY><JS>if (process.parentId != '0')
  { process.getParent().description; }
  </JS></KEY></RE>'; }</JS>
  <JS>if (process.parentId != '0')
  { '<RE key="requester"/>: ' + process.getParent().requestorName; }
  </JS>
  <JS>if (process.parentId != '0')
  { '<RE key="requestedFor"/>: ' + process.getParent().requesteeName; }
  </JS>
  <JS>if (process.parentId != '0')
  { '<RE key="subject"/>: ' + process.getParent().subject; }</JS>

```

Manual Activity Work Order Template

Provides default template for the work order workflow manual activity. By default, this template is enabled.

For example, the template provides this message:

```
Pending workflow action:  
Case 1401993364658803275.1402011582339065124
```

You have received a Work Order request

The subject statement is:

```
<RE key="pending_workitem_subject"><PARM><ID /></PARM></RE>
```

The plain text is:

```
<RE key="wiWorkOrder_message" />
```

New Account Template

Provides information that the workflow activity has created a new account. By default, this template is enabled.

For example, the template provides this message:

New Account Information from IBM Security Identity Manager

The following new ITIM Service [ITIM] account has been created for you:

```
View Changes: http://localhost:80/itim/console  
Process Reference: 8498649245880216244  
Password: bAMI#gai  
Account ID: myaccount  
Owner Name: firstname lastname  
Time of service provision: Jun 29, 2007 10:55:58 IST
```

The subject statement is:

```
<RE key="new_account_subject"/>
```

The plain text is:

```
<RE key="account_created"><PARM>  
<RE key="service_name_with_profile_name">  
<PARM><JS>EmailContext.getAccountServiceName();</JS></PARM>  
<PARM><RE><KEY><JS>EmailContext.getAccountServiceProfileName();  
</JS></KEY></RE></PARM></RE></PARM></RE>  
<ITIMURL/>  
<RE key="processRef"/>: <JS>process.id;</JS>  
<JS>if (EmailContext.getTransactionId() != '0')  
{ '<RE key="TRANSACTION_ID_LABEL"/>: '  
+ EmailContext.getTransactionId(); } </JS>  
<RE key="password"/>: <JS>EmailContext.getAccountPassword();</JS>  
<RE key="accountID"/>: <JS>EmailContext.getAccountUserId();</JS>  
<RE key="accountOwnerName"/>:  
<JS>EmailContext.getAccountOwnerName();</JS>  
<RE key="timeofprovision"/>: <RE key="readOnlyDateFormat">  
<PARM><JS>(new Date()).getTime();</JS></PARM></RE>  
<JS>if (EmailContext.hasNewAccess()) { '<RE key="accountNewAccess"/>:  
<JS>EmailContext.getAccountNewAccessAsString();</JS>\n'; }</JS>  
<JS>if (EmailContext.getTransactionId() != '0')  
{ '<RE key="RETRIEVE_PASSWORD_TITLE"/>: '  
+ EmailContext.getPasswordRetrievalUrl(); }</JS>  
<JS>if (EmailContext.getTransactionId() != '0')  
{ '<RE key="passwordExpireLabel"/>:  
<JS>if (EmailContext.getPasswordExpirePeriod() == 0)  
{ '<RE key="passwordneverexpire"/>'; }  
else { EmailContext.getPasswordExpirePeriod(); }</JS>'; }</JS>  
<JS>if (EmailContext.getTransactionId() != '0')  
{ '<JS>if (EmailContext.getPasswordExpirePeriod() == 0)  
{ '<RE key="additionalMsgForPwdRetrieval"/>'; }</JS>'; }</JS>
```

New Password Template

Provides information that there is a new password for an account. By default, this template is enabled.

For example, the template provides this message:

Account new password information

The following is your new password for account myaccount:

```
View Changes: http://localhost:9090/itim/console
Process Reference: 2855285841498421007
New Password: secret
Account ID: myaccount
Account Service: ITIM Service
Account Service Profile: ITIM
Owner Name: firstname lastname
Time of service provision: Apr 25, 2007 12:54:05 IST
```

The subject statement is:

```
<RE key="password_change_subject"/>
```

The plain text is:

```
<RE><KEY><JS>if (EmailContext.getTransactionId() == '0')
  { 'newAccountPassword' } else { 'newAccountPasswordPickUp'; }
</JS></KEY>
<PARM><JS>process.subject;</JS></PARM></RE>
<ITIMURL/>
<RE key="processRef"/>: <JS>process.id;</JS>
<JS>if (EmailContext.getTransactionId() != '0')
  { '<RE key="TRANSACTION_ID_LABEL"/>: ' +
    EmailContext.getTransactionId(); }
</JS>
<RE key="newPassword"/>: <JS>EmailContext.getAccountPassword();</JS>
<RE key="accountID"/>: <JS>EmailContext.getAccountUserId();</JS>
<RE key="accountService"/>:
  <JS>EmailContext.getAccountServiceName();</JS>
<RE key="accountServiceProfile"/>: <RE><KEY>
  <JS>EmailContext.getAccountServiceProfileName();</JS></KEY></RE>
<RE key="accountOwnerName"/>:
  <JS>EmailContext.getAccountOwnerName();</JS>
<RE key="timeofprovision"/>: <RE key="readOnlyDateFormat">
  <PARM><JS>(new Date()).getTime();</JS></PARM></RE>
<JS>if (EmailContext.getTransactionId() != '0')
  { '<RE key="RETRIEVE_PASSWORD_TITLE"/>: '
    + EmailContext.getPasswordRetrievalUrl(); }</JS>
<JS>if (EmailContext.getTransactionId() != '0')
  { '<RE key="passwordExpireLabel"/>:
    <JS>if (EmailContext.getPasswordExpirePeriod() == 0)
      { '<RE key="passwordneverexpire"/>'; }
    else { EmailContext.getPasswordExpirePeriod(); }</JS>'; }</JS>

<JS>if (EmailContext.getTransactionId() != '0')
  { '<JS>if (EmailContext.getPasswordExpirePeriod() == 0)
    { '<RE key="additionalMsgForPwdRetrieval"/>'; }</JS>'; }</JS>
```

Process Completion Template

Provides information that the workflow activity has completed. By default, this template is enabled.

For example, the template provides this message when an activity is completed without being canceled:

```
A workflow process, 1416721862784240178, has completed.
Result Summary: Success
The following process has completed
```

Process Information

```
View Changes: http://localhost:9090/itim/console
Process ID: 1416721862784240178
Activity:
Description: Modify Provisioning Policy Process
State: Completed
Date submitted: May 16, 2007 12:22:58 IST
Time Completed: May 16, 2007 01:44:17 IST
Result Summary: Success
Requester: System Administrator
```

Requestee:
Subject: Default Provisioning Policy for service Win Local Profile
Comment:
Detail:

For example, the template provides this message when an activity is canceled:

Subject: A workflow process, 6690130336188564930, has completed.
Result Summary: Failed
The following process has completed

Process Information

View Changes: <http://localhost:80/itim/console>
Process ID: 6690130336188564930
Activity: Person Add
Description: Person Add Process
State: Canceled
Date submitted: Jan 30, 2014 01:13:59 CST
Time Completed: Jan 29, 2014 01:13:22 CST
Result Summary: Failed
Requester: System Administrator
Requestee: firstname lastname
Subject:
Comment:
Detail:
Canceled By: System Administrator
Date Canceled: Jan 29, 2014 01:13:22 CST
Canceled Justification: No longer needed

The subject statement is:

```
<RE key="processCompletedSubject"><PARM><JS>process.id;</JS></PARM>  
<PARM><RE key="resultSummaryValue"><PARM><RE><KEY>  
<JS>process.STATE_PREFIX + process.resultSummary;  
</JS></KEY></RE></PARM></RE></PARM></RE>
```

The plain text is:

```
<RE key="process_completed_message" />  
  
<RE key="processInformation" />  
<ITIMURL/>  
<RE key="processID"/>: <JS>process.id;</JS>  
<RE key="name"/>: <RE><KEY><JS>process.name;</JS></KEY></RE>  
<RE key="description"/>: <RE><KEY><JS>process.description;</JS>  
</KEY></RE>  
<RE key="state"/>: <RE><KEY>  
<JS>process.STATE_PREFIX + process.state;</JS></KEY></RE>  
<RE key="timeScheduled"/>: <RE key="readOnlyDateFormat"><PARM>  
<JS>if (process.scheduled != null)  
  return process.scheduled.getTime();  
else return '';</JS></PARM></RE>  
<RE key="timeCompleted"/>: <RE key="readOnlyDateFormat"><PARM>  
<JS>if (process.completed != null)  
  return process.completed.getTime();  
else return '';</JS></PARM></RE>  
<RE key="resultSummary"/>: <RE><KEY>  
<JS>process.STATE_PREFIX + process.resultSummary;</JS>  
</KEY></RE>  
<RE key="requester"/>: <JS>process.requestorName;</JS>  
<RE key="requestedFor"/>: <JS>process.requesteeName;</JS>  
<RE key="subject"/>: <JS>process.subject;</JS>  
<RE key="comment"/>: <JS>process.comment;</JS>  
  
<RE key="detail"/>: <JS>process.resultDetail;</JS>  
<JS>if (process.cancelor_name != null)  
  { '<RE key="CanceledBy"/>: ' + process.cancelor_name; }</JS>  
<JS>if (process.cancelor_name != null)  
  { '<RE key="DateCanceled"/>: ' + process.cancelor_name; }</JS>  
<RE key="readOnlyDateFormat"><PARM>  
<JS>if (process.canceled_date != null) return process.canceled_date.getTime();  
else return '';</JS>  
</PARM></RE>
```

```

<JS>if (process.cancelor_name != null) { '<RE key="CanceledReason"/>:
<JS>if (process.canceled_justification == null) { return ' '; }
    else { return process.canceled_justification;}
</JS>'; }</JS>

```

Process Timeout Template

Provides information that the workflow process has timed out. By default, this template is enabled.

For example, the template provides this message:

```

Workflow activity is being timed out and will be
terminated by the workflow system

```

```

Activity Information
View Changes: http://localhost:9080/itim/console
Activity ID: RECERTAPPROVAL
Activity: $ITIM_RECERTIFY
Time Started: Aug 02, 2007 03:18:54 IST
Time Completed:
Result Summary: Pending
State: Running
Activity Type: Manual Approval/Reject

```

Process Information

```

Process ID: 8566433417513336819
Activity: Recertification of Account/Access
Description: Recertification of Account/Access
State: Running
Date submitted: Aug 02, 2007 03:18:54 IST
Time Completed:
Result Summary:
Requester: org
Requestee: Person B
Subject: personb
Comment:
Detail:

```

The subject statement is:

```
<RE key="process_timeout_subject" />
```

The plain text is:

```

<RE key="process_timeout_message" />

<RE key="processInformation" />
<ITIMURL/>
<RE key="processID"/>: <JS>process.id;</JS>
<RE key="name"/>: <RE><KEY><JS>process.name;</JS></KEY></RE>
<RE key="description"/>: <RE><KEY><JS>process.description;</JS></KEY></RE>
<RE key="state"/>: <RE><KEY>
    <JS>process.STATE_PREFIX + process.TIMEOUT;</JS></KEY></RE>
<RE key="timeScheduled"/>: <RE key="readOnlyDateFormat"><PARM>
    <JS>if (process.scheduled != null) return process.scheduled.getTime();
    else return '';</JS></PARM></RE>
<RE key="timeCompleted"/>: <RE key="readOnlyDateFormat"><PARM>
    <JS>if (process.completed != null) return process.completed.getTime();
    else return '';</JS></PARM></RE>
<RE key="resultSummary"/>: <RE><KEY>
    <JS>process.STATE_PREFIX + process.resultSummary;</JS></KEY></RE>
<RE key="requester"/>: <JS>process.requestorName;</JS>
<RE key="requestedFor"/>: <JS>process.requesteeName;</JS>
<RE key="subject"/>: <JS>process.subject;</JS>
<RE key="comment"/>: <JS>process.comment;</JS>

<RE key="detail"/>: <JS>process.resultDetail;</JS>

```

Restore Account Template

Provides information that an account has been restored. By default, this template is enabled.

For example, the template provides this message:

Restored Account Information from IBM Security Identity Manager

The following ITIM Service [ITIM] account has been restored:

View Changes: <http://localhost:9090/itim/console>
Process Reference: 2857890686820910405
New Password: secret
Account ID: myaccount
Owner Name: firstname lastname
Time Completed: Apr 25, 2007 01:04:08 IST

The subject statement is:

```
<RE key="restore_account_subject"/>
```

The plain text is:

```
<RE key="restore_account"><PARM>  
<RE key="service_name_with_profile_name"><PARM>  
<JS>EmailContext.getAccountServiceName();</JS></PARM>  
<PARM><RE><KEY>  
<JS>EmailContext.getAccountServiceProfileName();  
</JS></KEY></RE></PARM></RE></PARM></RE>  
<ITIMURL/>  
<RE key="processRef"/>: <JS>process.id;</JS>  
<JS>if (EmailContext.getTransactionId() != '0')  
{ '<RE key="TRANSACTION_ID_LABEL"/>: '  
+ EmailContext.getTransactionId(); } </JS>  
<RE key="newPassword"/>: <JS>EmailContext.getAccountPassword();</JS>  
<RE key="accountID"/>: <JS>EmailContext.getAccountUserId();</JS>  
<RE key="accountOwnerName"/>:  
<JS>EmailContext.getAccountOwnerName();</JS>  
<RE key="timeCompleted"/>: <RE key="readOnlyDateFormat">  
<PARM>  
<JS>(new Date()).getTime();</JS></PARM></RE>  
<JS>if (EmailContext.getTransactionId() != '0')  
{ '<RE key="RETRIEVE_PASSWORD_TITLE"/>: '  
+ EmailContext.getPasswordRetrievalUrl(); }</JS>  
<JS>if (EmailContext.getTransactionId() != '0')  
{ '<RE key="passwordExpireLabel"/>:  
<JS>if (EmailContext.getPasswordExpirePeriod() == 0)  
{ '<RE key="passwordneverexpire"/>'; }  
else { EmailContext.getPasswordExpirePeriod(); }</JS>'; }  
</JS>  
  
<JS>if (EmailContext.getTransactionId() != '0')  
{ '<JS>if (EmailContext.getPasswordExpirePeriod() == 0)  
{ '<RE key="additionalMsgForPwdRetrieval"/>'; }</JS>'; }</JS>
```

Suspend Account Template

Provides information that an account is suspended. By default, this template is enabled.

For example, the template provides this message:

Your account has been suspended by IBM Security Identity Manager

The following AD Service (RFI) [ADProfile] account has been suspended:

View Changes: <http://localhost:9090/itim/console>
Process Reference: 2857497715286893521
Account ID: myaccount
Owner Name: firstname lastname
Time Completed: Apr 25, 2007 01:02:43 IST

The subject statement is:

```
<RE key="suspend_account_subject" />
```

The plain text is:

```
<RE key="account_suspended"><PARM>  
<RE key="service_name_with_profile_name">  
<PARM><JS>EmailContext.getAccountServiceName();</JS></PARM>  
<PARM><RE><KEY><JS>EmailContext.getAccountServiceProfileName();  
</JS></KEY></RE></PARM></RE></PARM></RE>  
<ITIMURL/>
```

```
<RE key="processRef"/>: <JS>process.id;</JS>
<RE key="accountID"/>: <JS>EmailContext.getAccountUserId();</JS>
<RE key="accountOwnerName"/>:
  <JS>EmailContext.getAccountOwnerName();</JS>
<RE key="timeCompleted"/>: <RE key="readOnlyDateFormat"><PARM>
  <JS>(new Date()).getTime();</JS></PARM></RE>
```

To-Do Reminder Template

Provides the default template for workflow reminders, which are email messages that remind users about pending activities to which they not responded. By default, this template is disabled.

For example, the template provides this message:

```
Subject: Pending workflow action:
Case 6167063972298972180.6167064647650050990
```

```
The following request has been submitted for your approval
View Changes: http://localhost:9080/itim/console
Description: ApprovalWorkflow
Requestee: firstname lastname
Subject: subject
Request Initiated: Sep 05, 2007 05:42:18 IST
Process Reference: 6167063972298972180
```

```
Requested by process:
Process ID: 6167052766519381908
Process Name: Provision Account
Description: Provision Account Process
Requester: System Administrator
Requestee: firstname lastname
Subject: subject
```

This WorkItem will be escalated on: Saturday, September 8, 2007.

The subject statement is:

```
<originalSubject/>
```

The plain text is:

```
<textBody/>
```

```
<RE key="escalation_note"/> <escalationTime/>
```


Chapter 9. JavaScript extensions overview

JavaScript is used in IBM Security Identity Manager to specify identity policies, provisioning policy parameters, service selection policies, placement rules for identity feeds, and orphan account adoption.

In addition, JavaScript is used in workflows to specify transition conditions, loop conditions, JavaScript activities, activity postscripts, and workflow notification. Various scripting extensions are provided by IBM Security Identity Manager to expose useful data and services to each of these scripts. In addition to these extensions, system administrators can configure IBM Security Identity Manager to load custom JavaScript extensions. For more information about custom JavaScript extensions, see the `scriptframework.properties` file. Use the Update Property page from the **Appliance Dashboard** of the IBM Security Identity Manager virtual appliance console. See Managing the server properties.

IBM Security Identity Manager supports the IBM JSEngine Java Script interpreter. This interpreter supports the third edition (December 1999) of the ECMA-262 specification.

Table 7 lists the supported host components and script extensions.

Table 7. Host components and script extensions

Host Component	Supported Script Extension	Description
AccountTemplate	ProvisioningPolicyExtension	Extensions registered with this key are loaded by Account Default Template parameters.
	ServiceExtension	
	SubjectExtension	
Delegate	DelegateExtension	Extensions registered with this key are loaded by Delegation notifications.
	Model Extensions Package	
HostSelection	ServiceModelExtension	Extensions registered with this key are loaded by Service Selection Policies.
	SubjectExtension	
IdentityPolicy	IdentityPolicyExtension	Extensions registered with this key are loaded by Identity Policies.
	AttributesExtension	
	ServiceExtension	
	SubjectExtension	
OrphanAdoption	Model Extensions Package	Extensions registered with this key are loaded by adoption scripts.
	ServiceExtension	
	SubjectExtension	
PersonPlacementRules	PersonPlacementRulesExtension	Extensions registered with this key are loaded by placement rules during identity feeds.
	ServiceExtension	
	AttributesExtension	
PostOffice	PostOfficeExtension	Extensions registered with this key are loaded by Post Office templates.

Table 7. Host components and script extensions (continued)

Host Component	Supported Script Extension	Description
ProvisioningPolicy	ProvisioningPolicyExtension	Extensions registered with this key are loaded by Provisioning Policy parameters.
	Model Extensions Package	
	ServiceExtension	
	SubjectExtension	
	AttributesExtension (deprecated)	
Reminder	ReminderExtension	Extensions registered with this key are loaded by email reminder templates.
	SubjectExtension	
Workflow	WorkflowExtension	Extensions registered with this key are loaded by workflow scripts that include Workflow TODO Notifications.
	Model Extensions Package	
	LoopCountExtension	
Workflow Notification	WorkflowExtension	The extensions loaded are hardcoded and all supported extensions are loaded.
	EmailContextExtension	
	PersonModelExtension	
TODO Notification (Approval/RFI/ComplianceAlert/ WorkOrder)	WorkflowExtension	The extensions loaded are the same as Workflow.
	Model Extensions Package	
	LoopCountExtension	

Packaged extensions

The section describes the scripting extensions provided by IBM Security Identity Manager, the JavaScript objects they expose, and the scripts to which these extensions are applicable.

Do not remove these extensions from the properties file that you configure, because they are necessary for standard product operation. All of the extensions are configured for new installations.

AttributesExtension

The full extension name is `com.ibm.itim.script.extensions.AttributesExtension`.

This extension is responsible for making the ATTRIBUTES object available to scripts. ATTRIBUTES is a Map type object and is used internally to implement the deprecated `Enrole.getAttributeValue()` and `Enrole.getAttributeValues()` methods.

AttributesExtension and the ATTRIBUTES script object are deprecated. Do not use them in any new scripts.

Availability

IdentityPolicy
 PersonPlacementRules
 ProvisioningPolicy

JavaScript Objects

ATTRIBUTES

DelegateExtension

The full extension name is `com.ibm.itim.script.extensions.DelegateExtension`.

This extension is responsible for making the `Delegate` object available to delegation notification scripts.

Availability

Delegation Notification

JavaScript Objects

`Delegate`

EmailContextExtension

The full extension name is `com.ibm.itim.workflow.script.EmailContextExtension`.

The `EmailContextExtension` provides the `EmailContext` object that provides information about the workflow activity and process that is making the notification. `EmailContext` is of type `WorkflowRuntimeContext`, although it might be a more specific subtype, depending on what type of change triggered the notification.

Availability

Notification

JavaScript Objects

`EmailContext`

EnroleExtension

The full extension name is `com.ibm.itim.script.extensions.EnroleExtension`.

This extension is automatically loaded for all scripts. It is not in the `scriptframework.properties` file.

This extension exposes the `Enrole` object to scripts. This object provides the following miscellaneous functions:

- Converting to and from the generalized time format.
- Logging and tracing facilities to write to the Security Identity Manager logs.

Availability

All scripts

JavaScript Objects

`Enrole`
`Error`

IdentityPolicyExtension

The full extension name is `com.ibm.itim.policy.script.IdentityPolicyExtension`.

This extension exposes the `IdentityPolicy` object to identity policy scripts. This object provides a method to test for the existence of a user ID.

Availability

Identity Policy

JavaScript Objects

LoopCountExtension

The full extension name is `com.ibm.itim.workflow.script.LoopCountExtension`.

This extension provides the `loopcount` script object. The object is an integer that tells a script how many times a loop ran.

Availability

Workflow

JavaScript Objects

`loopcount`

Model extensions package

The model extensions expose JavaScript objects that can be used to search for people, accounts, services, and organizational units such as organizations, business units, and locations.

Important: The objects exposed by these extensions allow access to identity and service data without regard to specified access control rules for these data. The objects are considered privileged. Define access control items that manage access to IBM Security Identity Manager scripts.

All of the model extensions have the same availability and can be used with the following extension points:

- `AccountTemplate`
- `ProvisioningPolicy`
- `HostSelection`
- `OrphanAdoption`
- `Workflow`
- `Notification`

AccountModelExtension

The full extension name is `com.ibm.itim.script.extensions.model.AccountModelExtension`.

This extension exposes the `Account` constructor and `AccountSearch` constructor to applicable scripts. After it is constructed, an `Account` object represents an `Account Directory Object` in scripts. The `AccountSearch` object provides methods to search for existing accounts based on several parameters, which include **uid**, **owner**, and **service**.

JavaScript Objects

- `AccountSearch`
- `Account`

PersonModelExtension

The full extension name is `com.ibm.itim.script.extensions.model.PersonModelExtension`.

This extension exposes the `Person` constructor, `PersonSearch` constructor, and `ExtendedPerson` constructor to applicable scripts. After it is constructed, a `Person` object represents a `Person Directory Object` in script. A `ExtendedPerson` object

extends Person with ownership type information. The PersonSearch object provides methods to search for existing people based on a provided LDAP filter.

JavaScript Objects

- PersonSearch
- Person
- ExtendedPerson

OrganizationModelExtension

The full extension name is
`com.ibm.itim.script.extensions.model.OrganizationModelExtension`.

This extension exposes the ContainerSearch constructor to applicable scripts. The ContainerSearch object provides methods to search of Organizational containers based on LDAP filters.

JavaScript Objects

ContainerSearch

RoleModelExtension

The full extension name is
`com.ibm.itim.script.extensions.model.RoleModelExtension`.

This extension exposes the Role constructor and RoleSearch constructor to applicable scripts. After it is constructed, the Role object represents a Role Directory Object in scripts. The RoleSearch object provides a method to search for Roles based on role name.

JavaScript Objects

- RoleSearch
- Role

ServiceModelExtension

The full extension name is
`com.ibm.itim.script.extensions.model.ServiceModelExtension`.

This extension exposes the Service constructor and ServiceSearch constructor to applicable scripts. After it is constructed the Service object represents a Service Directory Object in scripts. The ServiceSearch object provides methods to search for Service based on several parameters, which include LDAP filter and service name.

JavaScript Objects

- ServiceSearch
- Service

PersonPlacementRulesExtension

The full extension name is
`com.ibm.itim.remoteservices.script.PersonPlacementRulesExtension`.

This extension provides the entry object to the scripting environment. The entry object is of type Map and contains the attribute values for the Person that is placed.

Availability

PersonPlacementRules

JavaScript Objects

entry

PostOfficeExtension

The full extension name is
`com.ibm.itim.mail.postoffice.script.PostOfficeExtension`.

The Post Office capability reduces the number of email messages received by workflow participants by combining similar notifications into a single email. The emails are combined with a template specified in the system configuration pages. This extension exposes a JavaScript object, `PostOffice`, to JavaScript snippets in these templates. This object provides methods for accessing all the distinct emails, the email address of the recipient, the email topic, and the recipient data.

Availability

Post Office Template

JavaScript Objects

`PostOffice`

ProvisioningPolicyExtension

The full extension name
`iscom.ibm.itim.policy.script.ProvisioningPolicyExtension`.

This extension provides the scripting objects `reason` and `parameters` to the scripting environment. The `reason` object is an integer that informs a script of the reason the evaluation is happening: 0 if a new account or 1 if an existing account. The `parameters` object is a map that contains the information about the account that is being evaluated. Currently, only the `uid` field is supported.

Availability

`AccountTemplate`
`ProvisioningPolicy`

JavaScript Objects

`parameters`
`reason`

ReminderExtension

The full extension name is `com.ibm.itim.script.extensions.ReminderExtension`.

This extension exposes the `reminderCtx` object to JavaScript snippets contained in email reminders. This object provides methods for accessing the original email text and subject. It also provides the due date and time for the associated to-do item.

Availability

E-mail reminders

JavaScript Objects

`reminderCtx`

ServiceExtension

The full extension name is `com.ibm.itim.script.extensions.ServiceExtension`.

This extension exports the service object to the scripting environment. The service object is a `DirectoryObject` type and represents the Service associated with a provisioning operation.

Availability

IdentityPolicy
OrphanAdoption
PersonPlacementRules
AccountTemplate
ProvisioningPolicy

JavaScript Objects

service

SubjectExtension

The full extension name is `com.ibm.itim.script.extensions.SubjectExtension`.

This extension provides the subject scripting object. In all of the scripting contexts except for `OrphanAdoption`, `subject` is a `DirectoryObject`. In the `OrphanAdoption` context, `subject` is a `Map` of the attributes returned by a reconciliation.

Availability

HostSelection
IdentityPolicy
OrphanAdoption
Reminder
AccountTemplate
ProvisioningPolicy

JavaScript Objects

subject

WorkflowExtension

The full extension name is `com.ibm.itim.workflow.script.WorkflowExtension`.

This extension exposes JavaScript objects that can be used to access data from a workflow process in progress. In addition, it exposes objects that can be used to get or set the status, state, and result of a workflow process or activity.

Availability

Workflows

JavaScript Objects

- process
- activity
- participant
- Relevant Data

Note: Relevant Data are objects defined by the workflow designer. Check with system administrator to find the names of specific Relevant Data objects.

Relevant data JavaScript objects

Each process has a set of relevant data, or process specific parameters, which can be read or changed from in a workflow script.

The name and syntax of these parameters, or relevant data items, are defined in the workflow designer and are typically specific to the workflow process purpose. For example when you add a user, an object that holds all the attributes of the new user can be a relevant data item. However, when you delete a user, the only required relevant data item can be the distinguished name of the user to delete.

Each relevant data item is represented in the workflow script as a variable with the same relevant data ID as defined in the workflow designer. These relevant data items all have the following functions:

get() This function returns a JavaScript object that represents the value of the relevant data item. There is a variable present for each relevant data item in the context of the script. For performance reasons, however, the values are not retrieved from the workflow engine until the script specifically requests it with this call. The returned JavaScript object is in the same syntax as defined in the workflow designer.

Usage:

```
dn = subjectDN.get();
```

where subjectDN is defined as a relevant data item for the current process.

set(Object value)

The set(Object value) function changes the value of the relevant data item. It not only updates the relevant data item in the script, but also in the workflow engine. The new value is a parameter to the function. The new value must be compatible with the syntax of the relevant data item as defined in the workflow designer. For example, if the relevant data item is an integer, the value cat is not a valid parameter to this function.

Usage:

```
ou.set("engineering");
```

where ou is defined as a relevant data item for the current process.

Registering JavaScript extensions

JavaScript extensions might not be useful or applicable to every scriptable function that IBM Security Identity Manager provides. For example, an extension used by Post Office templates might not be applicable to provisioning policy parameters. An extension designed for one class of script might not load or behave appropriately when loaded into another class of script.

Security Identity Manager has the classes of script that are listed in Table 8 on page 63. JavaScript extensions might be registered to load and run with any combination of these script classes.

JavaScript extensions are configured in these files:

scriptframework.properties (suggested)

For *all* new extensions. Use this file to configure script extensions and other scripting functions.

JavaScript extensions are registered in the scriptframework.properties file. This file is formatted with the standard Java Properties *key[.subkey]=value* format.

- The key is the name assigned to the target script class, described in Table 8 on page 63.

- The value is the full class name of the ScriptExtension interface.
- (Optional) The subkey is used when more than one extension is registered for a script class.

Use the Update Property page from the **Appliance Dashboard** of the IBM Security Identity Manager virtual appliance console. See Managing the server properties.

Note:

1. To prevent the possibility of a code injection attack, do not use the JavaScript function eval ().
2. By default, only the set of extensions registered in the scriptframework.properties file is available for the particular script. You can configure any supported extension for the script by registering JavaScript extensions in the scriptframework.properties file. For information about supported script extensions, see Table 7 on page 55. For information about the properties and methods available for each JavaScript extension object, see Chapter 10, “JavaScript extension reference,” on page 71.

The following line registers a single extension for use in Security Identity Manager scripts:

```
ITIM.extension.IdentityPolicy=com.ibm.itim.policy.script.IdentityPolicyExtension
```

These example lines register multiple extensions for use in Security Identity Manager scripts:

```
ITIM.extension.IdentityPolicy.1=com.ibm.itim.policy.script.IdentityPolicyExtension
ITIM.extension.IdentityPolicy.2=com.yourcompany.script>YourCustomExtension
```

Table 8. Script class keys

Host Component	Script Class Key
AccountTemplate	ITIM.extension.AccountTemplate
Delegate	ITIM.extension.Delegate
HostSelection	ITIM.extension.HostSelection
IdentityPolicy	ITIM.extension.IdentityPolicy
OrphanAdoption	ITIM.extension.OrphanAdoption
PersonPlacementRules	ITIM.extension.PersonPlacementRules
PostOffice	ITIM.extension.PostOffice
ProvisioningPolicy	ITIM.extension.ProvisioningPolicy
Reminder	ITIM.extension.Reminder
Workflow	ITIM.extension.Workflow
Workflow Notification	ITIM.extension.Notification
TODO Notification (Approval/RFI/ComplianceAlert/WorkOrder)	ITIM.extension.Notification

Configuring scriptframework.properties

Use the scriptframework.properties file, which provides extended documentation for these tasks, to configure major scripting functions. To update the file, use the Update Property page from the **Appliance Dashboard** of the IBM Security Identity Manager virtual appliance console. See Managing the server properties.

Following are the major scripting functions:

Extensions

Specifies which extensions to load for each host component. To load more than a single extension for any host component, add a suffix to the properties key (each key must be unique). For example:

```
ITIM.extension.IdentityPolicy=com.ibm.itim.policy.script.IdentityPolicyExtension
ITIM.extension.IdentityPolicy.service=com.ibm.itim.script.extensions.ServiceExtension
```

Interpreters

Configures the interpreter to use for each host component. The default is the IBM JSEngine.

Wrappers

All objects available to scripts are really Java objects that are used by IBM Security Identity Manager. To prevent security issues, IBM Security Identity Manager wraps these objects in wrappers. Use this area of the `scriptframework.properties` file to change the default wrappers that are used by IBM Security Identity Manager. Default scripts that are provided by IBM Security Identity Manager assume the use of default wrappers. If you change the scripts, functions might stop working. This area is for advanced use only.

Miscellaneous

Determines whether profiling information is collected and included in the trace log and whether plain text passwords can be accessed from Person and Account objects.

Migration of custom FESI extensions to the IBM JSEngine

Migration of a custom FESI extension to a script extension makes your code shorter, easier to read, and easier to understand.

Note: Support for FESI is deprecated in IBM Security Identity Manager Version 6.0.

For detailed information and examples about how to write new extensions, obtain a copy of the `extensions.zip` file. Do these steps:

1. Log on to the IBM Security Identity Manager virtual appliance console to open the **Appliance Dashboard**.
2. From the top-level menu of the Appliance Dashboard, select **Configure > Advanced Configuration > Custom File Management** to display the Custom File Management page.
3. Click the **All Files** tab.
4. Go to `directories/utilities`.
5. Select `extensions.zip` and click **Download**.
6. Extract the `extensions.zip` file.
7. See the documentation in `/extensions/doc/javascript/javascript.html`.

The following example illustrates the migration steps.

Best practice in handling function returns

You can minimize problems that might occur due to differences in how FESI and IBM JSEngine handle JavaScript. The differences involve implicit return values from functions.

For example, given these statements:

```
function sumValue() {
  var a = 3;
  var b = 2;
  a + b;
}
```

With FESI, the function `sumValue()` returns 5 because 5 is the result of the last statement run in the function. Using IBM JSEngine, the expression `sumValue()` returns null because there is no explicit return. The correct code for IBM JSEngine includes an explicit return statement:

```
function sumValue() {
  var a = 3;
  var b = 2;
  return a + b;
}
```

To keep JavaScript code consistent, always use an explicit return value in functions. In the previous release, some of the service selection script examples did not use an explicit return value. Update any JavaScript code that is based on these examples to have an explicit return value, to ensure that the code continues to work after an upgrade to use IBM JSEngine.

Plain Old Java Object (POJO) example

Start with a Plain Old Java Object (POJO, in this example) that contains all of the business logic for your extension.

For example:

```
public class Extension {
  public static void log(String msg) {
    System.out.println(msg);
  }
}
```

In this case, the POJO contains a single method. Your typical extension contains more logic. For example:

```
static class FESIExtension implements JSEExtension {
  public void initializeExtension(JSGlobalObject go) throws JSEException {
    // Create the prototype
    final JSObject prototype = go.makeJSObject();

    prototype.setMember("log", new JSFunctionAdapter() {
      public Object doCall(JSObject thisObject, Object[] args)
        throws JSEException {
        if (args.length >= 1) {
          Extension.log(args[0].toString());
        }

        return null;
      }
    });

    final JSObject obj = go.makeJSObject(prototype);

    // This is the name of the object to be used in JavaScript Code
    go.setMember("CustomExtension", obj);

    go.setMember("log", new JSFunctionAdapter() {
      public Object doCall(JSObject thisObject, Object[] args)
        throws JSEException {
        if (args.length >= 1) {
```


3. The third part of the extension creates a constructor that can be called from scripts. For example:

```
go.setMember("Logger", new JSFunctionAdapter() {
    public Object doNew(JSObject thisObject, Object[] args)
        throws JSEException {
        JSGlobalObject go = thisObject.getGlobalObject();
        JSObject proto = go.makeJSObject();

        proto.setMember("log", new JSFunctionAdapter() {
            public Object doCall(JSObject thisObject, Object[] args)
                throws JSEException {
                if (args.length >= 1) {
                    Extension.log(args[0].toString());
                }

                return null;
            }
        });
        final JSObject obj = go.makeJSObject(proto);
        return obj;
    }
});
```

With this constructor, scripts can do the following:

```
var logger = new Logger();
logger.log("message");
```

Conversion to a script extension

When you convert a FESI extension to a script extension, the root of a script extension is the `ScriptExtension` interface.

You must implement this interface to create script extension.

```
public class ITIMEExtension implements ScriptExtension {

    public List getContextItems() {
    }

    public void initialize(ScriptInterface si, ScriptContextDAO dao)
        throws ScriptException, IllegalArgumentException {
    }
}
```

To create object that can be used in scripts, create a POJO class that contains all of the business logic, and implements the marker interface `ExtensionBean`. A marker interface means that `ExtensionBean` does not require you to implement any methods and it does add any new data to your class. A POJO that implements `ExtensionBean` is treated specially by the IBM Security Identity Manager scripting components.

If your class does not implement `ExtensionBean`, then scripts cannot use the methods provided by the POJO. For example:

```
public class Extension implements ExtensionBean {
    public static void log(String msg) {
        System.out.println(msg);
    }
}
```

In the initialize method of your extension, create `ContextItem` that contains an instance of your extension and add that `ContextItem` to a `List`.

```
ContextItem custom = ContextItem.createItem("CustomExtension",
    new Extension());
items.add(custom);
```

To create global function, use `ContextItem`, but this time call `createGlobalFunction`. For example:

```
ContextItem func = ContextItem.createGlobalFunction("log",
    new GlobalFunction() {
        public Object call(Object[] parameters)
            throws ScriptEvaluationException {
            if (parameters.length >= 1) {
                Extension.log(parameters[0].toString());
            }
            return null;
        }
    });
items.add(func);
```

The second argument to `createGlobalFunction` is a `GlobalFunction` object. `GlobalFunction` has a single method that you must implement and call. It is similar to the `doCall` method from the `FESI JSFunctionAdapter`. `GlobalFunctions` are not suggested because, like the `doCall` method, they pass an array of parameters. You must check that all of the parameters exist and are the right types, which can be difficult to maintain over the life of your extension.

Creation of a constructor

To create a constructor, use `ContextItem` and the `createConstructor` method.

For example:

```
ContextItem logger = ContextItem.createConstructor("Logger",
    Extension.class);
items.add(logger);
```

The second parameter to `createConstructor` is the `Class` object for the object that you want to construct. It is usually a `POJO` that implements `ExtensionBean`.

In each of these examples, you add the `ContextItem` to a `List`. In the `getContextItems` method of `ScriptExtension`, you return that `List`. For example, the full code is:

```
public class ITIMEExtension implements ScriptExtension {

    private List<ContextItem> items;

    public List getContextItems() {
        return items;
    }

    public void initialize(ScriptInterface si, ScriptContextDAO dao)
        throws ScriptException, IllegalArgumentException {

        items = new ArrayList<ContextItem>();

        ContextItem custom = ContextItem.createItem("CustomExtension",
            new Extension());
        items.add(custom);

        ContextItem func = ContextItem.createGlobalFunction("log",
            new GlobalFunction() {
                public Object call(Object[] parameters)
                    throws ScriptEvaluationException {
                    if (parameters.length >= 1) {
```

```
        Extension.log(parameters[0].toString());
    }
    return null;
}
});
items.add(func);

ContextItem logger = ContextItem.createConstructor("Logger",
    Extension.class);
items.add(logger);
}
}
```

Chapter 10. JavaScript extension reference

The reference section is arranged alphabetically.

There are a number of IBM Security Identity Manager specific objects available for use. IBM Security Identity Manager uses JavaScript extensions to package JavaScript objects and APIs. An extension can also be a package of other extensions (for example, ModelExtension).

After an extension is defined, it can be registered in the scriptframework.properties file to be used in a specific JavaScript context. Use the Update Property page from the **Appliance Dashboard** of the IBM Security Identity Manager virtual appliance console. See Managing the server properties. In some cases, an environment needs to be created for an extension.

Table 9 shows these script extensions.

Table 9. Script extensions

Script Extension	Object Name	Object Type
AttributesExtension (deprecated)	ATTRIBUTES	Map
EmailContextExtension	EmailContext	EmailContext
EnroleExtension	Enrole error	Enrole Error
IdentityPolicyExtension	IdentityPolicy	IdentityPolicy
LoopCountExtension	loopcount	int
PersonPlacementRulesExtension	entry	Map
PostOfficeExtension	PostOffice	PostOffice
ProvisioningPolicyExtension	parameters reason	Map int (0: New Account, 1: Existing Account)
AccountModelExtension	Account constructor AccountSearch constructor	Account AccountSearch
OrganizationModelExtension	ContainerSearch constructor	ContainerSearch
PersonModelExtension	Person constructor ExtendedPerson constructor PersonSearch constructor	Person ExtendedPerson PersonSearch
RoleModelExtension	Role constructor RoleSearch constructor	Role RoleSearch
ServiceModelExtension	Service constructor ServiceSearch	Service ServiceSearch
ReminderExtension	reminderCtx	Reminder
ServiceExtension	service	DirectoryObject

Table 9. Script extensions (continued)

Script Extension	Object Name	Object Type
SubjectExtension	subject	Person Note: For Orphan Adoption Rule JavaScript, the subject is a Map, which contains the account attributes returned from reconciliation. The entries in the map are referred by the name of the account attributes, which might vary based on the service type.
WorkflowExtension	process activity Participant constructor ParticipantType \$RelevantDataName	Activity Participant ParticipantType ProcessDataProcess

Finding methods and properties for a specific JavaScript object

This example demonstrates how to find methods and properties for a specific JavaScript object.

If you are writing a workflow script, look in the `scriptframework.properties` file to see which extensions are available. By default, workflow loads the model extensions, the `WorkflowExtension`, and the `LoopCountExtension`.

Table 9 on page 71 shows that `WorkflowExtension` defines scripting objects that include `process`, `activity`, a `Participant` constructor, an object named `ParticipantType`, and a series of workflow-specific pieces of data.

In another column in the table, notice that the `process` object is of type `Process`. Now, locate `Process` in this reference to see that `Process` type has a property called `name`, and a method called `getParent()`.

To understand how to use maps, notice that objects, such as parameters from **ProvisioningPolicyExtension**, have a type of `Map`. A `Map`, also known as a dictionary, is a named JavaScript object that can hold many other objects which can be accessed by name. The `parameters` object holds another object named `uid`. To access `uid`, you can type `parameters.uid[0]`. (In this case `uid` is an array, so you must type `[0]` to get the first element of the array.) The values that a map holds will vary between each map. For more information, locate the specific map in the JavaScript reference.

How to read the reference pages

This section explains the structure of each reference item.

Title and Description

Every reference entry begins with a title and a one line description. The entries are alphabetized by title. The one-line description gives a quick summary of the item documented in the entry.

Availability

The IBM Security Identity Manager JavaScript extensions change over time. Unless otherwise noted, anything available in one version of the IBM Security Identity Manager extensions is also available in later versions. This section also specifies whether an existing item was enhanced with a

later version of the extensions and when an item is deprecated. Deprecated items are no longer supported and can be removed from future versions of the IBM Security Identity Manager extensions. Do not use deprecated items in new IBM Security Identity Manager JavaScript code.

Provided by

At installation, IBM Security Identity Manager provides this initial set of registered extensions:

- **EnroleExtension**
- **ProvisioningPolicyExtension**
- **PostOfficeExtension**
- **IdentityPolicyExtension**
- **PersonPlacementRulesExtension**
- **WorkflowExtension**
- **ReminderExtension**
- **ServiceExtension**
- **SubjectExtension**
- **AttributesExtension**
- **LoopCountExtension**
- **EmailContextExtension**
- **Model extensions package**

Inherits From

JavaScript classes can inherit properties and methods from other classes. When it occurs, an Inherits From section appears in the reference entry. The inherited fields and methods are in the listed superclasses. For example, the subject object inherits all of its fields and properties from the **DirectoryObject** class.

Synopsis

This section is a synopsis of how to use the object, method, property, or function.

Arguments

If the reference page describes a function or method that has arguments, the Synopsis is followed by an Arguments subsection that describes the arguments to the function or method. For some objects, the Synopsis section is replaced by a Constructor section which is also followed by an Arguments subsection.

Returns

If a function or a method has a return value, the Arguments subsection is followed by a Returns subsection that explains the return value of the function, method or constructor.

Properties

If the reference page documents an object, the Properties section lists the properties the object supports and provides short explanations of each.

Methods

The reference page for an object that defines methods includes a Methods section.

Description

Most reference entities contain a Description section, which is a basic description of whatever is documented. For some simple methods, the

Arguments and Returns sections document the method sufficiently by themselves, so the Description section is omitted.

Usage This section describes common techniques for using the item, or it contains cautionary information.

Account

Represents an account that is associated with a provisioning operation.

Availability

IBM Security Identity Manager 7.0.

Inherits From

DirectoryObject

Provided by

`com.ibm.itim.script.extensions.model.AccountModelExtension`

Constructor

new Account(dn)

Returns

The newly created Account object that represents the account with the specified DN, which is a String.

Methods

getAndDecryptPassword()

Decrypts and returns

The decrypted password of the account entity in plain text.

Note: This method is available in the scripting context of Security Identity Manager only if the `javascript.password.access.enabled` property is set to true in the `scriptframework.properties` file.

setAndEncryptPassword()

Encrypts

The given plaintext password and sets it on the account object.

Note: This method is available in the scripting context of Security Identity Manager only if the `javascript.password.access.enabled` property is set to true in the `scriptframework.properties` file.

Account.getAndDecryptPassword()

The method decrypts and returns the decrypted password of the account entity in plain text.

Availability

IBM Security Identity Manager 7.0.

Synopsis

`account.getAndDecryptPassword()`

Returns

String representing plain text password set in the account object.

Description

This method can be used in the scripting context of Security Identity Manager if the `javascript.password.access.enabled` property is set to true or

false in the scriptframework.properties file. It decrypts and returns the decrypted password set in the account object. This function will return null if the password is not present.

Note: This method does not decrypt the password of the Security Identity Manager account, which is hashed and stored in LDAP.

Usage

```
var password = account.getAndDecryptPassword();  
</page_ Account.getAndDecryptPassword(>
```

Account.setAndEncryptPassword()

The method encrypts the given plaintext password and sets it on account object.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
account.setAndEncryptPassword(String password)
```

Arguments

password

Plain text password string.

Description

This method can be used in the scripting context to set a given plain text password to an account object if the javascript.password.access.enabled property is set to true or false in the scriptframework.properties file. Internally, the function encrypts the password and sets the same on the account entity.

Usage

```
account.setAndEncryptPassword("secret");  
</page_ Account.setAndEncryptPassword(>
```

AccountSearch

You can search for an account with the AccountSearch object.

Availability

IBM Security Identity Manager 7.0.

Provided by

```
com.ibm.itim.script.extensions.model.AccountModelExtension
```

Constructor

```
new AccountSearch()
```

Returns

The newly created and initialized account search object.

Methods

searchByOwner()

Search for an account by owner.

searchByUid()

Search for an account by user ID.

searchByUidAndService()

Search for an account by user ID and service.

searchByURI()

Search for an account by URI within an organizational container.

Description

The entity implements the IBM Security Identity Manager Account Search class.

AccountSearch.searchByOwner()

The method finds an account entity by the distinguished name of the owner.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
AccountSearch.searchByOwner(personDN)
```

Arguments

personDN

String representing the distinguished name of the account owner.

Description

Given the distinguished name of the person, find the account entities owned by that person. This function will return null if the person is not found.

Usage

```
var account = (new AccountSearch()).searchByOwner(person.dn);
if (account!=null) {
  Enrole.log("script", "Found " + account.length + " accounts");}
```

AccountSearch.searchByUid()

The method finds an account entity by user ID and distinguished name of a service.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
AccountSearch.searchByUid(uid, serviceDN)
```

Arguments

uid String representing the user ID of the account.

serviceDN

String representing the distinguished name of the account.

Description

Given the user ID of the account and the distinguished name of the service, find the account entity. This function returns null if there is not exactly one matching account, or if the service is not found.

Usage

```
var account = (new AccountSearch()).searchByUid("pallen",
service.dn);
if (account!=null) {
  Enrole.log("script", "Found account pallen");
}
```

AccountSearch.searchByUidAndService()

The method finds an account entity by user ID, service name, and service profile name.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
AccountSearch.searchByUidAndService(uid, serviceName)
```

Arguments

uid String representing the user ID of the account.

serviceName
String representing the name of the service.

Description

Given the user ID of the account and the name of the service that has the same service profile as the script context service profile, find the account entity. This function returns null if:

- More than one matching account exists.
- The service is not found.
- More than one service with the given name exists.

Usage

```
var account = (new AccountSearch()).searchByUidAndService  
("pallen", "Domain Controller");  
if (account!=null) {  
  Enrole.log("script", "Found account pallen"); }  
}
```

Synopsis

```
AccountSearch.searchByUidAndService(uid, serviceName,  
serviceProfileName)
```

Arguments

uid String representing the user ID of the account.

serviceName
String representing the name of the service.

serviceProfileName
String representing the name of the service profile of the
serviceName service.

AccountSearch.searchByURI()

The method finds an account by URI in an organizational container.

Availability

IBM Security Identity Manager 7.0

Synopsis

```
AccountSearch.searchByURI(containerDN, uri)
```

Arguments

Container DN
String representing the distinguished name of the
organizational container.

uri String representing the URI of the account.

Returns

An Account object.

Description

Given the distinguished name of an organizational container and the account URI, this method finds the account. If the account is not found, this function returns null. If more than one account is found, this function throws a scripting exception.

Usage

```
var account = (new AccountSearch()).searchByURI(container.dn, uri);
if (account != null) {
  Enrole.log("script", "Found " + account.getProperty("eruid") );}
```

Activity

Activity is used to reference any activity in a IBM Security Identity Manager workflow.

Availability

IBM Security Identity Manager 7.0

Provided by

The activity JavaScript object in the WorkflowExtension returns an Activity object that represents the current workflow activity. The workflow activity can be used in the context of a workflow activity PostScript, or in a transition script, to reference the current activity. For a transition script, this object represents the activity whose completion has lead to the evaluation of the transition script.

Process.getActivity() can return any Activity object in the context of a workflow process. For more information, see the description of this method.

Activity Result Summary Code**APPROVED**

Approved process summary code. Result code is AA.

ESCALATED

Escalated process summary code. Result code is ES.

FAILED

Failed process summary code. Result code is SF.

PARTICIPANT_RESOLVE_FAILED

Participant resolved failure process summary code. Result code is PF.

PENDING

Pending process summary code. Result code is PE.

REJECTED

Rejected process summary code. Result code is AR.

SUBMITTED

Submitted process summary code. Result code is RS.

SUCCESS

Success process summary code. Result code is SS.

TIMEOUT

Time out process summary code. Result code is ST.

WARNING

Warning process summary code. Result code is SW.

Properties

description

Describes the purpose of the activity given when defined in the workflow designer.

duedate

Indicates the time in milliseconds by when the activity is due.

id

Assigned by the workflow designer to uniquely identify the workflow activity within the workflow engine.

index

Index of the instance of the activity.

name

Label given this activity when defined in the workflow designer.

participant

The activity participant, as defined in the workflow designer.

resultDetail

An application-specific string that provides more detail about the result of the activity.

resultSummary

An application-specific string that represents the summary result of the activity.

started

Indicates when the activity started.

state

Code that represents the current state of the activity.

subtype

Code that further categorizes the activity beyond the type of the activity, such as approval or request for information.

type

Code that categorizes the activity given when defined in the workflow designer, such as manual or application.

Methods

auditEvent()

Create an event in the audit trail specific to the activity.

setResult()

Change the result member of the activity in the current activity.

Description

This entity represents the current workflow activity that is being run. Within the context of a workflow transition script, this entity represents the activity whose completion has lead to the evaluation of the transition script. No constructor is available to create this object in any IBM Security Identity Manager context.

Activity.auditEvent()

The method creates an event in the audit trail.

Availability

IBM Security Identity Manager 7.0.

Synopsis

activity.auditEvent(event)

Arguments

event String representing the event to be audited.

Description

This method creates an event in the audit trail specific to the activity. The function takes in one parameter that can be any JavaScript object that can be translated into a String for storage. In the audit trail, the event is automatically time stamped.

Usage `activity.auditEvent("Task completed");`

Activity.description

The field provides information about the purpose of the activity.

Availability

IBM Security Identity Manager 7.0

Synopsis

`activity.description`

Description

This read-only field is a String that describes the purpose of the activity given when defined in the workflow designer.

Usage `x = activity.description;`

Activity.duedate

The field represents the time in milliseconds by when the activity is due.

Availability

IBM Security Identity Manager 7.0.

Synopsis

`activity.duedate`

Description

This read-only field is a long number of milliseconds by when this activity is due.

Usage

`x = activity.duedate;`

Activity.getSubProcesses()

The method returns the subordinate processes (if any) of the activity.

Availability

IBM Security Identity Manager 7.0.

Synopsis

`activity.getSubProcesses()`

Returns

The subordinate processes. If there are no subordinate processes, an empty array is returned.

Description

This method returns the subordinate processes (if any) of this activity.

Usage

```
var out = "subprocesses of the activity: \n";
var subProcesses = activity.getSubProcesses();
for (var i = 0; i < subProcesses.length; i++) {
    out += subProcesses[i].id + " type: " + subProcesses[i].type + " resultSummary: " + subProcesses[i].resultSummary + "\n";
}
activity.auditEvent(out);
```

Activity.guid

The generated unique identifier assigned to the activity at runtime.

Availability

IBM Security Identity Manager 7.0

Synopsis

activity.guid

Description

This read-only field is a String of the generated unique identifier for the workflow activity within the workflow engine.

Usage `x = activity.guid;`

Activity.id

The field is the unique identifier assigned to the activity.

Availability

IBM Security Identity Manager 7.0.

Synopsis

activity.id

Description

This read-only field is a String assigned by the workflow designer to uniquely identify the workflow activity within the workflow engine.

Usage `x = activity.id;`

Activity.index

The field is an index of the instance of the activity.

Availability

IBM Security Identity Manager 7.0.

Synopsis

activity.index

Description

This field is a read-only and a number. If there is more than one instance of this activity, such as in the case where the activity of the ID is called multiple times in a loop in the workflow process, the value starts at one. If there is only one instance of this activity, the index value is zero.

Usage `x = activity.index;`

Activity.name

The field is the label that is assigned to the activity.

Availability

IBM Security Identity Manager 7.0

Synopsis

activity.name

Description

This read-only field is a String assigned by the workflow designer to label this activity.

Usage `x = activity.name;`

Activity.participant

The field represents the activity participant.

Availability

IBM Security Identity Manager 7.0

Synopsis

activity.participant

Description

This read-only field is a Participant that represents the activity participant. Not all activities have a participant. If there is no participant associated with the activity, this member is empty.

Usage `x = activity.participant;`

Activity.resultDetail

You can get the details about the result of the activity with this field.

Availability

IBM Security Identity Manager 7.0.

Synopsis

activity.resultDetail

Description

This read-only field is an application-specific string that provides more detail about the result of the activity.

Usage `x = activity.resultDetail;`

Activity.resultSummary

The field helps you view the summary of the result of the activity.

Availability

IBM Security Identity Manager 7.0.

Synopsis

activity.resultSummary

Summary

This read-only field is an application-specific string that provides a summary of the result of the activity. It can represent a success or failure.

Usage `x = activity.resultSummary;`

Activity.setResult()

The method changes the result member of the activity.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
activity.setResult(summary)
activity.setResult(summary, detail)
```

Arguments

summary

String code that represents the result summary.

detail String representing the result details.

Description

This method changes the result member of the activity in the current activity. It is supported for current activities in the current workflow process. The result is composed by an application-specific summary code, and optional more detailed application-specific description. The summary code can indicate a success or failure. This summary code is stored as the `resultSummary` member locally and updated in the relevant data in the workflow engine. The detail is stored as the `resultDetail` member locally and updated in the relevant data in the workflow engine.

Usage

```
activity.setResult(activity.FAILED);
activity.setResult(activity.FAILED, "Unable to connect to resource");
```

Activity.started

The field represents the date that indicates when the activity started.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
activity.started
```

Description

This read-only field is a string that represents the date that indicates when the activity started.

Usage

```
x = activity.started;
```

Activity.state

The field represents the current state of the activity.

Availability

IBM Security Identity Manager 7.0

Synopsis

```
activity.state
```

Description

This read-only field is a code string that represents the current state of the activity. The state can have the following values:

- **R** for running
- **I** for not started
- **T** for terminated
- **A** for aborted

- **S** for suspended
- **C** for completed
- **B** for bypassed

Usage

```
if (activity.state == "S") {
    ...
}
```

Activity.subtype

The field represents the subtype of the activity.

Availability

IBM Security Identity Manager 7.0.

Synopsis

activity.subtype

Description

This read-only field is a code string that further categorizes the activity beyond the type of the activity, such as approval or request for information. This is defined in the workflow designer. Not all activities have a subtype. If there is no subtype associated with the activity, this member is empty. The currently supported subtypes are:

- **AP** for approval
- **RI** for request for input
- **WO** for work order

Usage `x = activity.subtype;`

Activity.type

The field represents the type of the activity.

Availability

IBM Security Identity Manager 7.0.

Synopsis

activity.type

Description

This read-only field is code string that categorizes the activity given when defined in the workflow designer, such as manual or application. The currently supported types are:

- **S** for subprocess
- **L** for loop
- **A** for application
- **R** for route
- **M** for manual
- **O** for operation

Usage `x = activity.type;`

AttributeChangeOperation

The object represents an entity about the attribute change operation.

Availability

IBM Security Identity Manager 7.0.

Provided by

AttributeChangeOperation objects are returned from the method **DirectoryObject.getChanges()** and are therefore not provided by any specific extension.

Properties

attr Name of the attribute that is being changed.

op An integer that identifies the type of change that is being made.

values[]

An array of objects that must be either added, removed, or replaced.

Description

This entity represents the changes made to a IBM Security Identity Manager object.

AttributeChangeOperation.attr

Represents the name of an attribute that is being changed.

Availability

IBM Security Identity Manager 7.0.

Synopsis

attributeChangeOperation.attr

Description

Value is the attribute that is being changed.

Usage `x = attributeChangeOperation.attr;`

AttributeChangeOperation.op

The field represents the type of change that is being made.

Availability

IBM Security Identity Manager 7.0.

Synopsis

attributeChangeOperation.op

Description

This read-only field is a number that identifies the type of change that is being made. The values are:

- 1 for add
- 2 for replace
- 3 for remove

Usage `x = attributeChangeOperation.op;`

AttributeChangeOperation.values[]

The field represents the name of attribute that is being changed.

Availability

IBM Security Identity Manager 7.0.

Synopsis

attributeChangeOperation.values[]

Description

This read-only field is an array of objects that must be added, removed, or replaced.

Usage `x = attributeChangeOperation.values[1];`

ContainerSearch

The object represents the search for an organizational container.

Availability

IBM Security Identity Manager 7.0.

Provided by

`com.ibm.itim.script.extensions.model.OrganizationModelExtension`

Constructor

`new ContainerSearch()`

Returns

The newly created and initialized container search object.

Methods**searchByFilter()**

Search for a container with a filter.

searchByURI()

Search for an organizational container by URI within a parent organizational container.

Description

Implements the IBM Security Identity Manager **OrganizationalContainerSearch** class.

ContainerSearch.searchByFilter()

The method represents the search for a container with a filter.

Availability

IBM Security Identity Manager 7.0.

Synopsis

`containerSearch.searchByFilter(profileName, filter, scope)`

Arguments**profileName**

The String name of the organizational container profile to use.

filter LDAP search filter String that defines the criteria for returned containers to meet. The filter must be in the format defined by RFC2254.

scope Optional Int search scope. Use 1 for One Level Scope and 2 for SubTree Scope. One Level Scope is the default scope.

Returns

An array of **DirectoryObjects** representing the results of the search.

Description

This method searches for a container with a filter.

Usage

```
var locationContainer = new ContainerSearch();
// use subtree scope
var thisLocation = locationContainer.searchByFilter("Location",
    "(l=Raleigh)", 2);

// use default one level scope
var otherLocation = locationContainer.searchByFilter("Location",
    "(l=Raleigh)");
```

ContainerSearch.searchByURI()

The method finds an organizational container by URI in a parent organizational container.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
ContainerSearch.searchByURI(containerDN, uri)
```

Arguments

Container DN

String representing the distinguished name of the parent organizational container.

uri String representing the URI of the organizational container.

Returns

A **DirectoryObject** representing the container.

Description

Given the distinguished name of the parent organizational container and the container URI, this method finds the container. If the container is not found, this function returns null. If more than one container is found, this function throws a scripting exception.

Usage

```
var container = (new ContainerSearch()).searchByURI(parentContainer.dn,
    uri);
if (container != null) {
    Enrole.log("script", "Found " + container.getProperty("ou") );}
```

Context

The object represents the context of the currently running workflow process (for example, requestor or subject). Only used for entitlement workflows.

Note: This object type is deprecated. Use workflow JavaScript objects, such as **Process**, **Activity**, and **Relevant Data**.

Some account-specific functions of the context JavaScript extension, including **getService()**, **isAccountDataChanged()**, and **getAccountParameter()** cannot be applicable to operation workflows that are not account related. The context JavaScript extension is not suggested for custom workflows.

Availability

IBM Security Identity Manager 7.0.

Provided by

com.ibm.itim.workflow.script.WorkflowExtension

Context Constants

APPROVED

This constant is used to describe the result of an activity. The member applies only to Approval types of activities.

Usage

```
if (context.getActivityResult() == context.APPROVED) {...
```

REJECTED

This constant is used to describe the result of an activity. This member applies only to Approval types of activities.

Usage

```
if (context.getActivityResult() == context.REJECTED) {...
```

NEWACCOUNT

This constant is used to identify the type of request that triggers the custom workflow run time.

Usage

```
if (context.getProcessType() ==  
context.NEWACCOUNT) {...
```

ACCOUNTDATACHANGE

This constant is used to identify the type of request that triggers the custom workflow in run time.

Usage

```
if (context.getProcessType() ==  
context.ACCOUNTDATACHANGE) {...
```

Methods

getAccountParameter()

Returns the value of an account attribute.

getActivityResult()

Returns the activity result for the current activity.

getActivityResultByID()

Returns the activity result for a specific activity.

getLoopCount()

Returns the loop count for the current loop activity.

getLoopCountByID()

Returns the current loop count for a specific loop activity.

getProcessType()

Returns the type of the request that triggers the custom workflow process.

getRequestee()

Returns the requestee associated with the request as a Person object.

getService()

Returns the target service as a Service entity object.

isAccountDataChanged()

Identifies whether a specific account attribute was changed in the request that triggers the custom workflow process.

Description

The context of the currently running workflow process (for example, requestor or subject) is represented within the JavaScript as an object named context.

Context.getAccountParameter()

The method returns the value of an account attribute.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
context.getAccountParameter(String attributeName)
```

Arguments

attributeName

String representing the attribute name.

Returns

String value of an account attribute.

Description

This member function returns the value of an account attribute as a string.

Usage `parameter=context.getAccountParameter("group");`

Context.getActivityResult()

The method returns the activity result for the current activity.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
context.getActivityResult()
```

Returns

String

Description

This member function returns the activity result for the current activity. The function returns APPROVED or REJECTED. If this function is used to specify a transition condition, the function refers to the activity from which the transition is coming.

Usage `if (context.getActivityResult() == context.APPROVED) {...`

Context.getActivityResultById()

The method returns the activity result for a specific activity.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
context.getActivityResultById(String activityDefinitionID)
```

Arguments

activityDefinitionID

String ID of the activity definition.

Returns

String

Description

This member function returns the activity result for a specific activity. The function returns APPROVED or REJECTED.

```
Usage if (context.getActivityResultByID("1234567890") == context.APPROVED)
{...
```

Context.getLoopCount()

The method returns the loop count for the current loop activity.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
getLoopCount()
```

Returns

Integer of loop count.

Description

This member function returns the loop count for the current loop activity. If this function is called before a loop is started, the loop count is 0. If this activity is called while the loop activity is in process, the loop count is the number of times the loop ran. If this function is called after the loop is completed, the loop count is the total number of times the loop is defined to run.

```
Usage currentiteration = context.getLoopCount();
```

Context.getLoopCountByID()

The method returns the current loop count for a specific loop activity.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
context.getLoopCountByID(String activityDefinitionID)
```

Arguments

activityDefinitionID

ID of the activity definition.

Returns

Integer

Description

This member function returns the current loop count for a specific loop activity. If this function is called before the loop is started, the loop count is 0. If this function is called while the loop activity is in process, the loop count is the number of times the loop ran. If this function is called after the loop is completed, the loop count is the total number of times the loop is defined to run.

```
Usage currentiteration = context.getLoopCount("1234567890");
```

Context.getProcessType()

The method returns the type of the request that triggers the custom workflow process.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
context.getProcessType()
```

Returns
String

Description

This member function returns the type of the request that triggers the custom workflow process. The function returns NEWACCOUNT or ACCOUNTDATACHANGE.

Usage `if (context.getProcessType() == context.NEWACCOUNT) {...`

Context.getRequestee()

The method returns the requestee associated with the request as a person object.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
context.getRequestee();
```

Returns

A DirectoryObject that represents a Person.

Description

This member function returns the requestee associated with the request as a Person object. The requestee is the user who owns the associated, provisioned account.

Usage `requestee = context.getRequestee();`

Context.getService()

The method returns the target service as a service entity object.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
context.getService()
```

Returns

DirectoryObject

Description

This member function returns the target service as a Service entity object. The service entity is the service associated with the provisioned account.

Usage `service = context.getService();`

Context.isAccountDataChanged()

The method identifies whether a specific account attribute was changed in the request that triggers the custom workflow process.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
isAccountDataChanged(String attributeName)
```

Description

This member function identifies whether a specific account attribute was changed in the request that triggers the custom workflow process. If the request that triggers the custom workflow is NEWACCOUNT and the attribute is in the new account parameters, this function returns TRUE. Otherwise,

this function returns FALSE. If the request that triggers the custom workflow is ACCOUNTDATACHANGE and the specified attribute is changed, this function returns TRUE. Otherwise, this function returns FALSE.

Usage `if (context.isAccountDataChanged("group")) {...`

Delegate

The object provides the Delegate JavaScript object for use in the JavaScript environment of delegation notification. The Delegate JavaScript object and their use is described in this section.

Delegate

The Delegate object contains all the information associated with the current delegation operation.

Availability

IBM Security Identity Manager 7.0

Delegation Notification context

Provided by

`com.ibm.itim.script.extensions.DelegateExtension`

Methods

Delegate.getDelegator()

Returns the `DirectoryObject` that represents a system user such as the IBM Security Identity Manager account, whose activities are delegated.

Delegate.getDelegatee()

Returns the `DirectoryObject` that represents a system user such as the IBM Security Identity Manager account, who is selected to be the delegate for the activities of the delegator.

Delegate.getStartDate()

Returns a `Date` that contains the date and time when the delegation starts.

Delegate.getEndDate()

Returns a `Date` that contains the date and time when the delegation ends.

Delegate.getRequester()

Returns the `DirectoryObject` that represents a system user such as the IBM Security Identity Manager account, who initiated the delegation.

Description

The Delegate object is available in the context of a delegation notification. The object retrieves the delegation information in the delegation notification template. The model script extensions are also available in the delegation notification context.

DirectoryObject

The object represents any IBM Security Identity Manager directory object or entity.

Availability

IBM Security Identity Manager 7.0

Constructor

There is no specific constructor for this object. Specific constructors for Account, Person, Role, and Service return DirectoryObject.

For example, new Service() returns a DirectoryObject.

Properties

dn String representing the distinguished name of the entity.

name String representing the logical name of the entity.

profileName

String representing the profile name of the entity.

Methods

addProperty()

Changes the value of the specified property, or adds the specified property if it does not exist. For multivalued objects, addProperty() adds the values to the specified property in the directory object and does not replace them.

getChanges()

Returns the changes made to the entity.

getProperty()

Returns the values of the property specified by the given name.

getPropertyNames()

Returns a list of properties (attributes and relationships).

removeProperty()

Removes the specified property.

setProperty()

Changes the value of the specified property, or adds the specified property if it does not exist.

getPropertyAsDate()

Returns the value of the specified property as a Date.

getPropertyAsString()

Returns the value of the specified property as a String.

Description

This Object represents a Security Identity Manager entity in the JavaScript environment. Each Security Identity Manager entity is wrapped in one of these object classes.

DirectoryObject.addProperty()

The method adds or updates the value for the specified property.

Availability

IBM Security Identity Manager 7.0

Synopsis

directoryObject.addProperty(name, value)

Arguments

name String representing the name of the property to be created or modified.

value The value to add to the property.

Description

This method changes the value of the specified property or adds the specified property if it does not exist. This change is made locally to the script environment, not to the data store. The value can be a single value object or an array of objects. For multivalued objects, `addProperty()` adds the values to the specified property in the directory object and does not replace them. The value type (syntax) of object must be compatible with the syntax of the specified property. This method is available for the following data types:

- `void addProperty(String name, Collection value);`
- `void addProperty(String name, Date value);`
- `void addProperty(String name, Map value);`
- `void addProperty(String name, boolean value);`
- `void addProperty(String name, byte value);`
- `void addProperty(String name, String value);`
- `void addProperty(String name, number value);`
- `void addProperty(String name, char value);`

Usage

```
directoryObject.addProperty("eruid", "jdoe");
```

The `getProperty` method returns a Java array of objects that is stored in a JavaScript `JSONArray` object. Unlike a standard JavaScript array, `JSONArray` objects are used to access members of a Java array. Because Java arrays cannot be resized, the size of a `JSONArray` object cannot be changed. Also, `JSONArray` objects are typed. Setting a `JSONArray` element to the wrong type throws a JavaScript error.

In Security Identity Manager, a `JSONArray` object cannot be passed directly back into a `addProperty` method. The `JSONArray` array might be converted into a standard JavaScript array as follows:

```
jsAliases = new Array();
myPerson = person.get();
aliases = myPerson.getProperty("eraliases");
for (i=0; i < aliases.length; i++) {
  jsAliases[i] = aliases[i];
}
jsAliases[aliases.length] = "myNewAlias";
myPerson.addProperty("eraliases", jsAliases);
person.set(myPerson);
```

DirectoryObject.dn

The field represents the distinguished name of the object.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
directoryObject.dn
```

Description

This read-only field is a string that provides the distinguished name of the object. If the object holds information that was not created, there is no value.

Usage `x = directoryObject.dn;`

DirectoryObject.getChanges()

The method returns the changes made to the entity.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
directoryObject.getChanges()
```

Returns

An array of change objects. If there are no changes, an empty array is returned. Each element in the array is an `AttributeChangeOperation`.

Description

This method returns the changes made to the entity. These changes are represented by change objects with the following members:

attr String name of the attribute that is being changed.

op An integer that identifies the type of change that is being made. The enumerated values are 1 for add, 2 for replace, and 3 for remove.

values An array of objects that must be either added, removed, or replaced.

The changes are returned as an array of these change objects. If there are no changes, an empty array is returned.

Usage

```
changes = directoryObject.getChanges();
for (i = 0; i < changes.length; i++) {
    name = changes[i].attr;
    if (changes[i].op == 1) {
        ...
    } else if (changes[i].op == 2) {
        ...
    } else {
        ...
    }
};
```

DirectoryObject.getProperty()

The method returns the values of the property specified by the given name.

Availability

IBM Security Identity Manager 7.0

Synopsis

```
directoryObject.getProperty(name)
```

Arguments

name String representing the name of the property to return.

Returns

Either a `String` or a `DirectoryObject`. The type of object returned depends on the property obtained. If the specified property does not exist, an empty array is returned.

Description

This method returns the values of the property specified by the given

name. The type of object returned depends on the property obtained. If the specified property does not exist, an empty array is returned.

The property name can be either an attribute name or a relationship name. For an attribute name, the return is a `String[]`; for a relationship name, an array of `DirectoryObjects` is returned. If an attribute and a relationship have the same name, then the attribute is returned. For example, an `Account` entity has both an `owner` attribute and an `owner` relationship.

Usage When operating on an account, for example, the user ID property can return a `String`, where the owner property can return another entity (`DirectoryObject`). The owner entity can then be operated on with the `getProperty()` member to obtain information about it.

```
userids = directoryObject.getProperty("eruid");
if (userids.length > 0)
    userid = userids[0];
owner = directoryObject.getProperty("owner");
if (owner.length > 0)
    ownerName = owner.getProperty("name")[0];
```

Note: These statements assume there is at least one value returned. If no values are returned, an array indexing violation occurs.

The `getProperty` method returns a Java array of objects that is stored in a JavaScript `JavaArray` object. Unlike a standard JavaScript array, `JavaArray` objects are used to access members of a Java array. Since Java arrays cannot be resized, the size of a `JavaArray` object cannot be changed. Also, `JavaArray` objects are typed. Setting a `JavaArray` element to the wrong type throws a JavaScript error.

DirectoryObject.getPropertyAsDate()

The method returns the value of the property specified by the given name as a date object.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
directoryObject.getPropertyAsDate(name)
```

Arguments

name String representing the name of the property to return.

Returns

A `Date` object. If the specified property does not exist, current date is returned.

Description

This method returns the value of the property specified by the given name as a date object. If the specified property does not exist, current date is returned.

Usage

```
var createDate = directotyObject. getPropertyAsDate("ercreatedate");
```

DirectoryObject.getPropertyAsString()

The method returns the value of the property specified by the given name as a string.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
directoryObject.getPropertyAsString(name)
```

Arguments

name String representing the name of the property to return.

Returns

A String object. If the specified property does not exist, empty is returned. If the specified property has multiple values, only the first value is returned.

Description

This method returns the value of the property specified by the given name as a String object. If the specified property does not exist, empty string is returned. If the specified property has multiple values, only the first value is returned.

Usage

```
var name = directotyObject.getPropertyAsString("erservicename");
```

DirectoryObject.getPropertyNames()

The method returns a list of properties, such as attributes and relationships.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
directoryObject.getPropertyNames()
```

Returns

An array of Strings.

Description

This method returns a list of properties as an array of Strings. A property can be either an attribute or a relationship.

Usage `properties = directoryObject.getPropertyNames();`

DirectoryObject.name

The field represents the logical name of the object.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
directoryObject.name
```

Description

This read-only field is a string that provides the logical name of the object, represented as a String. The physical attribute used as the name can be different for each type of object.

Usage `x = directoryObject.name;`

DirectoryObject.profileName

The field returns the object profile name.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
directoryObject.profileName()
```

Description

This read-only field is a string that provides the profile name of the object, represented as a String.

Usage

```
x = directoryObject.profileName;
```

DirectoryObject.removeProperty(name)

The method removes the property specified by the given name.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
directoryObject.removeProperty(name)
```

Arguments

name String representing the name of the property to remove.

Description

This method removes the specified property. This change is made locally to the script environment, not to the data store. The property name can be either an attribute name or a relationship name.

Usage *directoryObject*.removeProperty("eruid");

DirectoryObject.removeProperty(name,value)

The method removes the value from the specified property.

Availability

IBM Security Identity Manager 7.0

Synopsis

```
directoryObject.removeProperty(name, value)
```

Arguments

name String representing the name of the property to be modified.

value The value to remove from the property.

Description

This method removes the specified value from property if it exists. This change is made locally to the script environment, not to the data store. The value can be a single value object or an array of objects. For multivalued objects, `removeProperty(name,value)` removes the values from the specified property in the directory object. The object type of the value (syntax) must be compatible with the syntax of the specified property. This method is available for the following data types:

- void `removeProperty(String name, Collection value);`
- void `removeProperty(String name, Date value);`
- void `removeProperty(String name, Map value);`
- void `removeProperty(String name, boolean value);`

- void removeProperty(String name, byte value);
- void removeProperty(String name, String value);
- void removeProperty(String name, Number value);

Usage

```
var directoryObject = Entity.get();
directoryObject.removeProperty("eraliases", "jdoe");
Entity.set(directoryObject);
```

DirectoryObject.setProperty()

The method sets the value of the specified property.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
directoryObject.setProperty(name, value)
```

Arguments

name String representing the name of the property to be created or modified.

value The value to set the property to.

Description

This method changes the value of the specified property, or adds the specified property if it does not exist. This change is made locally to the script environment, not to the data store. The value can be a single value object or an array of objects. The value type (syntax) of object must be compatible with the syntax of the specified property. This method is available for the following data types:

- void setProperty(String name, Collection value);
- void setProperty(String name, Date value);
- void setProperty(String name, Map value);
- void setProperty(String name, boolean value);
- void setProperty(String name, byte value);
- void setProperty(String name, String value);
- void setProperty(String name, number value);
- void setProperty(String name, char value);

Usage *directoryObject.setProperty("eruid", "jdoe");*

The getProperty method returns a Java array of objects that is stored in a JavaScript JSONArray object. Unlike a standard JavaScript array, JSONArray objects are used to access members of a Java array. Since Java arrays cannot be resized, the size of a JSONArray object cannot be changed. Also, JSONArray objects are typed. Setting a JSONArray element to the wrong type throws a JavaScript error.

In IBM Security Identity Manager, a JSONArray object cannot be passed directly back into a setProperty method. The JSONArray array into a standard JavaScript array as follows:

```
jsAliases = new Array();
myPerson = person.get();
aliases = myPerson.getProperty("eraliases");
for (i=0; i < aliases.length; i++) {
    jsAliases[i] = aliases[i];
}
```

```
jsAliases[aliases.length] = "myNewAlias";  
  
myPerson.setProperty("eralias", jsAliases);  
person.set(myPerson);
```

EmailContext

The object provides access to contextual information specific to a type of notification that is sent.

Some methods for accessing information change are based upon the listed notification types. (The Reminder/Approval/RFI/WorkOrder/ComplianceAlert Notification does not support this.)

- Activity Timeout Template
- Change Account Template
- Compliance Template
- New Account Template
- New Password Template
- Process Completion Template
- Process Timeout Template
- Restore Account Template
- Suspend Account Template

Availability

IBM Security Identity Manager 7.0

Provided by

com.ibm.itim.workflow.script.EmailContextExtension

Synopsis

Call methods documented in this section as an EmailContext object. For example:

```
notificationActivity=EmailContext.getActivity();  
owner=EmailContext.getAccountOwnerName()
```

Common methods

These methods are available for all types of notifications:

getActivity()

Returns information about the most recent running activity. (Returns the ActivityInfo0C Java Object. To get the activity information in JavaScript object, use the object, 'activity'.

getActivity(java.lang.String actDefID)

Returns information about the activity with the specified definition ID. (Returns the ActivityInfo0C Java Object.) This obtains information by using the Process.\$dataName.get() workflow process. To get the activity information in JavaScript object, use 'process.getActivity(java.lang.String actDefID)'.

getParentProcess()

Returns information about the parent process of the currently running process. (Returns the ProcessInfo0C Java object.) To get the process information of the parent process in JavaScript object, use 'process.getParent()'.

getProcess()

Returns the information about the currently running process. (Returns the `ProcessInfo0C` Java object.) To get the process information of the parent process in JavaScript object, use the object, 'process'.

getRootProcess()

Returns information about the root process of the current running process. (Returns the `ProcessInfo0C` Java object.) To get the process information of the parent process in JavaScript object, use 'process.getRootProcess ()'.

Account notification methods

These methods are available for all types of account notifications:

getAccountOwnerName()

Returns the account owner name for the account.

getAccountServiceName()

Returns the account service name for the account.

getAccountServiceProfileName()

Returns the account service profile name for the account.

getAccountUserId()

Returns the account user ID for the account.

hasNewAccess()

Returns true if the account has new access and false otherwise.

hasRemovedAccess()

Returns true if the account removed access and false otherwise.

getAccountNewAccessAsString()

Returns String that contains list of new access separated by commas.

getAccountNewAccessList()

Returns Array of String that contains the new access.

getAccountRemovedAccessAsString()

Returns a string that contains the list of removed access separated by commas.

getAccountRemovedAccessList()

Returns Array of String that contains the list of removed access.

Account Suspend/Deprovisioning Notification Methods:

These methods are only available for all types of account suspend/deprovision notifications:

getAction()

Returns the action taken against the service (resource) itself.

getReason()

Returns a descriptive reason for the deprovision.

Account New/Modify/Restore Notification Methods:

These methods are only available for all types of notifications for new, modified, and restored accounts:

showPassword()

Returns whether to display the password when the user is notified of their new account.

getAccountPassword()

Returns the account password for the account. .

getPasswordExpirePeriod()

Returns the password delivery expiration period.

getPasswordRetrievalUrl()

Returns the password delivery URL in order to retrieve the password with the accounts shared secret.

getTransactionId()

Returns the password delivery transaction ID for picking up the password created for this account.

Account Password Change Notification Methods:

These methods are available for all types of account password change notifications:

getAccountPassword()

Returns the account password for the account.

getPasswordExpirePeriod()

Returns the password delivery expiration period.

getPasswordRetrievalUrl()

Returns the password delivery URL in order to retrieve the password with the accounts shared secret.

getTransactionId()

Returns the password delivery transaction ID for picking up the password created for this account.

Enrole

The object contains the general methods.

Availability

- All JavaScript contexts
- IBM Security Identity Manager 7.0

Provided by

com.ibm.itim.script.extensions.EnroleExtension

Methods**generatePassword()**

Generates a password for a specific service.

getAttributeValue()

Get a single value attribute value.

getAttributeValues()

Get a multi-valued attribute value.

localize()

Localized message specified in <Message> XML format.

log()

Logs a message to the IBM Security Identity Manager log at ERROR level.

logError()

Logs the specified text to the IBM Security Identity Manager message log (msg.log) at ERROR level.

logInfo()

Logs the specified text to the IBM Security Identity Manager message log (msg.log) at INFO level.

logWarning()

Logs the specified text to the IBM Security Identity Manager message log (msg.log) at WARN level.

toGeneralizedTime()

Converts a time or date to generalized time format.

toMilliseconds()

Converts a String in generalized time format to an integer value in milliseconds.

traceMax()

Logs the specified text to the IBM Security Identity Manager trace log (trace.log) at DEBUG_MAX level.

traceMid()

Logs the specified text to the IBM Security Identity Manager trace log (trace.log) at DEBUG_MID level.

traceMin()

Logs the specified text to the IBM Security Identity Manager trace log (trace.log) at DEBUG_MIN level.

Description

Provides some common utilities for use in many different scripting contexts.

Enrole.generatePassword()

The method generates a new valid password for an account.

Availability

generatePassword() requires a service to work, so generatePassword() is only available when the ServiceExtension is used.

Synopsis

```
Enrole.generatePassword()
```

Returns

A String that is a valid password for the Service DirectoryObject stored in the "service" variable.

Description

This method generates a new valid password for a service.

Enrole.getAttributeValue()

The method retrieves the attribute's value.

Availability

Deprecated as of IBM Security Identity Manager 7.0. Replace with DirectoryObject.getProperty()

Synopsis

```
Enrole.getAttributeValue(name, defaultValue)
```

Arguments

name String representing the name of the property to return.

defaultValue

Default value to return if there is no value to return.

Returns

An Object. The type of object returned depends on the property obtained. If the specified property does not exist, the default value is returned.

Description

This method retrieves the value of the specified property.

Enrole.getAttributeValues()

The method retrieves a multi-valued attribute value.

Availability

Deprecated as of IBM Security Identity Manager 7.0. Replace with `DirectoryObject.getProperty()`

Synopsis

`Enrole.getAttributeValues(name)`

Arguments

name String representing the name of the property to return.

Returns

An array of objects. The type of object returned depends on the property obtained. If the specified property does not exist, an empty array is returned.

Description

This method retrieves the value of the specified property.

Enrole.localize()

The method localizes a message specified in <Message> XML format.

Availability

IBM Security Identity Manager 7.0

Synopsis

`Enrole.localize(String xmlMsg, String localStr)`

Arguments**xmlMsg**

A message specified in XML.

localStr

A String that represents the locale to be used for globalization.

Returns

AA localized message.

Description

This method globalizes an XML message to the specified locale.

Enrole.log()

The method logs messages to the IBM Security Identity Manager message log (`msg.log`).

Availability

IBM Security Identity Manager 7.0

Synopsis

```
Enrole.log(category, message);
```

Arguments**category**

The category of the log entry, entered as a String. The category argument can be used or it can be left empty, but the argument must not be null.

message

The message to be logged, entered as a String.

Description

Logs a message to the IBM Security Identity Manager log at error level.

Usage

```
var roleDN = ..;(DN of role)
var role = new Role(roleDN);

// Put next statement on one line

Enrole.log("script", "The role name is
"+ role.getProperty("errolename")[0]);
```

Use the following new methods in IBM Security Identity Manager 7.0 to provide greater adaptability, control, or flexibility over the `Enrole.log()` method:

- `logError()`
- `logInfo()`
- `logWarning()`
- `traceMax()`
- `traceMid()`
- `traceMin()`

Enrole.logError()

The method logs text messages to the IBM Security Identity Manager message log (`msg.log`) with a message severity level of ERROR.

Availability

IBM Security Identity Manager 7.0

Synopsis

```
Enrole.logError(component, method, message);
```

Arguments**component**

The component of the log entry, entered as a String. The component can be any string. Logging can be controlled for components by setting specific log levels in the `enRoleLogging.properties` file.

method

The string to display in the "Method" record of the message log. Useful to point where in the script the message originated.

message

The string to represent the contents of the message log to be written to the log file.

Description

Writes an error message to the IBM Security Identity Manager message log (msg.log).

Usage An example to write a msg.log message at ERROR level with the component name com.ibm.myExtension and the method name postScriptOfAccountCreate:

```
var userName = "Joe";
// below is a single line
Enrole.logError("com.ibm.myExtension","postScriptOfAccountCreate",
"Recording error message after unsuccessful account creation for user "
+ userName + ".");
```

Enrole.logInfo()

The method logs text messages to the IBM Security Identity Manager message log (msg.log) with a message severity level of INFO.

Availability

IBM Security Identity Manager 7.0

Synopsis

```
Enrole.logInfo(component, method, message);
```

Arguments**component**

The component of the log entry, entered as a String. The component can be any string. Logging can be controlled for components by setting specific log levels in the enRoleLogging.properties file.

method

The string to display in the "Method" record of the message log. Useful to point where in the script the message originated.

message

The string to represent the contents of the message log to be written to the log file.

Description

Writes an error message to the IBM Security Identity Manager message log (msg.log).

Usage An example to write a msg.log message at INFO level with the component name com.ibm.myExtension and the method name postScriptOfAccountCreate:

```
var userName = "Joe";
// below is a single line
Enrole.logInfo("com.ibm.myExtension","postScriptOfAccountCreate",
"Recording information message after account creation for user " + userName + ".");
```

Enrole.logWarning()

The method logs text messages to the IBM Security Identity Manager message log (msg.log) with a message severity level of WARN.

Availability

IBM Security Identity Manager 7.0

Synopsis

```
Enrole.logWarning((component, method, message));
```

Arguments

component

The component of the log entry, entered as a String. The component can be any string. Logging can be controlled for components by setting specific log levels in the `enRoleLogging.properties` file.

method

The string to display in the "Method" record of the message log. Useful to point where in the script the message originated.

message

The string to represent the contents of the message log to be written to the log file.

Description

Writes a warning message to the IBM Security Identity Manager message log (`msg.log`).

Usage An example to write a `msg.log` message at WARN level with the component name `com.ibm.myExtension` and the method name `postScriptOfAccountCreate`:

```
var userName = "Joe";  
// below is a single line  
Enrole.logWarning("com.ibm.myExtension","postScriptOfAccountCreate",  
"Recording warning message after account creation for user " + userName + ".");
```

Enrole.toGeneralizedTime()

The method converts a time or date to generalized time format.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
Enrole.toGeneralizedTime(time)
```

Arguments

time Integer time in milliseconds or a Date object.

Description

This method converts a time or date to generalized time format. Can be used in either Identity Policies or in default entitlements.

Usage `genTime = Enrole.toGeneralizedTime(seconds);`

Enrole.toMilliseconds()

The method converts a string in generalized time format to an integer value in milliseconds.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
Enrole.toMilliseconds(genTime)
```

Arguments

genTime

String in generalized time format.

Description

This method converts a String in generalized time format to an integer value in milliseconds.

Usage `seconds = Enrole.toMilliseconds(genTime);`

Enrole.traceMax()

The method logs text messages to the IBM Security Identity Manager trace log (trace.log) with a message severity level of DEBUG_MAX.

Availability

IBM Security Identity Manager 7.0

Synopsis

`Enrole.traceMax((component, method, message);`

Arguments**component**

The component of the log entry, entered as a String. The component can be any string. Logging can be controlled for components by setting specific log levels in the `enRoleLogging.properties` file.

method

The string to display in the "Method" record of the message log. Useful to point where in the script the message originated.

message

The string to represent the contents of the trace message to be written to the log file.

Description

Writes a DEBUG_MAX message to the IBM Security Identity Manager trace log (trace.log).

Usage An example to write a trace.log message at DEBUG_MAX level with the component name `com.ibm.myExtension` and the method name `postScriptOfAccountCreate`:

```
var userName = "Joe";
// below is a single line
Enrole.traceMax("com.ibm.myExtension","postScriptOfAccountCreate",
"Recording DEBUG_MAX trace message after account creation for user " + userName + ".");
```

Enrole.traceMid()

Logs text messages to the IBM Security Identity Manager trace log (trace.log) with a message severity level of DEBUG_MID.

Availability

IBM Security Identity Manager 7.0

Synopsis

`Enrole.traceMid((component, method, message);`

Arguments**component**

The component of the log entry, entered as a String. The component can be any string. Logging can be controlled

for components by setting specific log levels in the `enRoleLogging.properties` file.

method

The string to display in the “Method” record of the message log. Useful to point where in the script the message originated.

message

The string to represent the contents of the trace message to be written to the log file.

Description

Writes a `DEBUG_MID` message to the IBM Security Identity Manager trace log (`trace.log`).

Usage An example to write a `trace.log` message at `DEBUG_MID` level with the component name `com.ibm.myExtension` and the method name `postScriptOfAccountCreate`:

```
var userName = "Joe";  
// below is a single line  
Enrole.traceMid("com.ibm.myExtension","postScriptOfAccountCreate",  
"Recording DEBUG_MID trace message after account creation for user " + userName + ".");
```

Enrole.traceMin()

The method logs text messages to the IBM Security Identity Manager trace log (`trace.log`) with a message severity level of `DEBUG_MIN`.

Availability

IBM Security Identity Manager 7.0

Synopsis

```
Enrole.traceMin(component, method, message);
```

Arguments

component

The component of the log entry, entered as a `String`. The component can be any string. Logging can be controlled for components by setting specific log levels in the `enRoleLogging.properties` file.

method

The string to display in the “Method” record of the message log. Useful to point where in the script the message originated.

message

The string to represent the contents of the trace message to be written to the log file.

Description

Writes a `DEBUG_MIN` message to the IBM Security Identity Manager trace log (`trace.log`).

Usage An example to write a `trace.log` message at `DEBUG_MIN` level with the component name `com.ibm.myExtension` and the method name `postScriptOfAccountCreate`:

```
var userName = "Joe";  
// below is a single line  
Enrole.traceMin("com.ibm.myExtension","postScriptOfAccountCreate",  
"Recording DEBUG_MIN trace message after account creation for user " + userName + ".");
```

Error

This object contains a script error description to notify the calling code of an exceptional runtime condition.

When an error is returned from a script evaluation, it is converted to a Java exception and thrown from the script evaluator class.

Availability

IBM Security Identity Manager 7.0

Provided by

com.ibm.itim.script.extensions.EnroleExtension

Methods

setMessage()

Sets the message for the error.

getMessage()

Retrieves the error message for the error.

setErrorCode()

Sets the error code for the error.

getErrorCode()

Retrieves the error code for the error.

Usage

```
var sn = subject.getProperty("sn");
if(sn == null || sn.length == 0) {
    error.setMessage("sn was missing");
    return error;
} else {
    return sn[0];
}
```

Error.setMessage()

The method sets the message for the error.

Availability

IBM Security Identity Manager 7.0

Synopsis

```
error.setMessage(String msg)
```

Arguments

msg String representing the message to be set.

Description

This method sets the text for an error message. The function takes in one String parameter.

Usage error.setMessage("sn was missing");

Error.getMessage()

The method retrieves the message set for an error.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
error.getMessage()
```


Returns

String message for an error.

Description

This method retrieves the text of an error message.

Usage `messageValue = error.getMessage();`

Error.setErrorCode()

The method sets the error code for the error.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
error.setErrorCode(int code)
```

Arguments

code Integer representing the error code.

Description

This method sets the error code for an error message. The function takes in one **Int** parameter.

Usage `error.setErrorCode(1);`

Error.getErrorCode()

The method retrieves the error code set for an error.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
error.getErrorCode()
```

Returns

Integer value for an error code.

Description

This method retrieves the error code of an error message.

Usage `errorCodeValue = error.getErrorCode();`

ExtendedPerson

This object extends the Person object with the ownership type information for account adoption.

Availability

IBM Security Identity Manager 7.0.

Inherited from

Person.

Provided by

`com.ibm.itim.script.extensions.model.PersonModelExtension`

Ownership type

INDIVIDUAL

String constant represents the default ownership type.

Constructor

new ExtendedPerson(dn)

Arguments

DN DN string of a specific person entity.

Returns

The new ExtendedPerson object that represents a person with the DN and INDIVIDUAL ownership type.

new ExtendedPerson(dn, ownershipType)

Arguments

DN DN string of a specific person entity.

ownershipType

String representing one of the ownership types configured in IBM Security Identity Manager.

Returns

The new ExtendedPerson object that represents a person with the DN and ownership type. If the ownership type is invalid, it throws ScriptException.

new ExtendedPerson(person)

Arguments

person

Person object.

Returns

The new ExtendedPerson object that represents the person with the INDIVIDUAL ownership type.

new ExtendedPerson(person, ownershipType)

Arguments

person

Person object.

ownershipType

String representing one of the ownership types configured in IBM Security Identity Manager.

Returns

The new ExtendedPerson object that represents the person with the ownership type. If the ownership type is invalid, it throws ScriptException.

Methods

getOwnershipType()

Returns the ownership type.

setOwnershipType()

Sets the ownership type.

ExtendedPerson.getOwnershipType()

The method return the ownership type as a string.

Availability

IBM Security Identity Manager 7.0.

Synopsis

ExtendedPerson.getOwnershipType()

Returns

String.

Description

This method returns the ownership type.

Usage

```
var ownershipType = extendedPerson.getOwnershipType();
```

ExtendedPerson.setOwnershipType()

The method sets the value of the ownership type.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
ExtendedPerson.setOwnershipType(value)
```

Arguments

value A string represents one of the ownership types configured in IBM Security Identity Manager.

Description

This method updates the ownership type. If the ownership type is invalid, it throws `ScriptException`.

Usage

```
var extendedPerson.setOwnershipType("System");
```

IdentityPolicy

The object represents the identity policy entity.

Availability

IBM Security Identity Manager 7.0
Identity Policy context

Provided by

```
com.ibm.itim.policy.script.IdentityPolicyExtension
```

Methods**getNextCount()**

Returns a number that can be appended to the end of a user name to make that user name unique.

userIDExists()

Checks if requested UID is already in use.

Description

This object represents a IBM Security Identity Manager Policy entity.

IdentityPolicy.getNextCount()

The method gets a number that can be appended to the end of a user name to make that user name unique. `ServiceExtension` must be loaded for `getNextCount()` to work.

Availability

IBM Security Identity Manager 7.0

Synopsis

`IdentityPolicy.getNextCount(baseId)`

Arguments

baseId

The base user name.

Returns

A number that can be appended to the end of a user name to make the user name unique. Returns -1 if the user name is already unique and -2 if an error occurs.

Description

This method checks whether requested UID is already in use.

Usage

```
num = IdentityPolicy.getNextCount(baseId);  
return baseId + num;
```

IdentityPolicy.userIDExists()

The method checks if the requested UID is in use.

Availability

IBM Security Identity Manager 7.0.

Synopsis

`IdentityPolicy.userIDExists(uid, checkAllServices, checkRecycleBin)`

Arguments

uid User identity.

checkAllServices

If set to true, all service instances are checked to see whether the uid is used on an account of any service type. If set to false, only the target service instance is checked. This argument is optional. Default value is false.

checkRecycleBin

If set to true, the recycle bin is checked for any deleted accounts. This parameter is intended to work in conjunction with the **checkAllServices** parameter. Set this parameter true only when the **checkAllServices** parameter is also set to true. This argument is optional. Default value is false.

Returns

True if the user ID exists, false otherwise.

Description

This method checks whether the requested UID is in use.

Usage

```
// To create a user ID without checking for it in the recycle bin but  
// checking it against all services.  
tf = IdentityPolicy.userIDExists("jason_jones", true, false);
```

PackagedApprovalDocument

A relevant data object used in multi-item approval, used exclusively in user recertification workflows. This object is made up of multiple `PackagedApprovalItem` objects from the user recertification approval and allows for searching and retrieving recertification items.

Availability

IBM Security Identity Manager 7.0.

Constructor

```
new PackagedApprovalDocument()
```

Constructs an empty approval document object. Instances might also be obtained in user recertification workflow and notifications by accessing the relevant data item "ApprovalDocument." For example, `ApprovalDocument.get()` returns a `PackagedApprovalDocument` in a user recertification workflow.

Properties

TYPE_ACCOUNT

A constant for approval items that are accounts.

TYPE_GROUP

A constant for approval items that are groups on other services but are not defined as an access.

TYPE_GROUP_ACCESS

A constant for approval items that are groups and also defined as accesses.

TYPE_ITIM_GROUP

A constant for approval items that are groups on services of type ITIM Service.

TYPE_ROLE

A constant for approval items that are roles.

Methods

addItem(PackagedApprovalItem item)

Returns a Boolean flag that indicates that a `PackagedApprovalItem` item is added in this approval document.

containsDecisionCode(decisionCode)

Returns a Boolean flag that indicates whether any of the items in this document that allow for decisions contain the specified decision code string. Valid decision codes are `activity.APPROVED` and `activity.REJECTED`.

getDecisionItemCountByType(type)

Returns the number of items in this document that support decisions and have the specified type. The types are defined as constants on this object, such as `TYPE_ROLE` or `TYPE_ACCOUNT`. This method considers all approval items in the document that supports decisions, including children of top-level items.

getDecisionItemCountByType(type, includeChildren)

Returns the number of items in this document that support decisions and have the specified type. The types are defined as constants on this object, such as `TYPE_ROLE` or `TYPE_ACCOUNT`. Depending on the value the `includeChildren` flag, this method

might also count all items in this document, including any items that are children of the top-level items.

getItemCountByType(type)

Returns the number of items in this document that are of the specified type. The types are defined as constants on this object, such as TYPE_ROLE or TYPE_ACCOUNT. This method considers all approval items in the document, including children of top-level items.

getItemCountByType(type, includeChildren)

Returns the number of items in this document that are of the specified type. The types are defined as constants on this object, such as TYPE_ROLE or TYPE_ACCOUNT. Depending on the value of the includeChildren flag, this method might also count all items in this document, including any items that are children of the top-level items.

getItemCountByTypeAndDecision(type, decisionCode)

Returns the number of items in this document that are of the specified type and that allow for decisions and contain the specified decision code string. The types are defined as constants on this object, such as TYPE_ROLE or TYPE_ACCOUNT. Valid decision codes are activity.APPROVED and activity.REJECTED. This method considers only top-level approval items and does not count the children of those items.

getItemsByType(type)

Returns the top-level items in this approval document that have the specified type as an array of PackagedApprovalItem objects. The types are defined as constants on this object, such as TYPE_ROLE or TYPE_ACCOUNT.

getItemsByTypeAndDecision(type, decisionCode)

Returns the top-level items in this approval document that have the specified type. If decisions are allowed, it contains the specified decision code string as an array of PackagedApprovalItem objects. The types are defined as constants on this object, such as TYPE_ROLE or TYPE_ACCOUNT. Valid decision codes are activity.APPROVED and activity.REJECTED.

removeItem(String identifier)

Returns a Boolean flag that indicates that a PackagedApprovalItem that corresponds to the identifier is removed from this approval document.

setDecisionCodeForAllItems(decisionCode)

Sets the specified decisionCode on all items in this document, including any children of top-level items. Any items that do not support decisions are skipped. Valid decision codes are activity.APPROVED and activity.REJECTED.

Description

The object represents the multi-item approval document in the JavaScript environment.

PackagedApprovalItem

A relevant data object used in IBM Security Identity Manager multi-item approval, used exclusively in user recertification workflows. This object represents the individual roles, accounts, and groups that are presented to the user during the recertification process. Some items might contain a decision code that indicates the choice of the approvers for that item. Each item also contains a list of children that is used to represent relationships between accounts and groups.

Availability

IBM Security Identity Manager 7.0.

Constructor

```
new PackagedApprovalItem(itemType, value)
```

Constructs a `PackagedApprovalItem` object that does not support decisions and is read-only during the recertification approval activity. The parameters are an item type constant and value, where the value is a `DirectoryObject` that matches the type, such as `Role` or `Account`.

```
new PackagedApprovalItem(itemType, value, decisionCode)
```

Constructs a `PackagedApprovalItem` object that supports decisions. The **decisionCode** parameter is either `activity.APPROVED`, `activity.REJECTED`, or `null`, where `null` indicates that a decision is required but not yet specified.

For example:

```
new PackagedApprovalItem(PackagedApprovalDocument.TYPE_ACCOUNT, acctObj)
```

```
new PackagedApprovalItem(PackagedApprovalDocument.TYPE_ROLE, roleObj, activity.APPROVED)
```

Properties

DECISION_NOT_APPLICABLE

A constant for approval items that do not support decisions and are read-only during the recertification.

Methods

getItemTypeString()

Returns the type of the item, where the constant values are defined on the `PackagedApprovalDocument` object (`TYPE_ROLE`, `TYPE_ACCOUNT`, `TYPE_GROUP`, `TYPE_GROUP_ACCESS`).

getDecisionCode()

Returns the decision code for this item, where the possible values are `activity.APPROVED` and `activity.REJECTED`. This method might also return `PackagedApprovalItem.DECISION_NOT_APPLICABLE` if this item is for informational purposes only, or `null` if the decision is not yet specified.

getValue()

Returns a `DirectoryObject` for the role, account, or group of this item.

getChildItems()

Returns an array of `PackagedApprovalItem` objects that are the children of this item. For example, account items can have groups as their children.

getChildItemsByDecision(decisionCode)

Returns an array of `PackagedApprovalItem` objects that are the

children of this item and have the specified decision code, such as `activity.APPROVED` or `activity.REJECTED`.

Description

The Object represents the Security Identity Manager multi-item approval element in the JavaScript environment.

Participant

Workflow participant entity, which specifies an activity participant. In a mail node, this entity specifies the mail recipient.

Participant applies only to manual activity types, including Approval, RFI, WorkOrder, and Mail.

The participant of an activity can be specified during workflow design as Custom Defined Participant. In this case, the Participant JavaScript object can be used to construct the appropriate participant based on the process context.

Availability

IBM Security Identity Manager 7.0

Provided by

`com.ibm.itim.workflow.script.WorkflowExtension`

Constructor

`new Participant(type, dn)`

Arguments

type Code that categorizes the participant type.

dn Optional DN of a specific entity.

Returns

The newly created and initialized participant object.

Properties

implementation

This property contains JavaScript that returns participant when the participant type is Custom.

name Identifies the participant.

type Code that categorizes the participant type.

Description

The participant specifies an activity participant. Participant applies only to manual activity types, including Approval, RFI, Work Order and Mail activities. The participant of an activity or recipient of a mail activity can be specified during workflow design as Custom Defined Participant. In this case, the Participant JavaScript object can be used to construct the appropriate participant based on the process context.

Usage

```
//assume person is one of the relevant data in the workflow
//process for the target user involved
if( person.get().getProperty("title")[0]=="Manager" )
    return new Participant(ParticipantType.SYSTEM_ADMIN);
else
    return new Participant(ParticipantType.SUPERVISOR);
```



```

//assume person is one of the relevant data in the workflow
//process for the target user involved
if( person.get().getProperty("title")[0]=="Manager")
    return new Participant(ParticipantType.USER, person.get().dn);
else
    ...

```

Participant.implementation

The field represents the custom defined participant.

Availability

IBM Security Identity Manager 7.0.

Synopsis

participant.implementation

Description

This read-only field is a string that provides the custom-defined participant, which contains the JavaScript code to return the participant.

Usage `x = participant.implementation;`

Participant.name

The field represents the DN of the participant.

Availability

IBM Security Identity Manager 7.0.

Synopsis

participant.name

Description

This read-only field is a Distinguished Name that identifies the participant. It is only applicable to participant types of ROLE and USER.

Usage `x = participant.name;`

Participant.type

the field represents the code that categorizes the participant type.

Availability

IBM Security Identity Manager 7.0.

Synopsis

participant.type

Description

This read-only field is a string that represents a code that categorizes the participant type.

Usage `x = participant.type;`

ParticipantType

An entity that represents the workflow participant type constants.

Availability

IBM Security Identity Manager 7.0.

Provided by

`com.ibm.itim.workflow.script.WorkflowExtension`

Properties

DOMAIN_ADMIN

Participant type for the domain administrator of the organizational container. It is associated with the Subject account service (as specified by the Subject context in the workflow properties window).

```
participant = new Participant(ParticipantType.DOMAIN_ADMIN);
```

REQUESTOR

Participant type for the person that initiated the request. If a person initiates a change request for a person that triggers policy enforcement, the participant is the person that requests the change. For data loads, the participant is the system user. Use the Update Property page from the **Appliance Dashboard** of the IBM Security Identity Manager virtual appliance console to set the following property in `enRole.properties` to true. See Managing the server properties. An approval request that has the requester as the participant is automatically approved by the system:

```
participant = new Participant(ParticipantType.REQUESTOR);
```

REQUESTEE

Participant type for the person designated as the requestee in the owner field of the relevant data.

```
participant = new Participant(ParticipantType.REQUESTEE);
```

ROLE Participant type for a specific organizational role. All user members of the role and its child roles are notified and are eligible to respond, the first response triggers the workflow to continue. In other words, specifying a role cannot be used to require multiple participants to approve the request.

```
participant = new Participant(ParticipantType.ROLE, roleDN);
```

ROLE_OWNER

Participant type for the owner of the role (if specified). The Role is resolved based on the owners specified in the `OrgRole` listed as an input parameter for the operational workflow operation. If there is no `OrgRole` specified as an input parameter in the workflow, the participant is not resolved.

```
participant = new Participant(ParticipantType.ROLE_OWNER);
```

SERVICE_OWNER

Participant type for the owner of the service (if specified). The Service is resolved based on the account object from the workflow relevant data that is marked as "Subject" in the properties window.

```
participant = new Participant(ParticipantType.SERVICE_OWNER);
```

SOD_POLICY_OWNER

Participant type for the owners of the separation of duty policy (if specified). The owners are resolved based on the `SeparationOfDutyRuleViolation` object from the workflow relevant data that is marked as "Subject" in the properties window. If there is no `SeparationOfDutyRuleViolation` specified as the Subject of the workflow, the participant is not resolved.

The `SOD_POLICY_OWNER` participant type is used only in the `approveSoDViolation` global operation.

```
participant = new Participant(ParticipantType.SOD_POLICY_OWNER);
```

SPONSOR

Participant type for the person designated as the sponsor with the sponsor relationship for the requestee (as marked in relevant data).

```
participant = new Participant(ParticipantType.SPONSOR);
```

SUPERVISOR

Participant type for the supervisor or manager of the requestee. If none is specified for the requestee, then the supervisor designated on the organizational container of the requestee becomes the participant. If no supervisor is specified for the organizational container of the requestee, then the next level up is checked for a supervisor. The search continues up the tree until the top of the organization is reached. If no supervisor is found, the participant is unresolved.

```
participant = new Participant(ParticipantType.SUPERVISOR);
```

SYSTEM_ADMIN

Participant type for a member of the Security Identity Manager System Administrator group.

```
participant = new Participant(ParticipantType.SYSTEM_ADMIN);
```

USER Participant type for a specific person to respond to the request. The person must have a Security Identity Manager account.

```
participant = new Participant(ParticipantType.USER, userDN);
```

ITIM GROUP

Participant type for a specific ITIM group. Though all members of the group are notified, and all are eligible to respond, the first response triggers the workflow to continue. Specifying a group cannot be used to require multiple participants to approve the request.

```
participant = new Participant(ParticipantType.GROUP, groupDN);
```

Description

This entity represents the workflow participant type constants.

Person

The object represents the person entity.

Availability

IBM Security Identity Manager 7.0.

Provided by

```
com.ibm.itim.script.extensions.model.PersonModelExtension
```

Inherits From

```
DirectoryObject
```

Constructors

new Person(String dn)

Arguments:

dn Optional DN of a specific entity.

new Person(DirectoryObject directoryObject)

Arguments:

directoryObject

DirectoryObject to be contained in the person

new Person(DirectoryObjectEntity directoryObjectEntity)

Arguments:

directoryObjectEntity

DirectoryObjectEntity to be contained in the person

Methods

getAllAssignmentAttributes()

Returns an array of the RoleAssignmentAttribute objects that are defined in all of authorized roles for this person. The authorized roles consist of both the direct roles for this person and also all of the parent roles of the direct roles.

getAndDecryptSynchPassword()

Decrypts and returns the decrypted synch password of the person entity in plain text.

Note: This method is available in the scripting context of IBM Security Identity Manager only if the **javascript.password.access.enabled** property is set to true in the *ISIM_HOME/data/scriptframework.properties* file.

getAndDecryptPersonPassword()

Decrypts and returns the decrypted person password of the person entity in plain text.

Note: This method is available in the scripting context of Security Identity Manager only if the **javascript.password.access.enabled** property is set to true in the *ISIM_HOME/data/scriptframework.properties* file.

getRoleAssignmentData()

Returns all role assignment data for the person.

getRoleAssignmentData(String roleAssignedDN)

Returns all role assignment data for the person for the specified role.

getRoles()

Returns an array of DirectoryObjects, each representing a role.

getNewRoles()

Returns an array of newly added roles for the person.

getRemovedRoles()

Returns an array of removed roles for the person.

isInRole(String roleName)

Determines whether the person belongs to the role. Returns Boolean.

removeRole()

Removes the person from the specified role.

removeRoleAssignmentData(String roleAssignedDN)

Removes all role assignment data for the person from the specified role.

updateRoleAssignmentData(RoleAssignmentObject[] roleAssignmentObject)

Updates a person with the role assignment attribute value changes that are defined in the set of RoleAssignmentObjects.

Person.getAllAssignmentAttributes()

The method returns an array of the RoleAssignmentAttribute objects that are defined for all of authorized roles for this person. The authorized roles consist of both the direct roles for this person and also all the parent roles of the direct roles.

Availability

IBM Security Identity Manager 7.0

Synopsis

```
person.getAllAssignmentAttributes()
```

Arguments

None

Description

This method is defined on the Person object. It returns an array of the RoleAssignmentAttribute objects that are defined in all of authorized roles for this person. The authorized roles consist of both the direct roles for this person and also all the parent roles of the direct roles. The method returns an empty array if no assignment attribute exists. RoleAssignmentAttribute objects contains role assignment attribute name, role name, and role DN.

Usage

```
//The script is used in a workflow, in which Entity is a person object.
var person = Entity.get();

//get assignment attributes of the person
var attributeList = person.getAllAssignmentAttributes();
if (attributeList.length == 0) {
    Enrole.log("script", "No assignment attribute for this role: "
        + role.name);
    return;
}

// print out the role assignment attribute name.
for (var i=0; i < attributeList.length; i++) {
    var roleAtr = attributeList[i];
    Enrole.log("script","attribute name-----: "+ roleAtr.getName());
}
```

Person.getAndDecryptSynchPassword()

The method decrypts and returns the decrypted sync password of the person entity in plain text.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
person.getAndDecryptSynchPassword()
```

Arguments

None

Description

This method is defined on the Person object. It returns a string that represents the plain text sync password for the person that is used for synchronization. It decrypts and returns the decrypted sync password set in the person object. This function returns null if the sync password is not present. This method can be used in IBM Security Identity Manager scripting context if the **javascript.password.access.enabled** property is set to true in the scriptframework.properties file.

Use the Update Property page to work with the scriptframework.properties file. See Managing the server properties.

Usage

```
//The script is used in a workflow, in which Entity is a person object.  
var person = Entity.get();  
//get sync password set on the person  
var synchPassword = person.getAndDecryptSynchPassword();
```

Person.getAndDecryptPersonPassword()

The method decrypts and returns the decrypted password of the person entity in plain text.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
person.getAndDecryptPersonPassword()
```

Arguments

None

Description

This method is defined on the Person object. It returns a string that represents the plain text password for the person. It decrypts and returns the decrypted password set in the person object. This function returns null if the password is not present. This method can be used in IBM Security Identity Manager scripting context if the **javascript.password.access.enabled** property is set to true in the scriptframework.properties file.

Use the Update Property page to work with the scriptframework.properties file. See Managing the server properties.

Usage

```
//The script is used in a workflow, in which Entity is a person object.  
var person = Entity.get();  
//get person password set on the person  
var personPassword = person.getAndDecryptPersonPassword();
```

Person.getRoleAssignmentData()

The method returns all the role assignment data for the person, as an array of RoleAssignmentObject objects that contain the role assignment values, defined Role DN and assigned Role DN.

Availability

IBM Security Identity Manager 7.0

Synopsis

```
person.getRoleAssignmentData()
```

Arguments

none

Description

This method is defined on the Person object. It returns an array of RoleAssignmentObject objects, containing the role assignment values, defined Role DN, and assigned Role DN. The method returns an empty array if no assignment data exists.

Usage

```
//The script is used in a workflow, in which Entity is a person object.
var person = Entity.get();
var assignmentObjects = person.getRoleAssignmentData();
if (assignmentObjects.length == 0) {
    Enrole.log("script", "There is no assignment values for " + person.name);
    return;
}
var str = "The number of role assignment objects returned from
    person.getRoleAssignmentData(): " +
    assignmentObjects.length + "\n";
for(var i=0; i<assignmentObjects.length; i++) {
    var obj = assignmentObjects[i];
    str += obj.toString() + "\n";
}
Enrole.log("script", "The assignment attribute data for person:"+
    person.name+" is:"+ str);
```

Person.getRoleAssignmentData(String roleAssignedDN)

The method returns all the role assignment data for the person. The data is an array of RoleAssignmentObject objects that contain the role assignment values, defined Role DN, and assigned Role DN for the specified assigned role.

Availability

IBM Security Identity Manager 7.0

Synopsis

```
person.getRoleAssignmentData(String roleAssignedDN)
```

Arguments

roleAssignedDN

The distinguished name of the assigned role

Description

This method is defined on the Person object. It returns an array of RoleAssignmentObject objects, containing the role assignment values, defined Role DN, and assigned Role DN for a specified assigned role. The method returns an empty array if no assignment data exists.

Usage

```
//The script is used in a workflow, in which Entity is a person object.
var person = Entity.get();
var roleDNs = person.getProperty("erroles");
if(roleDNs.length == 0) {
    Enrole.log("script", person.name + " does not have any role");
    return;
}
// Get role assignment data for the first role.
var roleDN = roleDNs[0];
var role = new Role(roleDN);
var assignmentObjects = person.getRoleAssignmentData(roleDNs[0]);
if (assignmentObjects.length == 0) {
    Enrole.log("script", person.name + " does not have any assignment
        objects for role: " + role.name);
    return;
}
var str = "The number of role assignment objects returned from
    person.getRoleAssignmentData() for "
    + role.name + " : " + assignmentObjects.length + "\n";
for(var i=0; i<assignmentObjects.length; i++) {
    var obj = assignmentObjects[i];
    str += obj.toString() + "\n";
}
Enrole.log("script", str);
```

Person.getRoles()

The method returns roles assigned to a Person.

Availability

IBM Security Identity Manager 7.0

Synopsis

```
person.getRoles()
```

Description

This method defined on the Person object returns an array of roles that the person belongs to. The return type is an array of entities, which are instances of role directory entity objects. The properties available on the Entity Objects are name and description.

Usage

```
// logs the names of all roles that a person belongs to
var per = person.get();
var rolesArray = per.getRoles();
if(rolesArray.length>0){
    Enrole.log("script", per.getProperty("cn")[0] +
        " belongs to following roles: ");

    for( var i=0; i<rolesArray.length;i++) {
        Enrole.log("script",
            rolesArray[i].getProperty("errolename")[0]);
    }
} else {
    Enrole.log("script", per.getProperty("cn")[0] +
        "does not belong to any roles");
}
```

Person.getNewRoles()

The method returns an array of newly added static roles for a Person.

Availability

IBM Security Identity Manager 7.0

Synopsis

```
person.getNewRoles()
```

Description

This method defined on the person object returns an array of new static roles associated with the person. The return type is an array of DirectoryObjects,

Note: The person object is often a runtime object in memory, and these new static roles were not added to the directory.

Usage

```
var newRoles = per.getNewRoles();
```

Person.getRemovedRoles()

The method returns an array of removed static roles for the Person.

Availability

IBM Security Identity Manager 7.0

Synopsis

```
person.getRemovedRoles()
```


Description

This method defined on the person object returns an array of static roles from which the person was removed. The return type is an array of `DirectoryObjects`.

Note: The person object is often a runtime object in memory, and these static roles were not removed from the directory.

Usage

```
var removedRoles = per.getRemovedRoles();
```

Person.isInRole()

The method evaluates whether a `Person` belongs to a role.

Availability

IBM Security Identity Manager 7.0

Synopsis

```
person.isInRole(roleName)
```

Arguments

roleName

The name of the role to check.

Description

Given a person object and the name of the role, determine whether the person belongs to the role. If the role is not uniquely determined by the `roleName` parameter or if the person cannot be found, then return an error object.

Usage

```
// Check whether the person is in the role Manager and log a
// message
var per=person.get();
if(!per.isInRole("Manager")) {
    Enrole.log("script",per.getProperty("cn")[0] +
        "does not belong to role Manager");
} else {
    Enrole.log("script",per.getProperty("cn")[0] +
        "belong to role Manager");
}
```

Person.removeRole()

The method removes the person from the specified role.

Availability

IBM Security Identity Manager 7.0

Synopsis

```
person.removeRole(role)
```

Arguments

role

Role object that represents the role from which the person is removed.

Description

Removes the person from the role.

Note: This operation removes only the role from the `Person` object in run time, and it does not remove the role from the directory.

Usage

```
//Remove the first role in the Person object
var roles = person.getRoles();
if (roles.length > 0) {
    person.removeRole(roles[0]);
}
```

Person.removeRoleAssignmentData()

The method removes all role assignment data of the person for an array of assigned Roles. It does not directly change data in the data source, but removes from memory the data inside the person object.

Availability

IBM Security Identity Manager 7.0

Synopsis

```
person.removeRoleAssignmentData(String [] roleAssignedDNs)
```

Arguments

roleAssignedDNs

An array of distinguished names of the assigned role.

Description

This method is defined on the Person object. It removes all role assignment data of the person for an array of assigned roles.

Usage

```
//The script is used in a workflow, in which Entity is a person object.
var person = Entity.get();
var roleDNs = person.getProperty("erroles");
if(roleDNs.length == 0) {
    Enrole.log("script", person.name + " does not have any roles");
    return;
}

//remove the role assignment attribute.
person.removeRoleAssignmentData(roleDNs);
```

Person.updateRoleAssignmentData()

The method updates a person with the role assignment attribute value changes that are defined in the set of RoleAssignmentObjects. It does not directly change data in the data source, but updates (in memory) the data inside the person object.

Availability

IBM Security Identity Manager 7.0

Synopsis

```
person.updateRoleAssignmentData(RoleAssignmentObject []
roleAssignmentObject)
```

Arguments

roleAssignmentObject

A list of roleAssignmentObjects that contains the role assignment attribute value change set to be applied.

Description

This method is defined on the Person object. It updates a person with the role assignment attribute value changes that are defined in the set of RoleAssignmentObjects.

Usage

```
//The script is used in a workflow, in which Entity is a person object.
var person = Entity.get();
var roleDNs = person.getProperty("erroles");
if(roleDNs.length == 0) {
    Enrole.log("script", person.name + " does not have any role");
    return;
}

//construct a new RoleAssignmentObject
var assignmentObj = new RoleAssignmentObject(roleDNs[0], roleDNs[0]);
assignmentObj.addProperty("attr_3", ["newv1", "newv2"]);
person.updateRoleAssignmentData([assignmentObj]);
```

PersonSearch

The object searches for a person.

Availability

IBM Security Identity Manager 7.0
Provisioning Policy context
Service Selection Policy context

Provided by

com.ibm.itim.script.extensions.model.PersonModelExtension

Constructor

new PersonSearch()

Returns

The newly created and initialized person search object.

Methods

searchByFilter()

Search for a person by a filter.

searchByURI()

Search for a person by URI in an organizational container.

Description

The entity implements the IBM Security Identity Manager PersonSearch class. The API Javadoc for this class is in the following directory:

`/extensions/version_number/api/com/ibm/itim/dataservices/model/domain/`

Do these steps to access contents from the extensions.zip file:

1. Log on to the IBM Security Identity Manager virtual appliance console to open the **Appliance Dashboard**.
2. From the top-level menu of the **Appliance Dashboard**, select **Configure > Advanced Configuration > Custom File Management** to display the Custom File Management page.
3. Click the **All Files** tab.
4. Go to directories/utilities.
5. Select extensions.zip and click **Download**.
6. Extract the extensions.zip file.
7. Go to `/extensions/version_number/api/com/ibm/itim/dataservices/model/domain/`. For example, *version_number* is 7.0.

PersonSearch.searchByFilter()

The method searches for a person by a filter.

Availability

IBM Security Identity Manager 7.0

Synopsis

```
personSearch.searchByFilter(profileName, filter, scope)
```

Arguments

profileName

The name of the person profile to use.

filter LDAP search filter that defines the criteria for returned containers to meet. The filter must be in the format defined by RFC2254.

scope Optional search scope. Use **1** for One Level Scope and **2** for SubTree Scope. One Level Scope is the default scope.

Returns

An array of DirectoryObjects representing the results of the search.

Description

This method searches for a person by a filter.

Usage

```
var personSearch = new PersonSearch();
var searchResult1 = personSearch.searchByFilter("Person",
    "(sn=Smith)", 2);

// use default one level scope
var searchResult2 = personSearch.searchByFilter("Person",
    "(sn=Smith)");
```

PersonSearch.searchByURI()

The method finds a person by URI within an organizational container.

Availability

IBM Security Identity Manager 7.0

Synopsis

```
PersonSearch.searchByURI(containerDN, uri)
```

Arguments

Container DN

String representing the distinguished name of the parent organizational container.

uri String representing the URI of the person.

Returns

A Person object.

Description

Given the distinguished name of the parent organizational container and the person URI, this method finds the person. If the person is not found, this function returns null. If more than one persons found, this function throws a scripting exception.

Usage

```
var person= (new PersonSearch()).searchByURI(container.dn, uri);
if (person != null) {
  Enrole.log("script", "Found " + person.getProperty("cn") );}
```

PostOffice

The object post office object that consolidates notifications.

Availability

IBM Security Identity Manager 7.0

Provided by

com.ibm.itim.mail.postoffice.script.PostOfficeExtension

Methods

getAllEmailMessages()

Obtains the Subject, Text Body, and HTML Body of each individual message contained in an aggregate message.

getEmailAddress()

Contains the email address that is the destination of the aggregate email message.

getPersonByEmailAddress()

Returns the Person that corresponds to the email address specified.

getTopic()

Returns the topic of the aggregated email message.

The `getAllEmailMessages()` extension allows access to the `NotificationMessage` object. Do not call the `getHtmlMessage()` method from a template. This call returns an XHTML version of the notification text. It is not possible to embed XML documents, so a call to this method results in a template execution failure. Use the text body of the original notifications by calling `getMessage()` instead.

PostOffice.getAllEmailMessages()

The message returns an array of `NotificationMessage` objects.

Availability

IBM Security Identity Manager 7.0

Synopsis

```
PostOffice.getAllEmailMessages()
```

Description

This JavaScript extension returns an array of `NotificationMessage` objects for obtaining the Subject, Text Body, and HTML Body of each message in an aggregate message.

Usage An example of how to iterate through the returned array in JavaScript is as follows:

Here are the email text bodies fetched using the JavaScript extension:

```
<JS>
```

```
var msgListIterator =
  PostOffice.getAllEmailMessages().iterator();
var returnString = "<br />";
while (msgListIterator.hasNext()) {
  returnString = returnString +
```

```
        msgListIterator.next().getMessage() + "<br />";
    }
    return returnString;
</JS>
```

PostOffice.getEmailAddress()

The method returns email address of aggregate email destination.

Availability

IBM Security Identity Manager 7.0

Synopsis

```
PostOffice.getEmailAddress()
```

Description

This JavaScript extension returns a String containing the email address that is the destination of the aggregate email message.

Usage destinationAddress = PostOffice.getEmailAddress();

PostOffice.getPersonByEmailAddress()

The method returns the Person object that corresponds to this email address.

Availability

IBM Security Identity Manager 7.0

Synopsis

```
PostOffice.getPersonByEmailAddress(String email)
```

Description

This JavaScript extension returns the Person object that corresponds to the email address specified.

Usage targetPerson = PostOffice.getPersonByEmailAddress()

Examples:

```
targetPerson = PostOffice.getPersonByEmailAddress("user@itim.com");
targetPerson =
    PostOffice.getPersonByEmailAddress(PostOffice.getEmailAddress());
```

PostOffice.getTopic()

The method returns the topic string of the aggregate email.

Availability

IBM Security Identity Manager 7.0

Synopsis

```
PostOffice.getTopic()
```

Description

This JavaScript extension returns a string containing the topic of the aggregated email message.

Usage topicString = PostOffice.getTopic();

Process

Represents the IBM Security Identity Manager workflow process.

Availability

IBM Security Identity Manager 7.0

Provided by

The Process JavaScript Object in the WorkflowExtension returns a Process object. The object represents the current workflow process. The parent processes of the current workflow can be returned by calling Process.getParent() recursively, and the parent process is also a Process object.

Properties

Note: Custom result codes are supported in the workflow designer for approval activities.

APPROVED

Approved process summary code. Result code is AA.

ESCALATED

Escalated process summary code. Result code is ES.

FAILED

Failed process summary code. Result code is SF.

PARTICIPANT_RESOLVE_FAILED

Participant resolved failure process summary code. Result code is PF.

PENDING

Pending process summary code. Result code is PE.

REJECTED

Rejected process summary code. Result code is AR.

SUBMITTED

Submitted process summary code. Result code is RS.

SUCCESS

Success process summary code. Result code is SS.

TIMEOUT

Time out process summary code. Result code is ST.

WARNING

Warning process summary code. Result code is SW.

comment

Provides additional information about the process given when defined in the workflow designer.

description

Describes the purpose of the process given when defined in the workflow designer.

id Assigned by the workflow designer to uniquely identify the workflow process within the workflow engine.

name Label given this activity when defined in the workflow designer.

parentId

Uniquely identifies the parent process (if any) that started this process.

requesteeDN

Uniquely identifies the requestee if the requestee is a user in the IBM Security Identity Manager data store.

- requesteeName**
Name of the process requestee.
- requestorName**
The name of the process requestor if the requestor is a user.
- requestorType**
Categorize the requestor
- resultDetail**
An application-specific string that provides more detail about the result of the process.
- resultSummary**
An application-specific string that represents the summary result of the process.
- started**
Indicates when the process started.
- state** Code that represents the current state of the process.
- subject**
Describes the object that is the focal point of the workflow process.
- type** Code that categorizes the process given when defined in the workflow designer.

Methods

- auditEvent()**
Create an event in the audit trail specific to the activity.
- getActivity()**
Returns an activity with the ID and index.
- getParent()**
Get the parent process (if any) that started this process.
- getRootProcess()**
Returns the JavaScript Process object that contains information about the root process.
- getRootRequesterName()**
Returns String of requester name of the root process.
- setRequesteeData()**
Change the requestee data for the current process.
- setResult()**
Change the result member of the activity in the current activity.
- setSubjectData()**
Change the subject data for the current process.

Description

This entity represents the current workflow process is running.

Process.auditEvent()

The method creates an event in the audit trail.

Availability

IBM Security Identity Manager 7.0

Synopsis

`process.auditEvent(event)`

Arguments

event String representing the event to be audited.

Description

This method creates an event in the audit trail specific to the process. The function takes in one parameter that can be any JavaScript object that can be translated into a string for storage. In the audit trail, the event is automatically time stamped.

Usage `process.auditEvent("Task completed");`

Process.comment

The field provides additional information about the process.

Availability

IBM Security Identity Manager 7.0

Synopsis

`process.comment`

Description

This read-only field is a string that provides additional information about the process given when defined in the workflow designer.

Usage `x = process.comment;`

Process.description

The field represents the purpose of the process.

Availability

IBM Security Identity Manager 7.0

Synopsis

`process.description`

Description

This read-only field is a string that describes the purpose of the process when defined in the workflow designer.

Usage `x = process.description;`

Process.getActivity()

The method returns an activity with the ID and index.

Availability

IBM Security Identity Manager 7.0

Synopsis

`process.getActivity(id, index)`

Arguments

id Activity ID assigned by the workflow designer.

index Optionally identifies specific activity if there is more than one activity with the ID.

Returns

The associated Activity.

Description

This method returns an activity with the ID and index in the event that there is more than one activity with the ID. This might occur if the activity of the given ID is called multiple times in a loop in the workflow process. If there is no activity with the ID and index, this function returns null. If the optional index is not specified and if there is more than one activity with the ID, the first activity with the ID is returned.

Usage

```
theFirstActivity = process.getActivity("id1", 3);
theActivityName = theFirstActivity.name;

theSecondActivity = process.getActivity("id2");
theActivityName = theSecondActivity.name;
```

Process.getParent()

The method returns the parent process (if any) that started this process.

Availability

IBM Security Identity Manager 7.0

Synopsis

```
process.getParent()
```

Returns

The parent Process. If there is no parent, a null is returned.

Description

This method returns the parent process (if any) that started this process.

Usage

```
parent = process.getParent();
parentName = parent.name;
```

Process.getRootProcess()

The method returns the root process (if any) that started this process.

Availability

IBM Security Identity Manager 7.0

Synopsis

```
process.getRootProcess()
```

Returns

The root process. If there is no root process, a null is returned.

Description

This method returns the root process (if any) of this process.

Usage

```
root = process.getRootProcess();
rootName = root.name;
```

Process.getRootRequesterName()

The method returns the root requester name.

Availability

IBM Security Identity Manager 7.0

Synopsis

```
process.getRootRequesterName()
```

Description

This method returns the root requester name of the workflow process initiator.

Usage `rootRequester = process.getRootRequesterName();`

Process.guid

The generated unique identifier assigned to the process at runtime.

Availability

IBM Security Identity Manager 7.0

Synopsis

```
process.guid
```

Description

This read-only field is a String of the generated unique identifier for the workflow process in the workflow engine.

Usage `x = process.guid;`

Process.getSubProcesses()

The method returns the subordinate processes (if any) of the process.

Availability

IBM Security Identity Manager 7.0

Synopsis

```
process.getSubProcesses()
```

Returns

The subordinate processes. If there are no subordinate processes, an empty array is returned.

Description

This method returns the subordinate processes (if any) of this process.

Usage

```
var out = "subprocesses of the process: \n";  
  
function traverse(p, prefix) {  
  var subProcesses = p.getSubProcesses();  
  prefix += "/" + p.name;  
  out += prefix + ": " + p.id + " type: " + p.type + " resultSummary: " + p.resultSummary + "\n";  
  for (var i = 0; i < subProcesses.length; i++) {  
    traverse(subProcesses[i], prefix);  
  }  
}
```

```
}  
traverse(process, "");  
activity.auditEvent(out);
```

Process.id

The generated unique identifier assigned to the process at runtime.

Availability

IBM Security Identity Manager 7.0

Synopsis

process.id

Description

This read-only field is a string of the generated unique identifier for the workflow process in the workflow engine.

Usage *x = process.id;*

Process.name

The label assigned to the process.

Availability

IBM Security Identity Manager 7.0

Synopsis

process.name

Description

This read-only field is a string assigned by the workflow designer to label this process.

Usage *x = process.name;*

Process.parentId

The field uniquely identifies the parent process that started this process.

Availability

IBM Security Identity Manager 7.0

Synopsis

process.parentId

Description

This read-only field is a string representation of the long integer that uniquely identifies the parent process (if any) that started this process.

Usage *x = process.parentId;*

Process.requesteeDN

The field uniquely identifies the requestee if the requestee is a user in the IBM Security Identity Manager data store.

Availability

IBM Security Identity Manager 7.0

Synopsis

process.requesteeDN

Description

This read-only field is a string that uniquely identifies the requestee if the requestee is a user in the IBM Security Identity Manager data store. Not all

requestees are users (that is, the process can act on a policy, not a user directly), so this member can be empty.

Usage `x = process.requesteeDN;`

Process.requestorDN

The field specifies the distinguished name of the process requester, if the requester is a user in the IBM Security Identity Manager data store.

Availability

IBM Security Identity Manager 7.0

Synopsis

`process.requestorDN`

Description

This read-only field is a string that represents the distinguished name of the process requester. This string is displayed only if the requester is a user in the IBM Security Identity Manager data store. Not all requesters are users (that is, the process can act on a policy, not a user directly), so this member can be empty.

Usage

```
if (process.requestorType == "U")
  x = process.requestorDN;
```

Process.requesteeName

The field represents the name of the process requestee as a string.

Availability

IBM Security Identity Manager 7.0

Synopsis

`process.requesteeName`

Description

This read-only field is a string that provides the name the requestee if the requestee is a user in the IBM Security Identity Manager data store. Not all requestees are users (that is, the process can act on a policy, not a user directly), so this member can be empty.

Usage `x = process.requesteeName;`

Process.requestorName

The field represents the name of the process requester if the requester is a user.

Availability

IBM Security Identity Manager 7.0

Synopsis

`process.requestorName`

Description

This read-only field is a string that represents the name of the process requester if the requester is a user.

Usage

```
if (process.requestorType == "U")
  x = process.requestorName;
```

Process.requestorType

The field categorize the requestor.

Availability

IBM Security Identity Manager 7.0

Synopsis

process.requestorType

Description

This read-only field is a string that categorizes the requestor. The potential categories, or types, are:

- **U** for user
- **S** for the workflow engine
- **P** for the system

Usage

```
x = process.requestorType;  
if (x == "U")  
    ...  
else if (x == "S")  
    ...  
else if (x == "P")  
    ...
```

Process.resultDetail

The field details about the result of the process.

Availability

IBM Security Identity Manager 7.0

Synopsis

process.resultDetail

Description

This read-only field is an application-specific string that provides more detail about the result of the process.

Usage *x = process.resultDetail;*

Process.resultSummary

The field represents the summary of the result of the process.

Availability

IBM Security Identity Manager 7.0

Description

This read-only field is an application-specific string that provides a summary of the result of the process.

Usage *x = process.resultSummary;*

Process.setRequesteeData()

The method changes the requestee data for the current process.

Availability

IBM Security Identity Manager 7.0

Synopsis

process.setRequesteeData(person)

Arguments

person

DirectoryObject representing the new requestee.

Description

This method changes the requestee data for the current process. It is not supported for a process that is not the current process. It not only updates the current process in the script, but also in the workflow engine. The requesteeData argument contains a person distinguished name or a collection of strings from which the requestee data can be extracted.

Usage `process.setRequesteeData(person);`

Process.setResult()

The method changes the result member of the process.

Availability

IBM Security Identity Manager 7.0

Synopsis

`process.setResult(summary, detail)`

Arguments

summary

String code that represents the result summary.

detail String representing the result details.

Description

This method changes the result member of the process in the current process. It is supported for current activities in the current workflow process. The result is composed by an application-specific summary code, and optional more detailed application-specific description. The summary code can indicate a success or failure. This summary code is stored as the resultSummary member locally and updated in the relevant data in the workflow engine. The detail is stored as the resultDetail member locally and updated in the relevant data in the workflow engine.

Usage

`process.setResult(process.FAILED, "Unable to connect to resource");`

Process.setSubjectData()

The method changes the subject data for the current process.

Availability

IBM Security Identity Manager 7.0

Synopsis

`process.setSubjectData(person)`

Arguments

person

DirectoryObject representing the new subject.

Description

This method changes the subject data for the current process. It is not supported for a process that is not the current process. It not only updates the current process in the script, but also in the workflow engine. The

subjectData argument contains a person distinguished name or a collection of strings from which the subject data can be extracted.

Usage `process.setSubjectData(person);`

Process.started

The field represents the JavaScript date that indicates when the process started.

Availability

IBM Security Identity Manager 7.0

Synopsis

`process.started`

Description

This read-only field is code string that represents the JavaScript Date that indicates when the process started.

Usage

`x = process.started;`

Process.state

The field represents the current state of the process.

Availability

IBM Security Identity Manager 7.0

Synopsis

`process.state`

Description

This read-only field is code string that represents the current state of the process. The state can have the following values:

- R for running
- I for not started
- T for terminated
- A for aborted
- S for suspended
- C for completed
- B for bypassed

Usage

```
if (process.state == "S") {  
    ...  
}
```

Process.subject

The field represents the object that is the focal point of the workflow process.

Availability

IBM Security Identity Manager 7.0

Synopsis

`process.subject`

Description

This read-only field is code string that describes the object that is the focal point of the workflow process. This string can be an identity in the system, an account, a policy, or another object.

Usage `x = process.subject;`

Process.type

The field represents the type of process.

Availability

IBM Security Identity Manager 7.0

Synopsis

`process.type`

Description

This read-only field is code string that categorizes the process when defined in the workflow designer.

Usage `x = process.type;`

ProcessData

The object represents the workflow process data entity.

Availability

IBM Security Identity Manager 7.0
Workflow context

Provided by

`com.ibm.itim.workflow.script.WorkflowExtension`

Methods

get() Returns a JavaScript object that represents the value of the relevant data item.

set() Changes the value of the relevant data item.

Description

Each workflow process has a set of relevant data, or process specific parameters, which can be read or changed from within a workflow script. The name and syntax of these parameters, or relevant data items, are defined in the workflow designer, and are typically specific to the workflow process purpose. For example, when adding a user, an object that holds all the attributes of the new user can be a relevant data item. However, when deleting a user, the only needed relevant data item can be the distinguished name of the user to delete.

Each relevant data item will be represented in the workflow script as a variable with the same relevant data ID as defined in the workflow designer.

ProcessData.get()

The method changes the subject data for the current process.

Availability

IBM Security Identity Manager 7.0

Synopsis

`processData.get()`

Returns

Returns a JavaScript object that represents the value of the relevant data item.

Description

This method returns a JavaScript object that represents the value of the relevant data item. There is a variable present for each relevant data item in the context of script. For performance reasons, the values are not retrieved from the workflow engine until the script specifically requests the values with this call. The returned JavaScript object is in the same syntax as defined in the workflow designer.

Usage `dn = subjectDN.get();`

ProcessData.set()

The method changes the value of the relevant data item.

Availability

IBM Security Identity Manager 7.0

Synopsis

`processData.set(value)`

Arguments

value Value to use to update the relevant data item.

Description

This method changes the value of the relevant data item. It not only updates the relevant data item in the script, but also in the workflow engine. The new value is a parameter to the function. The new value must be compatible with the syntax of the relevant data item as defined in the workflow designer. For example, if the relevant data item is an integer, the value `cat` would not be a valid parameter to this function.

Usage `processData.set("engineering");`

RecertificationWorkflow

Provides extended capabilities to user recertification workflows, including audit support for the reporting and view requests functions.

Availability

IBM Security Identity Manager 7.0.

Methods

auditCompletion(person, recertPolicy, approvalDoc)

Performs a full audit of the decisions made during a user recertification packaged approval activity, including data for reporting and view requests.

auditTimeout(person, recertPolicy, approvalDoc)

Perform full audit of the decisions set during a user recertification packaged approval activity timeout, including data for reporting and view requests.

auditCompletion(person, recertPolicy, approvalDoc, auditForReports, auditForViewRequests)

Performs an audit of the decisions made during a user recertification packaged approval activity. The value of the Boolean flag `auditForReports` determines whether an audit entry is created for reporting. The value of the Boolean flag `auditForViewRequests` determines whether an audit entry is created for view requests.

RecertificationWorkflow.auditTimeout(person, recertPolicy, approvalDoc, auditForReports, auditForViewRequests)

Performs an audit of the decisions set during a user recertification packaged approval activity timeout. The value of the Boolean flag `auditForReports` determines whether an audit entry is created for reporting. The value of the Boolean flag `auditForViewRequests` determines whether an audit entry is created for view requests.

Usage `RecertificationWorkflow.auditCompletion(Entity.get(), Policy.get(), ApprovalDocument.get())`

`RecertificationWorkflow.auditTimeout(Entity.get(), Policy.get(), ApprovalDocument.get(), false, true)`

Reminder

An activity to-do item reminder informs the participant that the IBM Security Identity Manager requires user action.

Availability

IBM Security Identity Manager 7.0
Reminder context

Provided by

`com.ibm.itim.script.extensions.ReminderExtension`

Methods

Reminder.getOriginalSubject()

This method returns the subject of the original notification sent when the work item was first assigned.

Reminder.getXhtmlBody()

This method returns the XHTML body of the original notification sent when the work item was first assigned.

Reminder.getTextBody()

This method returns the text body of the original notification sent when the work item was first assigned.

Reminder.getRemindersSent()

This method returns the number of reminders previously sent.

Reminder.getEscalationTime()

This method returns a string that contains the date and time when the work item is escalated unless acted upon.

Reminder.getEscalationDate()

This method returns a Date containing the date and time when the work item is escalated unless acted upon.

Description

An activity to-do item reminder informs the participant that IBM Security Identity Manager requires user action.

Role

The object represents the role associated with a provisioning operation.

Availability

IBM Security Identity Manager 7.0

Provided by

com.ibm.itim.script.extensions.model.RoleModelExtension

Constructor

```
new Role(dn)
```

Returns

A new Role object that represents the Role with the given DN.

Methods**getAssignmentAttributes()**

Returns an array of assignment attribute names. Returns an empty array if no assignment attribute exists.

getAllAssignmentAttributes()

Returns an array of RoleAssignmentAttribute objects containing assignment attribute name, role name, and role DN. Returns an empty array if no assignment attribute exists. Returns the role assignment attributes of the whole role hierarchy.

getOwner()

Returns an array of DirectoryObjects that represent any Person that has an Owner relationship with this role.

setAssignmentAttributes()

Sets role assignment attributes of the role.

Inherits from

DirectoryObject

Synopsis

```
role.dn;
```

Description

The role object is available in the context of a provisioning policy.

Note: For more information on role assignment attributes, see Defining assignment attributes when creating a role.

Role.getAssignmentAttributes()

The method returns an array of assignment attribute names. Returns an empty array if no assignment attribute exists.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
Role.getAssignmentAttributes()
```

Arguments

None

Description

This method is defined on the Role object and returns an array of assignment attribute names. The method returns an empty array if no assignment attribute exists.

Usage

```
var role = new Role(roleDN);

//get assignment attributes of the role
var attributeList = role.getAssignmentAttributes();
if (attributeList.length == 0) {
```

```

        Enrole.log("script", "No assignment attribute for this role: "
            + role.name);
        return;
    }

    // print out role assignment attribute name.
    for (var i=0; i < attributeList.length; i++) {
        var attrName = attributeList[i];
        Enrole.log("script","attribute name-----: "+ attrName);
    }
}

```

Role.getAllAssignmentAttributes()

The method returns an array of RoleAssignmentAttribute objects that contain the assignment attribute name, role name, and role DN. Returns an empty array if no assignment attribute exists. Returns the role assignment attributes of the whole role hierarchy.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
Role.getAllAssignmentAttributes()
```

Arguments

None

Description

This method is defined on the Role object and returns an array of RoleAssignmentAttribute objects. The array contains the assignment of the attribute name, role name, and role DN of the role. The method returns an empty array if no assignment attribute exists. It returns the role assignment attributes of the whole role hierarchy.

Usage

```

var role = new Role(roleDN);
//get assignment attributes of the role
var attributeList = role.getAllAssignmentAttributes();
if (attributeList.length == 0) {
    Enrole.log("script", "No assignment attribute for this role: "
        + role.name);
    return;
}

// print out role assignment attribute name.
for (var i=0; i < attributeList.length; i++) {
    var roleAtr = attributeList[i];
    Enrole.log("script","attribute name-----: "+ roleAtr.getName());
}

```

Role.getOwner()

The method returns an array of DirectoryObjects that represents any Person that has an Owner relationship with this role.

Availability

IBM Security Identity Manager 7.0

Synopsis

```
Role.getOwner()
```

Returns

Array of DirectoryObjects that represents the owners of this Role or null if there are no owners.

```
Usage var owners = role.getOwner();
```

Role.setAssignmentAttributes()

The method sets role assignment attributes of the role.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
Role.setAssignmentAttributes(String[] attributeNames)
```

Arguments

attributeNames

The array of assignment attribute names of the role. If an empty array is specified, all assignment attributes for the role are removed.

Description

This method is defined on the Role object and sets the role assignment attributes for a role.

Usage

```
var roleDN = roles[0];
var role = new Role(roleDN);
var roleAtr = new Array();
roleAtr[0] = "creditlimit";
//set assignment attribute names
role.setAssignmentAttributes(roleAtr);
```

RoleAssignmentAttribute

The object represents the role assignment attribute associated with a role.

Availability

IBM Security Identity Manager 7.0.

Methods

getName()

Returns the attribute name associated with the role assignment attribute object.

getRoleName()

Returns the name of the role. Returns an empty string if there is no name associated with the role assignment attribute object.

getRoleDN()

Returns the DN of the role. Returns an empty string if there is no DN associated with the role assignment attribute object.

Description

The RoleAssignmentAttribute object associated with the role assignment attribute.

RoleAssignmentAttribute.getName()

The method returns the name of the assignment attribute.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
RoleAssignmentAttribute.getName()
```

Arguments

None

Returns

The name of the assignment attribute.

Description

Returns the name of the assignment attribute that is defined on the role.

Usage

```

var role = new Role(roleDN);
//get assignment attributes of the role
var attributeList = role.getAllAssignmentAttributes();
if (attributeList.length == 0) {
    Enrole.log("script", "No assignment attribute for this role: "
        + role.name);
    return;
}

// print out role assignment attribute name.
for (var i=0; i < attributeList.length; i++) {
    var roleAtr = attributeList[i];
    Enrole.log("script","attribute name-----: "+ roleAtr.getName());
}

```

RoleAssignmentAttribute.getRoleName()

The method returns the name of the role that has the assignment attribute defined.

Availability

IBM Security Identity Manager 7.0.

Synopsis

RoleAssignmentAttribute.getRoleName()

Arguments

None

Returns

The name of the role that has the assignment attribute defined.

Description

Returns the name of the role that has the assignment attribute defined.

Usage

```

var role = new Role(roleDN);
//get assignment attributes of the role
var attributeList = role.getAllAssignmentAttributes();
if (attributeList.length == 0) {
    Enrole.log("script", "No assignment attribute for this role: "
        + role.name);
    return;
}

// print out all role names.
for (var i=0; i < attributeList.length; i++) {
    var roleAtr = attributeList[i];
    Enrole.log("script","role name-----: "+ roleAtr.getRoleName());
}

```

RoleAssignmentAttribute.getRoleDN

The method returns the distinguished name of the role that defines the assignment attributes.

Availability

IBM Security Identity Manager 7.0.

Synopsis

`RoleAssignmentAttribute.getRoleDN()`

Arguments

None

Returns

The distinguished name of the role that defines the assignment attributes.

Description

Returns the distinguished name of the role that defines the assignment attributes.

Usage

```
var role = new Role(roleDN);
//get assignment attributes of the role
var attributeList = role.getAllAssignmentAttributes();
if (attributeList.length == 0) {
    Enrole.log("script", "No assignment attribute for this role: "
        + role.name);
    return;
}

// print out the distinguished name of the role that defines
// assignment attributes.
for (var i=0; i < attributeList.length; i++) {
    var roleAtr = attributeList[i];
    Enrole.log("script","define role DN-----: "+ roleAtr.getRoleDN());
}
```

RoleAssignmentObject

The `RoleAssignmentObject` class is a `DataObject` class for role assignment data.

This class holds the assignment data that are associated with the defined role and the assigned role. The defined role is the role that holds a list of assignment attributes. The assigned role is the role to which the person is assigned.

Availability

IBM Security Identity Manager 7.0

Provided by

`com.ibm.itim.script.extensions.model.RAObjectModelExtension`

Constructors

new RoleAssignmentObject(RoleAssignmentObject assignmentObject)

Arguments:

assignmentObject

RoleAssignmentObject that is wrapped inside the RoleAssignmentObject.

new RoleAssignmentObject(String assignedRoleDN, String definedRoleDN)

Arguments:

assignedRoleDN

The String format of the distinguished name for the assigned role.

definedRoleDN

The String format of the distinguished name for the defined role.

Methods

addProperty()

Adds the values for specified assignment attribute.

getAssignedRoleDN()

Returns the distinguished name string for the role to which the person is assigned.

getDefinedRoleDN()

Returns the distinguished name string for the role in which the assignment attribute is defined.

getChanges()

Returns the changes made to this RoleAssignmentObject.

getProperty()

Returns the values of the property specified by the assignment attribute name.

getPropertyNames()

Returns a list of role assignment attribute names.

removeProperty()

Removes the values for the specified assignment attribute name.

setProperty()

Sets the values for a specified assignment attribute.

Description

RoleAssignmentObject contains the role assignment data, including the assigned role DN, the defined role DN and attribute values.

RoleAssignmentObject.getAssignedRoleDN()

The method returns the distinguished name string for the role to which a person is assigned.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
roleAssignmentObject.getAssignedRoleDN()
```

Arguments

None

Returns

The distinguished name string for the role to which a person is assigned.

Description

This method returns the distinguished name string for the role to which a person is assigned.

Usage

```
var assignedRoleDN = "globalid=111";  
var definedRoleDN = "globalid=222";  
var assignmentObj = new RoleAssignmentObject(assignedRoleDN, definedRoleDN);  
  
var assignedRoleDN2 = assignmentObj.getAssignedRoleDN();
```

RoleAssignmentObject.getDefinedRoleDN()

The method returns the distinguished name string for the role in which the assignment attribute is defined.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
roleAssignmentObject.getDefinedRoleDN()
```

Arguments

None

Returns

Returns the distinguished name string for the role in which the assignment attribute is defined.

Description

This method returns the distinguished name string for the role to which the person is assigned.

Usage

```
var assignedRoleDN = "globalid=111";
var definedRoleDN = "globalid=222";
var assignmentObj = new RoleAssignmentObject(assignedRoleDN, definedRoleDN);

var definedRoleDN2 = assignmentObj.getDefinedRoleDN();
```

RoleAssignmentObject.addProperty()

Use this method to add the values for specified assignment attribute.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
RoleAssignmentObject.addProperty(name, value)
```

Arguments

name String representing the name of the assignment attribute to be added.

value The value to be added.

Description

This method changes the value of the specified assignment attribute or adds the specified assignment attribute if it does not exist. This change is made locally to the script environment, not to the data store.

Usage

```
// Create assignment object with assigned role dn and defined role dn.
var assignmentObj = new RoleAssignmentObject("eruid=1111,dc=com",
    "eruid=2222,dc=com");
// Add some assignment attribute with values.
assignmentObj.addProperty("attr1", ["attr1val1","attr2val1"]);
assignmentObj.addProperty("attr2", ["attr2val1"]);
assignmentObj.addProperty("attr2", ["attr2val2"]);
```

RoleAssignmentObject.getChanges()

The method returns the changes made to an entity.

Availability

IBM Security Identity Manager 7.0.

Synopsis

RoleAssignmentObject.getChanges()

Returns

An array of change objects. If there are no changes, an empty array is returned. Each element in the array is an *AttributeChangeOperation*.

Description

This method returns the changes made to the entity. These changes are represented by change objects with the following members:

attr String name of the attribute that is being changed.

op An integer that identifies the type of change that is being made. The enumerated values are 1 for add, 2 for replace, and 3 for remove.

values An array of objects that can be either added, removed, or replaced. The changes are returned as an array of these change objects. If there are no changes, an empty array is returned.

Usage

```
changes = assignmentObject.getChanges();
for (i = 0; i < changes.length; i++) {
    name = changes[i].attr;
    if (changes[i].op == 1) {
        ...
    } else if (changes[i].op == 2) {
        ...
    } else {
        ...
    }
};
```

RoleAssignmentObject.getProperty()

The method returns the values of the assignment attribute specified by the given name.

Availability

IBM Security Identity Manager 7.0.

Synopsis

RoleAssignmentObject.getProperty(name)

Arguments

name String representing the name of the assignment attribute to return.

Returns

The array of strings that represents the values for an assignment attribute. If the specified assignment attribute does not exist, an empty array is returned.

Description

This method returns the values of the assignment attribute specified by the given name. If the specified assignment attribute does not exist, an empty array is returned.

Usage

```
// create assignment object with assigned role dn and defined role dn.
var assignmentObj = new RoleAssignmentObject("eruid=1111,dc=com",
    "eruid=2222,dc=com");
assignmentObj.addProperty("attr1", ["attr1val1", "attr1val2"]);

// get assignment attribute values for attr1.
var attrValues = assignmentObj.getProperty("attr1");
var attrValuesStr = "";
for (var j=0; j<attrValues.length; j++) {
    attrValuesStr += attrValues[j] + ", ";
}
Enrole.log("script", "The values for attr1:" + attrValuesStr);
```

RoleAssignmentObject.getPropertyNames()

The method returns a list of assignment attributes.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
RoleAssignmentObject.getPropertyNames()
```

Returns

An array of strings.

Description

This method returns a list of assignment attributes as an array of strings.

Usage `properties = RoleAssignmentObject.getPropertyNames();`

RoleAssignmentObject.removeProperty()

The method removes the assignment attribute specified by the given name.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
RoleAssignmentObject.removeProperty(name)
```

Arguments

name String representing the name of the assignment attribute to remove.

Description

This method removes the specified assignment attribute. This change is made locally to the script environment, not to the data store.

Usage `RoleAssignmentObject.removeProperty("assignmentAttr1");`

RoleAssignmentObject.setProperty()

The method sets the value of the specified assignment attribute.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
RoleAssignmentObject.setProperty(name, value)
```

Arguments

name String representing the name of the assignment attribute to be created or modified.

value Specifies the value to which the assignment attribute is set.

Description

This method changes the value of the specified assignment attribute, or adds the specified assignment attribute if it does not exist. This change is made locally to the script environment, not to the data store.

Usage `RoleAssignmentObject.setProperty("attr1",["val1","val2"]);`

RoleSearch

The object searches for a role.

Availability

IBM Security Identity Manager 7.0

Provided by

`com.ibm.itim.script.extensions.model.RoleModelExtension`

Constructor

`new RoleSearch()`

Returns

The newly created and initialized role search object.

Methods

`searchByName()`

Search for a role by name.

`searchByURI()`

Search for a role by URI within an organizational container.

RoleSearch.searchByName()

The method searches for a role by a name.

Availability

IBM Security Identity Manager 7.0

Synopsis

`RoleSearch.searchByName(name)`

Arguments

name The role name to use as the basis for the search.

Returns

Array of `DirectoryObjects` that represents a role.

Description

Given the name of a role, locate the Role entity. Will return `null` if there is not exactly one matching role.

Usage

```
// Given the name of a role, see if it exists and log its
// description
var roles = (new RoleSearch()).searchByName("testRole");
if (roles.length >= 1) {
    if (roles[0].getProperty("errolename")[0] == "testRole") {
        Enrole.log("script", "The Role " + roles[0].getProperty("errolename")[0] +
            "has Description :" + roles[0].getProperty("description")[0]);
    }
}
```

RoleSearch.searchByURI()

The method finds a role by URI in an organizational container.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
RoleSearch.searchByURI(containerDN, uri)
```

Arguments

Container DN

String representing the distinguished name of the organizational container.

uri String representing the URI of the role.

Returns

A Role object

Description

Given the distinguished name of the organizational container and the role URI, this method finds the container. If the role is not found, this function returns null. If more than one role is found, this function throws a scripting exception.

Usage

```
var role = (new RoleSearch()).searchByURI(container.dn, uri);  
if (role != null) {  
  Enrole.log("script", "Found " + role.getProperty("errolename") );}
```

SeparationOfDutyRuleViolation

Object that provides information about a specific separation of duty rule violation. Use this object to get specific information about a separation of duty policy violation. This object cannot be created for use by the user. The user can work only with SeparationOfDutyRuleViolation objects that the system has generated as part of the *approveSoDViolation* workflow.

Availability

IBM Security Identity Manager 7.0.

Provided by

com.ibm.itim.script.wrappers.generic.IRuleResultWrapper

Methods

getName()

Returns the name of the separation of duty policy rule to which this violation corresponds.

getViolationString()

Provides a string that represents the list of roles in violation. It describes the roles the person has that are in violation and which role in a separation of duty rule they correspond to. The role lists might be different due to role hierarchy.

getViolationStringHTMLTable()

Returns a string version of the roles in violation for use in an HTML table or email template.

getPolicyName()

Returns the name of the separation of duty policy which contains the rule in violation.

getPolicyDescription()

Returns a description of the separation of duty policy.

getPolicyOwnerDNs()

Returns a collection of the distinguished names of one or more separation of duty policy owners.

getCardinality()

Returns string that represents the number of allowed roles in the separation of duty policy rule in violation.

Service

The object represents the service associated with a provisioning operation.

Availability

IBM Security Identity Manager 7.0

Provided by

`com.ibm.itim.script.extensions.model.ServiceModelExtension`

Constructor

`new Service(dn)`

Returns

A new Service object that represents the Service with the DN.

Inherits From

DirectoryObject

Synopsis

`service.dn;`

Description

The service object is available in the context of a Provisioning Policy and Service Selection Policy.

ServiceSearch

Use the object to provide searching capability for IBM Security Identity Manager services.

Availability

IBM Security Identity Manager 7.0

Provisioning Policy context

Service Selection Policy context

Provided by

`com.ibm.itim.script.extensions.model.ServiceModelExtension`

Methods**searchByFilter()**

Search for a service by a filter.

searchByName()

Search for a service by a name.

searchByURI()

Search for a service by URI in an organizational container.

searchForClosestToPerson()

Search for the closest Service to a person.

Description

This object is used to provide searching capability for IBM Security Identity Manager services.

ServiceSearch.searchByFilter()

The method searches for a service by a filter.

Availability

IBM Security Identity Manager 7.0

Synopsis

```
ServiceSearch.searchByFilter(filter, scope)
```

Arguments

- filter** LDAP search filter that defines the criteria for returned containers to meet. The filter must be in the format defined by RFC2254.
- scope** Optional search scope. Use 1 for One Level Scope and 2 for SubTree Scope. One Level Scope is the default scope.

Returns

An array of DirectoryObjects representing the results of the search.

Description

This method searches for a service by a filter.

Usage

```
searchResult1 =  
    ServiceSearch.searchByFilter("(erntlocalservername=*srv)", 2);  
  
// use default one level scope, put statement on one line  
  
searchResult2 =  
    ServiceSearch.searchByFilter("(erntlocalservername=*srv)");
```

ServiceSearch.searchByName()

The method searches for a service by name.

Availability

IBM Security Identity Manager 7.0

Synopsis

```
ServiceSearch.searchByName(name, profileName, scope)
```

Arguments

- name** The service name, provided as a string, to use as the basis for the search.
- profileName** Optional profile name, provided as a string. The profile name of the service to use as the basis for the search.
- scope** Optional search scope, provided as an int. Use 1 for One Level Scope and 2 for Scope. One Level Scope is the

default scope. When you use this method in workflow JavaScripts, set the scope parameter to SubTree because the logical search context is limited to the tenant above the default organization. In this context, setting the scope to One Level Scope returns empty results during a search because there are no services at the tenant level.

Returns

An array of DirectoryObjects representing the results of the search.

Description

This method searches for a service by a name.

Usage

```
searchResult1 = ServiceSearch.searchByName("US Service", 2);  
  
// use default one level scope  
searchResult2 = ServiceSearch.searchByName("US Service");
```

ServiceSearch.searchByURI()

The method finds a service by URI in an organizational container.

Availability

IBM Security Identity Manager 7.0.

Synopsis

```
ServiceSearch.searchByURI(containerDN, uri)
```

Arguments

Container DN

String representing the distinguished name of the organizational container.

uri String representing the URI of the service.

Returns

A Service object

Description

Given the distinguished name of the organizational container and the service URI, this method finds the service. If the service is not found, this function returns null. If more than one service is found, this function throws a scripting exception.

Usage

```
var service = (new ServiceSearch()).searchByURI(container.dn, uri);  
if (service != null) {  
  Enrole.log("script", "Found " + service.getProperty("erservicename") );}
```

ServiceSearch.searchForClosestToPerson()

The method searches for a service closest to a person.

Availability

IBM Security Identity Manager 7.0

Synopsis

```
ServiceSearch.searchForClosestToPerson(person, profileName)
```

Arguments

person

The DirectoryObject representing a person to use as the basis for the search.

profileName

Optional service profile name.

Returns

An array of DirectoryObjects representing the results of the search.

Description

This method searches for a service closest to a person.

Usage

```
//Search for AIX service closest to the person.  
searchResult1 = ServiceSearch.searchForClosestToPerson(subject,  
"PosixAixProfile");  
  
//Search for any service closest to the person.  
searchResult2 = ServiceSearch.searchForClosestToPerson(subject);
```

Chapter 11. Provisioning policy parameter usage scenarios

The following scenarios illustrate usage of provisioning policy parameters.

Scenario 1: No attributes defined

If no parameter values are selected for a multi-valued attribute, all values are valid for this attribute.

If a parameter is added for a multi-valued attribute with the parameter type as Allowed (valid), all other values for this attribute are implicitly excluded for this policy.

If an attribute value is added to a policy as valid, all other values are implicitly excluded for that parameter for the policy.

For multiple applicable entitlements, a valid attribute value is determined by the join directive for the attribute. See the following scenarios.

Scenario 2: Priority-based provisioning policy join directive

The following table identifies two examples of provisioning policies:

Table 10. Provisioning policy examples

Policy	Description
Policy 1	Priority = 1 Attribute: erdivision = divisionA, enforcement = DEFAULT
Policy 2	Priority = 2 Attribute: erdivision = divisionB, enforcement = MANDATORY

Because Policy 1 has a higher priority, only Policy 1's definition for the erdivision attribute is used. Policy 2's definition for the erdivision attribute is ignored.

During policy validation, including reconciliation with policy check option turned on, divisionA might exist on the erdivision attribute. All other values are valid, because the only policy that is being considered in a priority join is Policy 1, which has DEFAULT enforcement on erdivision. DEFAULT enforcement by itself is interpreted as valid for all values, but the default value is the value specified on the new account.

Note: A priority join directive is the default join directive for all single-valued and string-typed attributes.

Scenario 3: Union-based provisioning policy join directive

The following table identifies two example provisioning policies:

Table 11. Sample provisioning policies

Policy	Description
Policy 1	Priority = 1 Attribute: localgroup = groupA, enforcement = DEFAULT
Policy 2	Priority = 2 Attribute: localgroup = groupB, enforcement = MANDATORY

Because the join directive is defined as UNION, the resulting policy uses the following definitions for the policies:

- During account creation, localgroup is defined as groupA and groupB.
- During reconciliations, localgroup is defined as groupB if the attribute is undefined or incorrectly defined.

Note: A union join directive is the default join directive for multi-valued attributes.

Chapter 12. Provisioning policy entitlement parameters

Provisioning policy parameters help system administrators define the attribute values that are required and the values that are allowed.

The following parameter types are valid:

- Constant value
- Null
- JavaScript
- Regular expression

The provisioning parameters in an entitlement can be statically or dynamically defined. Parameters are defined statically by selecting the constant parameter type and specifying literal values, such as strings or integers. For example, an attribute can be defined as Domain Users or Power® Users. A dynamically defined parameter value can be based on a JavaScript function. A range of values can be defined that use a regular expression.

Parameters can also be specified as Null, indicating that the parameter does not have a value. This situation is equivalent to having a JavaScript parameter type with a value of `return null;`

Provisioning parameters for single-valued attributes can be based only on JavaScript code or a constant. The provisioning parameters of a multi-valued attribute can use a constant, JavaScript code, or regular expression for their values.

However, a regular expression can be used only for provisioning parameter enforcement of the Allowed or Excluded type.

Provisioning policy constant

A static, constant value can be assigned to an entitlement parameter for a single or multivalued attribute with the provisioning policy Constant parameter type. You can define a provisioning parameter with a literal static value. You can enter the value or select a value based on the field widget.

Provisioning policy Null types

The null parameter type can be used to specify a null value for an account attribute. If the value of a parameter is specified as null with mandatory enforcement, no value is valid for that attribute. You can specifically define null value for the provisioning parameter, which is equivalent to specifying empty for the value.

Provisioning policy JavaScript functions

You can use a script to define provisioning parameters.

The provisioning parameters of an entitlement within a provisioning policy can be defined by a script. The context of the script is

- The person for whom the entitlement is being enforced.

- The service the entitlement is protecting.
- The `eruid` attribute of the target account.

The context of the script includes the following elements:

Subject

Owner of the account.

Service

Service on which the account exists or to be created.

uid User ID of the account.

Context

Information about the parameter evaluation, which can be validation of a new account or validation of existing account.

A special object named *parameters* is available for `eruid` to evaluate the script in the context of provisioning policy parameters. To obtain its value, use the following syntax:

```
parameters.eruid[0]
```

The value of zero in this syntax returns the first value of the array object.

A JavaScript object named *subject* represents a user for whom the entitlement is being enforced. The service is represented by another JavaScript data model entity named *service*. The script author uses both the subject and service object to access attributes of these objects.

The values of attributes of objects that are part of the evaluation context can also be retrieved with the IBM Security Identity Manager custom JavaScript functions.

To use JavaScript to define the value of an attribute, the JavaScript parameter type must be selected. Select **JavaScript/Constant** in the **Expression Type** field.

The following examples demonstrate the use of IBM Security Identity Manager custom JavaScript functions within provisioning policies. For a complete reference to all custom JavaScript functions, see the JavaScript Extension Reference.

Person attributes

Syntax:

```
subject.getProperty(String rowAttrName)
```

Example:

```
subject.getProperty("sn")[0];
```

Example:

```
# Concatenates user's given name and family name with space in between.
# Resulting string value may be used to on account attribute such as
# Description.
{subject.getProperty("givenname")[0] + " " + subject.getProperty("sn")[0];}
```

Example:

```
# Set a user's Password attribute to the user's Shared Secret Attribute
# (if the account is automatically provisioned)
{
```

```

function passInit()
{
  var password = subject.getProperty("ersharedsecret");
  if (password.length > 0){
    return password[0];
  } else {
    return ""
  }
}
return
passInit();
}

```

Search for person

Syntax:

```
PersonSearch.searchByFilter(String profileName, String filter, [int scope])
```

where scope =1 is a single level search and scope =2 is a subtree search.

Example:

```
PersonSearch.searchByFilter("Person", "(sn=Smith)", 1);
```

Search for service

Syntax:

```
ServiceSearch.searchByFilter(String filter, [int scope])
```

where scope=1 is a single level search and scope=2 is a subtree search.

Example:

```
ServiceSearch.searchByFilter("(erntllocalservername=*srv)", 1);
```

Service closest to the person

Syntax:

```
ServiceSearch.searchForClosestToPerson(Person person, [int scope])
```

where scope=1 is a single level search and scope=2 is a subtree search.

Example:

```
ServiceSearch.searchForClosestToPerson(subject);
```

Name of the business unit in which the person is located

Syntax:

```
subject.getProperty(String propertyName)
```

Example:

```
subject.getProperty("Parent")[0].name;
```

Specifying the current account Uid

Syntax:

```
uid = parameters.eruid[0];
```

Example:

```
var accountId = parameters.eruid[0];
```

Enrole.toGeneralizedTime statement

Syntax:

```
Enrole.toGeneralizedTime(Date date)
```

Examples:

Using the function to return today's date string:

```
var gt = Enrole.toGeneralizedTime(new Date());
```

Using the function to return today's date string as a default attribute:

```
{Enrole.toGeneralizedTime(new Date())}
```

Enrole.toMilliseconds statement

Syntax:

```
Enrole.toMilliseconds(String generalizedTime)
```

Examples:

```
var millis = Enrole.toMilliseconds("200101012004Z");  
var date = new Date(millis);
```

Provisioning policy regular expressions

Regular expressions are used to define a matching pattern that is checked against given text. Within IBM Security Identity Manager, regular expressions define allowed and excluded parameter values.

Within IBM Security Identity Manager, regular expressions define allowed and excluded parameter values. Parameter values with regular expressions are used against existing attribute values to determine which ones are valid.

To use a regular expression for a provisioning parameter value, select **Regular Expression** in the Expression Type menu.

Note: **Regular Expression** can be used only with excluded or allowed attributes. See the regex Java library for a syntax reference.

Chapter 13. Service selection policy JavaScript

A service selection policy identifies the service type for the service returned, and the JavaScript specifies the service. For example, the service definition can be based on attributes of an account owner.

Service selection policy JavaScript objects

The service selection policy JavaScript returns an object that represents a IBM Security Identity Manager service entity.

The “subject” JavaScript object is a Person object that represents the account owner. Attributes of the Person can be used to construct filters to search and return the service. The ServiceModelExtension is available for Service Selection policy by default.

The following list includes APIs for the ServiceSearch JavaScript object that can be used to return the service:

- ServiceSearch.searchByName
- ServiceSearch.searchByFilter
- ServiceSearch.searchForClosestToPerson

See a JavaScript API reference guide for detailed information for these APIs.

Service selection policy script example

This section includes examples of Service Selection policy scripts.

Service selection based on family name

The following script returns a service instance based on the family name of the account owner. Other person attributes such as job title and location can be used to select service, as in this example.

```
function selectService() {
  var sn = subject.getProperty("sn")[0];
  var serviceInstance = null;
  if(sn=="Jones") {
    serviceInstanceArr = ServiceSearch.searchByFilter(
      "(erservicename=NT40X)", 1);

    if (serviceInstanceArr != null && serviceInstanceArr.length > 0)
      serviceInstance = serviceInstanceArr[0];
  } else {
    serviceInstanceArr = ServiceSearch.searchByFilter(
      "(erservicename=NT40Y)", 1);

    if (serviceInstanceArr != null && serviceInstanceArr.length > 0)
      serviceInstance = serviceInstanceArr[0];
  }
  return serviceInstance;
}
return selectService();
```

Searching for the closest service to the person

The following example searches for the service closest to the level of the person, based on the organization tree structure.

```
function selectService() {
  var services = ServiceSearch.searchForClosestToPerson(subject);

  if (services != null && services.length > 0) {
    return services[0];
  }
}
return selectService();
```

Chapter 14. SubForm control type

The SubForm control type provides a means to use custom user interfaces for complex multi-valued attributes.

This control type is used infrequently by some IBM Security Identity Manager adapters.

SubForm is a special control type used to start a servlet, JSP, or static HTML page from a window that opens from a custom IBM Security Identity Manager form. Use subforms to submit an arbitrary number of parameter names and values to a custom servlet or JSP. They are used to create custom user interfaces for complex multi-valued attributes.

Table 12. SubForm parameters

Parameter	Description	Value
customServletURI	The URI to the servlet, JSP, or static HTML page to be started from the main form. If a servlet is implemented and deployed in the default web application for IBM Security Identity Manager, the value for this parameter is the same as the <i>URL-pattern</i> value defined by <i>web.xml</i> in the <i>servlet-mapping</i> tag, without the slash (/). If a JSP is implemented, the value for this parameter is the JSP file name that includes the jsp file extension. This parameter is required on all subforms.	Servlet name or JSP file name such as <i>sample.jsp</i>
<i>Parameter Name</i>	Arbitrary parameter name and value that is included in the HTTP request that starts the resource at <i>customServletURI</i> . For example: <code>objectClass=erracfgrp</code>	<i>Parameter Value</i>

From the Appliance Dashboard on the IBM Security Identity Manager virtual appliance console, click **Configure > Advanced Configuration > Custom File Management**. From the **All Files** tab, go to `directories/utilities` and download the `extensions.zip` file and extract it. Go to `\extensions\7.0\examples\subform`.

SubForm contextual parameters

As a child element of a main form, a SubForm is passed contextual parameters that help identify the context from which it is started.

These contextual parameters are included in the HTTP Request that brings up the SubForm:

Table 13. SubForm parameters

HTTP (contextual) Parameter Name	Person Create	Person Modify	Account Create	Account Modify
target_dn	empty	DN of Person	DN of account owner	DN of the account
container_dn	DN of the organization tree container where the Person is created.	DN of the organization tree container where the person is located.	DN of account owner	DN of the account owner
search_base	empty	empty	DN of service	DN of the service instance on which an account is provisioned

To assign the target_dn HTTP parameter value to a String declared inside a servlet:

```
String targetDN = request.getParameter("target_dn");
```

Account Modify example

For example, for Account Modify, the value of contextual parameters are:

target_dn

Is the DN of the entity whose attributes are displayed on the main form. If the SubForm is placed on a RACF® account form, this parameter value is the DistinguishedName of the RACF account.

container_dn

Is the entity container or parent. For example, if the SubForm is placed on a Person form, this parameter value is the DistinguishedName of the parent or container of the person. The container can be an organization, organizational unit, admin domain, or location.

search_base

For example, if the SubForm is placed on a RACF account form, this parameter value is the DistinguishedName for the RACF service instance on which the account is provisioned.

HTTP request parameter naming convention

A naming convention used on SubForm parameters prevents collisions with other parameters (such as contextual parameters).

The naming convention for SubForm parameters is:

```
[prefix].[attributename].[parametername]
```

where:

prefix property.data

attributename

Name of the attribute on which the SubForm is placed on the main form.

parametername

Name used in the SubForm Editor dialog. For example, an HTTP parameter named `property.erracfconnectgroup.objectClass` would contain the value defined in the SubForm editor dialog assigned to `objectClass`.

To assign this value to a string declared inside a servlet:

```
String objectClass =  
request.getParameter("property.data.erracfconnectgroup.objectClass");
```

Process to write a SubForm

To write a custom SubForm, create a servlet that generates the HTML user interface to manage the value of the attribute.

To save the value, create an instance of `com.ibm.itim.common.AttributeValue` and bind it to a user's `HttpSession` with the key defined in `com.ibm.itim.webclient.util.FormData` (on one line):

```
AttributeValue av = new AttributeValue("attributename", "customValue");  
HttpSession session = request.getSession(false);  
session.setAttribute("subFormAttrValue", av);
```

This ensures that the value gets picked up and added to the form data collected from the fields when the main form is submitted.

Chapter 15. Supplemental property files

The following section provides detailed information about the property keys and values contained in the IBM Security Identity Manager supplemental property files.

Properties files

Java properties files define attributes that allow customizing and control of the Java software.

Standard system properties files and custom properties files are used to configure user preferences and user customization. A Java properties file defines the values of named resources that can specify program options such as database access information, environment settings, and special features and functions.

A properties file defines named resources with a property key and value pair format:

```
property-key-name=value
```

The *property-key-name* is an identifier for the resource. The *value* is usually the name of the actual Java object that provides the resource, or a String representing the value of the property key, such as `database.name=itimdb`. The statement syntax allows spaces before and after the equal (=) sign, and can span multiple lines if you place a line continuation character \ (a backslash) at the end of the line. For more information about statement syntax, see Java language references.

IBM Security Identity Manager uses a number of properties files to control the program and to allow user customization of special features.

Modifiable property files

This table lists the IBM Security Identity Manager properties files that you can modify.

Table 14 lists the IBM Security Identity Manager properties files. Most files are in the **Identity server property files** tab of the Update Property page from the **Appliance Dashboard** of the IBM Security Identity Manager virtual appliance console.

Additional properties files are not configurable. Do not modify them.

Table 14. Properties files

Property file name	Description
adhocreporting	The adhocreporting.properties file supports the custom reporting module.
CustomLabels	The property key and value pairs in the CustomLabels.properties file are used by the Security Identity Manager user interface to display the label text for forms.
DataBaseFunctions.conf	The custom reporting feature of Security Identity Manager allows you to use database functions when designing custom report templates.

Table 14. Properties files (continued)

Property file name	Description
enRole	The enRole.properties system configuration file contains many of the properties that are used to configure IBM Security Identity Manager.
enroleAuditing	The property key and value pairs in the enroleAuditing.properties file are used to enable or disable the tracking of changes made by a Security Identity Manager user to business objects such as person, location, service, and other objects, or configuration of the system.
enRoleAuthentication	The enRoleAuthentication.properties file specifies the type of method that is used by the Security Identity Manager Server to authenticate users and identifies the Java object that provides the specified authentication mechanism.
enRoleDatabase	The enRoleDatabase.properties file specifies attributes that support the relational database used by Security Identity Manager.
enRoleLDAPConnection	The enRoleLDAPConnections.properties file provides standard configuration settings that allow successful communication between Security Identity Manager and the LDAP directory server.
enRoleLogging	The enRoleLogging.properties file specifies attributes that govern the operation of the jlog logging and tracing API that is bundled with Security Identity Manager.
enRoleMail	The enRoleMail.properties file contains attributes that specify the mail transport protocol that is used by the JavaMail API and other Security Identity Manager application-specific properties. You must provide the values for the application-specific properties.
enrolepolicies	The enrolepolicies.properties file provides standard and custom settings that support the functions of the provisioning policy.
enroleStartup	
enroleworkflow	The enroleworkflow.properties file specifies the XML file mappings for system-defined workflows.
fesiextensions	The fesiextensions.properties file (deprecated) provides support for Free EcmaScript Interpreter (FESI) JavaScript extensions before Version 5.0 of Security Identity Manager. Do not author <i>new</i> extensions using this deprecated architecture.
helpmappings	The helpmappings.properties file allows a customer to replace the installed Security Identity Manager help system with an alternative help system.
reportingLabels	This properties file is like other labels-related properties files such as labels.properties, or customLabels.properties, and holds labels that are used by Reports.
reporttabledeny	By default, this property holds a list of Security Identity Manager tables that are used by various Security Identity Manager components to store internal or configuration data that is inappropriate for a report.

Table 14. Properties files (continued)

Property file name	Description
scriptframework	For <i>all</i> new JavaScript extensions, use the scriptframework.properties file to configure script extensions and other scripting functions.
SelfServiceHelp	The SelfServiceHelp.properties file can be used to redirect help to a custom location for customers who want to have their own help content for the self-service user interface.
SelfServiceHomePage	The SelfServiceHomePage.properties file is used to configure the sections of the initially installed home page for the self-service user interface. You can add or remove tasks, and update icon URLs and labels of the home page from this file.
SelfServiceScreenText	The SelfServiceScreenText.properties file is a resource bundle containing the labels for the self-service user interface.
SelfServiceUI	The SelfServiceUI.properties file controls miscellaneous properties of the self-service user interface.
ui	The ui.properties file specifies attributes that affect the operation and display of the Security Identity Manager graphical user interface.

Modifying values of the property files from the IBM Security Identity Manager virtual appliance console

1. From the top-level menu of the **Appliance Dashboard**, select **Configure > Advanced Configuration > Update Property** to display the Update Property page. For more information, see Managing the server properties.
2. In the Update Property page, click the **Identity server property files** tab.
3. Select a properties file from its list. Depending on any property names and its values that are associated with the selected file, the right pane displays all of them.
4. Select a property name.

Note: You can also use the search box to find a specific property name that you want to update.

5. Click **Edit** to open the Update property window.
6. Edit the value in the **Property value** field.
7. Click **Save Configuration**.
8. On the **Appliance Dashboard**, you might be asked to restart the IBM Security Identity Manager Server.

adhocreporing.properties

The adhocreporing.properties file supports the custom reporting module.

Table 15 defines the properties used to configure reporting.

Table 15. adhocreporing.properties properties

Report Generation
reportPageSize

Table 15. *adhocreporting.properties* properties (continued)

	<p>Indicates the number of rows that are displayed on each page of a PDF report. The maximum number of rows on a page must not exceed 45.</p> <p>Example (default): reportPageSize=45</p>
reportColWidth	
	<p>Indicates the width, in centimeters (cm), of the report column in a PDF report output. You can adjust the size of all columns by modifying this value.</p> <p>Note: 2.54 cm equals 1 inch.</p> <p>Example (default): reportColWidth=20</p>
Access Control Item Enforcement on Report Data Generated	
availableForNonAdministrators	
	<p>Specifies whether to synchronize access control item-related information during data synchronization.</p> <p>Set this value to true to enable non-administrators to run reports.</p> <p>Set this value to false to disable all functions related to non-administrator execution of reports, such as access control item data synchronization and setting report access control items on reports.</p> <p>Example: availableForNonAdministrators=true</p>
Incremental schema Enforcement using Incremental Data Synchronizer	
enableDeltaSchemaEnforcer	
	<p>Specifies whether to synchronize any schema changes in reporting.</p> <p>Schema changes include new mappings that were created or existing mappings that were removed with the Schema Designer.</p> <p>When set to true, the Incremental Data Synchronizer manages the attributes that are mapped (changed) in the Schema Designer since the last full data synchronization was run.</p> <p>When set to false, the Incremental Data Synchronizer does not synchronize the attributes which are mapped (changed) since the last full data synchronization was run.</p> <p>Example (default): enableDeltaSchemaEnforcer=false</p>
Data Synchronization	
changeLogEnabled	

Table 15. *adhocreporting.properties* properties (continued)

	<p>Specifies whether the Incremental Data Synchronizer is used. Values include:</p> <ul style="list-style-type: none"> • true – Incremental Data Synchronizer is configured • false – Incremental Data Synchronizer is not configured <p>Example (default): changeLogEnabled=false</p>
changeLogBaseDN	
	<p>Specifies the DN in the directory where the change log is configured.</p> <p>Example (default): changeLogBaseDN=cn=changeLog</p>
changeLogFetchSize	
	<p>Specifies the number of change logs to be fetched at one time from the directory server.</p> <p>A value of 0, or a negative value, results in no fetch restriction. Fetch restriction is useful when the directory server cannot be heavily loaded for a time. For example, retrieving 100,000 change log entries at a time can delay the directory server response time for a few minutes.</p> <p>Example (default): changeLogFetchSize=200</p>
maximumChangeLogsToSynchronize	
	<p>Specifies the maximum number of change logs to be synchronized in a single use of the Incremental Data Synchronizer.</p> <p>Consider the available system memory and CPU utilization that is required for other processes in the system when you set this property. If the value is set to zero or a negative value, the Incremental Data Synchronizer synchronizes all change log entries.</p> <p>Example (default): maximumChangeLogsToSynchronize=10000</p>
changeLogsToAnalyzeBeforeSynchronization	

Table 15. *adhocreporting.properties* properties (continued)

	<p>Specifies the number of fetched change log entries to be analyzed before all analyzed entries are synchronized to the database.</p> <p>For example, consider the following values: <code>changeLogFetchSize=500</code> <code>changeLogsToAnalyzeBeforeSynchronization=20000</code> <code>maximumChangeLogsToSynchronize=100000</code></p> <p>500 change log entries are considered one batch. After 20,000 change log entries (40 batches) are analyzed, data synchronization occurs. This process repeats until 100,000 entries are analyzed (5 synchronizations).</p> <p>Setting this value to 0 or a negative value results in synchronization of all fetched change log entries.</p> <p>Example (default): <code>changeLogsToAnalyzeBeforeSynchronization=5000</code></p>
<code>enableChangeLogPruning</code>	
	<p>Specifies whether change log entries need to be pruned after they are successfully synchronized. This property takes effect only for the SunOne Version 5.2 directory server. For the IBM Security Directory Server, see its documentation about pruning change log entries.</p> <p>Example (default): <code>enableChangeLogPruning=false</code></p>
<code>itimAdminID</code>	
	<p>Specifies the administrator ID required to run the Incremental Data Synchronizer in a z/OS® environment.</p> <p>For example: <code>itimAdminID=myadminid</code></p>
<code>itimAdminCredential</code>	
	<p>Specifies the Security Identity Manager password required to run the Incremental Data Synchronizer in a z/OS environment.</p> <p>For example: <code>itimAdminCredential=myadmincredential</code></p>
<code>createIndex</code>	
	<p>Specifies whether to create database indexes for frequently used database columns. If this property is set to true, reports are generated more quickly.</p> <p>Valid values for this property are:</p> <ul style="list-style-type: none"> • true – Creates indexes for columns that are used by reporting. Enabling this value might increase the data synchronization time. • false – Does not create indexes during data synchronization. Disabling this value might increase the time that is needed to generate reports. <p>Example (default): <code>createIndex=true</code></p>

Table 15. *adhocreporting.properties* properties (continued)

reportIndexes	
	<p>Specifies a set of a set of <ENTITY:(ATTR1 ORDER1, ATTR2 ORDER2, ...) > values on which indexes are created.</p> <p>Both single and compound indexes can be created with this property. If you are creating a single index, use the name of entity that you see in the report designer or schema mapping.</p> <p>If you are defining a compound index, specify the exact table name, such as Account or Person_cn, instead of the entity name. You can specify an optional order asc or desc for an index. Observe the usage of a semi-colon as the delimiter between indexes. You must maintain the syntax of this property correctly, or indexes might not get created successfully.</p> <p>If you add additional indexes, follow the syntax for these default indexes: reportIndexes=Person:cn asc;Account:eraccountcompliance; Account:(eraccountstatus asc);Account:erlastaccessdate asc; Account:eruid asc;Service:(servicetype asc); Service:erservicename asc;ProvisioningPolicy:erpolicyitemname asc; ProvisioningPolicy:erpolicytarget asc; ProvisioningPolicy:erpolicymembership asc;Role:errolename asc; Account:(eraccountstatus asc, erservice asc); Person_cn:(dn, cn);Account_owner:(dn asc, owner asc)</p>
sqlBatchSize	
	<p>Indicates the size of batch updates that are processed during data synchronization. To improve performance, set this value to a larger number. This value is affected by the specific database settings for the transaction log file size, a database property. Setting the value too high might cause data synchronization to fail. Always use the default value of 50 to avoid data synchronization failure.</p> <p>A value of 0, or a negative value, causes all SQL updates to be processed as a single batch.</p> <p>Example (default): sqlBatchSize=50</p>
attribsSkippedInSchema	
	<p>These attributes contain XMLs as data. The reporting engine currently does not support reporting on these attributes.</p> <p>Example (on one line): attribsSkippedInSchema=erEntitlements erAc1 erHistoricalPassword erJavascript erLostPasswordAnswer erPassword erPlacementRule erxforms erXML</p>
reportsAllowedAttributes	
	<p>A set of attributes on which reporting engine does not enforce attribute-level access control.</p> <p>Example (default): reportsAllowedAttributes=servicetype</p>
reportsAllowedEntities	

Table 15. *adhocreporting.properties* properties (continued)

	<p>A set of entities on which reporting engine does not enforce attribute-level access control.</p> <p>Example (default): reportsAllowedEntities=RecertificationPolicy,Group</p>
reservedWords	
	<p>Database reserved words. These words are not used as table/column names during Schema Mapping and Data Synchronization.</p> <p>Example (on one line): reservedWords=ALL ADD ALTER BACKUP BEGIN BY BULK CASCADE CHECK CHECKPOINT CLUSTORED COLUMN CREATE CURRENT DUMMY DOMAIN DELETE DEFAULT DISTINCT DROP FORIGN FROM GROUP IDENTITY IDENTITY_INSERT IDENTITYCOL INSERT IN LIKE SET SELECT TABLE VALUES ORDER UID WHERE</p>
disallowedChars	
	<p>Characters that are not part of Table/Column name in database. If the entity/attribute name contains one or more of these characters, the characters are removed from the table or column name. In the following example, the double backslashes (\\) are used as escape characters.</p> <p>Example (default): disallowedChars=~!@#%^&*()+{} :\"<>? -=[]\;\';',./</p>
disallowedCharsForStart	
	<p>Characters are not used as the starting character of table or column name. In the following example, the double backslashes (\\) are used as escape characters.</p> <p>Example (default): disallowedCharsForStart=~!@#\$\$%^&*()_+{} :\"<>? -=[]\;\';',./0123456789</p>
maxTableNameLength	
	<p>Default maximum length for a table name.</p> <p>Example (default): maxTableNameLength=30</p>
maxColumnNameLength	
	<p>Default maximum length for a column name.</p> <p>Example (default): maxColumnNameLength=30</p>
maxTableNameLength_DB2	
	<p>Maximum name length for a table name in DB2®.</p> <p>Example (default): maxTableNameLength_DB2=128</p>
maxColumnNameLength_DB2	

Table 15. *adhocreporting.properties* properties (continued)

	<p>Maximum name length for a column name in DB2.</p> <p>Example (default): <code>maxColumnNameLength_DB2=30</code></p>
<code>maxTableNameLength_ZDB2</code>	
	<p>Maximum name length for a table name in DB2 z/OS.</p> <p>Example (default): <code>maxTableNameLength_ZDB2=128</code></p>
<code>maxColumnNameLength_ZDB2</code>	
	<p>Maximum name length for a column name in DB2 z/OS.</p> <p>Example (default): <code>maxColumnNameLength_ZDB2=30</code></p>
<code>maxTableNameLength_ORACLE=30</code>	
	<p>Maximum name length for a table name in Oracle.</p> <p>Example (default): <code>maxTableNameLength_ORACLE=30</code></p>
<code>maxColumnNameLength_ORACLE</code>	
	<p>Maximum name length for a column name in Oracle.</p> <p>Example (default): <code>maxColumnNameLength_ORACLE=30</code></p>
<code>maxTableNameLength_MS_SQL_SERVER</code>	
	<p>Maximum name length for a table name in Microsoft SQL Server.</p> <p>Example (default): <code>maxTableNameLength_MS_SQL_SERVER=128</code></p>
<code>maxColumnNameLength_MS_SQL_SERVER</code>	
	<p>Maximum name length for a column name in Microsoft SQL Server.</p> <p>Example (default): <code>maxColumnNameLength_MS_SQL_SERVER=128</code></p>
<code>populateGroupMembers</code>	

Table 15. *adhocreporting.properties* properties (continued)

	<p>Specifies whether Service group membership changes need to be synchronized during incremental synchronization. Service group membership information is stored in the GROUPMEMBERS table.</p> <p>Valid values for this property are:</p> <ul style="list-style-type: none"> • true – Synchronizes membership changes to service groups and accesses (for example, because of a new access request). • false – Does not synchronize group membership changes, since this type of synchronization is performance intensive. <p>Example (default): <code>populateGroupMembers=false</code></p>
--	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

CustomLabels.properties

The property key and value pairs in the CustomLabels.properties file are used by the IBM Security Identity Manager user interface to display the label text for forms.

The key name must be entirely lowercase in each property key and value pair.

A separate CustomLabels.properties file exists for each individual language supported by IBM Security Identity Manager.

This file is used to provide localized versions of graphical user interface elements when IBM Security Identity Manager is installed in international environments.

Add the property key and value pairs in the CustomLabels.properties properties file to display any labels.

For example, to display a two word access type - **Business Applications**,

1. Specify the access key as **businessApplications**. The access type key cannot contain a space.
2. Specify the value as **Business Applications**.

The entry in the CustomLabels.properties file to have "Business Applications" displayed in the user interface as the access type is **businessApplications=Business Applications**.

Access types that are part of a hierarchy of types have a special notation that you must use in the CustomLabels.properties file. Each node of the hierarchy must be in the key and separated by a period (.). For example, an access type that is called **Applications** has a child **businessApplications**. You want **businessApplications** to display as "Business Applications". The entry that you define in the CustomLabels.properties file is **Applications.businessApplications=Business Applications**.

A file name extension identifies the specific language. For example:

English

CustomLabels_en.properties

Japanese

CustomLabels_ja.properties

enroleAuditing.properties

The property key and value pairs in the `enroleAuditing.properties` file are used to enable or disable the tracking of changes made by a Security Identity Manager user to business objects such as person, location, service, and other objects, or configuration of the system.

Any user request to change the IBM Security Identity Manager directory store or database can be audited and published in a report.

The following is a comprehensive list of events audited:

- ACI Management (**Add, Add Authorization Owner, Delete, Delete Authorization Owner, Modify**)
- Account Management (**Add, Adopt, Change Password, Delete, Modify, Orphan, Password Pickup, Restore, Suspend, Synchronize Password**)
- Access Management (**Add, Remove**)
- Access Configuration (**Add, Remove, Modify**)
- Authentication (**Authenticate ITIM user**)
- Container Management (**Add, Delete, Modify**)
- Delegate Authority (**Add, Delete, Modify**)
- Entitlement Workflow Management (**Add, Delete, Modify**)
- Entity Operation Management (**Add, Delete, Modify**)
- IBM Security Identity Manager Configuration (**Add, Delete, Enforce, Install Profile, Modify, Uninstall Profile**)
- Group Management (**Add, Add Member, Delete, Modify, Remove Member**)
- Migration (**Agent Profile Install, Start Export, Start Import, Stop Export, Stop Import**)
- Role Management (**Add, Add Member, Delete, Modify, Remove Member**)
- Person Management (**Add, Delete, Modify, Restore, Self Register, Suspend, Transfer**)
- Policy Management (**Add, Commit Draft, Delete, Enforce Entire Policy, Modify, Save as Draft, Add Account Template, Change Account Template, Remove Account Template**)
- Reconciliation (**Run Recon, Set Recon Unit, Set Service Recon Parameters**)
- Runtime Events (**Start IBM Security Identity Manager, Stop IBM Security Identity Manager**)
- Self Password Change (**Change Password, Reset Password**)
- Service Management (**Add, Add Adoption Rule, Delete, Delete Adoption Rule, Modify, ModifyAdoption Rule**)
- Service Policy Enforcement (**Correct Non-Compliant, Mark Non-Compliant, Suspend Non-Compliant, Use Global Setting, Use Workflow For Non-Compliant**)

Audited information specifically includes:

- The identity of the user who takes the action.
- The time the action was taken.
- The type of action taken.
- The data effected by the action.

Table 16 defines the properties used to configure how the auditing feature behaves.

Table 16. *enroleAuditing.properties properties*

IBM Security Identity Manager audit configuration settings	
itim.auditing	
	<p>Specifies whether to enable or disable auditing for IBM Security Identity Manager events.</p> <p>Valid values include:</p> <ul style="list-style-type: none"> • true – IBM Security Identity Manager events are audited • false – IBM Security Identity Manager events are not audited, regardless of the settings of individual events or categories <p>Example (default): itim.auditing=true</p>
itim.auditing.retrycount	
	<p>The number of times auditing is tried again in case of failure.</p> <p>Valid values include any integer.</p> <p>Example (default): itim.auditing.retrycount=1</p>
itim.auditing.retrydelay	
	<p>The wait time in milliseconds before trying again.</p> <p>Example (default): itim.auditing.retrydelay=5000</p>
enrole.auditing.errorpopup.enabled	
	<p>Enables or disables the process failure display.</p> <p>Example (default): enrole.auditing.errorpopup.enabled=false</p>
enrole.auditing.errorpopup.fields	
	<p>The process failure display always contains these attributes and their values: {name, subject, type, result_summary}</p> <p>You can additionally specify one or more of these attributes: {subject, comments, name, type, requester_type, requester_name, description, scheduled, started, completed, lastmodified, submitted, state, notify, requestee_name, subject_profile, subject_service, result_summary, result_detail}</p> <p>Example: enrole.auditing.errorpopup.fields=subject, comments</p>
enrole.auditing.errorpopup.textwrap	

Table 16. *enroleAuditing.properties* properties (continued)

	<p>Specifies whether the text wraps at the end of the display.</p> <p>Example (default): <code>enrole.auditing.errorpopup.textwrap=false</code></p>
<code>enrole.auditing.pageSize</code>	
	<p>Specifies the page size in lines that displaying unsuccessful processes or activities on the failed activity popup.</p> <p>Example (default): <code>enrole.auditing.pageSize=10</code></p>
<code>enrole.auditing.pageLinkMax</code>	
	<p>Specifies the number of page links for multi-page result sets on the failed activity.</p> <p>Example (default): <code>enrole.auditing.pageLinkMax=10</code></p>
<code>enrole.auditing.viewRequests.skipServiceLookup.customProcessTypes</code>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the custom process type that does not have a service or an account as subject data in the input parameters of its corresponding workflow operation. To use this property, add it to the <code>\$ISIM_HOME/data/enroleAuditing.properties</code> file with a custom process type value.</p> <p>Valid values: A comma-separated custom process type value.</p> <p>Example (default): <code>enrole.auditing.viewRequests.skipServiceLookup.customProcessTypes=CP</code></p>

enRoleAuthentication.properties

The `enRoleAuthentication.properties` file specifies the type of method that is used by the Security Identity Manager Server to authenticate users and identifies the Java object that provides the specified authentication mechanism.

Additionally, the file specifies objects that support IBM Security Access Manager WebSEAL single sign-on and administration of IBM Security Identity Manager to managed remote services.

Authentication properties are specified with a property key and value pair format:
property-key-name=value

The *property-key-name* is an identifier for the authentication mechanism or resource. The *value* is the name of the Java object that provides the authentication service, expressed also as a key and value pair.

factory=value

The **factory** key name represents a special category for authentication support within the IBM Security Identity Manager software. The *value* is the actual name of the Java object.

For example (entered on one line):

```
enrole.authentication.provider.service=
    factory=com.ibm.enrole.authentication.service.
    ServiceAuthenticationProviderFactory
```

Table 17 defines the properties used to configure IBM Security Identity Manager authentication.

Table 17. enRoleAuthentication.properties properties

Authentication method	
enrole.authentication.requiredCredentials={simple}	
	<p>Specifies the required authentication method for users who log in to the IBM Security Identity Manager Server.</p> <p>The valid value for this property is:</p> <ul style="list-style-type: none"> • simple - User name and password. <p>Example (default):</p> <pre>enrole.authentication.requiredCredentials=simple</pre>
Authentication providers (factories)	
enrole.authentication.provider.simple	
	<p>Specifies the Java object that handles authentication with user name and password.</p> <p>Example (entered on a single line):</p> <pre>enrole.authentication.provider.simple=\ factory=com.ibm.itim.authentication.simple. SimpleAuthenticationProviderFactory</pre>
Authentication service provider	
enrole.authentication.provider.service	
	<p>Specifies the Java object that transparently handles IBM Security Identity Manager access to managed remote services and to manage changes in the accounts to these remote services.</p> <p>These changes include addition, deletion, suspension, restoration, and modification of accounts on the remote service. When you log in to IBM Security Identity Manager, you can change the login and password information for an account on the managed remote service.</p> <p>The ServiceAuthenticationProviderFactory mechanism works with the agent for a given remote service and processes the changed information.</p> <p>Example (entered on a single line):</p> <pre>enrole.authentication.provider.service=\ factory=com.ibm.itim.authentication.service. ServiceAuthenticationProviderFactory</pre>
WebSEAL single sign-on	
enrole.authentication.provider.webseal	

Table 17. *enRoleAuthentication.properties* properties (continued)

	<p>Specifies the Java object that allows single sign-on in a WebSEAL environment.</p> <p>Example (entered on a single line):</p> <pre>enrole.authentication.provider.webseal=\ factory=com.ibm.itim.authentication.webseal.WebsealProviderFactory</pre>
enrole.authentication.idsEqual	
	<p>Indicates the appropriate algorithm for mapping the IBM Security Access Manager user ID to an IBM Security Identity Manager user ID. An internal identity mapping algorithm is used to ensure the success of the single sign-on operation.</p> <p>Valid values for this property are:</p> <ul style="list-style-type: none"> • true – The Security Access Manager user ID is the same as the IBM Security Identity Manager user ID. • false – The Security Access Manager user ID is not the same as the IBM Security Identity Manager user ID. <p>Example:</p> <pre>enrole.authentication.idsEqual=true</pre>

enRoleLogging.properties

The `enRoleLogging.properties` file specifies attributes that govern the operation of the `jlog` logging and tracing API that is bundled with Security Identity Manager.

`jlog` is a logging package for Java. With this package, you can log messages by message type and priority. At run time, you also can control how these messages are formatted and where they are reported.

Table 18 defines the properties used to configure IBM Security Identity Manager logging properties.

Table 18. *enRoleLogging.properties* properties

General settings	
logger.refreshInterval	
	<p>Specifies the refresh interval [in milliseconds] of the logging properties.</p> <p>Example:</p> <pre>logger.refreshInterval=300000</pre>
logger.msg.com.ibm.itim.security.logChoice	
	<p>Specifies the type of authentication attempts to log.</p> <p>Valid values are:</p> <ul style="list-style-type: none"> • failure — Log authentication failures. • success — Log authentication successes. • both — Log both authentication failures and successes. <p>Example:</p> <pre>logger.msg.com.ibm.itim.security.logChoice=failure</pre>

Table 18. *enRoleLogging.properties* properties (continued)

logger.msg.com.ibm.itim.security.logging	
	<p>Specifies whether authentication attempts are logged or not.</p> <p>Valid values are:</p> <ul style="list-style-type: none"> • true — Log authentication attempts. • false — Do not log authentication attempts. <p>Example: logger.msg.com.ibm.itim.security.logging=true</p>
handler.file.security.maxFiles	
	<p>Specifies the maximum number of security log files.</p> <p>Example: handler.file.security.maxFiles=10</p>
logger.msg.level	
	<p>Specifies the logging level for messages.</p> <p>Valid values are:</p> <ul style="list-style-type: none"> • INFO • WARN • ERROR <p>Example: logger.msg.level=INFO</p>
handler.file.msg.maxFiles	
	<p>Specifies the maximum number of message log files.</p> <p>Example: handler.file.msg.maxFiles=5</p>
logger.trace.level	
	<p>Specifies the tracing level.</p> <p>The supported trace levels are:</p> <ul style="list-style-type: none"> • DEBUG_MIN • DEBUG_MID • DEBUG_MAX <p>DEBUG_MAX is the most verbose trace level and can effect system performance. When you debug a problem, avoid setting DEBUG_MAX at logger.trace. Set the DEBUG_MAX at the effected components or packages.</p> <p>Example: logger.trace.level=DEBUG_MIN</p>
handler.file.trace.maxFiles	

Table 18. *enRoleLogging.properties* properties (continued)

	<p>Specifies the maximum number of trace log files.</p> <p>Example: handler.file.trace.maxFiles=10</p>
handler.file.maxFileSize	
	<p>Specifies the maximum log file size in kilobytes</p> <p>Example: handler.file.maxFileSize=1024</p>
Logger root properties	
jlog.noLogCmd	
	<p>Do not modify this property key and value.</p> <p>Disables the log command server.</p> <p>Example: jlog.noLogCmd=true</p>
logger.className	
	<p>Do not modify this property key and value.</p> <p>Specifies the class name of the logger.</p> <p>Example: logger.className=com.ibm.log.PDLogger</p>
logger.description	
	<p>Specifies the description of the logger.</p> <p>Example: logger.description=TIM PD Logger</p>
logger.product	
	<p>Do not modify this property key and value.</p> <p>Specifies the product name.</p> <p>Example: logger.product=CTGIM</p>
logger.productInstance	
	<p>Do not modify this property key and value.</p> <p>Specifies the server instance name. The value is supplied during the installation of Security Identity Manager.</p> <p>Example: logger.productInstance=myserver</p>

Table 18. *enRoleLogging.properties* properties (continued)

Message logger properties	
logger.msg.description	
	<p>Specifies the description of the message logger.</p> <p>Example: logger.msg.description=TIM PD Message Logger</p>
logger.msg.logging	
	<p>Turns logging on or off for messages.</p> <p>Valid values are:</p> <ul style="list-style-type: none"> • true — Turns logging on. • false — Turns logging off. <p>Example: logger.msg.logging=true</p>
logger.msg.messageFile	
	<p>Do not modify this property key and value.</p> <p>Specifies the resource bundle name of localizable messages.</p> <p>Example: logger.msg.messageFile=tmsMessages</p>
logger.msg.com.ibm.itim.ui.messageFile	
	<p>Do not modify this property key and value.</p> <p>Specifies the resource bundle name of localizable messages.</p> <p>Example: (on a single line) logger.msg.com.ibm.itim.ui.messageFile= com.ibm.itim.ui.resources.UIMessageResources</p>
logger.msg.listenerNames	
	<p>Do not modify this property key and value.</p> <p>Specifies the listener names attached to the message logger.</p> <p>Example: logger.msg.listenerNames=handler.file.msg handler.ffdc.fileCopy</p>
Security logger properties	
logger.msg.com.ibm.itim.security.listenerNames	

Table 18. *enRoleLogging.properties* properties (continued)

	<p>Do not modify this property key and value.</p> <p>Specifies the listener names attached to the security logger.</p> <p>Example: <code>logger.msg.com.ibm.itim.security.listenerNames=handler.file.security</code></p>
Trace logger properties	
<code>logger.trace.description</code>	
	<p>Specifies the description of the trace logger.</p> <p>Example: <code>logger.trace.description=TIM PD Trace Logger</code></p>
<code>logger.trace.logging</code>	
	<p>Turns trace logging on or off.</p> <p>Valid values are:</p> <ul style="list-style-type: none"> • true — Turns logging on. • false — Turns logging off. <p>Example: <code>logger.trace.logging=true</code></p>
<code>logger.trace.listenerNames</code>	
	<p>Do not modify this property key and value.</p> <p>Specifies the listener names attached to the trace logger.</p> <p>Example: <code>logger.trace.listenerNames=handler.file.trace</code></p>
<code>logger.trace.com.ibm</code>	

Table 18. *enRoleLogging.properties* properties (continued)

	<p>Edit the level of these component loggers to adjust the amount of tracing information written to the trace log.</p> <p>The supported trace levels are:</p> <ul style="list-style-type: none"> • DEBUG_MIN • DEBUG_MID • DEBUG_MAX <p>Component loggers are:</p> <p>Note: The <code>logger.trace.com.ibm.itim.script.level</code> component logger is equivalent to <code>logger.trace.com.ibm.itim.fesiextensions.level</code> (deprecated).</p> <p><code>logger.trace.com.ibm.itim.adhocreport.level</code> <code>logger.trace.com.ibm.itim.adhocreport.changelog.level</code> <code>logger.trace.com.ibm.itim.apps.level</code> <code>logger.trace.com.ibm.itim.apps.ejb.adhocreport.level</code> <code>logger.trace.com.ibm.itim.authentication.level</code> <code>logger.trace.com.ibm.itim.authorization.level</code> <code>logger.trace.com.ibm.itim.common.level</code> <code>logger.trace.com.ibm.itim.fesiextensions.level</code> <code>logger.trace.com.ibm.itim.script.level</code> <code>logger.trace.com.ibm.itim.mail.level</code> <code>logger.trace.com.ibm.itim.messaging.level</code> <code>logger.trace.com.ibm.itim.dataservices.model.level</code> <code>logger.trace.com.ibm.itim.passworddelivery.level</code> <code>logger.trace.com.ibm.itim.policy.level</code> <code>logger.trace.com.ibm.itim.remoteservices.level</code> <code>logger.trace.com.ibm.itim.remoteservices.installation.level</code> <code>logger.trace.com.ibm.itim.report.level</code> <code>logger.trace.com.ibm.itim.security.level</code> <code>logger.trace.com.ibm.itim.scheduling.level</code> <code>logger.trace.com.ibm.itim.script.level</code> <code>logger.trace.com.ibm.itim.systemConfig.level</code> <code>logger.trace.com.ibm.itim.util.level</code> <code>logger.trace.com.ibm.itim.webclient.level</code> <code>logger.trace.com.ibm.itim.workflow.level</code> <code>logger.trace.com.ibm.daml.level</code> <code>logger.trace.com.ibm.erma.level</code></p>
Applet tracing properties	
<code>logger.trace.com.ibm.itim.applet.logging</code>	
	<p>Enables or disables applet trace logging.</p> <p>Example:</p> <p><code>logger.trace.com.ibm.itim.applet.logging=true</code></p>
<code>logger.trace.com.ibm.itim.applet.level</code>	
	<p>Specifies the applet tracing level.</p> <p>The supported trace levels are:</p> <ul style="list-style-type: none"> • DEBUG_MIN • DEBUG_MID • DEBUG_MAX <p>Example:</p> <p><code>logger.trace.com.ibm.itim.applet.level=DEBUG_MIN</code></p>

Table 18. *enRoleLogging.properties* properties (continued)

File handler properties	
<code>handler.file.className</code>	
	<p>Do not modify this property key and value.</p> <p>Specifies the class name of the file handler.</p> <p>Example: <code>handler.file.className=com.ibm.log.FileHandler</code></p>
<code>handler.file.description</code>	
	<p>Specifies the description of the file handler.</p> <p>Example: <code>handler.file.description=TIM File Handler</code></p>
<code>handler.file.fileDir</code>	
	<p>Do not modify this property key and value.</p> <p>Specifies the base directory of the file handler. This value is supplied during installation.</p> <p>Example: <code>handler.file.fileDir=c:/tivoli_comm_dir/CTGIM/logs</code></p>
<code>handler.file.formatterName</code>	
	<p>Do not modify this property key and value.</p> <p>Specifies the formatter of the file handler.</p> <p>Example: <code>handler.file.formatterName=formatter.PDXML</code></p>
Message logging file handler properties	
<code>handler.file.msg.fileName</code>	
	<p>Specifies the message log file.</p> <p>Example: <code>handler.file.msg.fileName=msg.log</code></p>
<code>handler.file.msg.formatterName</code>	
	<p>Do not modify this property key and value.</p> <p>Specifies the formatter of the message file handler.</p> <p>Example: <code>handler.file.msg.formatterName=formatter.PDXML.msg</code></p>
Security logging file handler properties	

Table 18. *enRoleLogging.properties* properties (continued)

handler.file.security.fileDir	
	<p>Specifies the security log directory.</p> <p>Example: handler.file.security.fileDir=c:/tivoli_comm_dir/CTGIM/logs</p>
handler.file.security.fileName	
	<p>Specifies the security log file.</p> <p>Example: handler.file.security.fileName=access.log</p>
handler.file.security.formatterName	
	<p>Do not modify this property key and value.</p> <p>Specifies the formatter of the security file handler.</p> <p>Example: handler.file.security.formatterName=formatter.PDXML.security</p>
Trace file handler properties	
handler.file.trace.fileName	
	<p>Specifies the trace file name.</p> <p>Example: handler.file.trace.fileName=trace.log</p>
handler.file.trace.formatterName	
	<p>Do not modify this property key and value.</p> <p>Specifies the formatter of the trace file handler.</p> <p>Example: handler.file.trace.formatterName=formatter.PDXML.trace</p>
FFDC (First-Failure Data Capture) file copy handler properties	
handler.ffdc.baseDir	
	<p>Do not modify this property key and value.</p> <p>Specifies the ffdc base directory.</p> <p>Example: handler.ffdc.baseDir=c:/tivoli_comm_dir/CTGIM/ffdc</p>
handler.ffdc.triggerRepeatTime	

Table 18. *enRoleLogging.properties* properties (continued)

	<p>Specifies the minimum time [in milliseconds] after an initial triggering that the handler responds to subsequent triggering events.</p> <p>Example: <code>handler.ffdc.triggerRepeatTime=300000</code></p>
<code>handler.ffdc.fileCopy.className</code>	
	<p>Do not modify this property key and value.</p> <p>Specifies the handler class name.</p> <p>Example: <code>handler.ffdc.fileCopy.className=com.tivoli.log.FileCopyHandler</code></p>
<code>handler.ffdc.fileCopy.triggerFilter</code>	
	<p>Specifies the filter to control which events trigger an FFDC action.</p> <p>Example: <code>handler.ffdc.fileCopy.triggerFilter=filter.msgId</code></p>
<code>handler.ffdc.fileCopy.fileTimestampFormat</code>	
	<p>Do not modify this property key and value.</p> <p>Specifies the time stamp format which is appended to the FFDC folder name and file names.</p> <p>Example: <code>handler.ffdc.fileCopy.fileTimestampFormat=yyyy.MM.dd-HH.mm.ss</code></p>
<code>handler.ffdc.fileCopy.filesToCopy</code>	
	<p>Specifies the files to be copied to the FFDC directory when the FFDC is triggered.</p> <p>Example (on a single line): <code>handler.ffdc.fileCopy.filesToCopy= " c:/tivoli_comm_dir/CTGIM/logs/trace.log" " c:/tivoli_comm_dir/CTGIM/logs/msg.log"</code></p>
FFDC message id filter properties	
<code>filter.msgId.className</code>	
	<p>Do not modify this property key and value.</p> <p>Specifies the class name of the message ID filter.</p> <p>Example: <code>filter.msgId.className=com.tivoli.log.MsgIdFilter</code></p>
<code>filter.msgId.description</code>	

Table 18. *enRoleLogging.properties* properties (continued)

	<p>Specifies the description of the message ID filter.</p> <p>Example: <code>filter.msgId.description=IBM Security Identity Manager FFDC Message Id Filter</code></p>
<code>filter.msgId.msgIds</code>	
	<p>Specifies the TMS message IDs that trigger the FFDC action. The listed message IDs represent the most severe system errors.</p> <p>Example (on a single line): <code>filter.msgId.msgIds=CTGIMA401E CTGIMA438W CTGIME013E CTGIME035E CTGIME203E CTGIMF003E CTGIMF011E CTGIMF012E CTGIMF013E CTGIMF014E</code></p>
<code>filter.msgId.mode</code>	
	<p>Do not modify this property key and value.</p> <p>Specifies the filter mode.</p> <p>Example: <code>filter.msgId.mode=PASSTHRU</code></p>
<code>filter.msgId.msgIdRepeatTime</code>	
	<p>Specifies the minimum time in milliseconds to wait after a log event is passed with a TMS message ID before it passes another one with the same ID.</p> <p>Example: <code>filter.msgId.msgIdRepeatTime=300000</code></p>
Formatter properties	
<code>formatter.className</code>	
	<p>Do not modify this property key and value.</p> <p>Specifies the class name of the formatter.</p> <p>Example: <code>formatter.className=com.ibm.log.Formatter</code></p>
<code>formatter.description</code>	
	<p>Specifies the description of the formatter.</p> <p>Example: <code>formatter.description=formatter</code></p>
<code>formatter.dateFormat</code>	
	<p>Specifies the Java SimpleDateFormat pattern to format event dates.</p> <p>Example: <code>formatter.dateFormat=yyyy.MM.dd</code></p>
<code>formatter.timeFormat</code>	

Table 18. *enRoleLogging.properties* properties (continued)

	<p>Specifies the Java SimpleDateFormat pattern to format event time.</p> <p>Example: <code>formatter.timeFormat=HH:mm:ss.SSS</code></p>
PDXML formatter properties	
<code>formatter.PDXML.className</code>	
	<p>Do not modify this property key and value.</p> <p>Specifies the formatter class name which formatting log event in LOG XML format.</p> <p>Example: <code>formatter.PDXML.className=com.ibm.itim.logging.LogXMLFormatter</code></p>
<code>formatter.PDXML.description</code>	
	<p>Specifies the description of the formatter.</p> <p>Example: <code>formatter.PDXML.description=TIM Log XML Formatter</code></p>
<code>formatter.PDXML.msg.forceAsMessage</code>	
	<p>Force the message formatter to format all output as message events, regardless of their contents.</p> <p>Example: <code>formatter.PDXML.msg.forceAsMessage=true</code></p>

enrolepolicies.properties

The `enrolepolicies.properties` file provides standard and custom settings that support the functions of the provisioning policy.

Functions supported by this properties file includes:

- Specifying Java classes to process provisioning policy conflicts with join directives
- Specifying default and non-default join directive caching timeouts
- Declaring policy attributes to be ignored during policy compliance validation

A join directive is a set of rules that is used to determine how attributes are handled when a provisioning policy conflicts with another. Join directives use logical constructs to resolve conflicts. Examples include combining all policy attributes (union), with only common attributes (intersection), and resolving conflicts with Boolean AND or OR logic.

There are 12 types of join directives that you can use. Provisioning policy join directives take effect when more than one provisioning policy is defined for the same user (or group of users) for the same target service, service instance, or service type.

Custom join directives can be defined by writing a custom Java class, adding it to your class path, and then providing the fully qualified Java class name in the policy configuration GUI. If you extend or replace one of the existing join directive classes, you must add the custom property key and value to the `enrolepolicies.properties` file. For example if you developed a new class (`com.abc.TextualEx`) to replace the existing class for textual joins, the registration line is as follows:

```
provisioning.policy.join.Textual= com.abc.TextualEx
```

Table 19 defines the properties used to configure IBM Security Identity Manager policies.

Table 19. enrolepolicies.properties properties

Join directive classes	
<pre>provisioning.policy.join.PrecedenceSequence=com.ibm.itim.policy.join.PrecedenceSequence provisioning.policy.join.Boolean=com.ibm.itim.policy.join.Boolean provisioning.policy.join.Bitwise=com.ibm.itim.policy.join.Bitwise provisioning.policy.join.Numeric=com.ibm.itim.policy.join.Numeric provisioning.policy.join.Textual=com.ibm.itim.policy.join.Textual provisioning.policy.join.Textual.AppendSeparator=<<<>> provisioning.policy.join.Multivalued=com.ibm.itim.policy.join.Multivalued</pre>	
	<p>Do not modify these property keys and values.</p> <p>Each property key specifies a Java class. It can be used to process the logic of a join directive that is required to resolve a provisioning policy conflict.</p>
Append separator characters	
<pre>provisioning.policy.join.Textual.AppendSeparator</pre>	
	<p>Specifies the character that is used by the textual join directive Java class to separate individual values of a multi-value attribute.</p> <p>Example: <pre>provisioning.policy.join.Textual.AppendSeparator=<<<>></pre></p>
Join directive cache timeouts	
<pre>provisioning.policy.join.defaultCacheTimeout</pre>	
	<p>Specifies the timeout interval [in seconds] between refreshes of the cache that stores default join directive cache values.</p> <p>The default is 86400 seconds, which is 24 hours.</p> <p>Example (default): <pre>provisioning.policy.join.defaultCacheTimeout=86400</pre></p>
<pre>provisioning.policy.join.overridingCacheTimeout</pre>	

Table 19. *enrolepolicies.properties properties (continued)*

	<p>Specifies the timeout interval [in seconds] between refreshes of the cache that stores non-default join directive values.</p> <p>The default is 300 seconds, which is 5 minutes.</p> <p>Example: <code>provisioning.policy.join.overridingCacheTimeout=300</code></p>
Account attributes ignored by policy compliance validation	
Excluded generic attributes (default value=1):	
	<p> <code>nonvalidateable.attribute.eraccountcompliance</code> <code>nonvalidateable.attribute.erac1</code> <code>nonvalidateable.attribute.eraccountstatus</code> <code>nonvalidateable.attribute.erauthorizationowner</code> <code>nonvalidateable.attribute.erglobalid</code> <code>nonvalidateable.attribute.erhistoricalpassword</code> <code>nonvalidateable.attribute.erisdeleted</code> <code>nonvalidateable.attribute.erlastmodifiedtime</code> <code>nonvalidateable.attribute.erlogontimes</code> <code>nonvalidateable.attribute.ernumlogons</code> <code>nonvalidateable.attribute.erparent</code> <code>nonvalidateable.attribute.erpassword</code> <code>nonvalidateable.attribute.erservice</code> <code>#nonvalidateable.attribute.eruid</code> <code>nonvalidateable.attribute.objectclass</code> <code>nonvalidateable.attribute.owner</code> <code>nonvalidateable.attribute.ercreatedate</code> <code>nonvalidateable.attribute.erlaststatuschangedate</code> <code>nonvalidateable.attribute.erpswdlastchanged</code> <code>nonvalidateable.attribute.erlastaccessdate</code> <code>nonvalidateable.attribute.ernumlogonattempt</code> </p>
Excluded Windows Server attributes:	
	<p> <code>nonvalidateable.attribute.erntpasswordexpired</code> <code>nonvalidateable.attribute.erntuserbadpwdcount</code> <code>nonvalidateable.attribute.erntlockedout</code> </p>
	<p>Declares account attributes that are to be ignored during policy compliance validation. This exclusion list reduces overhead during compliance validation. It also reduces the risk of system failure that can be caused by attributes that cannot logically be resolved during validation.</p>
Partition size	
	<p><code>policy.partition.size</code></p>

Table 19. *enrolepolicies.properties properties (continued)*

	<p>To analyze many persons during a policy change event without incurring transaction timeouts, you must break apart or partition the total number of affected persons. It is done, not for starting the concurrent policy analysis, but strictly to avoid waiting in a single database transaction for all persons to be processed. Creating multiple transactions or quickly partitioning the total number of users diminishes the chance of any (smaller) transactions to exceed the transaction timeout value. When a Application server cluster is used with IBM Security Identity Manager, it is helpful to note that partitioning operation itself is not clustered. It is done on the same Application server node which receives the policy change request.</p> <p>Specifies the number of persons or accounts to be evaluated in each thread during high volume policy analysis. High volume policy analysis occurs when a policy change or a service enforcement level change affects a large group of persons or accounts. A larger partition size results in fewer threads. A smaller partition size results in more executed threads in parallel, which requires more memory.</p> <p>Example (default): policy.partition.size=2500</p>
policy.message.size	
	<p>Specifies the number of persons that are analyzed as part of policy change within a single JMS message. Since Application server polled and reuses threads, the JMS mechanism queues the individual units of analysis work for all assigned Application server threads or message consumers. It is likely that during large policy changes that affect large numbers of people, all JMS consumer threads are busy processing policy analysis and enforcement; the queue for each thread is saturated with more messages to process.</p> <p>Example (default): policy.message.size=25</p>

enroleStartup.properties

The enroleStartup file is used to specify startup activities in the Application server environment.

Table 20 defines the properties used to configure IBM Security Identity Manager policies.

Table 20. *enroleStartup.properties properties*

enrole.startup.names	
	<p>Lists the background services that are started during IBM Security Identity Manager startup. Do not modify this property.</p>
enrole.startup.shutdownTrigger.name	
	<p>The registered class used during shutdown of processes. Do not modify this property.</p>
enrole.startup.WAS50J2EEShutdownTrigger.attributes	
	<p>Additional parameters to be passed in to the registered shutdown class. Do not modify this property.</p>

Table 20. *enroleStartup.properties* properties (continued)

These properties define the background services startup. Do not modify these properties.	
	<code>enrole.startup.Scheduler.attributes</code> <code>enrole.startup.PasswordExpiration.attributes</code> <code>enrole.startup.DataServices.attributes</code> <code>enrole.startup.PostOffice.attributes</code> <code>enrole.startup.RemotePending.attributes</code> <code>enrole.startup.PolicyAnalysis.attributes</code> <code>enrole.startup.ReconcilerCleanup.attributes</code> <code>enrole.startup.PasswordSynchStore.attributes</code> <code>enrole.startup.Monitoring.attributes</code> <code>enrole.startup.WebServices.attributes</code>
<code>enrole.startup.MessageListeners.attributes</code>	
	The JMS queue endpoint listeners can be deactivated during startup for a node in a cluster with disaster recovery configuration. Do not modify this attribute in a single server setup. Deactivating endpoint listeners can cause JMS queue errors if none of the messages is being processed.
<code>enrole.appServer.standby</code>	
	Defines whether the node that is participating in a cluster setup should be a standby node. A standby node does not participate in background shared workload. Available for cluster setup. Do not modify this attribute in a single server setup.
<code>enrole.appServer.standby.inactiveMessageListeners</code>	
	Provides an override to the list of message endpoint listeners to be deactivated in a standby mode. Effective only when <code>enrole.appServer.standby</code> is true.
<code>enrole.appServer.standby.inactiveStartupInitializer</code>	
	Provides an override to the list of background services to be deactivated in a standby mode. Effective only when <code>enrole.appServer.standby</code> is true.

enroleworkflow.properties

The `enroleworkflow.properties` file specifies the XML file mappings for system-defined workflows.

A workflow is a process that specifies the flow of operations that involve business operations and human interactions. A workflow design defines the manner in which a particular business logic is processed. The XML files specified in the `enroleworkflow.properties` file implement workflow designs.

The system workflow is identified by a unique type ID and an associated XML file. The XML workflow files are in the following directory:

```
\data\workflow_systemprocess
```

Do not remove or modify the default system workflow type IDs and XML file values in the `enroleworkflow.properties` file.

The updating of the following XML files is not supported.

Table 21 defines the properties used to configure IBM Security Identity Manager workflows.

Table 21. enroleworkflow.properties properties

Policy enforcement workflow
enrole.workflow.PS=enforcepolicyforservice.xml
Account fulfillment for noncompliant accounts workflow
enrole.workflow.EN=fulfillpolicyforaccount.xml
Service selection management workflow
enrole.workflow.SA=addserviceselectionpolicy.xml enrole.workflow.SC=changeserviceselectionpolicy.xml enrole.workflow.SD=removeserviceselectionpolicy.xml
Provisioning policy management workflow
#Add policy enrole.workflow.PA=addpolicy.xml #Modify policy enrole.workflow.PC=changepolicy.xml #Delete policy enrole.workflow.PD=removepolicy.xml #User BU change enrole.workflow.UO=userbuchange.xml
Reconciliation workflow
enrole.workflow.RC=reconciliation.xml enrole.workflow.HR=hrfeed.xml
Dynamic role workflow
#Add dynamic role enrole.workflow.DA=adddynamicrole.xml #Modify dynamic role enrole.workflow.DC=changedynamicrole.xml #Delete dynamic role enrole.workflow.DD=removedynamicrole.xml #Import Policy Enforcement enrole.workflow.PE=importpolicyenforcement.xml #Process Lifecycle Rule enrole.workflow.LC=lifecyclerule.xml

helpmappings.properties

The helpmappings.properties file allows a customer to replace the installed Security Identity Manager help system with an alternative help system.

The helpmappings.properties file contains the following properties:

Table 22. helpmappings.properties properties

url.contexthelp

Table 22. *helpmappings.properties* properties (continued)

	<p>Specifies an external URL for help. The default is blank, which uses the URL of the IBM Security Identity Manager help system. The URL will also add the resolved locale based on the IBM Security Identity Manager language packs that are installed. For example, <code>http://www.timcustomer.com/help/en/ui_login.html</code></p> <p>Example: <code>url.contexthelp=www.timcustomer.com/help</code></p> <p>Clicking on the help icon (?) in the IBM Security Identity Manager graphical user interface will load the html file from the key mapping (<code>http://www.timcustomer.com/help/customerfilename.html</code>). For a login page, the value of <i>customerfilename</i> might be <code>ui_login.html</code>, and the full address might be <code>http://www.timcustomer.com/help/ui_login.html</code>.</p>
--	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

reportingLabels.properties

This properties file is like other labels-related properties files such as `labels.properties`, or `customLabels.properties`, and holds labels that are used by Reports.

reportabledeny.properties

By default, this property holds a list of Security Identity Manager tables that are used by various Security Identity Manager components to store internal or configuration data that is inappropriate for a report.

This file is used by IBM Security Identity Manager Server for Reporting Engine purposes.

The following table defines the properties that determine which information is not exposed in reports.

Table 23. *reportabledeny.properties*

	<p>tables</p> <p>Holds a comma-separated list of all IBM Security Identity Manager database tables that are excluded from report production.</p> <p>If a table is part of this property, the table and its columns are not in the Report Designer; a report cannot be designed on columns of this table. A user who wants to deny a specific database table from being used by the Report Designer can choose to add the table against the tables property.</p> <p>Example: <code>tables=JMSState, JMSStore, entity_column, column_report, report, synchronization_history, synchronization_lock, changelog, resources_synchronizations, NextValue, ListData, AUTH_KEY, ATTR_CHANGE, ACCT_CHANGE, LCR_INPROGRESS_TABLE, WORKFLOW_CALLBACK, POLICY_ANALYSIS, POLICY_ANALYSIS_ERROR, PO_TOPIC_TABLE, PO_NOTIFICATION_TABLE, BULK_DATA_SERVICE, MIGRATION_STATUS, SYNCH_POINT, COMPLIANCE_ALERT, PO_NOTIFICATION_HTMLBODY_TABLE, BULK_DATA_STORE, BULK_DATA_INDEX, MANUAL_SERVICE_RECON_ACCOUNTS, SCRIPT, ACTIVITY_LOCK</code></p>
	allowedRestrictedColumns

Table 23. *reportabledeny.properties* (continued)

	<p>Allows IBM Security Identity Manager administrators to explicitly allow columns of restricted data types, to be used for designing and running custom reports. Such reports however work for IBM Security Identity Manager Administrators only. If a non-administrator attempts to run such reports, the user receives an <code>AuthorizationException</code>.</p> <p>By default, columns of the following restricted data types are not available when you design or run custom reports: BLOB, CLOB, BINARY, VARBINARY, LONGVARBINARY and LONGVARCHAR</p> <p>The value of the property is a comma-separated list of <code><TABLE_NAME>.<COLUMN_NAME></code>. If this property is undefined, then none of the columns of the restricted data type is available for reporting.</p> <p>Example (on a single line): <code>allowedRestrictedColumns=ACTIVITY.RESULT_DETAIL, PROCESS.RESULT_DETAIL, PROCESSLOG.NEW_DATA</code></p>
--	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

scriptframework.properties (Suggested)

For *all* new JavaScript extensions, use the `scriptframework.properties` file to configure script extensions and other scripting functions.

JavaScript is used in IBM Security Identity Manager to specify identity policies, provisioning policy parameters, service selection policies, placement rules for identity feeds, and orphan account adoption.

In addition, JavaScript is used in workflows to specify transition conditions, loop conditions, JavaScript activities, activity postscripts, and workflow notification. Various scripting extensions are provided by IBM Security Identity Manager to expose useful data and services to each of these scripts. In addition to these extensions, system administrators can configure IBM Security Identity Manager to load custom JavaScript extensions.

The file `scriptframework.properties` is used to configure all parts of scripting support in IBM Security Identity Manager. It includes which script extensions to use, which script interpreter to use, and other properties that relate to scripting.

The major parts of the `scriptframework.properties` are divided by these host components: `PostOffice`, `ProvisioningPolicy`, `AccountTemplate`, `HostSelection`, `PersonPlacementRules`, `Workflow`, `Reminder`, `IdentityPolicy`, `Notification`, and `OrphanAdoption`.

The most heavily used section of the property file is for configuring which extensions to load for each host component. To have the script framework load an extension, add a key-value line to the `scriptframework.properties` file that is similar to this example:

```
ITIM.extension.{Host Component}=com.ibm.itim.class_name
```

where `ITIM.extension.{Host Component}` is the key and `com.ibm.itim.class_name` is the value. The value of `{Host Component}` can be any of the previously listed components. If you want to load more than a single extension for a host component, you can add a suffix to host component, such as:

```
ITIM.extension.{Host Component}.suffix=com.ibm.itim.class_name
```

The only rule is that each key must be unique in the file.

The `scriptframework.properties` file comes pre-configured to load the extensions necessary to use IBM Security Identity Manager with its default scripts. Do not remove any lines in `scriptframework.properties` because removal might cause IBM Security Identity Manager to stop functioning properly.

The next section of the `scriptframework.properties` file configures which script interpreter to use for each host component. IBM Security Identity Manager currently supports two different script interpreters, the IBM JSEngine and the FESI JavaScript Interpreter.

To configure which interpreter to use for each host component, there is a line in the file that looks like:

```
ITIM.interpreter.{Host Component}={Engine}
```

The value of `{Host Component}` can be any of the previously listed components. The value of `{Engine}` can be either IBMJS or FESI. The `{Engine}` variable is not case-sensitive, so typing `fesi` works as well as typing `FESI`. IBMJS is the default scripting engine, so any value for `{Engine}` other than IBMJS or FESI, or no value, uses the IBMJS engine. The FESI engine is deprecated. Use it only if you upgraded from IBM Security Identity Manager Version 4.6 or earlier and have custom FESI extensions.

The next section in the configuration file enables configuring custom JavaScript wrappers. For security reasons, IBM Security Identity Manager does not expose all objects to the scripting environment. Instead, most objects are wrapped in a more restrictive wrapper class that exposes only certain methods. IBM Security Identity Manager has a default wrapper configuration that you can override or extend in this section. This feature is for an advanced user; in most cases do not use it. For more details on how to configure custom wrappers, see the comments in the `scriptframework.properties` file.

In the next section, you can configure direct Java access from scripts run by the IBM JSEngine interpreter. Direct Java access is powerful, but scripts can bypass some of the security built into the script framework. Consider carefully before you do so. See the comments in the `scriptframework.properties` file for more information about how to enable direct Java access.

The final section of the configuration file configures specific properties that might be useful. Each specific property is explained in comments in the `scriptframework.properties` file, including default and allowed values.

SelfServiceHelp.properties

The `SelfServiceHelp.properties` file can be used to redirect help to a custom location for customers who want to have their own help content for the self-service user interface.

Table 24 defines the properties used to redirect help to a custom location.

Table 24. *SelfServiceHelp* properties

IBM Security Identity Manager SelfServiceHelp settings
helpBaseUrl

Table 24. *SelfServiceHelp* properties (continued)

	<p>Specifies the base url to send help requests to. A blank value indicates that help goes to the URL for Self Service application help.</p> <p>Valid values include the URL of the Self Service application help.</p> <p>Example: <code>helpBaseUrl=http://myserver:80</code></p>
<p>Help Id mappings include: <code>helpId = relative page URL</code></p>	
	<p>The help mappings section maps ids from specific pages to a relative URL sent to the help server.</p> <p>For example: <code>helpBaseUrl=http://myserver:80</code> <code>locale = en_US</code> <code>loginId/relativeURL = login_help_url=ui/ui_eui_login.html</code> Final URL = <code>http://myserver:80/en_US/ui/ui_eui_login.html</code></p> <p>Locale is determined by resolving the <code>SelfServiceScreenText.properties</code> resource bundle for the current logged in user and with the associated locale.</p>

SelfServiceHomePage.properties

The `SelfServiceHomePage.properties` file is used to configure the sections of the initially installed home page for the self-service user interface. You can add or remove tasks, and update icon URLs and labels of the home page from this file.

The file has these types of entries:

- `Sections=ActionNeeded, Password, sectionConfigName ...`
Defines the section configuration names in the order in which they are displayed.
- Section definition
Defines the label keys, icons, and other objects for the home page section.
- Task definitions
Defines the NLS key and link for the URL, the NLS key for the task description, and other attributes that enable displaying the task.

For more information about these properties, see documentation in the properties file.

SelfServiceScreenText.properties

The `SelfServiceScreenText.properties` file is a resource bundle containing the labels for the self-service user interface.

Versions of the file might be available for the installed languages. For example: `SelfServiceScreenText_en.properties` and `SelfServiceScreenText_es.properties`, which are editable by users.

SelfServiceUI.properties

The SelfServiceUI.properties file controls miscellaneous properties of the self-service user interface.

Table 25 defines the properties used to configure the self-service user interface.

Table 25. SelfServiceUI.properties

enrole.ui.pageSize	
	Specifies the page size for displaying lists. Example: enrole.ui.pageSize=10
enrole.ui.pageLinkMax	
	Specifies the number of page links to be shown for multi-page result sets. Example: enrole.ui.pageLinkMax=100
enrole.ui.maxSearchResults	
	Specifies the maximum number of items returned from a search. The results that are returned can be less than, but not larger than the values specified in ui.properties. Example: enrole.ui.maxSearchResults=1000
enrole.ui.maxSearchResults.users	
	Specifies the maximum displayable search results for the task Delegate Activities - Search for User . Example: enrole.ui.maxSearchResults.users=100
enrole.ui.maxNrOfIteration	
	Specifies the maximum number of wait iterations for RequestInfo status. Example: enrole.ui.maxNrOfIteration=20
enrole.ui.waitTime	
	Specifies the time to wait until the request is asked for next status. The product of (maxNrOfIteration * waitTime) is a maximum of 60 seconds. The value is interpreted in milliseconds. Example: enrole.ui.waitTime=3000
enrole.ui.logoffURL	

Table 25. SelfServiceUI. properties (continued)

	<p>Specifies the URL to forward the browser to when the user logs off.</p> <p>Example: <code>enrole.ui.logoffURL=myLogoffURL</code></p>
<code>enrole.ui.timeoutURL</code>	
	<p>Specifies the URL to which forward the browser on timeout.</p> <p>Example: <code>enrole.ui.timeoutURL=myTimeoutURL</code></p>
<code>ui.layout.showBanner</code>	
	<p>Specifies a change to the values of <code>ui.layout</code> properties to show or hide the banner of the self-service user interface.</p> <p>Example: <code>ui.layout.showBanner=true</code></p>
<code>ui.layout.showFooter</code>	
	<p>Specifies a change to the values of <code>ui.layout</code> properties to show or hide the footer of the self-service user interface.</p> <p>Example: <code>ui.layout.showFooter=true</code></p>
<code>ui.layout.showToolBar</code>	
	<p>Specifies a change to the values of <code>ui.layout</code> properties to show or hide the toolbar of the self-service user interface.</p> <p>Example: <code>ui.layout.showToolBar=true</code></p>
<code>ui.layout.showNav</code>	
	<p>Specifies a change to the values of <code>ui.layout</code> properties to show or hide the page navigation of the self-service user interface.</p> <p>Example: <code>ui.layout.showNav=false</code></p>
<code>ui.usersearch.attr.cn</code>	
	<p>Specifies the attribute that is listed in the searchBy field for a user search. The attribute is prefixed with <code>ui.usersearch.attr</code>. For more information about mapping and syntax, see the documentation in the <code>SelfServiceUI.properties</code> file.</p> <p>Example: <code>ui.usersearch.attr.cn=cn</code></p>
<code>ui.usersearch.attr.sn</code>	

Table 25. *SelfServiceUI.properties* (continued)

	<p>Specifies the attribute that is listed in the searchBy field for a user search. The attribute is prefixed with <code>ui.usersearch.attr</code>. For more information about mapping and syntax, see the documentation in the <code>SelfServiceUI.properties</code> file.</p> <p>Example: <code>ui.usersearch.attr.sn=sn</code></p>
<code>ui.usersearch.attr.telephonenumber</code>	
	<p>Specifies the attribute that is listed in the searchBy field for a user search. The attribute is prefixed with <code>ui.usersearch.attr</code>. For more information about mapping and syntax, see the documentation in the <code>SelfServiceUI.properties</code> file.</p> <p>Example: <code>ui.usersearch.attr.telephonenumber=telephonenumber</code></p>
<code>ui.usersearch.attr.mail</code>	
	<p>Specifies the attribute that is listed in the searchBy field for a user search. The attribute is prefixed with <code>ui.usersearch.attr</code>. For more information about mapping and syntax, see the documentation in the <code>SelfServiceUI.properties</code> file.</p> <p>Example: <code>ui.usersearch.attr.mail=mail</code></p>
<code>ui.view.accounts.expandedbydefault</code>	
	<p>Specifies whether the accounts affected twistie state on the change password page are expanded or collapsed (<code>true false</code>) by default. Valid values are:</p> <ul style="list-style-type: none"> • true – Expand the accounts affected twistie state on the change password page by default • false – Do not expand the accounts affected twistie state on the change password page by default <p>Example (default): <code>ui.view.accounts.expandedbydefault=false</code></p>
<code>ui.select.all.accounts</code>	
	<p>Specifies whether all the accounts under the account twistie are to be selected by default. Valid values are:</p> <ul style="list-style-type: none"> • all – To select all the accounts under the account twistie • none – To select none of the accounts under the account twistie • default – To retain the default behavior <p>Example (default): <code>ui.select.all.accounts=default</code></p>

ui.properties

The `ui.properties` file specifies attributes that affect the operation and display of the Security Identity Manager graphical user interface.

The following table defines the properties for configuring the IBM Security Identity Manager graphical user interface.

Table 26. *ui.properties* properties

IBM Security Identity Manager GUI configuration settings	
enrole.ui.customerLogo.image	
	<p>Specifies the file name of the graphic that is displayed on the right side of the IBM Security Identity Manager title banner. The graphic is usually a company logo. For display over the web in a browser, the format of the file must be type that the browser supports. The actual graphics file must be stored in the following location: <code>directories/itim_console.war/html/images/</code></p> <p>To store the files, use the Custom File Management page from the Appliance Dashboard of the IBM Security Identity Manager virtual appliance console. See <i>Managing custom files</i>.</p> <p>You can also specify a value, <code>ibm_banner.gif</code> to update it.</p> <p>Example: <code>enrole.ui.customerLogo.image=ibm_banner.gif</code></p> <p>Use the Update Property page from the Appliance Dashboard of the IBM Security Identity Manager virtual appliance console. See <i>Managing the server properties</i>.</p>
enrole.ui.customerLogo.url	
	<p>Specifies the URL link that is activated when you click the custom graphic image (company logo) on the right side of the IBM Security Identity Manager banner.</p> <p>Example: <code>enrole.ui.customerLogo.url=www.ibm.com</code></p>
enrole.ui.pageSize	
	<p>Specifies the number of list items that is initially displayed on the screen. If there are more items in the list, links are at the bottom of the list view that activate continuations of the list. For example, <i>Page 2, Page 3, Page 4</i>.</p> <p>Example: <code>enrole.ui.pageSize=50</code></p>
enrole.ui.maxSearchResults	
	<p>Specifies the maximum number of items that are returned for a search. This property limits the number of items that are returned when a search is done on the directory server. The evaluation of the ACIs is done later on these returned items. The number of items in the directory server is greater than the value specified for this property. So, the number of items that are displayed on the IBM Security Identity Manager Console might be less than the value specified.</p> <p>The value for this property can control possible system performance degradation when a large return of items is encountered. If you modify the value for this property, you must restart the application server.</p> <p>Example: <code>enrole.ui.maxSearchResults=1000</code></p>
ui.banner.showForLogin	

Table 26. *ui.properties* properties (continued)

	<p>Specifies whether to show the console banner on the login page, rather than the default login banner. Any customization to the console banner is also on the login page when this property is in effect.</p> <p>yes Show the console banner in the login page.</p> <p>no Show the default login banner. An empty value assumes no.</p> <p>Example (default): <code>ui.banner.showForLogin=no</code></p>
<code>ui.footer.URL</code>	
	<p>Specifies the URL for the IBM Security Identity Manager Console. Specify either the full address (<code>http://yourhost.com/footer.html</code>) or an address from the IBM Security Identity Manager web server (<code>/itim/console/custom/footer.html</code>). A blank value uses the default address of the IBM Security Identity Manager footer.</p> <p>Example: <code>ui.footer.URL=http://itim99.mylab.raleigh.ibm.com:9080/itim/console/main</code></p> <p>Use the Update Property page from the Appliance Dashboard of the IBM Security Identity Manager virtual appliance console. See Managing the server properties.</p>
<code>ui.footer.height</code>	
	<p>Specifies the height in pixels of the footer on the IBM Security Identity Manager Console.</p> <p>Example (default): <code>ui.footer.height=50</code></p>
<code>ui.footer.isVisible</code>	
	<p>Shows or hides the footer of the IBM Security Identity Manager Console.</p> <p>Valid values are as follows:</p> <p>yes (or blank) Shows the footer.</p> <p>no Hides the footer.</p> <p>Example (default): <code>ui.footer.isVisible=yes</code></p>
<code>ui.banner.URL</code>	
	<p>Specifies the URL for the banner on the IBM Security Identity Manager Console.</p> <p>Specify either the full address (<code>http://yourhost.com/banner.html</code>) or a path from the IBM Security Identity Manager web server (<code>/itim/console/custom/banner.html</code>). A blank value uses the default address of the IBM Security Identity Manager banner.</p> <p>Example: <code>ui.banner.URL=http://itim99.mylab.raleigh.ibm.com:9080/itim/console/main</code></p>
<code>ui.banner.height</code>	
	<p>Specifies the height in pixels of the banner on the IBM Security Identity Manager Console.</p> <p>Example (default): <code>ui.banner.height=48</code></p>
<code>ui.homepage.path</code>	

Table 26. *ui.properties* properties (continued)

	<p>IBM Security Identity Manager Console home page location. Specify a relative path from the IBM Security Identity Manager Console context root (/itim/console).</p> <p>For example, if the full path to the home page was <code>http://yourhost:9080/itim/console/custom/home.html</code>, then the following value is <code>ui.homepage.path=custom/home.html</code>.</p> <p>The custom home page must be in the IBM Security Identity Manager web application. For example: <code>path/ITIM.ear/itim_console.war/custom/home.html</code>). A blank value uses the default address of the IBM Security Identity Manager home page.</p> <p>Example: <code>ui.homepage.path=custom/home.html</code></p>
<code>ui.titlebar.text</code>	
	<p>Specifies the text in the title bar of the browser for the IBM Security Identity Manager Console. A blank value uses the default name of the IBM Security Identity Manager product.</p> <p>Example: <code>ui.titlebar.text=Our Home Page</code></p>
<code>ui.userManagement.includeAccounts</code>	
	<p>Specifies the default behavior for including accounts when you suspend, restore, or delete users. Valid values are as follows:</p> <p>true Accounts are included.</p> <p>false Accounts are excluded.</p> <p>Example (default): <code>ui.userManagement.includeAccounts=true</code></p>
<code>ui.userManagement.search.attributes</code>	
	<p>Adds a search attribute to the default list for the Manage Users page in the IBM Security Identity Manager Console.</p> <p>Provide one or more attribute names in the <code>ui.userManagement.search.attributes</code> property value that is separated by a comma. Make sure to provide valid and non-repetitive attributes. Do not specify attributes that cannot be searched by using plain text. For example, audio, photo, and other similar items.</p> <p>Example: <code>ui.userManagement.search.attributes=homepostaladdress,employeenumber</code></p> <p>By default, this property value is empty.</p> <p>The property adds user attributes that display in the Search By list on the Manage Users page for the person search filter.</p>
<code>ui.challengeResponse.showAnswers</code>	

Table 26. *ui.properties* properties (continued)

	<p>Specifies whether the answers to challenge response questions is treated as passwords or as clear text in the IBM Security Identity Manager Console of the following pages:</p> <ul style="list-style-type: none"> • Forgot Password page • Challenge response question and answer definition page <p>Valid values are as follows:</p> <p>true Answers to challenge response questions is clear text.</p> <p>false Answers to challenge response questions is treated as passwords.</p> <p>Example (default):</p> <pre>ui.challengeResponse.showAnswers=true</pre>
<code>ui.challengeResponse.bypassChallengeResponse</code>	
	<p>Specifies whether the challenge response questions can be bypassed when the user first logs on to the IBM Security Identity Manager Console or the self service web user interface. Valid values:</p> <p>true When true, the user can cancel and not answer the challenge questions.</p> <p>false When false, the user cannot cancel. The user is forced to respond to the challenge questions.</p> <p>Default value: true</p> <p>Example:</p> <pre>ui.challengeResponse.bypassChallengeResponse=true</pre>
<code>ui.viewAllRequests.loadDefaultQueryResult</code>	
	<p>Specifies whether the View All Requests page loads the default query result.</p> <p>true Loads the View All Requests page with default query result.</p> <p>false Does not load the View All Requests page with default query result.</p> <p>Default value: false</p> <p>Example:</p> <pre>ui.viewAllRequests.loadDefaultQueryResult=false</pre>
<code>ui.allowLaunchingNewTaskWithoutWarningForActiveTask</code>	
	<p>Specifies whether to start selected task or not, if the same task is already active in the IBM Security Identity Manager Console. The examples of the tasks are as follows: Create Service, Change Service, Create User, Change User.</p> <p>true When you try to start an already active task, the existing task is closed. Starts the new task without displaying any warning message.</p> <p>false When you try to start an already active task, a warning message is displayed. Does not start the new task.</p> <p>Default value: false</p> <p>Example:</p> <pre>ui.allowLaunchingNewTaskWithoutWarningForActiveTask=false</pre>
<code>ui.policyManagement.manageProvisioningPolicies.create.defaultMemberType</code>	

Table 26. *ui.properties properties (continued)*

	<p>Controls default selection of policy membership. This property allows default member type to be selected while you create a provisioning policy. Allowed values are as follows:</p> <p>users All users in the organization.</p> <p>roles Roles that are specified later.</p> <p>others All other users who are not granted to the entitlements that are defined by this provisioning policy by way of other policies.</p> <p>Default value: users</p> <p>Example: <code>ui.policyManagement.manageProvisioningPolicies.create.defaultMemberType=users</code></p>
<p><code>ui.manageServices.reconcileNow.defaultSelectQuery</code></p>	
	<p>Specifies the default reconciliation query option. Allowed values are as follows:</p> <p>none None.</p> <p>use_query Use query from existing schedule.</p> <p>define_query Define query.</p> <p>Default value: none</p> <p>Example: <code>ui.manageServices.reconcileNow.defaultSelectQuery=none</code></p>
<p><code>ui.passwordManagement.defaultSelection.typePassword</code></p>	
	<p>Specifies Allow me to type a password as default over the current Generate a password for me option. Allowed values are as follows:</p> <p>true Selects the Allow me to type a password option and additionally none of the accounts get selected by default.</p> <p>false Selects the Generate a password for me option if this property is set to false or not present.</p> <p>Default value: false</p> <p>Example: <code>ui.passwordManagement.defaultSelection.typePassword=false</code></p>
<p><code>ui.advancedUserSearch.AllTypes.defaultSearchAttribute.names</code> <code>ui.advancedUserSearch.AllTypes.defaultSearchAttribute.labels</code></p>	

Table 26. *ui.properties* properties (continued)

	<p>When you select User type as All types in the Select User Type page, the properties add the default search attributes and its labels on the Advanced Search page for users in the IBM Security Identity Manager Console. If the <code>ui.advancedUserSearch.AllTypes.defaultSearchAttribute.names</code> property is removed or if no value is specified, then IBM Security Identity Manager does not display any default search attribute field.</p> <p>Provide one or more attribute names in the <code>ui.advancedUserSearch.AllTypes.defaultSearchAttribute.names</code> property value, and corresponding attribute labels in the <code>ui.advancedUserSearch.AllTypes.defaultSearchAttribute.labels</code> property value.</p> <p>Make sure to provide valid, non-repetitive, and comma-separated values. Do not specify attributes that cannot be searched by using plain text. For example, audio, photo, and other similar items.</p> <p>Example (default):</p> <pre>ui.advancedUserSearch.AllTypes.defaultSearchAttribute.names=cn ui.advancedUserSearch.AllTypes.defaultSearchAttribute.labels=\$cn</pre> <p>The property adds the default search attributes and its labels on the Advanced Search page for users when you select User type as All types in the Select User Type page.</p>
<p>WfDesigner and FormDesigner applet properties</p>	
	<pre>enrole.build.version enrole.java.plugin enrole.java.plugin.classid enrole.java.plugin.page enrole.java.plugin.jpj-version enrole.java.plugin.version enrole.java.entWflowHeightIE enrole.java.entWflowWidthIE enrole.java.entWflowHeightMZ enrole.java.entWflowWidthMZ enrole.java.opWflowHeightIE enrole.java.opWflowWidthIE enrole.java.opWflowHeightMZ enrole.java.opWflowWidthMZ enrole.java.joinDirHeightIE enrole.java.joinDirWidthIE enrole.java.joinDirHeightMZ enrole.java.joinDirWidthMZ enrole.java.formDesignHeightIE enrole.java.formDesignWidthIE enrole.java.formDesignHeightMZ enrole.java.formDesignWidthMZ express.java.formDesignHeightIE express.java.formDesignWidthIE express.java.formDesignHeightMZ express.java.formDesignWidthMZ #enrole.ui.logoffURL (default is commented out) #enrole.ui.timeoutURL (default is commented out)</pre>
	<p>You must not modify or remove any information for these properties in the property file.</p> <p>These property key and value pairs provide the necessary Java applet support required by the web browser that runs the IBM Security Identity Manager Console.</p>

Table 26. *ui.properties* properties (continued)

Report menu properties	
enrole.ui.report.maxRecordsInReport	
	<p>Displays the number of records that can be displayed in a PDF report without encountering an “Out of Memory” error. The number does not ensure that PDF report generation is successful. If the report contains more records than specified by this property, PDF report generation is not attempted.</p> <p>Example: enrole.ui.report.maxRecordsInReport=5000</p>
Enable or disable WebSEAL single sign-on (SSO)	
enrole.ui.ssoEnabled	
	<p>The property key and value pairs do not pertain to the IBM Security Identity Manager Console.</p> <p>Enable or disables WebSEAL single sign-on.</p> <p>More configuration is required for WebSEAL single sign-on. Valid values are as follows:</p> <p>true WebSEAL single sign-on is enabled.</p> <p>false WebSEAL single sign-on is disabled.</p> <p>Example (default): enrole.ui.ssoEnabled=false</p>
enrole.ui.ssoEncoding	
	<p>Specifies the encoding that is used to decode user credentials with WebSEAL single sign-on.</p> <p>Example (default): enrole.ui.ssoEncoding=UTF-8</p>
Refresh properties	
enrole.ui.httpRefreshSecs	
	<p>Defines, in seconds, the refresh rate for pages within the IBM Security Identity Manager Console. This property is used during policy previews.</p> <p>Example (default): enrole.ui.httpRefreshSecs=10</p>
Search class mapping for ObjectProfileCategory	
	<p>The property key and value pairs do not pertain to the IBM Security Identity Manager Console and must not be modified or removed.</p>
Justification field configuration properties	
ui.displayJustification	

Table 26. *ui.properties* properties (continued)

	<p>Specifies whether the Justification field is displayed in the user interface. By default, the Justification field is not displayed.</p> <p>Use in conjunction with the <code>enrole.justificationRequired</code> property in the <code>enRole.properties</code> file.</p> <p>Example (default): <code>ui.displayJustification=false</code></p>
Identity Service Center as the default user interface configuration property	
<code>ui.defaulttui.redirectSelfToISC</code>	
	<p>Specifies whether the Identity Service Center user interface is set as the default user interface. If a user is already authenticated to the IBM Security Identity Manager, and starts the self-service user interface, no redirection happens.</p> <p>true If the Identity Service Center is deployed and if a user starts the self-service user interface, then the self-service user interface redirects the user to the Identity Service Center.</p> <p>false When a user starts the self-service user interface, it does not redirect a user to the Identity Service Center. The self-service user interface starts.</p> <p>Example (default): <code>ui.defaulttui.redirectSelfToISC=false</code></p>
Generate password configuration property	
<code>ui.passwordManagement.generatePassword</code>	
	<p>Specifies which change password options to enable on the Identity Service Center user interface. This property is applicable only when the Enable password editing is selected in the administrative console. The valid values are:</p> <p>true Enables both the Generate a password for me and Allow me to type a password options.</p> <p>The <code>ui.passwordManagement.defaultSelection.typePassword</code> property is applicable only if the property <code>ui.passwordManagement.generatePassword</code> is set to true.</p> <p>false Enables the Generate a password for me option and disables the Allow me to type a password option.</p> <p>Example (default): <code>ui.passwordManagement.generatePassword=true</code></p>
Challenge response answers display configuration property	
<code>ui.challengeResponse.showAnswers</code>	
	<p>Shows or hides the challenge response answers that a user types in the text box. The valid values are:</p> <p>true Shows what a user types.</p> <p>false Hides what a user types.</p> <p>Example (default): <code>ui.challengeResponse.showAnswers=true</code></p>

UIConfig.properties

The config/UIconfig.properties file contains the several properties that affect the Identity Service Center interface.

Table 27. UIConfig.properties

password.change.pollingTime	
	<p>Specifies in milliseconds the time to wait before checking whether the expired password change request is processed. A value that is less than 0 is invalid.</p> <p>Example (default): password.change.pollingTime=1000</p>
password.change.pollingIterations	
	<p>Specifies the maximum number of times that the server checks whether the password change is processed. A value that is less than 1 is invalid.</p> <p>Example (default): password.change.pollingIterations=5</p>
isim.ui.rtlLocales	
	<p>A comma-separated list of right-to-left locales. The default values are ARABIC(ar) and HEBREW(iw).</p> <p>Example (default): isim.ui.rtlLocales=ar,iw</p>
property.refresh.interval.seconds	
	<p>Defines how frequently the Identity Service Center server refreshes the value of properties by reading the UIConfig.properties file to pick up new values for the changed properties. A user can change this property even while the Identity Service Center server is running. A user does not need to restart the server to pick up the changes.</p> <p>Example (default): property.refresh.interval.seconds=300</p>
LOGO_IMAGE	
	<p>Specifies the file name in custom/ui/images directory that displays the company logo image.</p> <p>Example: LOGO_IMAGE=companyLogo.png</p>
HEADER_LOGO_IMAGE	
	<p>Specifies the file name in custom/ui/images directory that displays the page header logo image.</p> <p>Example: HEADER_LOGO_IMAGE=headerLogo.png</p>
access.selection.maximum.number	

Table 27. *UIConfig.properties* (continued)

	<p>Specifies the maximum number of accesses that can be selected in the manage access flow. For example, in the Request Access wizard, and Edit and Delete Access wizard.</p> <p>Example (default): <code>access.selection.maximum.number=25</code></p>
<code>timeout.notify</code>	
	<p>Specifies the seconds left before the session end that the expiration notification message is sent.</p> <p>Example (default): <code>timeout.notify=20</code></p>

Chapter 16. System property configuration in enRole.properties

Detailed information about the property keys and values that are contained in the enRole.properties system configuration file are described here.

The enRole.properties system configuration file contains many of the properties used to configure IBM Security Identity Manager. The file properties control the program functions and enable user customization of special features.

From the **Appliance Dashboard** of the IBM Security Identity Manager virtual appliance console, use the Update Property page to work with the enRole.properties. See Managing the server properties.

Properties files

Java properties files define attributes that allow customizing and control of the Java software. Standard system properties files and custom properties files are used to configure user preferences and user customization.

A Java properties file defines the values of named resources. It can specify program options such as database access information, environment settings, and special features and functions.

A properties file defines named resources with a property key and value pair format:

property-key-name=value

The *property-key-name* is an identifier for the resource. The *value* is typically the name of the actual Java object. It provides the resource or a String representing the value of the property key, such as database.name=itimdb. The statement syntax allows spaces before and after the equal (=) sign. It can span multiple lines if you place a line continuation character \ (a backslash) at the end of the line. For more information about statement syntax, see the Java language references.

Application server properties

Application server properties define values that are specific to integrating IBM Security Identity Manager with the Application server.

Table 28 lists these Application server properties.

Table 28. Application server properties

Platform Context Factory Name
enrole.platform.contextFactory

Table 28. Application server properties (continued)

	<p>Do not modify this property key and value.</p> <p>Specifies the Java class for the platform context factory that defines the integration point for IBM Security Identity Manager with the Application server.</p> <p>Example (default, entered as a single line): <code>enrole.platform.contextFactory=com.ibm.itim.apps.impl.websphere. WebSpherePlatformContextFactory</code></p>
Application server	
<code>enrole.appServer.contextFactory</code>	
	<p>Do not modify this property key and value.</p> <p>Specifies the Java class that determines which JNDI factory to use with the Application server.</p> <p>Example (default): <code>enrole.appServer.contextFactory=com.ibm.websphere.naming. WsnInitialContextFactory</code></p>
<code>enrole.appServer.url</code>	
	<p>This property key and value can be changed only by a qualified administrator.</p> <p>Specifies the location of the application server naming service. This value is obtained during IBM Security Identity Manager installation.</p> <p>Example: <code>enrole.appServer.url=iio://localhost:2809</code></p>
<code>enrole.appServer.usertransaction.jndiname</code>	
	<p>Do not modify this property key and value.</p> <p>Specifies the JNDI name of the JTA (Java Transaction API) User Transaction object.</p> <p>Example (default): <code>enrole.appServer.usertransaction.jndiname=jta/usertransaction</code></p>
<code>enrole.appServer.realm</code>	
	<p>This property key and value can be changed only by a qualified administrator.</p> <p>Specifies the target server security realm name if IBM Security Identity Manager is running on a different Application server instance that is configured to run with different security realm.</p> <p>Example (on a single line): <code>enrole.appServer.realm=itimCustomRealm</code></p> <p>The default value is <code>itimCustomRealm</code>; it can be updated during the installation of IBM Security Identity Manager.</p>
<code>enrole.appServer.registry</code>	

Table 28. Application server properties (continued)

	<p>Do not modify this property key and value.</p> <p>Describes the registry to which IBM Security Identity Manager is configured.</p> <p>Example (default): <code>enrole.appServer.registry=ITIM_Custom_registry</code></p>
<code>enrole.appServer.security.domain</code>	
	<p>Do not modify this property key and value.</p> <p>Specifies the name of the Security domain that is created for IBM Security Identity Manager.</p> <p>Example (default): <code>enrole.appServer.security.domain=ISIMSecurityDomain</code></p>
<code>enrole.appServer.alwayssetisolevelrc</code>	
	<p>Do not modify this property key and value.</p> <p>This property specifies that IBM Security Identity Manager must always set the transaction isolation level to Read-Committed when it acquires database connections.</p> <p>Because the Application server has internal support for setting the isolation level, this property must be set to false.</p> <p>Example (default): <code>enrole.appServer.alwayssetisolevelrc=false</code></p>
Login helper	
<code>enrole.appServer.loginHelper.class</code>	
	<p>Do not modify this property key and value.</p> <p>Specifies the Java class that is used to log each thread in to J2EE Security.</p> <p>Example (default): <code>enrole.appServer.loginHelper.class=com.ibm.itim.util.was.WAS40LoginHelper</code></p>
Application server servlet path separator	
<code>enrole.servlet.path.separator</code>	
	<p>Do not modify this property key and value.</p> <p>Specifies the separator character that is used to specify path names to required resources.</p> <p>Example (default): <code>enrole.servlet.path.separator=.</code></p>
Event notification system login	
<code>SystemLoginContextFactory</code>	

Table 28. Application server properties (continued)

	<p>Do not modify this property key and value.</p> <p>Specifies the Java factory class for event notification system login appropriate for Application server.</p> <p>Example (default, entered as a single line):</p> <pre>SystemLoginContextFactory=com.ibm.itim.remoteservices.provider.itim. websphere.WSSystemLogonContextFactory</pre>
User-selected locale	
locale	
	<p>Specifies the locale setting for the IBM Security Identity Manager environment.</p> <p>Example (default):</p> <pre>locale=en</pre>
Context factory name	
enrole.appServer.name	
	<p>Specifies the unique name of the application server.</p> <p>In a cluster environment, it is important that this name is unique for each member within a node in the cluster. Cluster members on different nodes can have same names.</p> <p>Example (default):</p> <pre>enrole.appServer.name=myserver</pre>

Remote services properties

The `enrole.remoteservices.assemblyline.encodeusingUTF8` property is referred whenever IBM Security Identity Manager sends the assembly line to IBM Security Directory Integrator dispatcher before running any operation. Use the UTF-8 encoding when the assembly line contains special characters such as German umlaut characters.

The value of the `enrole.remoteservices.assemblyline.encodeusingUTF8` property determines whether the assembly line sent to IBM Security Directory Integrator is encoded with the UTF-8 format or not.

Table 29. Remote services properties

<code>enrole.remoteservices.assemblyline.encodeusingUTF8</code>

Table 29. Remote services properties (continued)

	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies whether the UTF-8 encoding is used or not.</p> <p>Values include:</p> <ul style="list-style-type: none"> • true – Only the UTF-8 encoding is used. • false – The platform default encoding is used. <p>Example (default):</p> <pre>enrole.remoteservices.assemblyline.encodeusingUTF8=false</pre>
--	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Web services properties

The web services properties define the properties that are used by IBM Security Identity Manager to manage the web services API.

Table 30 determines the web services properties.

Table 30. Web services properties

<code>enrole.webServices.version</code>	
	<p>Do not change this property key.</p> <p>Specifies the web services version. The value is returned by the <code>WSUnAuthService.getWebServicesVersion</code> web services API.</p> <p>Values include the version of the web services.</p> <p>Example (default):</p> <pre>enrole.webServices.version=1.0</pre>
<code>enrole.webseal.ltpa.cookie.name</code>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the property to identify the name of the HTTP header, which carries the LTPA token. Use this property in SSO mode only.</p> <p>The default value is <code>LtpaToken2</code>. Do not change this property unless the HTTP header name that carries the LTPA token is other than the default specified.</p> <p>Example (default):</p> <pre>enrole.webseal.ltpa.cookie.name=LtpaToken2</pre>
<code>enrole.webServices.session.cache.maxRetry</code>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Use this property key in cluster environment, and when the <code>enrole.webServices.session.mgmt.clientSide</code> property is set to <code>false</code>.</p> <p>Values must be a valid integer.</p> <p>Example (default):</p> <pre>enrole.webServices.session.cache.maxRetry=5</pre>
<code>enrole.webServices.session.mgmt.clientSide</code>	

Table 30. Web services properties (continued)

	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies whether the session management is client side or server side.</p> <p>Values include:</p> <ul style="list-style-type: none"> • true – indicates that client side management is enabled. • false – indicates that a server-side management is expected. <p>Example (default): enrole.webServices.session.mgmt.clientSide=true</p>
authTokenTimeout	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the time in hours for how long a session can be valid. For example, even if you keep a session active by continuously using it, the session expires every two days, and you must log in again.</p> <p>Use this property key when the enrole.webServices.session.mgmt.clientSide property is set to false.</p> <p>Values include:</p> <p>Example (default): authTokenTimeout=48</p>
sessionInactivityTime	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the time in minutes for how long an unused session is active.</p> <p>Use this property key when the enrole.webServices.session.mgmt.clientSide property is set to false.</p> <p>Values include:</p> <p>Example (default): sessionInactivityTime=15</p>

Organization properties

Organization properties define the organization name that is used by the directory server.

Table 31 defines the properties for the organization name that is used by the directory server.

Table 31. Organization properties

enrole.defaulttenant.id

Table 31. Organization properties (continued)

	<p>Use the ldapConfig utility to modify this property.</p> <p>Specifies the short format of the organization name that is used by the directory server.</p> <p>This value is specified during installation of IBM Security Identity Manager or by running the ldapConfig utility.</p> <p>Example (default): enrole.defaulttenant.id=org</p> <p>In LDAP, this value is expressed as: ou=org</p>
enrole.organization.name	
	<p>Use the ldapConfig utility to modify this property.</p> <p>Specifies the long format of the organization name that is used by the directory server.</p> <p>This value is specified during installation of IBM Security Identity Manager or by running the ldapConfig utility.</p> <p>Example (default): enrole.organization.name=Organization</p>

LDAP server properties

LDAP server properties define the properties that are used by the directory server in which IBM Security Identity Manager stores data.

Table 32 defines the properties that are used the directory server.

Table 32. LDAP server properties

enrole.ldapservers.root	
	<p>Specifies the top-level entry node of the directory server data structure (dc=domain control). Use the ldapConfig utility to modify this value.</p> <p>This value is specified during installation of IBM Security Identity Manager.</p> <p>Example (default): enrole.ldapservers.root=dc=com</p>
enrole.ldapservers.home	
	<p>Do not modify this property key and value.</p> <p>Specifies the location of the system configuration information in the directory server.</p> <p>Example (default): enrole.ldapservers.home=ou=itim</p>
enrole.ldapservers.agelimit	

Table 32. LDAP server properties (continued)

	<p>Do not change this property key and value unless you are a qualified administrator. Use the runConfig utility to modify this value.</p> <p>Specifies the number of days that an object remains in the recycle bin before it can be deleted when the cleanup script is started. The recycle bin age limit protects objects in the recycle bin from cleanup scripts for the specified length of time.</p> <p>Cleanup scripts can remove only those objects that are older than the age limit setting. If the age limit setting is 62 days (default), only objects in the recycle bin for more than 62 days can be deleted by starting the cleanup script.</p> <p>Example (default): enrole.ldapserver.ageLimit=62</p>
enrole.ldapserver.ditlayout	
	<p>Do not modify this property key and value.</p> <p>Specifies the Java class that defines the structure of the data that is stored in the directory server.</p> <p>Example (default, flat structure): enrole.ldapserver.ditlayout=com.ibm.itim.dataservices.dit.itim.FlatHashedLayout</p>
enrole.ldap.provider	
	<p>Example (default): enrole.ldap.provider=IBM</p>

Search and LDAP control properties

Search and LDAP control properties are used to configure search strategy and LDAP control.

For more information about setting these parameters for your environment, see the tuning guide that is provided for IBM Security Identity Manager.

Table 33 defines the properties used to configure search strategy and LDAP control.

Table 33. Search and LDAP control properties

enrole.search.sss.enable	
	<p>Do not modify this property key and value.</p> <p>Specifies whether Server Side Sorting is used for searches of the directory server. Enabling server-side sorting with this property can have a large negative impact when you view large organizational units. It is suggested that you disable this option in most environments.</p> <p>Example (default): enrole.search.sss.enable=false</p>
enrole.search.vlv.enable	

Table 33. Search and LDAP control properties (continued)

	<p>Do not modify this property key and value.</p> <p>Specifies whether Virtual List View (VLV) is used for all return data from the directory server. This property can be enabled only when supported by the directory server. This option reduces the memory load on the application server but places a significant load on the LDAP server.</p> <p>Example (default): enrole.search.vlv.enable=false</p>
enrole.search.paging.enable	
	<p>Do not modify this property key and value.</p> <p>Specifies whether Paged Sorting is used for searches of the directory server. This option reduces the memory load on the application server. Enabling it is not suggested because the directory server might place a limit on the number of outstanding paged searches.</p> <p>Example (default): enrole.search.paging.enable=false</p>
enrole.search.paging.pagesize	
	<p>Do not modify this property key and value.</p> <p>Specifies the page size used for paged LDAP searches when enrole.search.paging.enable=true.</p> <p>Example (default): enrole.search.paging.pagesize=128</p>
enrole.search.cache.enable	
	<p>Do not modify this property key and value.</p> <p>Specifies the use of cached searching to speed up LDAP searches.</p> <p>Example (default): enrole.search.cache.enable=true</p>
enrole.search.cache.secondary.enable	
	<p>Do not modify this property key and value.</p> <p>Specifies the use of secondary cached searching to speed up LDAP searches.</p> <p>Example (default): enrole.search.cache.secondary.enable=true</p>
enrole.search.cache.secondary.filter.1	
	<p>Do not modify this property key and value.</p> <p>Use a filter fragment for people to prevent LDAP search filters from getting cached. Filtered out LDAP search filters are cached in the secondary cache, if enabled.</p> <p>Example (default): enrole.search.cache.secondary.filter.1=ou=people</p>

Table 33. Search and LDAP control properties (continued)

enrole.search.cache.secondary.filter.2	
	<p>Do not modify this property key and value.</p> <p>Use a filter fragment for accounts to prevent LDAP search filters from getting cached. Filtered out LDAP search filters are cached in the secondary cache, if enabled.</p> <p>Example (default): enrole.search.cache.secondary.filter.2=ou=accounts</p>
enrole.search.cache.secondary.filter.3	
	<p>Do not modify this property key and value.</p> <p>Use a filter fragment for the systemuser to prevent LDAP search filters from getting cached. Filtered out LDAP search filters are cached in the secondary cache, if enabled.</p> <p>Example (default): enrole.search.cache.secondary.filter.3=ou=systemuser</p>
enrole.search.cache.secondary.filter.4	
	<p>Do not modify this property key and value.</p> <p>Use a filter fragment for orphan accounts to prevent LDAP search filters from getting cached. Filtered out LDAP search filters are cached in the secondary cache, if enabled.</p> <p>Example (default): enrole.search.cache.secondary.filter.4=ou=orphans</p>
enrole.search.clientside.filtering.enable	
	<p>Do not modify this property key and value.</p> <p>Specifies the use of client-side filtering as a performance alternative on complex LDAP searches.</p> <p>Example (default): enrole.search.clientside.filtering.enable=true</p>
enrole.search.strategy	

Table 33. Search and LDAP control properties (continued)

	<p>Do not modify this property key and value.</p> <p>Specifies the Java class that defines the search strategy to process the return data from the directory server.</p> <p>Strategy values include:</p> <ul style="list-style-type: none"> • <code>com.ibm.itim.apps.ejb.search.EnumeratedSearch</code> (process data on demand) Avoids the use of collections, if possible. Maintains a cache of the number of search links multiplied by the page size. The underlying connection is closed when the page cache is filled. Access control items are applied as results are retrieved. • <code>com.ibm.itim.apps.ejb.search.CollectedException</code> (process all data) This is the previous search mechanism, which converts the search results into a collection and sort it. Applying access control items on the collection as pages are retrieved. The underlying LDAP connection is freed as soon as the results are transformed into a collection. <p>Example (default): <code>enrole.search.strategy=com.ibm.itim.apps.ejb.search.EnumeratedSearch</code></p>
<p><code>enrole.recyclebin.enable</code></p>	
	<p>Disable use of the recycle bin for a majority of objects to improve search times.</p> <p>Example (default for new installations): <code>enrole.recyclebin.enable=false</code></p>

Person profile properties

Person profile properties identify a person profile.

Table 34 defines the property used to identify a person profile. This property selects the profile by default when you create people or do advanced person searches in the administrative console.

Table 34. Person profile property

<p><code>enrole.personProfile</code></p>	
	<p>Searches in IBM Security Identity Manager use the default person profile <i>Person</i>. If you want to use custom person schemas, set this property to your profile.</p> <p>Example (default): <code>enrole.personProfile=Person</code></p> <p>Example: <code>enrole.personProfile=your_profile</code></p>

Profile and schema cache properties

Profile and schema cache properties define system cache performance.

Table 35 defines the properties used to configure system cache performance.

Table 35. Profile and schema cache properties

enrole.profile.timeout	
	<p>This property key and value affects performance tuning for IBM Security Identity Manager. Do not change it unless you are a qualified administrator.</p> <p>Specifies the timeout value in minutes for information in the profile section of the cache. Information exceeding this timeout value is removed from the cache.</p> <p>Example (default): enrole.profile.timeout=10</p>
enrole.schema.timeout	
	<p>This property key and value affects performance tuning for IBM Security Identity Manager. Do not change it unless you are a qualified administrator.</p> <p>Specifies the timeout value in minutes for information in the schema section of the cache. Information exceeding this timeout value is removed from the cache.</p> <p>Example (default): enrole.schema.timeout=10</p>
password.attributes	
	<p>Specifies which attribute is encrypted by the dataservices component.</p> <p>Example (default, on a single line): password.attributes=ersynchpassword erServicePassword erServicePwd1 erServicePwd2 erServicePwd3 erServicePwd4 erADDomainPassword erPersonPassword erNotesPasswdAddCert eritamcred erep6umds</p>
enrole.reminder.timeout	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the cache interval (in minutes) for a workflow reminder.</p> <p>Example: enrole.reminder.timeout=10</p>
signedObjectsCacheTimeout	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the cache interval (in hours) for a signed objects.</p> <p>Example: signedObjectsCacheTimeout=8</p>

Messaging properties

Messaging properties configure the internal communication between components of the Java Message Service (JMS) used by IBM Security Identity Manager.

Table 36 defines the properties used to configure the internal communication between components of the Java Message Service (JMS) used by IBM Security Identity Manager.

The adjustment of these property values is important to accurate performance tuning and scalability of the IBM Security Identity Manager product. Do not change property values in this section unless you are a qualified administrator.

Table 36. Messaging properties

Message timeout configuration	
enrole.messaging.ttl	
	<p>This property key and value affects performance tuning for JMS. Do not change the value unless you are a qualified administrator.</p> <p>Specifies the lifetime in minutes of a message in the queue. A value of zero specifies an unlimited lifetime.</p> <p>Example (default): enrole.messaging.ttl=0</p>
Messaging queue configuration	
<pre>enrole.messaging.managers= \ enrole.messaging.adhocSyncQueue \ enrole.messaging.workflowQueue \ enrole.messaging.sharedWorkflowQueue \ enrole.messaging.partitioningServiceQueue \ enrole.messaging.remoteServicesQueue \ enrole.messaging.remotePendingQueue \ enrole.messaging.mailServicesQueue \ enrole.messaging.policyAnalysisQueue \ enrole.messaging.policySimulationQueue \ enrole.messaging.importExportQueue</pre>	
	<p>Do not modify these property keys and values.</p> <p>Specifies the key names of supported IBM Security Identity Manager queues.</p>
<pre>enrole.messaging.adhocSyncQueue=adhocSyncQueue enrole.messaging.workflowQueue=workflowQueue enrole.messaging.sharedWorkflowQueue=sharedWorkflowQueue enrole.messaging.partitioningServiceQueue=partitioningServiceQueue enrole.messaging.remoteServicesQueue=remoteServicesQueue enrole.messaging.remotePendingQueue=remotePendingQueue enrole.messaging.mailServicesQueue=mailServicesQueue enrole.messaging.policyAnalysisQueue=policyAnalysisQueue enrole.messaging.policySimulationQueue=policySimulationQueue enrole.messaging.importExportQueue=importExportQueue</pre>	
	<p>Do not modify these property keys and values.</p> <p>Specifies the actual queue name as referenced by the application server.</p>
Queue attribute configuration	

Table 36. Messaging properties (continued)

	<ul style="list-style-type: none"> • SHARED A Boolean value that indicates whether the queue is shared across a clustered deployment. In a cluster, a shared queue can be read and written to by all cluster members. Do not modify this property. Example (on a single line): <code>enrole.messaging.sharedWorkflowQueue.attributes=SHARED=true</code> <code>enrole.messaging.policyAnalysisQueue.attributes=SHARED=true</code> <code>enrole.messaging.policySimulationQueue.attributes=SHARED=true</code> <p>Message processing errors detected by the messaging system cause individual messages to be redelivered and additional attempts to handle the message. Following the first indication of process failure, a retry is scheduled immediately. If the first attempt fails, another is scheduled with a delay that matches the value of the FIRST_RETRY_DELAY property. If the second attempt fails, another is scheduled with a delay that matches the value of the RETRY_DELAY property. Subsequent retries are attempted with the value of the RETRY_DELAY property until the MAX_RETRY_TIME threshold is reached.</p> <p>Set the following properties to manage how the system handles the retry attempts.</p> <ul style="list-style-type: none"> • FIRST_RETRY_DELAY The amount of time in milliseconds to delay before retrying after the initial immediate retry. Default value is 900000 (15 minutes). • RETRY_DELAY The amount of time [in milliseconds] to delay before retrying after the immediate and first attempts fail. Default value is 3600000 (60 minutes). • MAX_RETRY_TIME The maximum amount of time allowed for attempts, beginning with the first failure. Default value is 86400000 (24 hours) <p>Example (on a single line): <code>enrole.messaging.workflowQueue.attributes=SHARED=false</code> <code>FIRST_RETRY_DELAY=300000 RETRY_DELAY=900000 MAX_RETRY_TIME=3600000</code></p>
--	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Scheduling properties

The scheduling properties are used to configure the internal scheduler that runs calendar-based and scheduled events.

Table 37 defines the properties used to configure the internal scheduler responsible for running calendar-based scheduled events. Events and their schedules are stored in a database table.

Table 37. Scheduling properties

<code>enrole.scheduling.heartbeat</code>	
	<p>This property key and value affects performance tuning for IBM Security Identity Manager. Do not change it unless you are a qualified administrator.</p> <p>Specifies the interval [in seconds] that the event monitor checks the database table for scheduled events.</p> <p>Example (default): <code>enrole.scheduling.heartbeat=30</code></p>

Table 37. Scheduling properties (continued)

enrole.scheduling.timeout	
	<p>This property key and value affects performance tuning for IBM Security Identity Manager. Do not change it unless you are a qualified administrator.</p> <p>Specifies the timeout value [in minutes] for the event processor.</p> <p>Example (default): enrole.scheduling.timeout=10</p>
enrole.scheduling.fetchsize	
	<p>This property key and value affects performance tuning for IBM Security Identity Manager. Do not change it unless you are a qualified administrator.</p> <p>Specifies the number of messages to retrieve at a time when in batch mode.</p> <p>Example (default): enrole.scheduling.fetchsize=50</p>

Password transaction monitor properties

Password transaction monitor properties checks responses to password transactions. It expires those transactions when the user fails to respond in the specified interval.

When a password for a user is changed or automatically generated, an email notification is sent to a user. The email contains either the actual password or a link that the user can follow to obtain the new password. This activity is called a password transaction. The user must respond to the email and incorporate the new password within a specified amount of time. If the user fails to respond within the allowed time period, the password transaction expires.

The password transaction monitor is responsible for checking responses to password transactions. It expires those transactions when the user fails to respond to the email.

Table 38. Password transaction monitor properties

enrole.passwordtransactionmonitor.heartbeat	
	<p>Specifies how often [in hours] the password transaction monitor checks for expired password transactions.</p> <p>Example (default): enrole.passwordtransactionmonitor.heartbeat=1</p>

XML and DTD properties

XML and DTD properties are no longer used.

These properties are no longer used.

Table 39. XML and DTD properties

enrole.dtd.uri	
	Not used.

LDAP connection pool properties

LDAP connection pool properties are used to configure cache connection requests to the directory server.

Table 40 defines the properties used to configure the values that affect cache connection requests to the IBM Security Identity Manager directory server.

Table 40. LDAP connection pool properties

enrole.connectionpool.incrementcount	
	<p>This property key and value affect performance tuning for IBM Security Identity Manager. They must be changed only by a qualified administrator.</p> <p>Specifies the number of connections that are created any time the LDAP connection pool is incremented to accommodate an increasing demand.</p> <p>Example (default): enrole.connectionpool.incrementcount=3</p>
enrole.connectionpool.authentication	
	<p>This property key and value affect performance tuning for IBM Security Identity Manager. They must be changed only by a qualified administrator.</p> <p>Specifies a list of space-separated authentication types of connections that can be pooled.</p> <p>Valid types are:</p> <ul style="list-style-type: none">• none - No authentication is required.• simple• DIGEST-MD5 - <p>Example (default): enrole.connectionpool.authentication=none simple</p>
enrole.connectionpool.debug	

Table 40. LDAP connection pool properties (continued)

	<p>This property key and value specify the level of debug output. Valid values are "fine" (trace connection creation and removal) and "all" (all debugging information).</p> <p>Valid values are:</p> <ul style="list-style-type: none"> • fine - Trace connection creation and removal. • all - All debugging information. <p>Example (default, commented out): #enrole.connectionpool.debug=fine</p>
enrole.connectionpool.initialpoolsize	
	<p>This property key and value affect performance tuning for IBM Security Identity Manager. They must be changed only by a qualified administrator.</p> <p>Specifies the initial number of physical LDAP connections to create for the LDAP connection pool. This value must be less than or equal to the value of the maxpoolsize property.</p> <p>Example (default): enrole.connectionpool.initialpoolsize=50</p>
enrole.connectionpool.maxpoolsize	
	<p>This property key and value affect performance tuning for IBM Security Identity Manager. They must be changed only by a qualified administrator.</p> <p>Specifies the maximum number of physical LDAP connections that can be created.</p> <p>Example (default): enrole.connectionpool.maxpoolsize=100</p>
enrole.connectionpool.prefsiz	
	<p>This property key and value affect performance tuning for IBM Security Identity Manager. They must be changed only by a qualified administrator.</p> <p>Specifies the preferred number of physical LDAP connections that must be maintained concurrently. This number includes both in-use and idle connections. A size of zero or no value means that there is no preferred size. In that case, a request for a pooled connection results in a newly created connection if no idle ones are available.</p> <p>Example (no value): enrole.connectionpool.prefsiz=</p>
enrole.connectionpool.protocol	

Table 40. LDAP connection pool properties (continued)

	<p>This property key and value affect performance tuning for IBM Security Identity Manager. They must be changed only by a qualified administrator.</p> <p>Specifies a list of space-separated protocol types of connections that can be pooled.</p> <p>Valid values are:</p> <ul style="list-style-type: none"> • plain • ssl • plain ssl <p>Example (default): <code>enrole.connectionpool.protocol=plain ssl</code></p>
<code>enrole.connectionpool.timeout</code>	
	<p>This property key and value affect performance tuning for IBM Security Identity Manager. They must be changed only by a qualified administrator.</p> <p>Specifies the number of milliseconds that an idle connection can remain in the pool without being closed and removed from the pool.</p> <p>Example (default, commented out): <code>#enrole.connectionpool.timeout=10000</code></p>

Password encryption properties

Password encryption properties are used to configure password encryption.

Table 41 defines the properties used to configure password encryption.

Table 41. Encryption properties

<code>enrole.encryption.algorithm</code>	
	<p>Do not modify this property key and value.</p> <p>Specifies the cipher suite to use for encryption. For example, AES or PBEWithMD5AndDES.</p> <p>Example (default): <code>enrole.encryption.algorithm=AES</code></p>
<code>enrole.encryption.password</code>	

Table 41. Encryption properties (continued)

	<p>Do not modify this property key and value. This value is specified during IBM Security Identity Manager installation.</p> <p>The value of the <code>enrole.encryption.password</code> property is moved into the <code>encryptionKey</code> property file. The value is encoded by default and is stored in the <code>encryptionKey</code> property file.</p> <p>For Password-Based Encryption (PBE) encryption algorithms (used for upgraded IBM Tivoli Identity Manager Version 4.6 installations), specifies the encrypted password used as an input parameter for Password-Based Encryption (PBE). PBE is a method of encrypting and decrypting data with a secret key based on a user-supplied password. For example, encrypted data includes shared secrets, service passwords, and some protected account attributes.</p> <p>Specifies the keystore password, in encrypted format, when AES is the encryption algorithm. For non-PBE based encryption algorithms (used for new IBM Tivoli Identity Manager Version 5.0 installations), the password is used to encrypt the keystore that stores the private key. For more information about this property, see the <code>enrole.encryption.keystore</code> property.</p> <p>This value is specified during IBM Security Identity Manager installation.</p>
<p><code>enrole.encryption.passwordDigest</code></p>	
	<p>Do not modify this property key and value.</p> <p>Specifies the type of password digest used for an IBM Security Identity Manager password. Upgrading Tivoli® Identity Manager from Version 4.6 continues to use the original hash algorithm until users change their passwords. This original algorithm is defined by the property <code>enrole.pre50.encryption.passwordDigest</code>. Valid values are:</p> <ul style="list-style-type: none"> • SHA-256 – Federal Information Processing Standards (FIPS)-approved hashing algorithm used by IBM Tivoli Identity Manager Version 5.0 for passwords. A random salt value is added to the data before it is hashed. • SHA-384 – Federal Information Processing Standards (FIPS)-approved hashing algorithm, providing 384 bits of security (by truncating the output of the SHA-512 algorithm). A random salt value is added to the data before it is hashed. • SHA-512 – Federal Information Processing Standards (FIPS)-approved hashing algorithm, providing 512 bits of security. A random salt value is added to the data before it is hashed. <p>Example (default): <code>enrole.encryption.passwordDigest=SHA-256</code></p>
<p><code>enrole.pre50.encryption.passwordDigest</code></p>	
	<p>Do not modify this property key and value. Upgrading IBM Tivoli Identity Manager from Version 4.6 adds this property dynamically to this properties file.</p> <p>Specifies the type of password digest used for IBM Security Identity Manager password data from IBM Tivoli Identity Manager versions before 5.0. The lack of a ":" in an encrypted IBM Security Identity Manager password value is used to identify such migrated data.</p> <p>Note: All new passwords, including changed migrated passwords, are stored with the <code>enrole.encryption.passwordDigest</code> algorithm.</p> <p>Example (default for migrated installations, not present for new installations): <code>enrole.pre50.encryption.passwordDigest=MD5</code></p>

Table 41. Encryption properties (continued)

enrole.encryption.keystore	
	<p>Do not modify this property key and value.</p> <p>Specifies the keystore file name used to contain the randomly generated secret key for non-PBE based encryption algorithms, such as AES. This keystore file is protected with the enrole.encryption.password value. This file is in the <i>ISIM_HOME\data\keystore</i> directory.</p> <p>Example (default): enrole.encryption.keystore=itimKeystore.jceks</p>

Challenge response encoding properties

Challenge response encoding properties determine whether a response is encoded as case sensitive or insensitive.

Table 42 defines the properties used to encode a response as case sensitive or insensitive.

Table 42. Challenge response encoding properties

enrole.challengeresponse.responseConvertCase	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies how CR responses are encoded before they are stored in the directory. Valid values are:</p> <ul style="list-style-type: none"> • lower – Encode the CR as lowercase. • upper – Encode the CR as uppercase. • none – Do not encode the CR. Retain the case-sensitive response as is. <p>Example (default): enrole.challengeresponse.responseConvertCase=lower</p>

System listening port properties

System listening port properties are used to configure the listening port settings for the IBM Security Identity Manager Server.

Table 43 defines the properties used to configure the listening port settings for the IBM Security Identity Manager Server.

Table 43. System configuration properties

enrole.system.listenPort	
	<p>Do not modify this property key and value.</p> <p>Specifies the TCP (non-secure communication) listening port value. This value is set during IBM Security Identity Manager installation.</p> <p>Example (default): enrole.system.listenPort=80</p>

Table 43. System configuration properties (continued)

enrole.system.SSLlistenPort	
	<p>Do not modify this property key and value.</p> <p>Specifies the Secure Sockets Layer (SSL) listening port value.</p> <p>This value is set during IBM Security Identity Manager installation.</p> <p>Example (default): enrole.system.SSLlistenPort=443</p>

Mail properties

Mail properties are used to configure internal mail notification.

Table 44 defines the properties used to configure internal mail notification.

Table 44. Mail services properties

enrole.mail.notify	
	<p>Specifies whether the sending of workflow internal email is synchronized or not.</p> <p>Values include:</p> <ul style="list-style-type: none"> • SYNC - Synchronized. • ASYNC - Asynchronized. <p>Example (default): enrole.mail.notify=ASYNC</p>

Workflow properties

Workflow properties are used to configure the core IBM Security Identity Manager workflow engine.

Table 45 defines the properties used to configure the core IBM Security Identity Manager workflow engine.

Table 45. Workflow configuration properties

Workflow configuration	
enrole.workflow.lrucache.size	
	<p>Specifies the size of the cache used to temporarily use and access workflow objects. Do not change it unless directed by IBM support. Making this value too large can result in out of memory conditions of IBM Security Identity Manager Server.</p> <p>Example (default, commented out): ## enrole.workflow.lrucache.size=number_of_entries where the default value of <i>number_of_entries</i> is 2000.</p>
enrole.workflow.notifyoption	

Table 45. Workflow configuration properties (continued)

	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the behavior of workflow email notifications. Values are:</p> <ul style="list-style-type: none"> • 0 (NOTIFY_NONE) – Security Identity Manager does not send email notifications when the workflow process completes. • 1 (NOTIFY_REQUESTER) – A process completion notification is sent to the requester when the workflow process completes. Account email notifications are then sent to the requestee for the following account requests: <ul style="list-style-type: none"> New Account New Password Change Account Deprovision Account Suspend Account Restore Account <p>For example, when the workflow process completes for a new account request, a process completion notification is sent to the requester. A new account notification is then sent to the requestee.</p> <p>Example (default): enrole.workflow.notifyoption=1</p>
enrole.workflow.notifypassword	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the type of email notification in a password transaction (caused when a user password is changed or automatically generated). Values are:</p> <ul style="list-style-type: none"> • true – email notification of a password change can be sent to a user. The actual notification mechanism and whether to include the actual password in the email is dictated by the configuration of the enrole.workflow.notification.newpassword property value. • false – email notification of a password change is sent to a user. The email contains a URL where the user can obtain the password. The URL prompts the user for the shared secret. <p>Example (default): enrole.workflow.notifypassword=true</p>
enrole.workflow.notifyaccountsonwarning	
	<p>Specifies whether account email notifications are sent when the account operation results in a warning. Values are:</p> <ul style="list-style-type: none"> • true – Sends account email notifications. • false – Does not send account email notifications. <p>Example (default): enrole.workflow.notifyaccountsonwarning=false</p>
enrole.workflow.maxretry	

Table 45. Workflow configuration properties (continued)

	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the number of times an attempt is made to start a workflow that initially failed. See also <code>enrole.workflow.retrydelay</code>.</p> <p>Example (default): <code>enrole.workflow.maxretry=2</code></p>
<code>enrole.workflow.retrydelay</code>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the time delay [in milliseconds] between successive attempts to start a workflow application that initially failed. See also <code>enrole.workflow.maxretry</code>.</p> <p>Example (default): <code>enrole.workflow.retrydelay=60000</code></p>
<code>enrole.workflow.skipapprovalforrequester</code>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>For a workflow activity that requires approval, this property specifies whether to skip the approval for other approvers if the requester is also an approver. Values are:</p> <ul style="list-style-type: none"> • true – Skips approval for other approvers if the requester is also an approver. • false – Forces an approval check from other required approvers of the activity, <i>except</i> the requester (if the requester is also an approver). If the requester is a single approver as a result of participant resolution, then the approval is skipped even when value is set to false. <p>Example (default): <code>enrole.workflow.skipapprovalforrequester=false</code></p>
<code>enrole.workflow.disablerequesteeapproval</code>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>For a workflow activity that requires approval, this property specifies whether to disable the requestee approval if the requestee is also an approver. Values are:</p> <ul style="list-style-type: none"> • true – Disables the requestee approval if the requestee is also an approver. • false – Sends an approval check to the requestee and other resolved participants if the requestee is also an approver. <p>The default value is false.</p> <p>Example (default): <code>enrole.workflow.disablerequesteeapproval=false</code></p> <p>For more information, see <i>Planning > Workflow planning > Workflow participants > Disable requestee or requester approval on the IBM Security Identity Manager documentation</i>.</p>
<code>enrole.workflow.disablerequesterapproval</code>	

Table 45. Workflow configuration properties (continued)

	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>IBM Security Identity Manager considers this property value only when the <code>enrole.workflow.skipapprovalforrequester</code> property value is set to false.</p> <p>For a workflow activity that requires approval, this property specifies whether to disable the requester approval if the requester is an approver. Values are:</p> <ul style="list-style-type: none"> • true – A value set to false for the <code>enrole.workflow.skipapprovalforrequester</code> property disables automatic approval if the requester is a lone approver. • false – Works according to the value that you set for the <code>enrole.workflow.skipapprovalforrequester</code> property. <p>Example (default): <code>enrole.workflow.disablerequesterapproval=false</code></p> <p>For more information, see <i>Planning > Workflow planning > Workflow participants > Disable requestee or requester approval on the IBM Security Identity Manager documentation</i>.</p>
<code>enrole.workflow.skipfornoncompliantaccount</code>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies whether to engage the entitlement workflow that is associated with the account. Specifies when a system account modification is triggered as a result of a policy enforcement action. Values are:</p> <ul style="list-style-type: none"> • true – Skips this action. • false – Does not skip this action. <p>Example (default): <code>enrole.workflow.skipfornoncompliantaccount=true</code></p>
<code>enrole.workflow.distribution</code>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies whether workflow requests use the IBM Security Identity Manager shared queues, which allow for workload distribution. Values are:</p> <ul style="list-style-type: none"> • true – Workflow requests are eligible for distribution. • false – Workflow requests are not eligible for distribution. <p>Example (default): <code>enrole.workflow.distribution=true</code></p>
<code>enrole.workflow.async_completion_enabled</code>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies whether the system uses asynchronous completion checking for some system workflows, which can decrease database lock contention and improve performance. Values are:</p> <ul style="list-style-type: none"> • true – Uses asynchronous completion checking. • false – Does not use asynchronous completion checking. <p>Example (default): <code>enrole.workflow.async_completion_enabled=true</code></p>
<code>enrole.workflow.async_completion_interval_sec</code>	

Table 45. Workflow configuration properties (continued)

	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the interval in seconds that the system checks to see whether certain system workflows are complete. Only applicable when <code>enrole.workflow.async_completion_enabled=true</code>.</p> <p>Example (default): <code>enrole.workflow.async_completion_interval_sec=30</code></p>
<code>enrole.workflow.notification.activitytimeout</code>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the default Java class that generates the workflow activity timeout notification.</p> <p>Example (default, entered as a single line): <code>enrole.workflow.notification.activitytimeout=com.ibm.itim.workflow.notification.TemplateActivityTimeoutNotification</code></p>
<code>enrole.workflow.notification.processtimeout</code>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the default Java class that generates the workflow process timeout notification.</p> <p>Example (default, entered as a single line): <code>enrole.workflow.notification.processtimeout=com.ibm.itim.workflow.notification.TemplateProcessTimeoutNotification</code></p>
<code>enrole.workflow.notification.processcomplete</code>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the default Java class that generates the notification for when a workflow process is completed.</p> <p>Example (default, entered as a single line): <code>enrole.workflow.notification.processcomplete=com.ibm.itim.workflow.notification.TemplateProcessCompleteNotification</code></p>
<code>enrole.workflow.notification.pendingwork</code>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the default Java class that generates the notification for when a workflow process is completed for manual activities (Approvals and Requests for Information).</p> <p>Example (default, entered as a single line): <code>enrole.workflow.notification.pendingwork=com.ibm.itim.workflow.notification.TemplatePendingWorkNotification</code></p>
<code>enrole.workflow.notification.newaccount</code>	

Table 45. Workflow configuration properties (continued)

	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the default Java class that generates the notification for when a workflow process is completed for a new account.</p> <p>Example (default, entered as a single line):</p> <pre>enrole.workflow.notification.newaccount=com.ibm.itim.workflow.notification.TemplateNewAccountNotification</pre>
<pre>enrole.workflow.notification.newpassword</pre>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the default Java class that generates a notification when a user changes a password. This property is used only when the value for the property is true.</p> <pre>enrole.workflow.notifypassword=true</pre> <p>This property responds to the following three-password change scenarios:</p> <ul style="list-style-type: none"> • When a user changes the password for the account • When the administrator forces a password change on the account • When a user is successfully identified through the password challenge/response feature, and challenge/response is configured. <p>Valid classes include:</p> <ul style="list-style-type: none"> • NewPasswordNotification Email notification that includes the password (in ASCII text) is sent to a user (default). • EmptyNotificationFactory Suppresses email notification. The preferred method for suppressing any notification is through the Workflow Notification GUI. • PasswordChangeNotificationFactory Email notification that does not include the password is sent to a user. Message body says: "Process completed". <p>The EmptyNotificationFactory and PasswordChangeNotificationFactory classes are in the examples.jar package in the examples directory.</p> <p>Example (default, entered as a single line):</p> <pre>enrole.workflow.notification.newpassword=com.ibm.itim.workflow.notification.TemplateNewPasswordNotification</pre>
<pre>enrole.workflow.notification.deprovision</pre>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the default Java class that generates deprovisioning notification.</p> <p>Example (default, entered as a single line):</p> <pre>enrole.workflow.notification.deprovision=com.ibm.itim.workflow.notification.TemplateDeprovisionNotification</pre>
<pre>enrole.workflow.notification.workorder</pre>	

Table 45. Workflow configuration properties (continued)

	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the default Java class that generates work order notifications.</p> <p>Example (default, entered as a single line):</p> <pre>enrole.workflow.notification.workorder=com.ibm.itim.workflow.notification.TemplateWorkOrderNotification</pre>
enrole.workflow.notification.changeaccount	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the default Java class that generates account change notifications.</p> <p>Example (default, as a single line):</p> <pre>enrole.workflow.notification.changeaccount=com.ibm.itim.workflow.notification.TemplateChangeAccountNotification</pre>
enrole.workflow.notification.restoreaccount	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the default Java class that generates account restoration notifications.</p> <p>Example (as a single line):</p> <pre>enrole.workflow.notification.restoreaccount=com.ibm.itim.workflow.notification.TemplateRestoreAccountNotification</pre>
enrole.workflow.notification.suspendaccount	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the default Java class that generates account suspension notifications.</p> <p>Example (as a single line):</p> <pre>enrole.workflow.notification.suspendaccount=com.ibm.itim.workflow.notification.TemplateSuspendAccountNotification</pre>

Reconciliation properties

Reconciliation properties are used to configure the reconciliation process where data retrieved from agents is synchronized in the IBM Security Identity Manager database.

Table 46 defines the properties used to configure the values that affect the reconciliation process where data retrieved from agents is synchronized in the IBM Security Identity Manager database.

Table 46. Reconciliation properties

Reconciliation configuration
enrole.reconciliation.accountcachesize

Table 46. Reconciliation properties (continued)

	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the maximum size of the cache for existing accounts cache that is used for the reconciliation process. Setting a value larger than the default might cause processing of reconciliations to fail.</p> <p>Example (default): <code>enrole.reconciliation.accountcachesize=2000</code></p>
<code>enrole.reconciliation.threadcount</code>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the number of threads that are used to handle reconciled entries. This number of threads is created for each reconciliation process.</p> <p>Example (default): <code>enrole.reconciliation.threadcount=8</code></p>
<code>enrole.reconciliation.failurethreshold</code>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the maximum number of local accounts to delete at the end of reconciliation. If the value is exceeded, then no local account or supporting data entries are deleted. If the value is followed by a percent sign (%), specifies the maximum as percentage compared with total of (local accounts at reconciliation start plus the new accounts returned by reconciliation). A value of 100% specifies that there is no limit.</p> <p>Example (default, commented out): <code>#enrole.reconciliation.failurethreshold=100%</code></p>
<code>enrole.reconciliation.logTimeInterval</code>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the time interval in seconds for reconciliation progress trace log messages. A value of zero disables this time interval.</p> <p>Example (default, commented out): <code>#enrole.reconciliation.logTimeInterval=600</code></p>
<code>enrole.reconciliation.logEveryNResults</code>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies the count for reconciliation progress trace log messages. A value of zero disables this count.</p> <p>Example (default, commented out): <code>#enrole.reconciliation.logEveryNResults=5000</code></p>
Unsolicited notification events	
<code>account.EventProcessorFactory</code>	

Table 46. Reconciliation properties (continued)

	<p>Do not modify this property key and value.</p> <p>Specifies the built-in Java class for the account event processor factory.</p> <p>Example (default, entered as a single line):</p> <pre>account.EventProcessorFactory=com.ibm.itim.remoteservices.ejb.reconciliation.AccountEventProcessorFactory</pre>
<pre>person.EventProcessorFactory</pre>	
	<p>Do not modify this property key and value.</p> <p>Specifies the built-in Java class for the person event processor factory.</p> <p>Example (default, entered as a single line):</p> <pre>person.EventProcessorFactory=com.ibm.itim.remoteservices.ejb.reconciliation.PersonEventProcessorFactory</pre>
<p>Reconciliation processing</p>	
<pre>account.ReconEntryHandlerFactory</pre>	
	<p>Do not modify this property key and value.</p> <p>Specifies the built-in Java class for the account entry handler factory.</p> <p>Example (default, entered as a single line):</p> <pre>account.ReconEntryHandlerFactory=com.ibm.itim.remoteservices.ejb.mediation.AccountEntryHandlerFactory</pre>
<pre>person.ReconEntryHandlerFactory</pre>	
	<p>Do not modify this property key and value.</p> <p>Specifies the built-in Java class for the person entry handler factory.</p> <p>Example (default, entered as a single line):</p> <pre>person.ReconEntryHandlerFactory=com.ibm.itim.remoteservices.ejb.mediation.PersonEntryHandlerFactory</pre>
<pre>enrole.reconciliation.accountChangeFormatter</pre>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>When specified, this property allows you to customize how local attribute changes that are detected during reconciliation are formatted and stored. The default behavior can be overridden by specifying the fully qualified Java class name of an alternative implementation.</p> <p>Example (assuming Java class <code>com.example.custom.AccountChangeFormatter</code> is a custom implementation of interface <code>com.ibm.itim.remoteservices.ejb.mediation.IAccountChangeFormatter</code>). The example is entered as a single line:</p> <pre>enrole.reconciliation.accountChangeFormatter=com.example.custom.AccountChangeFormatter</pre>
<p>Deferring requests for failed remote resources</p>	

Table 46. Reconciliation properties (continued)

com.ibm.itim.remoteservices.ResourceProperties.DEFER_FAILED_RESOURCE	
	<p>Do not modify this property key and value.</p> <p>Specifies whether to defer requests to failed resources and wait for resource to restart before it sends them. Valid values are:</p> <ul style="list-style-type: none"> • true – Defers requests to failed resources and waits for the resource to restart. • false – If the resource fails, requests follows the configured workflow retry mechanism before it terminates as failed. See <code>enrole.workflow.maxretry</code> and <code>enrole.workflow.retrydelay</code>. <p>Example (default): <code>com.ibm.itim.remoteservices.ResourceProperties.DEFER_FAILED_RESOURCE=true</code></p>
remoteservices.remotepending.interval	
	<p>Do not modify this property key and value.</p> <p>Specifies the interval in seconds (120 minimum to 3600 maximum) to check whether failed resources restart.</p> <p>Example (default): <code>remoteservices.remotepending.interval=600</code></p>
com.ibm.itim.remoteservices.ResourceProperties.MAX_REQUEST_TIME	
	<p>Do not modify this property key and value.</p> <p>Specifies the maximum time in seconds that a request to a resource can be outstanding. It includes time in pending state for asynchronous requests, or deferred requests due to a service failure or request backlog. Valid values are:</p> <ul style="list-style-type: none"> • -1 – Unlimited • 60 + (value of <code>remoteservices.remotepending.interval</code>) – Minimum time interval for outstanding requests. <p>Example (default): <code>com.ibm.itim.remoteservices.ResourceProperties.MAX_REQUEST_TIME=-1</code></p>
remoteservices.remotepending.restart.retry	
	<p>Do not modify this property key and value.</p> <p>Specifies the time interval in minutes that pending requests generated from the restart of a failed service are given to complete. When the time interval ends, the server retries the requests.</p> <p>Example (default): <code>remoteservices.remotepending.restart.retry=1440</code></p>
com.ibm.itim.remoteservices.DSML2ServiceProvider.modifyAsREPLACE	

Table 46. Reconciliation properties (continued)

	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>For remote services, specifies the DSMLv2 (deprecated) provider mode of sending a modify request for attributes.</p> <p>Values include:</p> <ul style="list-style-type: none"> • true – Use the REPLACE operation. • false – Use the ADD and DELETE operations. <p>Example (default):</p> <pre>com.ibm.itim.remoteservices.DSML2ServiceProvider.modifyAsREPLACE=true</pre>
--	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Shared secret properties

Shared secret properties are used to configure the level of protection of the shared secret code.

Table 47 defines the properties used to configure the level of protection of the shared secret code.

The shared secret is used by an account owner to retrieve a new or changed password for an account when the system is configured to not email passwords in the clear (that is, the value of `enrole.workflow.notifypassword=false`). This property determines whether the stored shared secret is hashed for additional protection.

Table 47. Shared secret hashing properties

<code>enrole.sharedsecret.hashed</code>	
	<p>Do not change this property key and value unless you are a qualified administrator.</p> <p>Specifies whether the shared secret code is hashed (secure) or not hashed (not secure).</p> <p>Values include:</p> <ul style="list-style-type: none"> • true – Store the shared secret as hashed. • false – Store the shared secret as not hashed. <p>Example (default):</p> <pre>enrole.sharedsecret.hashed=false</pre>

Lifecycle rule properties

Lifecycle rule properties define values such as the partition size used for lifecycle rules.

Table 48 defines the properties used to configure lifecycle rules.

Table 48. Lifecycle rule properties

<code>enrole.lifecyclerule.partition.size</code>

Table 48. Lifecycle rule properties (continued)

	<p>Do not change this value unless requested by IBM support. Specifies the size of the data partitions for processing lifecycle rules. This parameter determines how much data is processed in a single step.</p> <p>Example (default): enrole.lifecyclerule.partition.size=100</p>
--	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Product name properties

Product name properties identify this product.

Table 49 defines the property used to identify the product.

Table 49. Product property

enrole.product.name	
	<p>Do not change this name. This property key identifies the product name as IBM Security Identity Manager.</p> <p>Example (default): enrole.product.name=ITIM Enterprise</p>

Application client request properties

Application client request properties define the properties used to configure the lifetime, or timeout, value for the authentication token used to allow third-party communication with IBM Security Identity Manager Server.

Table 50 defines the properties used to configure the lifetime, or timeout, value for the authentication token used by the IBM Security Identity Manager application API to allow third-party applications to communicate with the IBM Security Identity Manager Server.

Table 50. Application client request properties

authTokenTimeout	
	<p>Specifies timeout value in hours for the authentication token that is used for communication between third-party applications (with the IBM Security Identity Manager application API) and the IBM Security Identity Manager Server.</p> <p>A value of -1 indicates that there is no timeout for the authentication token.</p> <p>Example (default): authTokenTimeout=48</p>

Reverse password synchronization properties

Reverse password synchronization properties are used to configure reverse password synchronization.

Table 51 on page 253 defines the properties used to configure reverse password synchronization.

Table 51. Reverse password synchronization properties

reversePasswordSynch.bypassPwdValidationOnOrphanAccount	
	<p>Specifies whether to bypass the password validation on the orphan account when the request is submitted from the agent. Valid values are:</p> <ul style="list-style-type: none"> • true – Bypass password validation. • false – Validate passwords. <p>Example (default): reversePasswordSynch.bypassPwdValidationOnOrphanAccount=false</p>
enrole.passwordsynch.module.sendMail	
	<p>Specifies whether to enable or disable email notifications when password synchronization is triggered by the reverse password synchronization agent, not from the IBM Security Identity Manager graphical user interface. Valid values are:</p> <ul style="list-style-type: none"> • true – Enable email notifications. • false – Disable email notifications. <p>Example (default): enrole.passwordsynch.module.sendMail=false</p>

Post office properties

Post office properties are used to configure the post office for email collection.

Table 52 defines the properties for testing post office configuration.

Table 52. Post office properties

enrole.postoffice.test.subject1 enrole.postoffice.test.textbody1 enrole.postoffice.test.xhtmlbody1	
	<p>Specifies the contents of the emails that are used when you test the post office configuration. It is one of three emails to which the template is applied.</p> <p>Example (default): enrole.postoffice.test.subject1=This is subject 1 enrole.postoffice.test.textbody1=This is the text body 1 enrole.postoffice.test.xhtmlbody1=This is the html body 1</p>
enrole.postoffice.test.subject2 enrole.postoffice.test.textbody2 enrole.postoffice.test.xhtmlbody2	
	<p>Specifies the contents of the emails that are used when you test the post office configuration. It is one of three emails to which the template is applied.</p> <p>Example (default): enrole.postoffice.test.subject2=This is subject 2 enrole.postoffice.test.textbody2=This is the text body 2 enrole.postoffice.test.xhtmlbody2=This is the html body 2</p>
enrole.postoffice.test.subject3 enrole.postoffice.test.textbody3 enrole.postoffice.test.xhtmlbody3	

Table 52. Post office properties (continued)

	<p>Specifies the contents of the emails that are used when you test the post office configuration. It is one of three emails to which the template is applied.</p> <p>Example (default):</p> <pre>enrole.postoffice.test.subject3=This is subject 3 enrole.postoffice.test.textbody3=This is the text body 3 enrole.postoffice.test.xhtmlbody3=This is the xhtml body 3</pre>
<pre>enrole.postoffice.test.topic</pre>	
	<p>Specifies the topic of the email that is used when you test the post office configuration. The three test emails, whose content is defined by the preceding properties, all have this topic. The post office function gathers and stores emails by topic and locale, It then aggregates and sends them as one email on a configured interval, such as once a day or once a week. This method prevents flooding the recipient with many individual emails for a type of event. The topic data usually indicates the type of event. It is also made available to the programming environment that is activated when the gathered emails are aggregated into one summarizing email. In this way, the topic under which all of these emails were gathered can be prominently displayed in the aggregate email that is sent.</p> <p>Example (default):</p> <pre>enrole.postoffice.test.topic=topic1</pre>
<pre>enrole.postoffice.test.locale</pre>	
	<p>Specifies the locale for the language that is used in an email.</p> <p>Example (default):</p> <pre>enrole.postoffice.test.locale=en_US</pre>

Database resource bundle properties

Database resource bundle properties determine the refresh interval for the database resource bundle.

Table 53 defines the properties used to determine the refresh interval for the database resource bundle.

Table 53. Database resource bundle properties

<pre>enrole.databaseresourcebundle.refreshInterval</pre>	
	<p>Specifies how many minutes to wait before DatabaseResourceBundle is checked for changes and reloaded.</p> <p>Example (default):</p> <pre>enrole.databaseresourcebundle.refreshInterval=5</pre>

Database cleanup properties

Database cleanup properties define the parameters to clean up session information in the database.

Table 54 defines the parameters for the policy analysis scavenger thread to clean up session information in the database.

Table 54. Database cleanup properties

provisioning.policy.preview.cleanup.interval	
	Specifies the interval in minutes that the scavenger thread scans the database. Example: provisioning.policy.preview.cleanup.interval=30
provisioning.policy.analysis.idle.timeout	
	Represents the expired time setting for a policy analysis session. The scavenger thread cleans up the staged data of a policy analysis session if the session ends at an interval that is greater than the timeout value. The timeout value might be 120 minutes. Example: provisioning.policy.analysis.idle.timeout=120

Create password check box properties

Create password check box properties define the default check box properties to create a password.

Table 55 defines the default create password check box properties.

Table 55. Create password check box default properties

enrole.CreatePassword	
	Specifies whether a password is created automatically. Valid values are: <ul style="list-style-type: none"> • true – Create a password. • false – Do not create a password. The user must type in the password. Example (default): enrole.CreatePassword=true

Access catalog properties

The `com.ibm.itim.accesscatalog.groupIntersectionJoin.enabled` enables support for searching group access when requesting access in the Identity Service Center when Intersection Join directive is used for the group attribute. The `com.ibm.itim.accesscatalog.customJoin.enabled` enables support for searching group access when requesting access in the Identity Service Center when Custom Join directive is used for the group attribute.

Table 56. Access catalog properties

<code>com.ibm.itim.accesscatalog.groupIntersectionJoin.enabled</code>

Table 56. Access catalog properties (continued)

	<p>Do not change this property value unless you are a qualified administrator.</p> <p>Enables support for searching group access when requesting access in the Identity Service Center in the case where Intersection Join directive is used for the group attribute.</p> <p>Values include:</p> <ul style="list-style-type: none"> • true • false <p>The default is false.</p> <p>Example (default):</p> <pre>com.ibm.itim.accesscatalog.groupIntersectionJoin.enabled=false</pre>
<pre>com.ibm.itim.accesscatalog.customJoin.enabled</pre>	
	<p>Do not change this property value unless you are a qualified administrator.</p> <p>Enables support for searching group access when requesting access in the Identity Service Center in the case where Custom Join directive is used for the group attribute.</p> <p>Values include:</p> <ul style="list-style-type: none"> • true • false <p>The default is false.</p> <p>Example (default):</p> <pre>com.ibm.itim.accesscatalog.customJoin.enabled=false</pre>

Identity feed properties

Identity feed properties define a default identity feed action, such as whether to suspend an account.

Table 57 defines the default identity feed properties.

Table 57. Default identity feed properties

<pre>enrole.suspend.accounts.identity.feed</pre>	
	<p>Specifies whether all of a user's accounts are suspended when the person is suspended during an identity feed. Valid values are:</p> <ul style="list-style-type: none"> • true – Suspend all accounts of a suspended user. • false – Do not suspend all accounts of a suspended user. <p>Example (default):</p> <pre>enrole.suspend.accounts.identity.feed=true</pre>

Upgrade properties

Upgrade properties define values for the upgrade of a specific release of IBM Security Identity Manager.

Table 58 defines the product upgrade properties.

Table 58. Default upgrade properties

minUpgradeVersion	
	Specifies the minimum version that the upgrade supports for a specific release of IBM Security Identity Manager. Example (default): minUpgradeVersion=5.1
file.merge.list	
	Specifies which properties files are merged during the upgrade of IBM Security Identity Manager. Example (default): file.merge.list=enRole \ enRoleLDAPConnection \ enRoleDatabase \ enRoleLogging \ enRoleMail \ ui \ CustomLabels \ CustomLabels_en \ enRoleAuthentication \ adhocreporting \ enroleworkflow \ enroleAuditing \ SelfServiceScreenText \ SelfServiceScreenText_en \ SelfServiceHelp \ SelfServiceUI \ SelfServiceHomePage\ scriptframework\ encryptionKey\ KMIPServer

Multiple password-synch agent properties

Multiple password-synch agent properties are used to configure the IBM Security Identity Manager Server to support multiple password-synchronization agents.

Table 59 defines the properties used to configure the support for multiple password-synch agents.

Table 59. Multiple password-synch agent properties

enrole.passwordsynch.enabledonresource

Table 59. Multiple password-synch agent properties (continued)

	<p>Specifies whether to enable or disable the support for multiple password-synch agents. Valid values are:</p> <ul style="list-style-type: none"> • true – Enable the support for multiple password-synch agents • false – Disable the support for multiple password-synch agents <p>Example (default): enrole.passwordsynch.enabledonresource=false</p>
enrole.passwordsynch.toleranceperiod	
	<p>Specifies the maximum time duration, in <i>seconds</i>, between a password change request sent from the IBM Security Identity Manager Server to the password synch resource, and receiving a reverse password synch request from the plug-in installed on the password synch resource.</p> <p>Example (default): enrole.passwordsynch.toleranceperiod=60</p>
enrole.PasswordSynchStoreMonitor.heartbeat	
	<p>Specifies the password synch transaction monitor heartbeat, in <i>hours</i>.</p> <p>Example (default): enrole.PasswordSynchStoreMonitor.heartbeat=1</p>

Concurrency properties

Account concurrency properties determine how to resolve multiple provisioning requests for the same account ID.

Table 60. Account concurrency properties

account.provision.concurrency.resolution	
	<p>Specifies which conflict resolution method is used when a concurrency issue occurs.</p> <p>Select from the following values:</p> <ul style="list-style-type: none"> • 0 - Change the concurrent account add operations to account modify operations. • 1 - Add the account with a newly generated account user ID • 2 - No operation override. Fail the account provisioning. <p>Example (default): account.provision.concurrency.resolution=0</p>

Required field properties

These properties are used to configure whether fields in the user interface are required to be completed by the user.

Table 61 defines the properties that are used to determine whether a field in the user interface is a required field.

Table 61. Required field properties

enrole.justificationRequired

Table 61. Required field properties (continued)

	<p>Specifies whether the Justification field is a required field.</p> <p>By default, the Justification field is not displayed in the user interface. Setting this property to true causes the Justification property to be displayed. It also sets the field as required to be completed by the user.</p> <p>Example (default): <code>enrole.justificationRequired=false</code></p>
--	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Chapter 17. IBM Security Identity Manager virtual appliance command line interface

Access the command line interface (CLI) of the virtual appliance by using either an ssh session or the console.

The following paragraphs are general notes about the usage of the CLI. Examples of specific commands by using the CLI are provided through the remainder of this document.

The following example shows the transcript of using an ssh session to access the virtual appliance.

```
usernameA@example.com> ssh -l admin isimva.example.com
admin@isimva.example.com's password:
Welcome to the IBM Security Identity Manager appliance
Enter "help" for a list of available commands
isimva.example.com> isim
isimva.example.com:isim> help
Current mode commands:
firmware_update    Work with the ISIM firmware settings.
service_trace      Work with the ISIM trace settings.
Global commands:
back                Return to the previous command mode.
exit                Log off from the appliance.
help                Display information for using the specified command.
reboot              Reboot the appliance.
shutdown            End system operation and turn off the power.
top                 Return to the top level.
isimva.example.com:isim>
```

You can also access the console by using the appropriate VMware software. For example, VMware vSphere Client.

Note: The CLI contains only a subset of the function available from the graphical user interface.

IBM Security Identity Manager virtual appliance command line interface commands

The IBM Security Identity Manager virtual appliance CLI commands are broadly divided into the two sections such as current mode commands and global commands. The topic provides information about the IBM Security Identity Manager virtual appliance CLI commands for the following functions.

The following list gives a high-level overview of the functions available from the command line interface.

fixpacks

The function works with the fix packs. The corresponding task can be completed by using the graphical user interface. Go to **Manage > Updates and Licensing > Fix Packs**.

install Installs the available fix packs on the inserted USB device.

list Lists the available fix packs on the inserted USB device.

rollback

Uninstalls the most recently installed fix pack.

view_history

Shows the installation history for all fix packs.

license

The function works with the licenses.

management

dns Works with the virtual appliance DNS settings.

hostname

Works with the virtual appliance host name.

interfaces

Works with the management interface settings.

set_password

Sets the virtual appliance password.

snapshots

The function works with the snapshots. The corresponding task can be completed by using the graphical user interface. Go to **Manage > System Settings > Snapshots**.

Note: You must restart the virtual appliance after you apply the snapshot.

apply Applies a policy snapshot file to the system.

create Creates a snapshot of current policy files.

delete Deletes a policy snapshot file.

download

Downloads a policy snapshot file to a USB flash drive.

get_comment

Views the comment that is associated with a policy snapshot file.

list Lists the policy snapshot files.

set_comment

Replaces the comment that is associated with a policy snapshot file.

upload

Uploads a policy snapshot file from a USB flash drive.

support

The function generates the support files. The corresponding task can be completed by using the graphical user interface. Go to **Manage > System Settings > Support Files**.

create Creates a support information file.

delete Deletes a support information file.

download

Downloads a support information file to a USB flash drive.

get_comment

Views the comment that is associated with a support information file.

list Lists the support information files.

set_comment

Replaces the comment that is associated with a support information file.

tools**nslookup**

Queries internet domain name servers.

ping Sends an ICMP ECHO_REQUEST to network hosts.

traceroute

Traces a packet from a computer to a remote destination. Shows the required number of hops for a packet that is required to reach the destination and the duration of each hop.

connect

Test network connection to a certain port on a specified host.

IBM Security Identity Manager virtual appliance command line interface commands for IBM Security Identity Manager

The initial virtual appliance settings wizard runs the first time that an Administrator logs on to the command line interface (CLI) of an unconfigured IBM Security Identity Manager virtual appliance. The topic provides information about the sub sections of the IBM Security Identity Manager virtual appliance CLI command that is specific to IBM Security Identity Manager.

The IBM Security Identity Manager virtual appliance CLI commands are broadly divided into the following main sections:

- Current mode commands
- Global commands

In the current mode commands, the **isim** command is used to work with the IBM Security Identity Manager settings. When an Administrator or a user enters the **isim** command, the following sub sections are listed.

firmware_update

The sub section provides options to work with IBM Security Identity Manager firmware updates.

delete_firmware

Deletes firmware updates from the system.

install_firmware

Installs the available firmware update to the system.

list_firmware

Lists firmware updates from a USB device.

transfer_firmware

Transfers firmware update from a USB device to the system.

Tailing logs and archiving logs

You can generate tailing logs and archiving logs through the command-line interface in the IBM Security Identity Manager virtual appliance.

About this task

To see a list of available commands, enter the `help` command at the command-line prompt. The `help` command provides detailed information about each command from the list.

Procedure

1. From the command-line interface, log on to the IBM Security Identity Manager virtual appliance. The following message is displayed:

```
Welcome to the IBM Security Identity Manager appliance
Enter "help" for a list of available commands
```

2. Enter the `help` command at the `isimvasrv` prompt for a list of available commands. The following result is displayed:

```
Current mode commands:
firmware          Work with firmware images.
fixpacks          Work with fix packs.
isim              Work with the ISIM settings.
license           Work with licenses.
management        Work with management settings.
snapshots         Work with policy snapshot files.
support           Work with support information files.
tools             Work with network diagnostic tools.
updates           Work with firmware and security updates.
Global commands:
back              Return to the previous command mode.
exit              Log off from the appliance.
help              Display information for using the specified command.
reboot            Reboot the appliance.
shutdown          End system operation and turn off the power.
top               Return to the top level.
```

3. Enter the `isim` command at the `isimvasrv` prompt.
4. Enter the `help` command at the `isimvasrv:isim` prompt for a list of available commands. The following result is displayed:

```
Current mode commands:
firmware_update  Work with the ISIM Appliance firmware settings.
keystore_password Work with the middleware keystore.
logs              Work with the ISIM log files.
service_trace    Work with the ISIM trace settings.
Global commands:
back              Return to the previous command mode.
exit              Log off from the appliance.
help              Display information for using the specified command.
reboot            Reboot the appliance.
shutdown          End system operation and turn off the power.
top               Return to the top level.
```

5. Enter the `logs` command at the `isimvasrv:isim` prompt.
6. Enter the `help` command at the `isimvasrv:isim:logs` prompt for a list of available commands. The following result is displayed:

```
Current mode commands:
clear_ffdc        Clear all FFDC log files on the system.
clear_tranlog     Clearing transaction logs for application server.
monitor           Monitor log files on the system.
Global commands:
back              Return to the previous command mode.
exit              Log off from the appliance.
help              Display information for using the specified command.
reboot            Reboot the appliance.
shutdown          End system operation and turn off the power.
top               Return to the top level.
```

For more information on clearing transaction logs, see [Clearing the transaction logs](#).

7. Enter the `monitor` command at the `isimvasrv:isim:logs` prompt.

8. Enter the help command at the `isimvasrv:isim:logs:monitor` prompt for a list of available commands. The following result is displayed:

```
Options:
1: System
2: LMI
3: Configuration
4: Cluster Manager
5: Application Server
6: Message Server
7: ISIM Server
```

Note: Similarly, you can enter the `clear_ffdc` command at the `isimvasrv:isim:logs` prompt to clear all FFDC log files on the system.

9. Enter the index number to view a list of logs. For example, to view the cluster manager logs, specify 4 at **Enter index**.

The following message is displayed:

```
Options:
1: SystemErr.log
2: SystemOut.log
3: native_stderr.log
4: native_stdout.log
5: startServer.log
6: stopServer.log
```

10. Enter the index number to view the tailing logs of the cluster manager. For example, specify 1 at **Enter index**.

The following message is displayed:

```
***** Start Display Current Environment *****
Log file started at: [3/13/15 17:42:49:673 EDT]
***** End Display Current Environment *****
```

11. Enter the index number to view the tailing logs of the IBM Security Identity Manager Server. For example, specify 7 at **Enter index**.

The following message is displayed:

```
1: SystemErr.log
2: SystemOut.log
3: SystemOut_15.03.17_02.42.19.log
4: native_stderr.log
5: native_stdout.log
6: startServer.log
7: stopServer.log
8: SystemErr.log
9: SystemOut.log
10: native_stderr.log
11: native_stdout.log
12: startServer.log
13: stopServer.log
14: msg.log
15: trace.log
```

12. Enter the index number to view the trace logs of the IBM Security Identity Manager Server. For example, specify 15 at **Enter index**.

The following message is displayed:

```
<Time Millis="1426836005522"> 2015.03.20 03:20:05.522-04:00</Time>
<Server Format="IP">isim1175.in.ibm.com</Server>
<ProductId>CTGIM</ProductId>
<Component>com.ibm.itim.pim.serviceprovider.db</Component>
<ProductInstance>ISIMVa_APP_MEMBER</ProductInstance>
<LogText><![CDATA[ISPIM DB manager is processing asynchronous requests? true]]></LogText>
<Source FileName="PIMDBManager" Method="run"/>
<Thread>Thread-139</Thread>
</Trace>
```

Adding a JVM property

As part of configuring an application server, you might define settings that enhance the way your operating system uses of the Java virtual machine (JVM). Use the steps to add a JVM property in the Application server.

About this task

The JVM is an interpretive computing engine that is responsible for running the byte codes in a compiled Java program. The JVM translates the Java byte codes into the default instructions of the host server. The application server, being a Java process, requires a JVM to run and to support the Java applications that run on it. JVM settings are part of an application server configuration.

Access the command-line interface (CLI) of the virtual appliance by using either an ssh session or the console.

To see a list of available commands, enter the `help` command at the command-line prompt. The `help` command provides detailed information about each command from the list.

Procedure

1. From the command-line interface, log on to the IBM Security Identity Manager virtual appliance. The following message is displayed:

```
Welcome to the IBM Security Identity Manager appliance
Enter "help" for a list of available commands
```

2. Enter the `help` command at the `isimvasrv` prompt for a list of available commands. The following result is displayed:

```
Current mode commands:
firmware           Work with firmware images.
fixpacks           Work with fix packs.
isim                Work with the ISIM settings.
license            Work with licenses.
management         Work with management settings.
snapshots          Work with policy snapshot files.
support            Work with support information files.
tools              Work with network diagnostic tools.
updates            Work with firmware and security updates.
Global commands:
back               Return to the previous command mode.
exit               Log off from the appliance.
help               Display information for using the specified command.
reboot             Reboot the appliance.
shutdown           End system operation and turn off the power.
top                Return to the top level.
```

3. Enter the `isim` command at the `isimvasrv` prompt.
4. Enter the `help` command at the `isimvasrv:isim` prompt for a list of available commands. The following result is displayed:

```
Current mode commands:
firmware_update   Work with the ISIM Appliance firmware settings.
jvm_property       Work with the Application Server JVM properties.
keystore_password Work with the middleware keystore.
logs               Work with the ISIM log files.
service_trace     Work with the ISIM trace settings.
Global commands:
back               Return to the previous command mode.
exit               Log off from the appliance.
help               Display information for using the specified command.
reboot             Reboot the appliance.
shutdown           End system operation and turn off the power.
top                Return to the top level.
```

5. Enter the `jvm_property` command at the `isimvasrv:isim` prompt.
6. Enter the `help` command at the `isimvasrv:jvm_property` prompt for a list of available commands. The following result is displayed:

```
Current mode commands:
add               Add a JVM Property in Application server.
delete            Delete an existing JVM Property in Application server.
update            Update an existing JVM Property in Application server.
Global commands:
back               Return to the previous command mode.
exit               Log off from the appliance.
```

```
help          Display information for using the specified command.
reboot       Reboot the appliance.
shutdown     End system operation and turn off the power.
top          Return to the top level.
```

7. Enter the add command at the `isimvasrv:jvm_property` prompt. The following result is displayed:

```
Property name : com.ibm.websphere.webservices.soap.enable.legacy.get.behavior
Property value : true
```

```
Adding JVM property
JVM Property added successfully.
Restart Identity Manager server to apply the new settings.
```

What to do next

Restart the IBM Security Identity Manager Server to apply the new settings.

Management SSL certificate

Use either the local management interface or web service to work with the management SSL certificate.

If the certificate expires, the local management interface is not reachable. In this situation, use the **reset_lmi_cert** CLI command within the local management interface menu to generate a self-signed certificate so that access to the local management interface can be re-established. Then, use the restart CLI command to restart the local management interface.

You can type help in the command-line interface for a list of commands available in the current mode. For example:

```
isig.ibm.com:lmi>help
Current mode commands:
reset_lmi_cert  Reset the server certificate for the local management interface
                to a self-signed certificate.
restart        Restart the local management interface.
```

Chapter 18. Sample configuration response file

Set your configuration parameters for the IBM Security Identity Manager virtual appliance in a response file. After you update the response file with correct values, upload the response file to configure the virtual appliance in the advanced configuration mode.

```
#####  
#  
# You can do initial configuration of IBM Security Identity Manager  
# Appliance by using a response file.  
# Update the response file with correct values and provide it during the advanced  
# mode of Initial configuration wizard.  
#  
#####  
#  
# Appliance Administrator User Credentials  
#  
isim.appliance.adminUserPwd=<admin user password>  
  
#  
# Identity Data store configuration Properties  
#  
isim.datastore.dbType=<IBM_DB or ORACLE_DB>  
isim.datastore.hostName=<hostname>  
isim.datastore.port=50000  
isim.datastore.adminUser=db2admin  
isim.datastore.adminUserPwd=<admin password>  
isim.datastore.user=itimuser  
isim.datastore.userPwd=<user password>  
isim.datastore.dbName=idmdb  
isim.datastore.connection.type=non-ssl  
isim.datastore.isOracleServiceName=<true or false>  
  
#  
# Directory Server configuration properties  
#  
isim.ldap.hostName=<hostname>  
isim.ldap.port=389  
isim.ldap.organization.shortname=org  
isim.ldap.organization.name=Organization  
isim.ldap.bindDN=cn=root  
isim.ldap.bindDNPwd=<password>  
isim.ldap.dnLocation=dc=com  
isim.ldap.connection.type=non-ssl  
  
#  
# Mail Server configuration properties  
#  
isim.mail.server=localhost  
isim.mail.from=admin@in.ibm.com
```

Index

A

access control
 API 6
account
 object, JavaScript extension 74
Account.getAndDecryptPassword object
 JavaScript extension 74
Account.setAndEncryptPassword object
 JavaScript extension 75
AccountModelExtension, JavaScript
 extensions 58
AccountSearch object, JavaScript
 extension 75
AccountSearch.searchByOwner object
 JavaScript extension 76
AccountSearch.searchByUid object,
 JavaScript extension 76
AccountSearch.searchByURI object,
 JavaScript extension 77
activity object, JavaScript extension 78
Activity.auditEvent object, JavaScript
 extension 79
Activity.description object, JavaScript
 extension 80
Activity.duedate object, JavaScript
 extension 80
Activity.getSubProcesses(), JavaScript
 extension 80
Activity.guid object, JavaScript
 extension 81
Activity.id object, JavaScript
 extension 81
Activity.index object, JavaScript
 extension 81
Activity.name object, JavaScript
 extension 82
Activity.participant object, JavaScript
 extension 82
Activity.resultDetail object, JavaScript
 extension 82
Activity.resultSummary object, JavaScript
 extension 82
Activity.setResult object, JavaScript
 extension 83
Activity.started object, JavaScript
 extension 83
Activity.state object, JavaScript
 extension 83
Activity.subtype object, JavaScript
 extension 84
Activity.type object, JavaScript
 extension 84
adhocreporting.properties 175
APIs
 access control 6
 authentication 8
 data services 5, 8
 group 6
 IBM Directory Integration API 8
 JavaScript 9
 mail 9
 APIs (*continued*)
 overview 5
 password rules 9
 policy analysis 9
 reconciliation 7
 self registration 6
 service provider 10
 single sign-on 10
 web services API 11
 workflow 14
APIsgroup
 recertification policy 7
application client request
 configuration 252
application extension methods 1
Application server-specific
 configuration 221
archiving logs
 command line interface 264
AttributeChangeOperation object,
 JavaScript extension 85
AttributeChangeOperation.attr object,
 JavaScript extension 85
AttributeChangeOperation.op object,
 JavaScript extension 85
AttributeChangeOperation.values,
 JavaScript extension 85
AttributesExtension, JavaScript
 extensions 56
authentication
 API 8
authentication properties
 enRoleAuthentication.properties 185

C

cache information 232
challenge response encoding
 information 240
command line interface
 global commands 261
 tailing logs 264
 virtual appliance 261
commands, IBM Security Identity
 Manager 263
concurrency
 enrole properties 258
configuration response samples 269
constructor
 JavaScript migration, example 68
ContainerSearch object, JavaScript
 extension 86
ContainerSearch.searchByFilter object,
 JavaScript extension 86
ContainerSearch.searchByURI object,
 JavaScript extension 87
content tags
 dynamic tags 31
 examples 31
Context object, JavaScript extension 87

Context.getAccountParameter object,
 JavaScript extension 89
Context.getActivityResult object,
 JavaScript extension 89
Context.getActivityResultById object,
 JavaScript extension 89
Context.getLoopCount object, JavaScript
 extension 90
Context.getLoopCountById object,
 JavaScript extension 90
Context.getProcessType object, JavaScript
 extension 90
Context.getRequestee object, JavaScript
 extension 91
Context.getService object, JavaScript
 extension 91
control type
 SubForm 169
 contextual parameters 169
 parameter names 170
 writing 171
create password checkbox
 information 255
customization
 date range 19
CustomLabels.properties
 supplemental properties 182

D

data services
 API 5
database cleanup information 255
database resource bundle 254
dataservices attributes
 recertification 17
date range
 customization 19
default notification templates
 manual service 36
default recertification templates
 recertification default messages 38
default workflow templates
 workflow default messages 44
DelegateExtension, JavaScript
 extensions 57
dictionary
 password policy 15
DirectoryObject object, JavaScript
 extension 92
DirectoryObject.addProperty object,
 JavaScript extension 93
DirectoryObject.dn object, JavaScript
 extension 94
DirectoryObject.getChanges object,
 JavaScript extension 95
DirectoryObject.getProperty object,
 JavaScript extension 95
DirectoryObject.getPropertyAsDate
 object 96

- DirectoryObject.getPropertyAsString object 97
- DirectoryObject.getPropertyNames object, JavaScript extension 97
- DirectoryObject.name object, JavaScript extension 97
- DirectoryObject.profileName object, JavaScript extension 98
- DirectoryObject.setProperty, JavaScript extension object 99
- dynamic tags
 - content tags
 - examples 31

E

- EmailContext object, JavaScript extension 100
- EmailContextExtension, JavaScript extensions 57
- encryption information 238
- enrole
 - concurrency 258
- Enrole object, JavaScript extension 102
- Enrole.generatePassword object, JavaScript extension 103
- Enrole.getAttributeValue object, JavaScript extension 103
- Enrole.getAttributeValues object, JavaScript extension 104
- Enrole.localize object, JavaScript extension 104
- Enrole.log object, JavaScript extension 105
- Enrole.logError object, JavaScript extension 105
- Enrole.logInfo object, JavaScript extension 106
- Enrole.logWarning object, JavaScript extension 106
- enRole.properties file 221
 - application client request configuration 252
 - Application server-specific configuration 221
 - cache information 232
 - challenge response encoding information 240
 - create password checkbox 255
 - database cleanup 255
 - database resource bundle 254
 - encryption information 238
 - identity feed 256
 - LDAP connection pool information 236
 - LDAP server information 227
 - life cycle rule 251
 - mail services configuration 241
 - messaging information 233
 - organization name 226
 - password synchronization 257
 - password transaction monitor settings 235
 - person profile 231
 - post office 253
 - product name 252

- enRole.properties file *(continued)*
 - reconciliation information 247
 - required fields 258
 - reverse password
 - synchronization 252
 - scheduling information 234
 - search strategy and LDAP control configuration 228
 - shared secret hashing 251
 - system configuration program 240
 - tenant information, default 226
 - upgrade 257
 - workflow configuration information 241
 - XML and DTD information 236
- Enrole.toGeneralizedTime object, JavaScript extension 107
- Enrole.toMilliseconds object, JavaScript extension 107
- Enrole.traceMax object, JavaScript extension 108
- Enrole.traceMid object, JavaScript extension 108
- Enrole.traceMin object, JavaScript extension 109
- enroleAuditing.properties 183
- enRoleAuthentication.properties
 - authentication properties 185
- EnroleExtension, JavaScript extensions 57
- enRoleLogging.properties 187
- enrolepolicies.properties 197
- enroleStartup.properties 200
- enroleworkflow.properties 201
- entitlement parameters 163
- Error object, JavaScript extension 110
- Error.getErrorCode object, JavaScript extension 111
- Error.getMessage object, JavaScript extension 110
- Error.setErrorCode object, JavaScript extension 111
- Error.setMessage object, JavaScript extension 110
- examples
 - mail templates 36
- ExtendedPerson.getOwnershipType(), JavaScript extension 112
- ExtendedPerson.setOwnershipType(), JavaScript extension 113
- extensions
 - JavaScript
 - AccountModelExtension 58
 - AttributesExtension 56
 - DelegateExtension 57
 - EmailContextExtension 57
 - EnroleExtension 57
 - IdentityPolicyExtension 57
 - LoopCountExtension 58
 - Model 58
 - OrganizationModelExtension 59
 - PersonModelExtension 58
 - PersonPlacementRules
 - Extension 59
 - PostOfficeExtension 60
 - ProvisioningPolicyExtension 60
 - registering 62

- extensions *(continued)*
 - JavaScript *(continued)*
 - ReminderExtension 60
 - RoleModelExtension 59
 - ServiceExtension 61
 - ServiceModelExtension 59
 - SubjectExtension 61
 - WorkflowExtension 61
 - migrating
 - constructor 68
 - example 65
 - FESI 64
 - script conversion 67
 - scriptframework.properties 64

F

- FESI
 - migrating
 - example 64
 - fesixtensions.properties 62
- function differences, FESI and IBM JSEngine
 - JavaScript extensions 65

G

- getRoleName()
 - RoleAssignmentAttribute 149
- global commands, command line interface 261

H

- helpmappings.properties 202

I

- identity feed information 256
- IdentityPolicy object, JavaScript extension 113
- IdentityPolicy.getNextCount object, JavaScript extension 113
- IdentityPolicy.userIDExists object, JavaScript extension 114
- IdentityPolicyExtension, JavaScript extensions 57

J

- Javascript extension
 - RoleAssignmentAttribute.getName() 148
 - RoleAssignmentAttribute.getRoleDN 150
 - RoleAssignmentObject.getAssignedRoleDN() 151
- JavaScript extension object
 - account 74
 - AccountSearch 75
 - AccountSearch.searchByUid 76
 - AccountSearch.searchByURI 77
 - activity 78
 - Activity.auditEvent 79
 - Activity.description 80
 - Activity.duedate 80
 - Activity.getSubProcesses() 80

JavaScript extension (continued)
object (continued)

Activity.guid 81
Activity.id 81
Activity.index 81
Activity.name 82
Activity.participant 82
Activity.resultDetail 82
Activity.resultSummary 82
Activity.setResult 83
Activity.started 83
Activity.state 83
Activity.subtype 84
Activity.type 84
AttributeChangeOperation 85
AttributeChangeOperation.attr 85
AttributeChangeOperation.op 85
ContainerSearch 86
ContainerSearch.searchByFilter 86
ContainerSearch.searchByURI 87
Context 87
Context.getAccountParameter 89
Context.getActivityResult 89
Context.getActivityResultById 89
Context.getLoopCount 90
Context.getLoopCountById 90
Context.getProcessType 90
Context.getRequestee 91
Context.getService 91
DirectoryObject 92
DirectoryObject.
 getPropertyNames 97
DirectoryObject.addProperty 93
DirectoryObject.dn 94
DirectoryObject.getChanges 95
DirectoryObject.getProperty 95
DirectoryObject.name 97
DirectoryObject.profileName 98
EmailContext 100
Enrole 102
Enrole.generatePassword 103
Enrole.getAttributeValue 103
Enrole.getAttributeValues 104
Enrole.localize 104
Enrole.log 105
Enrole.logError 105
Enrole.loginfo 106
Enrole.logWarning 106
Enrole.toGeneralizedTime 107
Enrole.toMilliseconds 107
Enrole.traceMax 108
Enrole.traceMid 108
Enrole.traceMin 109
Error 110
Error.getErrorCode 111
Error.getMessage 110
Error.setErrorCode 111
Error.setMessage 110
ExtendedPerson.getOwnershipType() 112
ExtendedPerson.setOwnershipType() 113
IdentityPolicy 113
IdentityPolicy.getNextCount 113
IdentityPolicy.userIDExists 114
PackagedApprovalDocument 115
PackagedApprovalItem 117
Participant 118
Participant.implementation 119

JavaScript extension (continued)
object (continued)

Participant.name 119
Participant.type 119
ParticipantType 119
Person 121
Person.getAllAssignmentAttributes() 123
Person.getAndDecryptPersonPassword() 123
Person.getAndDecryptSynchPassword() 123
Person.getNewRoles 126
Person.getRemovedRoles 126
Person.getRoleAssignmentData 125
Person.getRoleAssignmentData() 124
Person.getRoles 126
Person.isInRole 127
Person.removeRole 127
Person.removeRoleAssignmentData() 128
Person.updateRoleAssignmentData() 128
PersonSearch 129
PersonSearch.searchByFilter 130
PersonSearch.searchByURI 130
PostOffice 131
PostOffice.getAllEmailMessages() 131
PostOffice.getEmailAddress 132
PostOffice.getPerson
 ByEmailAddress 132
PostOffice.getTopic 132
Process 132
Process.auditEvent 134
Process.comment 135
Process.description 135
Process.getActivity 135
Process.getParent 136
Process.getRootProcess() 136
Process.getRootRequesterName() 137
Process.getSubProcesses() 137
Process.guid 137
Process.id 138
Process.name 138
Process.parentId 138
Process.requesteeDN 138
Process.requesteeName 139
Process.requestorDN 139
Process.requestorName 139
Process.requestorType 140
Process.resultDetail 140
Process.resultSummary 140
Process.setRequesteeData 140
Process.setResult 141
Process.setSubjectData 141
Process.started 142
Process.state 142
Process.subject 142
Process.type 143
ProcessData 143
ProcessData.get 143
ProcessData.set 144
RecertificationWorkflow 144
Reminder 145
Role 145
Role.getAssignmentAttributes 146
Role.getOwner 147
Role.setAssignmentAttributes 148
RoleSearch 155
RoleSearch.searchByName 155
RoleSearch.searchByURI 156
service 157

JavaScript extension (continued)
object (continued)

ServiceSearch 157
objects 71
Role.getAllAssignmentAttributes 147
RoleAssignment.addAttributeProperty 152
RoleAssignmentAttribute 148
RoleAssignmentObject.getChanges() 152
RoleAssignmentObject.getDefinedRoleDN() 152
RoleAssignmentObject.getProperty
 object 153
RoleAssignmentObject.getPropertyNames
 object 154
RoleAssignmentObject.removeProperty
 object 154
RoleAssignmentObject.setProperty
 object 154
SeparationOfDutyRuleViolation
 object 156
ServiceSearch.searchByFilter
 object 158
ServiceSearch.searchByName
 object 158
ServiceSearch.searchByURI
 object 159
ServiceSearch.searchForClosestToPerson
 object 159
JavaScript extensions
 AttributesExtension 56
 DelegateExtension 57
 EmailContextExtension 57
 EnroleExtension 57
 fesiextensions.properties 62
 function differences, FESI and IBM
 JSEngine 65
 IdentityPolicyExtension 57
 LoopCountExtension 58
 migrating
 FESI 64
 Model 58
 AccountModelExtension 58
 OrganizationModelExtension 59
 PersonModelExtension 58
 RoleModelExtension 59
 ServiceModelExtension 59
 overview 55
 packaged extensions 56
 PersonPlacementRulesExtension 59
 PostOfficeExtension 60
 ProvisioningPolicyExtension 60
 registering 62
 ReminderExtension 60
 scriptframework.properties 62, 64
 ServiceExtension 61
 SubjectExtension 61
 WorkflowExtension 61
JavaScript functions 163
JavaScript objects
 relevant data 62
 service selection policy 167
L
LDAP connection pool information 236
LDAP server information 227
life cycle rule 251

Log4j 187
LoopCountExtension, JavaScript
extensions 58

M

mail services configuration 241
mail templates
examples 36
manual service
default notification templates 36
messaging information 233
methods
RoleAssignmentObject 150
migrating
JavaScript
constructor example 68
FESI 64
FESI example 65
script example 67
Model, JavaScript extensions 58
modifiable property files
property files 173

N

null types 163

O

object 85
Context.isAccountDataChanged object,
JavaScript extension 91
delegate JavaScript extension 92
DirectoryObject.getPropertyAsDate 96
DirectoryObject.getPropertyAsString 97
DirectoryObject.removeProperty,
JavaScript extension 98
DirectoryObject.removeProperty(name,value)
, JavaScript extension 98
DirectoryObject.setProperty object,
JavaScript extension 99
JavaScript extension
account 74
AccountSearch 75
AccountSearch.searchByUid 76
AccountSearch.searchByURI 77
activity 78
Activity.auditEvent 79
Activity.description 80
Activity.duedate 80
Activity.getSubProcesses() 80
Activity.guid 81
Activity.id 81
Activity.index 81
Activity.name 82
Activity.participant 82
Activity.resultDetail 82
Activity.resultSummary 82
Activity.setResult 83
Activity.started 83
Activity.state 83
Activity.subtype 84
Activity.type 84
AttributeChangeOperation 85
AttributeChangeOperation.attr 85

object (continued)

JavaScript extension (continued)
AttributeChangeOperation.op 85
ContainerSearch 86
ContainerSearch.searchByFilter 86
ContainerSearch.searchByURI 87
Context 87
Context.getAccountParameter 89
Context.getActivityResult 89
Context.getActivityResultById 89
Context.getLoopCount 90
Context.getLoopCountById 90
Context.getProcessType 90
Context.getRequestee 91
Context.getService 91
DirectoryObject 92
DirectoryObject.
getPropertyNames 97
DirectoryObject.addProperty 93
DirectoryObject.dn 94
DirectoryObject.getChanges 95
DirectoryObject.getProperty 95
DirectoryObject.name 97
DirectoryObject.profileName 98
EmailContext 100
Enrole 102
Enrole.generatePassword 103
Enrole.getAttributeValue 103
Enrole.getAttributeValues 104
Enrole.localize 104
Enrole.log 105
Enrole.logError 105
Enrole.loginInfo 106
Enrole.logWarning 106
Enrole.toGeneralizedTime 107
Enrole.toMilliseconds 107
Enrole.traceMax 108
Enrole.traceMid 108
Enrole.traceMin 109
Error 110
Error.getErrorCode 111
Error.getMessage 110
Error.setErrorCode 111
Error.setMessage 110
ExtendedPerson.getOwnershipType() 112
ExtendedPerson.setOwnershipType() 113
IdentityPolicy 113
IdentityPolicy.getNextCount 113
IdentityPolicy.userIDExists 114
Oerson.isInRole 127
PackagedApprovalDocument 115
PackagedApprovalItem 117
Participant 118
Participant.implementation 119
Participant.name 119
Participant.type 119
ParticipantType 119
Person 121
Person.getAllAssignmentAttributes() 124
Person.getAndDecryptPersonPassword() 124
Person.getAndDecryptSynchPassword() 124
Person.getNewRoles 126
Person.getRemovedRoles 126
Person.getRoleAssignmentData 125
Person.getRoleAssignmentData() 124
Person.getRoles 126
Person.removeRole 127

object (continued)

JavaScript extension (continued)
Person.removeRoleAssignmentData() 128
Person.updateRoleAssignmentData() 128
PersonSearch 129
PersonSearch.searchByFilter 130
PersonSearch.searchByURI 130
PostOffice 131
PostOffice.getAllEmailMessages() 131
PostOffice.getEmailAddress 132
PostOffice.getPerson
ByEmailAddress 132
PostOffice.getTopic 132
Process 132
Process.auditEvent 134
Process.comment 135
Process.description 135
Process.getActivity 135
Process.getParent 136
Process.getRootProcess() 136
Process.getRootRequesterName() 137
Process.getSubProcesses() 137
Process.guid 137
Process.id 138
Process.name 138
Process.parentId 138
Process.requesteeDN 138
Process.requesteeName 139
Process.requestorDN 139
Process.requestorName 139
Process.requestorType 140
Process.resultDetail 140
Process.resultSummary 140
Process.setRequesteeData 140
Process.setResult 141
Process.setSubjectData 141
Process.started 142
Process.state 142
Process.subject 142
Process.type 143
ProcessData 143
ProcessData.get 143
ProcessData.set 144
RecertificationWorkflow 144
Reminder 145
Role 145
Role.getAssignmentAttributes 146
Role.getOwner 147
Role.setAssignmentAttributes 148
RoleSearch 155
RoleSearch.searchByName 155
RoleSearch.searchByURI 156
service 157
ServiceSearch 157

Objects

AccountSearch.searchByUidAndService
object
JavaScript extension 77
OrganizationModelExtension, JavaScript
extensions 59
JavaScript extensions 55

P

packaged extensions
JavaScript extensions 56

- PackagedApprovalDocument, JavaScript extension 115
- PackagedApprovalItem, JavaScript extension 117
- Participant object, JavaScript extension 118
- Participant.implementation object, JavaScript extension 119
- Participant.name object, JavaScript extension 119
- Participant.type object, JavaScript extension 119
- ParticipantType object, JavaScript extension 119
- password policy dictionary 15
- password transaction monitor settings 235
- Person object, JavaScript extension 121
- person profile 231
- Person.getAllAssignmentAttributes(), JavaScript extension 123, 124
- Person.getAndDecryptPersonPassword(), JavaScript extension 124
- Person.getAndDecryptSynchPassword(), JavaScript extension 123
- Person.getNewRoles object, JavaScript extension 126
- Person.getRemovedRoles object, JavaScript extension 126
- Person.getRoleAssignmentData, JavaScript extension 125
- Person.getRoles object, JavaScript extension 126
- Person.isInRole object, JavaScript extension 127
- Person.removeRoleAssignmentData(), JavaScript extension 128
- Person.removeRoles object, JavaScript extension 127
- Person.updateRoleAssignmentData(), JavaScript extension 128
- PersonModelExtension, JavaScript extensions 58
- PersonPlacementRulesExtension, JavaScript extensions 59
- PersonSearch object, JavaScript extension 129
- PersonSearch.searchByFilter object, JavaScript extension 130
- PersonSearch.searchByURI object, JavaScript extension 130
- post office information 253
- PostOffice object, JavaScript extension 131
- PostOffice.getAllEmailMessages(), JavaScript extension 131
- PostOffice.getEmailAddress object, JavaScript extension 132
- PostOffice.getPersonByEmailAddress object, JavaScript extension 132
- PostOffice.getTopic object, JavaScript extension 132
- PostOfficeExtension, JavaScript extensions 60
- Process object, JavaScript extension 132
- Process.auditEvent object, JavaScript extension 134
- Process.comment object, JavaScript extension 135
- Process.description object, JavaScript extension 135
- Process.getActivity object, JavaScript extension 135
- Process.getParent object, JavaScript extension 136
- Process.getRootProcess(), JavaScript extension 136
- Process.getRootRequesterName(), JavaScript extension 137
- Process.getSubProcesses(), JavaScript extension 137
- Process.guid object, JavaScript extension 137
- Process.id object, JavaScript extension 138
- Process.name object, JavaScript extension 138
- Process.parentId object, JavaScript extension 138
- Process.requesteeDN object, JavaScript extension 138
- Process.requesteeName object, JavaScript extension 139
- Process.requestorDN object, JavaScript extension 139
- Process.requestorName object, JavaScript extension 139
- Process.requestorType object, JavaScript extension 140
- Process.resultDetail object, JavaScript extension 140
- Process.resultSummary object, JavaScript extension 140
- Process.setRequesteeData object, JavaScript extension 140
- Process.setResult object, JavaScript extension 141
- Process.setSubjectData object, JavaScript extension 141
- Process.started object, JavaScript extension 142
- Process.state object, JavaScript extension 142
- Process.subject object, JavaScript extension 142
- Process.type object, JavaScript extension 143
- ProcessData object, JavaScript extension 143
- ProcessData.get object, JavaScript extension 143
- ProcessData.set object, JavaScript extension 144
- product name 252
- properties files
 - adhocreporting.properties 175
 - enroleAuditing.properties 183
 - enRoleLogging.properties 187
 - enrolepolicies.properties 197
 - enroleStartup.properties 200
 - enroleworkflow.properties 201
 - helpmappings.properties 202
- properties files (*continued*)
 - reportingLabels.properties 203
 - reporttabledeny.properties 203
 - scriptframework.properties 204
 - SelfServiceHelp.properties 205
 - SelfServiceHomePage 206
 - SelfServiceScreenText 206
 - SelfServiceUI.properties 207
 - supplemental properties 173
 - system properties 173
 - ui.properties 209
- property files
 - modifiable property files 173
- provisioning policies
 - constant 163
 - JavaScript 163
 - null types 163
 - parameter
 - scenarios 161
 - parameters 163
 - regular expressions 166
- provisioning policy
 - group 7
- ProvisioningPolicyExtension, JavaScript extensions 60

R

- recertification default messages
 - default recertification templates 38
- RecertificationWorkflow object, JavaScript extension 144
- reconciliation information 247
- registering application extensions 2
- registering, JavaScript extensions 62
- regular expressions 166
- relevant data JavaScript objects 62
- Reminder object, JavaScript extension 145
- ReminderExtension, JavaScript extensions 60
- reportingLabels.properties 203
- reporttabledeny.properties 203
- required fields
 - configuring 258
- reverse password synchronization 252
- Role object, JavaScript extension 145
- Role.getAllAssignmentAttributes object
 - JavaScript extension 147
- Role.getAssignmentAttributes object, JavaScript extension 146
- Role.getOwner object, JavaScript extension 147
- Role.setAssignmentAttributes object, JavaScript extension 148
- RoleAssignment.addProperty object
 - JavaScript extension 152
- RoleAssignmentAttribute
 - getRoleName() 149
- RoleAssignmentAttribute object, JavaScript extension 148
- RoleAssignmentAttribute.getName()
 - JavaScript extension 148
- RoleAssignmentAttribute.getRoleDN
 - JavaScript extension 150
- RoleAssignmentObject
 - methods 150

- RoleAssignmentObject.getAssignedRoleDN() SubForm control type *(continued)*
 - Javascript extension 151
- RoleAssignmentObject.getChanges()
 - JavaScript extension 152
- RoleAssignmentObject.getDefinedRoleDN()
 - JavaScript extension 152
- RoleAssignmentObject.getProperty object
 - JavaScript extension 153
- RoleAssignmentObject.getPropertyNames object
 - JavaScript extension 154
- RoleAssignmentObject.removeProperty object
 - JavaScript extension 154
- RoleAssignmentObject.setProperty object
 - JavaScript extension 154
- RoleModelExtension, JavaScript extensions 59
- RoleSearch object, JavaScript extension 155
- RoleSearch.searchByName object, JavaScript extension 155
- RoleSearch.searchByURI object, JavaScript extension 156

S

- scheduling information 234
- script
 - service selection policy 167
- scriptframework.properties 62, 204
 - JavaScript
 - configuring 64
- search strategy and LDAP control
 - configuration 228
- SelfServiceHelp.properties 205
- SelfServiceHomePage.properties 206
- SelfServiceScreenText.properties 206
- SelfServiceUI.properties 207
- SeparationOfDutyRuleViolation object
 - JavaScript extension 156
- service
 - service selection policy
 - Javascript 167
- service object, JavaScript extension 157
- service selection policy
 - JavaScript objects 167
 - script 167
- ServiceExtension, JavaScript extensions 61
- ServiceModelExtension, JavaScript extensions 59
- ServiceSearch object, JavaScript extension 157
- ServiceSearch.searchByFilter object
 - JavaScript extension 158
- ServiceSearch.searchByName object
 - JavaScript extension 158
- ServiceSearch.searchByURI object
 - JavaScript extension 159
- ServiceSearch.searchForClosestToPerson object
 - JavaScript extension 159
- shared secret hashing 251
- sub sections, IBM Security Identity Manager commands 263
- SubForm control type 169
- SubForm control type *(continued)*
 - contextual parameters 169
 - parameter names 170
 - writing 171
- SubjectExtension, JavaScript extensions 61
- supplemental properties
 - adhocreporting.properties 175
 - CustomLabels.properties 182
 - enroleAuditing.properties 183
 - enRoleLogging.properties 187
 - enrolepolicies.properties 197
 - enroleStartup.properties 200
 - enroleworkflow.properties 201
 - helpmappings.properties 202
 - properties files 173
 - reportingLabels.properties 203
 - reporttabledeny.properties 203
 - scriptframework.properties 204
 - SelfServiceHelp.properties 205
 - SelfServiceHomePage 206
 - SelfServiceScreenText 206
 - SelfServiceUI.properties 207
 - ui.properties 209
- system configuration program 240
- system properties
 - access catalog properties files 255
 - application client request
 - configuration 252
 - Application server-specific
 - configuration 221
 - cache information 232
 - challenge response encoding
 - information 240
 - create password checkbox 255
 - database cleanup 255
 - database resource bundle 254
 - encryption information 238
 - enRole.properties file 221
 - identity feed 256
 - LDAP connection pool
 - information 236
 - LDAP server information 227
 - life cycle rule 251
 - mail services configuration 241
 - messaging information 233
 - organization name 226
 - password synchronization 257
 - password transaction monitor
 - settings 235
 - person profile 231
 - post office 253
 - product name 252
 - properties files 173
 - reconciliation information 247
 - remote services properties files 224
 - required fields 258
 - reverse password
 - synchronization 252
 - scheduling information 234
 - search strategy and LDAP control
 - configuration 228
 - shared secret hashing 251
 - system configuration program 240
 - tenant information, default 226
 - understanding properties files 221
 - upgrade 257
- system properties *(continued)*
 - web services properties files 225
 - workflow configuration
 - information 241
 - XML and DTD information 236

T

- tenant information, default 226

U

- ui.properties 209
- UIConfig.properties
 - descriptions 218
 - properties 218
- upgrade information 257

V

- virtual appliance
 - command line interface 261

W

- workflow
 - application extensions 1
 - workflowApplication interface 1
- workflow configuration information 241
- workflow default messages
 - default workflow templates 44
- workflow extensions
 - intro 21
 - policy enforcement 21
 - recertification 21
 - wait 24
- WorkflowExtension, JavaScript extensions 61
- workflows
 - application extension
 - methods 1
 - registering 2
 - JavaScript objects
 - relevant data 62

X

- XML and DTD information 236



Printed in USA