Updates that apply to IBM® DB2® Analytics Accelerator Loader for z/OS® V2R1 User's Guide (SC27-6777-00)

Date of change: September 2016

Topics: Setting up accelerator groups in Ch. 2

Using the ISPF interface to create or edit a Consistent or Image Copy load profile in Ch. 6 Using the ISPF interface to create or edit a profile to load from an external file in Ch. 7 Using the ISPF interface to create or edit a high availability load (Multi) Profile in Ch. 8 Change description: Documentation changes made in support of PTF UI40888 APAR

PI67510(+PI64557) Support Accelerator Groups.

New Topic: "Setting up accelerator groups" will be added as the last topic in Chapter 2. Customizing DB2 Analytics Accelerator Loader

Setting up accelerator groups

Accelerator group support allows users to load multiple accelerators by specifying a single accelerator group name. To use this feature, you must identify the accelerator group name to the DB2 system. To add a group name, a row must be inserted into the SYSIBM.LOCATIONS table using the following rules:

COLUMN NAME	DESCRIPTION
LOCATION	The accelerator group name.
LINKNAME	This must have the value "DSNACCELERATORALIAS"
DBALIAS	The list of accelerators that belong to the group. Accelerator names must be separated by spaces.

Using the ISPF interface to create or edit a Consistent or Image Copy load profile in Ch. 6 Using the ISPF interface to create or edit a profile to load from an external file in Ch. 7 Using the ISPF interface to create or edit a high availability load (Multi) Profile in Ch. 8

Step 9 in each of these topics will be changed to read:

9. To select the accelerators onto which you want to load data, issue the A panel command. From the DB2 Analytics Accelerator Selection panel, select the accelerators or an accelerator group and press Enter.